

Package: AMARETTO (via r-universe)

June 30, 2024

Type Package

Title Regulatory Network Inference and Driver Gene Evaluation using Integrative Multi-Omics Analysis and Penalized Regression

Version 1.21.0

Date 2016-06-06

Author Jayendra Shinde, Celine Everaert, Shaimaa Bakr, Mohsen Nabian, Jishu Xu, Vincent Carey, Nathalie Pochet and Olivier Gevaert

Maintainer Olivier Gevaert <olivier.gevaert@gmail.com>

Depends R (>= 3.6), impute, doParallel, grDevices, dplyr, methods, ComplexHeatmap

Description Integrating an increasing number of available multi-omics cancer data remains one of the main challenges to improve our understanding of cancer. One of the main challenges is using multi-omics data for identifying novel cancer driver genes. We have developed an algorithm, called AMARETTO, that integrates copy number, DNA methylation and gene expression data to identify a set of driver genes by analyzing cancer samples and connects them to clusters of co-expressed genes, which we define as modules. We applied AMARETTO in a pancancer setting to identify cancer driver genes and their modules on multiple cancer sites. AMARETTO captures modules enriched in angiogenesis, cell cycle and EMT, and modules that accurately predict survival and molecular subtypes. This allows AMARETTO to identify novel cancer driver genes directing canonical cancer pathways.

License Apache License (== 2.0) + file LICENSE

LazyLoad yes

LazyData true

Encoding UTF-8

biocViews

StatisticalMethod,DifferentialMethylation,GeneRegulation,GeneExpression,MethylationArray,Transcription,Preprocessing

Suggests testthat, MASS, knitr, BiocStyle

NeedsCompilation no

Imports callr (>= 3.0.0.9001), Matrix, Rcpp, BiocFileCache, DT, MultiAssayExperiment, circlize, curatedTCGAData, foreach, glmnet, httr, limma, matrixStats, readr, reshape2, tibble, rmarkdown, graphics, grid, parallel, stats, knitr, ggplot2, gridExtra, utils

Roxygen list(markdown = TRUE)

RoxygenNote 6.1.1.9000

LinkingTo Rcpp

VignetteBuilder knitr

Repository <https://bioc.r-universe.dev>

RemoteUrl <https://github.com/bioc/AMARETTO>

RemoteRef HEAD

RemoteSha c18b40e9e8b88967116ffd832049aa69a4f920b4

Contents

AMARETTO_CreateModuleData	2
AMARETTO_CreateRegulatorPrograms	3
AMARETTO_Download	4
AMARETTO_EvaluateTestSet	4
AMARETTO_ExportResults	5
AMARETTO_HTMLreport	6
AMARETTO_Initialize	7
AMARETTO_Preprocess	9
AMARETTO_Run	10
AMARETTO_VisualizeModule	10
BatchData	11
Driver_Genes	12
MsigdbMapping	12
plot_run_history	13
ProcessedDataLIHC	13
read_gct	14
Index	15

AMARETTO_CreateModuleData

AMARETTO_CreateModuleData

Description

AMARETTO_CreateModuleData

Usage

```
AMARETTO_CreateModuleData(AMARETTOinit, AMARETTOresults)
```

Arguments

```
AMARETTOinit    List output from AMARETTO_Initialize().  
AMARETTOresults  
                List output from AMARETTO_Run()
```

Value

```
result
```

Examples

```
data('ProcessedDataLIHC')  
AMARETTOinit <- AMARETTO_Initialize(ProcessedData = ProcessedDataLIHC,  
                                   NrModules = 2, VarPercentage = 50)  
AMARETTOresults <- AMARETTO_Run(AMARETTOinit)  
AMARETTO_MD <- AMARETTO_CreateModuleData(AMARETTOinit, AMARETTOresults)
```

```
AMARETTO_CreateRegulatorPrograms  
    AMARETTO_CreateRegulatorPrograms
```

Description

```
AMARETTO_CreateRegulatorPrograms
```

Usage

```
AMARETTO_CreateRegulatorPrograms(AMARETTOinit, AMARETTOresults)
```

Arguments

```
AMARETTOinit    List output from AMARETTO_Initialize().  
AMARETTOresults  
                List output from AMARETTO_Run()
```

Value

```
result
```

Examples

```
data('ProcessedDataLIHC')
AMARETTOinit <- AMARETTO_Initialize(ProcessedData = ProcessedDataLIHC,
                                   NrModules = 2, VarPercentage = 50)
AMARETTOresults <- AMARETTO_Run(AMARETTOinit)
AMARETTO_RP <- AMARETTO_CreateRegulatorPrograms(AMARETTOinit,AMARETTOresults)
```

```
AMARETTO_Download      AMARETTO_Download
```

Description

Downloading TCGA dataset for AMARETTO analysis

Usage

```
AMARETTO_Download(CancerSite = "CHOL",
                  TargetDirectory = TargetDirectory)
```

Arguments

```
CancerSite      TCGA cancer code for data download
TargetDirectory Directory path to download data
```

Value

result

Examples

```
TargetDirectory <- file.path(getwd(),"Downloads/");dir.create(TargetDirectory)
CancerSite <- 'CHOL'
DataSetDirectories <- AMARETTO_Download(CancerSite,TargetDirectory = TargetDirectory)
```

```
AMARETTO_EvaluateTestSet
      AMARETTO_EvaluateTestSet
```

Description

Code to evaluate AMARETTO on a new gene expression test set. Uses output from AMARETTO_Run() and CreateRegulatorData().

Usage

```
AMARETTO_EvaluateTestSet(AMARETTOresults = AMARETTOresults,
  MA_Data_TestSet = MA_Data_TestSet,
  RegulatorData_TestSet = RegulatorData_TestSet)
```

Arguments

AMARETTOresults
AMARETTO output from AMARETTO_Run().

MA_Data_TestSet
Gene expression matrix from a test set (that was not used in AMARETTO_Run()).

RegulatorData_TestSet
Test regulator data from CreateRegulatorData().

Value

result

Examples

```
data('ProcessedDataLIHC')
AMARETTOinit <- AMARETTO_Initialize(ProcessedData = ProcessedDataLIHC,
  NrModules = 2, VarPercentage = 50)

AMARETTOresults <- AMARETTO_Run(AMARETTOinit)
AMARETTOtestReport <- AMARETTO_EvaluateTestSet(AMARETTOresults = AMARETTOresults,
  MA_Data_TestSet = AMARETTOinit$MA_matrix_Var,
  RegulatorData_TestSet = AMARETTOinit$RegulatorData)
```

AMARETTO_ExportResults
AMARETTO_ExportResults

Description

Retrieve a download of all the data linked with the run (including heatmaps)

Usage

```
AMARETTO_ExportResults(AMARETTOinit, AMARETTOresults, data_address,
  Heatmaps = TRUE, CNV_matrix = NULL, MET_matrix = NULL)
```

Arguments

AMARETTOinit AMARETTO initialize output
 AMARETTOresults AMARETTO results output
 data_address Directory to save data folder
 Heatmaps Output heatmaps as pdf
 CNV_matrix CNV_matrix
 MET_matrix MET_matrix

Value

result

Examples

```
data('ProcessedDataLIHC')
TargetDirectory <- file.path(getwd(),"Downloads/");dir.create(TargetDirectory)
AMARETTOinit <- AMARETTO_Initialize(ProcessedData = ProcessedDataLIHC,
                                   NrModules = 2, VarPercentage = 50)

AMARETTOresults <- AMARETTO_Run(AMARETTOinit)
AMARETTO_ExportResults(AMARETTOinit,AMARETTOresults,TargetDirectory,Heatmaps = FALSE)
```

AMARETTO_HTMLreport *AMARETTO_HTMLreport*

Description

Retrieve an interactive html report, including gene set enrichment analysis if asked for.

Usage

```
AMARETTO_HTMLreport(AMARETTOinit, AMARETTOresults, ProcessedData,
  show_row_names = FALSE, SAMPLE_annotation = NULL, ID = NULL,
  hyper_geo_test_bool = FALSE, hyper_geo_reference = NULL,
  output_address = "./", MSIGDB = TRUE, driverGSEA = TRUE,
  phenotype_association_table = NULL)
```

Arguments

AMARETTOinit AMARETTO initialize output
 AMARETTOresults AMARETTO results output
 ProcessedData List of processed input data
 show_row_names if True, sample names will appear in the heatmap

SAMPLE_annotation	SAMPLE annotation will be added to heatmap
ID	ID column of the SAMPLE annotation data frame
hyper_geo_test_bool	Boolean if a hyper geometric test needs to be performed. If TRUE provide a GMT file in the hyper_geo_reference parameter.
hyper_geo_reference	GMT file with gene sets to compare with.
output_address	Output directory for the html files.
MSIGDB	TRUE if gene sets were retrieved from MSIGDB. Links will be created in the report.
driverGSEA	if TRUE, module drivers will also be included in the hypergeometric test.
phenotype_association_table	a Data Frame, containing all modules phenotype association data. Optional.

Value

result

Examples

```
## Not run:
data('ProcessedDataLIHC')
AMARETTOinit <- AMARETTO_Initialize(ProcessedData = ProcessedDataLIHC,
                                   NrModules = 2, VarPercentage = 50)

AMARETTOresults <- AMARETTO_Run(AMARETTOinit)

AMARETTO_HTMLreport(AMARETTOinit= AMARETTOinit,AMARETTOresults= AMARETTOresults,
                    ProcessedData = ProcessedDataLIHC,
                    hyper_geo_test_bool=FALSE,
                    output_address='./')

## End(Not run)
```

AMARETTO_Initialize *AMARETTO_Initialize (version: reorder and filter MA_Matrix)*

Description

Code used to initialize the seed clusters for an AMARETTO run. Requires processed gene expressions (rna-seq or microarray), CNV (usually from a GISTIC run), and methylation (from MethylMix, provided in this package) data. Uses the function CreateRegulatorData() and results are fed into the function AMARETTO_Run().

Usage

```
AMARETTO_Initialize(ProcessedData = ProcessedData, Driver_list = NULL,
  NrModules, VarPercentage, PvalueThreshold = 0.001,
  RsquareThreshold = 0.1, pmax = 10, NrCores = 1, OneRunStop = 0,
  method = "union", random_seeds = NULL, convergence_cutoff = 0.01)
```

Arguments

ProcessedData	List of Expression, CNV and MethylMix data matrices, with genes in rows and samples in columns.
Driver_list	Custom list of driver genes to be considered in analysis
NrModules	How many gene co-expression modules should AMARETTO search for? Usually around 100 is acceptable, given the large number of possible driver-passenger gene combinations.
VarPercentage	Minimum percentage by variance for filtering of genes; for example, 75% would indicate that the CreateRegulatorData() function only analyses genes that have a variance above the 75th percentile across all samples.
PvalueThreshold	Threshold used to find relevant driver genes with CNV alterations: maximal p-value.
RsquareThreshold	Threshold used to find relevant driver genes with CNV alterations: minimal R-square value between CNV and gene expression data.
pmax	'pmax' variable for glmnet function from glmnet package; the maximum number of variables aver to be nonzero. Should not be changed by user unless she/he fully understands the AMARETTO algorithm and how its parameters choices affect model output.
NrCores	A numeric variable indicating the number of computer/server cores to use for parallelization. Default is 1, i.e. no parallelization. Please check your computer or server's computing capacities before increasing this number. Parallelization is done via the RParallel package. Mac vs. Windows environments may behave differently when using parallelization.
OneRunStop	OneRunStop
method	Perform union or intersection of the driver genes evaluated from the input data matrices and custom driver gene list provided.
random_seeds	A numeric vector of length 2, containing two seed numbers for randomization : 1st for kmeans and 2nd for glmnet
convergence_cutoff	A numeric value (E.g. 0.01) representing the fraction of the total number of genes, in which, The algorithm is considered reaching convergence and will stop, if Nr of Gene-replacements in an iteration falls below this threshold * total number of genes.

Value

result

Examples

```
data('ProcessedDataLIHC')
data('Driver_Genes')
AMARETTOinit <- AMARETTO_Initialize(ProcessedData = ProcessedDataLIHC,
                                   NrModules = 2, VarPercentage = 50)

## Not run:
AMARETTOinit <- AMARETTO_Initialize(ProcessedData = ProcessedDataLIHC,
                                   Driver_list = Driver_Genes[['MSigDB']],
                                   NrModules = 2, VarPercentage = 50)

## End(Not run)
```

AMARETTO_Preprocess *AMARETTO_Preprocess*

Description

Wrapper code that analyzes process TCGA GISTIC (CNV) and gene expression (rna-seq or microarray) data via one call

Usage

```
AMARETTO_Preprocess(DataSetDirectories = DataSetDirectories,
                    BatchData = BatchData)
```

Arguments

DataSetDirectories	DataSetDirectories
BatchData	BatchData

Value

result

Examples

```
## Not run:
TargetDirectory <- "Downloads" # path to data download directory
CancerSite <- 'CHOL'
DataSetDirectories <- AMARETTO_Download(CancerSite,TargetDirectory)
ProcessedData <- AMARETTO_Preprocess(DataSetDirectories,BatchData)

## End(Not run)
```


Arguments

AMARETTOinit List output from AMARETTO_Initialize().
 AMARETTOresults List output from AMARETTO_Run().
 ProcessedData List of processed input data
 ModuleNr Module number to visualize
 show_row_names If TRUE, row names will be shown on the plot.
 SAMPLE_annotation Matrix or Dataframe with sample annotation
 ID Column used as sample name
 order_samples Order samples in heatmap by mean or by clustering

Value

result

Examples

```

data('ProcessedDataLIHC')
AMARETTOinit <- AMARETTO_Initialize(ProcessedData = ProcessedDataLIHC,
                                   NrModules = 2, VarPercentage = 50)

AMARETTOresults <- AMARETTO_Run(AMARETTOinit)

AMARETTO_VisualizeModule(AMARETTOinit = AMARETTOinit, AMARETTOresults = AMARETTOresults,
                         ProcessedData = ProcessedDataLIHC, ModuleNr = 1)

```

BatchData

BatchData

Description

A dataset for conducting batch corection in TCGA samples

Usage

BatchData

Format

A data frame with 23263 observations and 3 variables:

Source

AMARETTO

Driver_Genes

Driver_Genes

Description

A list of cancer driver genes described in literature.

Usage

Driver_Genes

Format

List

Source

AMARETTO

MsigdbMapping

MsigdbMapping

Description

A dataset containing all MSIGDB pathways and their descriptions. .

Usage

MsigdbMapping

Format

List

Source

AMARETTO

plot_run_history	<i>Title plot_run_history</i>
------------------	-------------------------------

Description

Title plot_run_history

Usage

```
plot_run_history(AMARETTOinit, AMARETTOresults)
```

Arguments

```
AMARETTOinit  AMARETTO initialize output  
AMARETTOresults  
              AMARETTO results output
```

Value

plot

Examples

```
data('ProcessedDataLIHC')  
AMARETTOinit <- AMARETTO_Initialize(ProcessedData = ProcessedDataLIHC,  
                                   NrModules = 2, VarPercentage = 50)  
  
AMARETTOresults <- AMARETTO_Run(AMARETTOinit)  
  
plot_run_history(AMARETTOinit,AMARETTOresults)
```

ProcessedDataLIHC	<i>ProcessedDataLIHC</i>
-------------------	--------------------------

Description

A list of dataframes of processed toy example dataset from TCGA-LIHC.

Usage

```
ProcessedDataLIHC
```

Format

List

Source

AMARETTO

read_gct	<i>read_gct</i>
----------	-----------------

Description

Function to turn a .gct data files into a matrix format

Usage

```
read_gct(file_address)
```

Arguments

file_address Address of the input gct file.

Value

result

Examples

```
data_matrix<-read_gct(file_address="")
```

Index

* datasets

- BatchData, [11](#)
- Driver_Genes, [12](#)
- MsigdbMapping, [12](#)
- ProcessedDataLIHC, [13](#)

- AMARETTO_CreateModuleData, [2](#)
- AMARETTO_CreateRegulatorPrograms, [3](#)
- AMARETTO_Download, [4](#)
- AMARETTO_EvaluateTestSet, [4](#)
- AMARETTO_ExportResults, [5](#)
- AMARETTO_HTMLreport, [6](#)
- AMARETTO_Initialize, [7](#)
- AMARETTO_Preprocess, [9](#)
- AMARETTO_Run, [10](#)
- AMARETTO_VisualizeModule, [10](#)

- BatchData, [11](#)

- Driver_Genes, [12](#)

- MsigdbMapping, [12](#)

- plot_run_history, [13](#)
- ProcessedDataLIHC, [13](#)

- read_gct, [14](#)