

Package: AnVIL (via r-universe)

October 10, 2026

Title Bioconductor on the AnVIL compute environment

Version 1.25.2

Description The AnVIL is a cloud computing resource developed in part by the National Human Genome Research Institute. The AnVIL package provides programatic access to the Dockstore, Leonardo, Rawls, TDR, and Terra RESTful programming interfaces. For platform-specific user-level functionality, see either the AnVILGCP or AnVILAz package.

License Artistic-2.0

Encoding UTF-8

Depends R (>= 4.5.0), dplyr, AnVILBase

Imports stats, utils, methods, futile.logger, GCPtools, jsonlite, httr, digest, keyring, rapiclient, yaml, tibble, shiny, DT, miniUI, htmltools, BiocBaseUtils

Suggests knitr, rmarkdown, testthat, withr, readr, BiocStyle, devtools, AnVILAz, AnVILGCP, lifecycle

Collate utilities.R authenticate.R api.R AnVIL-package.R Service.R Services.R Leonardo.R Terra.R Rawls.R Dockstore.R TDR.R gadgets.R zzz.R

URL <https://github.com/Bioconductor/AnVIL>

BugReports <https://github.com/Bioconductor/AnVIL/issues>

VignetteBuilder knitr

biocViews Infrastructure

RoxygenNote 7.3.3

Roxygen list(markdown = TRUE)

Date 2026-04-24

Config/pak/sysreqs cmake make libicu-dev libsecret-1-dev libuv1-dev libssl-dev zlib1g-dev

Repository <https://bioc.r-universe.dev>

Date/Publication 2026-08-10 21:29:08 UTC

RemoteUrl <https://github.com/bioc/AnVIL>

RemoteRef HEAD
RemoteSha 7425a6c44ab228ca200128f26c19a4e618ee2747

Contents

.gadget_run	2
anvil_set_auth_json	3
avworkspace_gadget	4
Service	5
Services	6
utilities	9
Index	10

.gadget_run	<i>Functions to implement AnVIL gadget interfaces</i>
-------------	---

Description

Functions documented on this page are primarily intended for package developers wishing to implement gadgets (graphical interfaces) to navigating AnVIL-generated tables.

.gadget_run() presents the user with a tibble-navigating gadget, returning the value of DONE_FUN if a row of the tibble is selected, or NULL.

Usage

.gadget_run(title, tibble, DONE_FUN)

Arguments

- title character(1) (required) title to appear at the base of the gadget, e.g., "AnVIL Workspaces".
- tibble a tibble or data.frame to be displayed in the gadget.
- DONE_FUN a function of two arguments, tibble and row_selected. The tibble is the tibble provided as an argument to .gadget_run(). row_selected is the row selected in the gadget by the user. The function is only invoked when the user selects a valid row.

Value

.gadget_run() returns the result of DONE_FUN() if a row has been selected by the user, or NULL if no row is selected (the user presses Cancel, or Done prior to selecting any row).

Examples

```
tibble <- avworkspaces(platform = AnVILGCP::gcp())
DONE_FUN <- function(tibble, row_selected) {
  selected <- slice(tibble, row_selected)
  with(selected, paste0(namespace, "/", name))
}
.gadget_run("AnVIL Example", tibble, DONE_FUN)
```

anvil_set_auth_json	<i>Store and retrieve authentication credentials using a secure keyring</i>
---------------------	---

Description

anvil_set_auth_json() stores the content of an auth.json file in the system keyring. This is the recommended way to store credentials safely.

Usage

```
anvil_set_auth_json(service, path)
```

Arguments

service	character(1) The name of the service (e.g., "terra", "dockstore") for which the credentials are being set.
path	character(1) The path to the auth.json file.

Value

anvil_set_auth_json() returns NULL invisibly.

Examples

```
jsonlite::write_json(
  list(token = "example_token"),
  "terratcgadata-test-key.json",
)
anvil_set_auth_json(
  "terra",
  "terratcgadata-test-key.json"
)
AnVIL:::.authenticate_get_access("terra")
unlink("terratcgadata-test-key.json")
```

Description

`workspace()` allows choice of workspace for subsequent use. It is the equivalent of displaying workspaces with `avworkspaces()`, and setting the selected workspace with `avworkspace()`.

`browse_workspace()` uses `browseURL()` to open a browser window pointing to the Terra workspace.

`table()` allows choice of table in the current workspace (selected by `avworkspace()` or `workspace()`) to be returned as a tibble. It is equivalent to invoking `avtables()` to show available tables, and `avtable()` to retrieve the selected table.

`workflow()` allows choice of workflow for retrieval. It is the equivalent of `avworkflows()` for listing available workflows, and `avworkflow_configuration_get()` for retrieving the workflow.

Usage

```
avworkspace_gadget()
```

```
browse_workspace(use_avworkspace = TRUE)
```

```
avtable_gadget()
```

```
avworkflow_gadget()
```

Arguments

`use_avworkspace`

logical(1) when TRUE (default), use the selected workspace (via `workspace()` or `avworkspace()` if available. If FALSE or no workspace is currently selected, use `workspace()` to allow the user to select the workspace.

Value

`workspace()` returns the selected workspace as a character(1) using the format namespace/name, or character(0) if no workspace is selected.

`browse_workspace()` returns the status of a `system()` call to launch the browser, invisibly. The default app URL prefix (<https://app.terra.bio>) can be changed with the `AnVIL.terra_app_url` option.

`table()` returns a tibble representing the selected AnVIL table.

`workflow()` returns an `avworkflow_configuration` object representing the inputs and outputs of the selected workflow. This can be edited and updated as described in the "Running an AnVIL workflow within R" vignette.

Examples

```
workspace()
browse_workspace(use_avworkspace = FALSE)
tbl <- table()
wkflw <- avworkflow_gadget()
```

Service	<i>RESTful service constructor</i>
---------	------------------------------------

Description

RESTful service constructor

Usage

```
Service(
  service,
  host,
  config = httr::config(),
  authenticate = TRUE,
  api_url = character(),
  package = "AnVIL",
  schemes = "https",
  api_reference_url = api_url,
  api_reference_md5sum = character(),
  api_reference_version = character(),
  api_reference_headers = NULL,
  ...
)
```

Arguments

service	character(1) The Service class name, e.g., "terra".
host	character(1) host name that provides the API resource, e.g., "leonardo.dsde-prod.broadinstitute".
config	httr::config() curl options
authenticate	logical(1) use credentials from authentication service? See ?anvil_set_auth_json for the recommended way to securely store credentials.
api_url	optional character(1) url location of OpenAPI .json or .yaml service definition.
package	character(1) (default AnVIL) The package where 'api.json' yaml is located.
schemes	character(1) (default 'https') Specifies the transfer protocol supported by the API service.
api_reference_url	character(1) path to reference API. See Details.

```

api_reference_md5sum
    character(1) the result of tools::md5sum() applied to the reference API.
api_reference_version
    character(1) the version of the reference API. This is used to check that the
    version of the service matches the version of the reference API. It is usually set
    by the service generation function,. e.g., AnVIL::Rawls().
api_reference_headers
    character() header(s) to be used (e.g., c(Authorization = paste("Bearer",
    token))) when retrieving the API reference for validation.
...
    additional arguments passed to rapiclient::get_api()

```

Details

This function creates a RESTful interface to a service provided by a host, e.g., "leonardo.dsde-prod.broadinstitute.org". The function requires an OpenAPI .json or .yaml specification. The specification file is located in the source directory of a package, at <package>/inst/service/<service>/api.json, or at api_url.

Authentication credentials can be stored securely in the system keyring using `anvil\_set\_auth\_json()`.

When provided, the api_reference_md5sum is used to check that the file described at api_reference_url has the same checksum as an author-validated version.

The service is usually a singleton, created at the package level during .onLoad().

Value

An object of class Service.

Examples

```

.MyService <- setClass("MyService", contains = "Service")

MyService <- function() {
  .MyService(Service("my_service", host="my.api.org"))
}

```

Services

RESTful services useful for AnVIL developers

Description

RESTful services useful for AnVIL developers

Usage

```

empty_object

operations(x, ..., .deprecated = FALSE)

## S4 method for signature 'Service'
operations(x, ..., auto_unbox = FALSE, .deprecated = FALSE)

schemas(x)

tags(x, .tags, .deprecated = FALSE)

## S4 method for signature 'Service'
x$name

Leonardo()

Terra()

Rawls()

Dockstore()

TDR()

```

Arguments

<code>x</code>	A Service instance, usually a singleton provided by the package and documented on this page, e.g., <code>leonardo</code> or <code>terra</code> .
<code>...</code>	additional arguments passed to methods or, for operations, Service-method, to the internal <code>get_operation()</code> function.
<code>.deprecated</code>	optional logical(1) include deprecated operations?
<code>auto_unbox</code>	logical(1) If FALSE (default) do not automatically 'unbox' R scalar values from JSON arrays to JSON scalars.
<code>.tags</code>	optional character() of tags to use to filter operations.
<code>name</code>	A symbol representing a defined operation, e.g., <code>leonardo\$listRuntimes()</code> .

Format

An object of class `list` of length 0.

Details

Note the services `Terra()`, `Rawls()`, and `Leonardo()` require the `GCPtools` package for authentication to the Google Cloud Platform. See `?GCPtools::gcloud_access_token()` for details.

When using `$` to select a service, some arguments appear in 'body' of the REST request. Specify these using the `.__body__=` argument, as illustrated for `createBillingProjectFull()`, below.

Value

`empty_object` returns a representation to be used as arguments in function calls expecting the empty json object `{}`.

`Leonardo()` creates the API of the Leonardo container deployment service at <https://leonardo.dsde-prod.broadinstitute.org/api-docs.yaml>. The default API url value can be changed with the `AnVIL.leonardo_api_url` option.

`Terra()` creates the API of the Terra cloud computational environment at <https://api.firecloud.org/>. The default API url value can be changed with the `AnVIL.firecloud_api_url` option.

`Rawls()` creates the API of the Rawls cloud computational environment at <https://rawls.dsde-prod.broadinstitute.org>. The default API url value can be changed with the `AnVIL.rawls_api_url` option.

`Dockstore()` represents the API of the Dockstore platform to share Docker-based tools in CWL or WDL or Nextflow at <https://dockstore.org>. The default API url value can be changed with the `AnVIL.dockstore_api_url` option.

`TDR()` creates the API of the Terra Data Repository to work with snapshot data in the Terra Data Repository at <https://data.terra.bio>. The default API url value can be changed with the `AnVIL.tdr_api_url` option.

Examples

`empty_object`

```
## Arguments to be used as the 'body' (``__body__``) of a REST query
Terra()$createBillingProjectFull      # 6 arguments...
## ... passed as ``__body__ = list(...)``
args(Terra()$createBillingProjectFull)
```

```
library(GCPTools)
if (gcloud_exists())
  Leonardo()
```

```
library(GCPTools)
if (gcloud_exists()) {
  tags(Terra())
  tags(Terra(), "Billing")
}
```

```
library(GCPTools)
if (gcloud_exists()) {
  tags(Rawls())
  tags(Rawls(), "billing")
}
```

```
Dockstore()
```

```
library(GCPTools)
if (gcloud_exists())
  TDR()
```

utilities*Utilities for managing library paths*

Description

`add_libpaths()`: Add local library paths to `.libPaths()`.

Usage

```
add_libpaths(paths)
```

Arguments

<code>paths</code>	<code>character()</code> : vector of directories to add to <code>.libPaths()</code> . Paths that do not exist will be created.
--------------------	--

Value

`add_libpaths()`: updated `.libPaths()`, invisibly.

Examples

```
add_libpaths("/tmp/host-site-library")
```

Index

- * **datasets**
 - Services, [6](#)
 - .DollarNames.Service (Services), [6](#)
 - .gadget_run, [2](#)
 - \$, Service-method (Services), [6](#)
 - add_libpaths (utilities), [9](#)
 - anvil_set_auth_json, [3](#)
 - avtable_gadget (avworkspace_gadget), [4](#)
 - avworkflow_gadget (avworkspace_gadget), [4](#)
 - avworkspace_gadget, [4](#)
 - browse_workspace (avworkspace_gadget), [4](#)
 - Dockstore (Services), [6](#)
 - Dockstore-class (Services), [6](#)
 - empty_object (Services), [6](#)
 - Leonardo (Services), [6](#)
 - Leonardo-class (Services), [6](#)
 - operations (Services), [6](#)
 - operations, Dockstore-method (Services), [6](#)
 - operations, Leonardo-method (Services), [6](#)
 - operations, Rawls-method (Services), [6](#)
 - operations, Service-method (Services), [6](#)
 - operations, TDR-method (Services), [6](#)
 - operations, Terra-method (Services), [6](#)
 - Rawls (Services), [6](#)
 - Rawls-class (Services), [6](#)
 - schemas (Services), [6](#)
 - schemas, Rawls-method (Services), [6](#)
 - schemas, Service-method (Services), [6](#)
 - schemas, Terra-method (Services), [6](#)
 - Service, [5](#)
 - Service-class (Services), [6](#)
 - Services, [6](#)
 - show, Service-method (Services), [6](#)
 - tags (Services), [6](#)
 - TDR (Services), [6](#)
 - TDR-class (Services), [6](#)
 - Terra (Services), [6](#)
 - Terra-class (Services), [6](#)
 - utilities, [9](#)