

# Package: DELocal (via r-universe)

October 1, 2026

**Title** Identifies differentially expressed genes with respect to other local genes

**Version** 1.13.0

**Description** The goal of DELocal is to identify DE genes compared to their neighboring genes from the same chromosomal location. It has been shown that genes of related functions are generally very far from each other in the chromosome. DELocal utilizes this information to identify DE genes comparing with their neighbouring genes.

**License** MIT + file LICENSE

**URL** <https://github.com/dasroy/DELocal>

**BugReports** <https://github.com/dasroy/DELocal/issues>

**Encoding** UTF-8

**LazyData** false

**RoxygenNote** 7.2.3

**biocViews** GeneExpression, DifferentialExpression, RNASeq, Transcriptomics

**Imports** DESeq2, dplyr, reshape2, limma, SummarizedExperiment, ggplot2, matrixStats, stats

**Suggests** biomaRt, knitr, rmarkdown, stringr, BiocStyle

**VignetteBuilder** knitr

**Config/pak/sysreqs** libicu-dev zlib1g-dev

**Repository** <https://bioc.r-universe.dev>

**Date/Publication** 2026-04-28 13:00:32 UTC

**RemoteUrl** <https://github.com/bioc/DELocal>

**RemoteRef** HEAD

**RemoteSha** 0616957671987b9f5e4bdbbe9c680dcd44d681a1

Contents

|                             |          |
|-----------------------------|----------|
| DELocal . . . . .           | 2        |
| plotNeighbourhood . . . . . | 3        |
| <b>Index</b>                | <b>5</b> |

---

|         |                                                                            |
|---------|----------------------------------------------------------------------------|
| DELocal | <i>Finds differentially expressed genes by comparing neighboring genes</i> |
|---------|----------------------------------------------------------------------------|

---

Description

Finds differentially expressed genes by comparing neighboring genes

Usage

```
DELocal(  
  pSmrExpt,  
  nearest_neighbours,  
  pDesign,  
  pValue_cut = 0.05,  
  pLogFold_cut = 0  
)
```

Arguments

- pSmrExpt      SummarizedExperiment object
- nearest\_neighbours      How many nearest neighbours within 1 Mb window to evaluate?
- pDesign      design formula
- pValue\_cut      cut off value for adjusted p-value
- pLogFold\_cut      cut off value for relative log fold change compared to neighbouring genes

Value

A data.frame with top significant genes with the following columns:  
relative.logFC: relative logFC compared to neighbouring genes  
P.Value: raw p-value  
adj.P.Value: adjusted p-value  
B: log-odds that the gene is differentially expressed

**Examples**

```

count_matrix <- as.matrix(read.table(file = system.file("extdata",
                                                    "tooth_RNASeq_counts.txt",
                                                    package = "DELocal")))

colData <- data.frame(condition=gsub("\\.*",x=colnames(count_matrix),
                                replacement = ""))
gene_location <- read.table(file = system.file("extdata", "gene_location.txt",
                                package = "DELocal"))
smrExpt <- SummarizedExperiment::SummarizedExperiment(
                                assays=list(counts=count_matrix),
                                rowData = gene_location,
                                colData=colData)

contrast= c("condition","ME13","ME14")
require(dplyr)
x_genes <- SummarizedExperiment::rowData(smrExpt) %>%
  as.data.frame() %>%
  filter(chromosome_name=="X") %>% rownames()
DELocal_result <- DELocal(pSmrExpt = smrExpt[x_genes,],
                          nearest_neighbours = 5, pDesign = ~ condition,
                          pValue_cut = 0.05, pLogFold_cut = 0)

```

---

|                   |                                                                                                                |
|-------------------|----------------------------------------------------------------------------------------------------------------|
| plotNeighbourhood | <i>Returns median expression from different conditions of genes from a neighbourhood of a gene of interest</i> |
|-------------------|----------------------------------------------------------------------------------------------------------------|

---

**Description**

Returns median expression from different conditions of genes from a neighbourhood of a gene of interest

**Usage**

```

plotNeighbourhood(
  pSmrExpt,
  pNearest_neighbours = 5,
  pDesign = ~condition,
  colorFactor = "condition",
  pGene_id
)

```

**Arguments**

|                     |                                                        |
|---------------------|--------------------------------------------------------|
| pSmrExpt            | SummarizedExperiment object                            |
| pNearest_neighbours | How many nearest neighbours within 1 Mb window to plot |
| pDesign             | design formula                                         |
| colorFactor         | The coloring factor                                    |
| pGene_id            | The gene of interest                                   |

**Value**

a list which contains both the data from the neighbourhood and a ggplot object

**Examples**

```
count_matrix <- as.matrix(read.table(file = system.file("extdata",
                                                         "tooth_RNASeq_counts.txt",
                                                         package = "DELocal")))
colData <- data.frame(condition=gsub("\\.\\.*",x=colnames(count_matrix),
                                                         replacement = ""))
gene_location <- read.table(file = system.file("extdata", "gene_location.txt",
                                                         package = "DELocal"))
smrExpt <- SummarizedExperiment::SummarizedExperiment(assays=list(counts=count_matrix),
                                                         rowData = gene_location,
                                                         colData = colData)

contrast= c("condition","ME13","ME14")
require(dplyr)
x_genes <- SummarizedExperiment::rowData(smrExpt) %>%
  as.data.frame() %>%
  filter(chromosome_name=="X") %>% rownames()
DELocal::plotNeighbourhood(pSmrExpt = smrExpt, pGene_id = "ENSMUSG00000059401")
```

# Index

DELocal, [2](#)

plotNeighbourhood, [3](#)