

Package: GOSemSim (via r-universe)

October 10, 2026

Type Package

Title GO-terms Semantic Similarity Measures

Version 2.39.4

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

Description Semantic similarity analysis of Gene Ontology (GO) annotations provides a quantitative framework for comparing GO terms, gene products, and gene clusters. GOSemSim implements widely used information content- and graph-based similarity measures, including the methods of Resnik, Schlicker, Jiang, Lin, Wang and TCSS. It also provides utilities for preparing annotation data and combining term-level similarities into gene- and cluster-level scores.

Depends R (>= 4.2.0)

LinkingTo Rcpp

Imports AnnotationDbi, DBI, digest, GO.db, methods, Rcpp, rlang, stats, utils, yulab.utils (>= 0.2.3)

Suggests AnnotationHub, BiocParallel, BiocManager, clusterProfiler, DOSE, gson, knitr, org.Hs.eg.db, quarto, readr, testthat, tidyselect, tidyr, tibble, ROCR

VignetteBuilder quarto

ByteCompile true

License Artistic-2.0

Encoding UTF-8

URL <https://yulab-smu.top/biomedical-knowledge-mining-book/>

BugReports <https://github.com/YuLab-SMU/GOSemSim/issues>

biocViews Annotation, GO, Clustering, Pathways, Network, Software

Roxygen list(markdown = TRUE)

Config/roxygen2/version 8.1.0

Config/pak/sysreqs cmake make libpng-dev libuv1-dev libssl-dev zlib1g-dev

Repository <https://bioc.r-universe.dev>

Date/Publication 2026-10-09 13:23:38 UTC
RemoteUrl https://github.com/bioc/GOSemSim
RemoteRef HEAD
RemoteSha c7dfc140a7fb290093f8d074d6e47a28274557a6

Contents

buildGOMap	2
clusterSim	3
combineScores	4
geneSim	4
get_organism	5
go_term_table	6
godata	6
GOSemSimDATA-class	7
goSim	7
infoContentMethod	8
mclusterSim	9
mgeneSim	10
mgoSim	11
read.blast2go	12
read.gaf	12
set_auto_update	13
tcss_cutoff	13
termSim	15
wangMethod_internal	16
Index	17

buildGOMap	<i>buildGOMap</i>
------------	-------------------

Description

Adding indirect GO annotation

Usage

buildGOMap(TERM2GENE)

Arguments

TERM2GENE	data.frame with two or three columns of GO TERM, GENE and ONTOLOGY (optional)
-----------	---

Details

provided by a data.frame of GO TERM (column 1), GENE (column 2) and ONTOLOGY (optional) that describes GO direct annotation, this function will add indirect GO annotation of genes.

Value

data.frame, GO annotation with direct and indirect annotation

Author(s)

Yu Guangchuang

clusterSim

Semantic similarity between two gene clusters

Description

Semantic similarity between two gene clusters

Usage

```
clusterSim(  
  cluster1,  
  cluster2,  
  semData,  
  measure = "Wang",  
  drop = "IEA",  
  combine = "BMA"  
)
```

Arguments

cluster1	A set of gene IDs
cluster2	Another set of gene IDs
semData	GOSemSimDATA object
measure	One of "Resnik", "Lin", "Rel", "Jiang", "TCSS" and "Wang" methods.
drop	Evidence codes to drop; use NULL to keep all GO annotations
combine	One of "max", "avg", "rcmax", "BMA" methods, used to combine multiple term scores.

Value

similarity

Author(s)

Guangchuang Yu <https://yulab-smu.top>

See Also

```
goSim() mgoSim() geneSim() mgeneSim() clusterSim() mclusterSim()
```

Examples

```
d <- godata('org.Hs.eg.db', ont = "MF", computeIC = FALSE)
cluster1 <- c("835", "5261", "241", "994")
cluster2 <- c("307", "308", "317", "321", "506", "540", "378", "388", "396")
clusterSim(cluster1, cluster2, semData = d, measure = "Wang")
```

combineScores	<i>combining similarity matrix to similarity score</i>
---------------	--

Description

Functions for combining similarity matrix to similarity score

Usage

```
combineScores(SimScores, combine)
```

Arguments

SimScores	similarity matrix
combine	combine method

Value

similarity value

Author(s)

Guangchuang Yu <https://yulab-smu.top>

geneSim	<i>Semantic similarity between two genes</i>
---------	--

Description

Given two genes, calculate their semantic similarity and return the score with corresponding GO terms.

Usage

```
geneSim(gene1, gene2, semData, measure = "Wang", drop = "IEA", combine = "BMA")
```

Arguments

gene1	Entrez gene ID
gene2	Another Entrez gene ID
semData	GOSemSimDATA object
measure	One of "Resnik", "Lin", "Rel", "Jiang", "TCSS" and "Wang" methods.
drop	Evidence codes to drop; use NULL to keep all GO annotations
combine	One of "max", "avg", "rcmax", "BMA" methods, used to combine multiple term scores.

Value

A list containing similarity value and corresponding GO terms

Author(s)

Guangchuang Yu <https://yulab-smu.top>

See Also

[goSim\(\)](#) [mgoSim\(\)](#) [mgeneSim\(\)](#) [clusterSim\(\)](#) [mclusterSim\(\)](#)

Examples

```
d <- godata('org.Hs.eg.db', ont = "MF", computeIC = FALSE)
geneSim("241", "251", semData = d, measure = "Wang")
```

get_organism	<i>Get organism name from OrgDb object</i>
--------------	--

Description

Get organism name from OrgDb object

Usage

```
get_organism(object)
```

Arguments

object	OrgDb object or OrgDb package name
--------	------------------------------------

Value

Organism name

Author(s)

Guangchuang Yu

go_term_table	Information content of GO terms
---------------	---------------------------------

Description

These datasets are the information contents of GOterms.

References

Yu et al. (2010) GOSemSim: an R package for measuring semantic similarity among GO terms and gene products *Bioinformatics* (Oxford, England), 26:7 976–978, April 2010. ISSN 1367-4803 <http://bioinformatics.oxfordjournals.org/cgi/content/abstract/26/7/976> PMID: 20179076

godata	godata
--------	--------

Description

prepare GO DATA for measuring semantic similarity

Usage

```
godata(  
  OrgDb = NULL,  
  annoDb = NULL,  
  keytype = "ENTREZID",  
  ont,  
  computeIC = TRUE,  
  processTCSS = FALSE,  
  cutoff = NULL  
)
```

Arguments

OrgDb	OrgDb object (will be removed in future, please use annoDb instead)
annoDb	GO annotation database, can be OrgDb, a 'GSON' object of GO annotations (e.g. the output of <code>clusterProfiler::gson_GO()</code>) or a data.frame contains three columns of 'GENE', 'GO' and 'ONTOLOGY'.
keytype	keytype
ont	one of 'BP', 'MF', 'CC'
computeIC	logical, whether computer IC
processTCSS	logical, whether to prepare TCSS data. TCSS requires computeIC = TRUE, which is enabled automatically when processTCSS = TRUE.
cutoff	topology cutoff for TCSS subgraph construction. If NULL, empirical defaults are used; users can estimate a cutoff with <code>tcss_cutoff()</code> .

Value

GOSemSimDATA object

Author(s)

Guangchuang Yu

GOSemSimDATA-class	<i>Class "GOSemSimDATA" This class stores IC and gene to go mapping for semantic similarity measurement</i>
--------------------	---

Description

Class "GOSemSimDATA" This class stores IC and gene to go mapping for semantic similarity measurement

Slots

keys gene ID
ont ontology
IC IC data
geneAnno gene to GO mapping
tcssdata tcssdata
metadata metadata

goSim	<i>Semantic similarity between two GO terms</i>
-------	---

Description

Given two GO IDs, calculate their semantic similarity.

Usage

```
goSim(GO1, GO2, semData, measure = "Wang")
```

Arguments

GO1	GO ID 1
GO2	GO ID 2
semData	GOSemSimDATA object
measure	One of "Resnik", "Lin", "Rel", "Jiang", "TCSS" and "Wang" methods.

Value

similarity

Author(s)

Guangchuang Yu <https://yulab-smu.top>

See Also

[goSim\(\)](#) [mgoSim\(\)](#) [geneSim\(\)](#) [mgeneSim\(\)](#) [clusterSim\(\)](#) [mclusterSim\(\)](#)

Examples

```
d <- godata('org.Hs.eg.db', ont = "MF", computeIC = FALSE)
goSim("GO:0004022", "GO:0005515", semData = d, measure = "Wang")
```

infoContentMethod	<i>information content based methods</i>
-------------------	--

Description

Information Content Based Methods for semantic similarity measuring

Usage

```
infoContentMethod(ID1, ID2, method, godata)
```

Arguments

ID1	Ontology Term
ID2	Ontology Term
method	one of "Resnik", "Jiang", "Lin" and "Rel", "TCSS".
godata	GOSemSimDATA object

Details

implemented for methods proposed by Resnik, Jiang, Lin and Schlicker.

Value

semantic similarity score

Author(s)

Guangchuang Yu <https://yulab-smu.top>

mclusterSim	<i>Pairwise semantic similarities for a list of gene clusters</i>
-------------	---

Description

Calculate pairwise semantic similarities for a list of gene clusters.

Usage

```
mclusterSim(  
  clusters,  
  semData,  
  measure = "Wang",  
  drop = "IEA",  
  combine = "BMA",  
  BPPARAM = NULL  
)
```

Arguments

clusters	A list of gene clusters
semData	GOSemSimDATA object
measure	One of "Resnik", "Lin", "Rel", "Jiang", "TCSS" and "Wang" methods.
drop	Evidence codes to drop; use NULL to keep all GO annotations
combine	One of "max", "avg", "rcmax", "BMA" methods, used to combine multiple term scores.
BPPARAM	optional BiocParallel::BiocParallelParam object for parallel pairwise similarity calculation. The default NULL uses serial calculation.

Value

similarity matrix

Author(s)

Guangchuang Yu <https://yulab-smu.top>

See Also

[goSim\(\)](#) [mgoSim\(\)](#) [geneSim\(\)](#) [mgeneSim\(\)](#) [clusterSim\(\)](#) [mclusterSim\(\)](#)

Examples

```
d <- godata('org.Hs.eg.db', ont = "MF", computeIC = FALSE)
cluster1 <- c("835", "5261", "241")
cluster2 <- c("578", "582")
cluster3 <- c("307", "308", "317")
clusters <- list(a = cluster1, b = cluster2, c = cluster3)
mclusterSim(clusters, semData = d, measure = "Wang")
```

mgeneSim

Pairwise semantic similarity for a list of genes

Description

Calculate pairwise semantic similarities for a given list of genes.

Usage

```
mgeneSim(
  genes,
  semData,
  measure = "Wang",
  drop = "IEA",
  combine = "BMA",
  verbose = TRUE,
  BPPARAM = NULL
)
```

Arguments

genes	A list of Entrez gene IDs
semData	GOSemSimDATA object
measure	One of "Resnik", "Lin", "Rel", "Jiang", "TCSS" and "Wang" methods.
drop	Evidence codes to drop; use NULL to keep all GO annotations
combine	One of "max", "avg", "rcmax", "BMA" methods, used to combine multiple term scores.
verbose	Whether to show a progress bar
BPPARAM	optional BiocParallel::BiocParallelParam object for parallel pairwise similarity calculation. The default NULL uses the original serial implementation.

Details

Parallel calculation is opt-in. With the default BPPARAM = NULL, mgeneSim() keeps the original serial behavior and can show a progress bar when verbose = TRUE. When a BPPARAM object is supplied, pairwise similarities are calculated through [BiocParallel::bplapply\(\)](#) and the progress bar is not shown.

Value

similarity matrix

Author(s)

Guangchuang Yu <https://yulab-smu.top>

See Also

[goSim\(\)](#) [mgoSim\(\)](#) [geneSim\(\)](#) [mgeneSim\(\)](#) [clusterSim\(\)](#) [mclusterSim\(\)](#)

Examples

```
d <- godata('org.Hs.eg.db', ont = "MF", computeIC = FALSE)
mgeneSim(c("835", "5261", "241"), semData = d, measure = "Wang")
```

mgoSim	<i>Semantic similarity between two GO term sets</i>
--------	---

Description

Given two sets of GO terms, calculate their semantic similarity.

Usage

```
mgoSim(GO1, GO2, semData, measure = "Wang", combine = "BMA")
```

Arguments

GO1	A set of GO terms
GO2	Another set of GO terms
semData	GOSemSimDATA object
measure	One of "Resnik", "Lin", "Rel", "Jiang", "TCSS" and "Wang" methods.
combine	One of "max", "avg", "rcmax", "BMA" methods, used to combine multiple term scores.

Value

similarity

Author(s)

Guangchuang Yu <https://yulab-smu.top>

See Also

[goSim\(\)](#) [mgoSim\(\)](#) [geneSim\(\)](#) [mgeneSim\(\)](#) [clusterSim\(\)](#) [mclusterSim\(\)](#)

Examples

```
d <- godata('org.Hs.eg.db', ont = "MF", computeIC = FALSE)
go1 <- c("GO:0004022", "GO:0004024", "GO:0004023")
go2 <- c("GO:0009055", "GO:0020037")
mgoSim("GO:0003824", go2, semData = d, measure = "Wang")
mgoSim(go1, go2, semData = d, measure = "Wang")
```

read.blast2go

read.blast2go

Description

given a BLAST2GO file, this function extracts the information from it and make it use for TERM2GENE.

Usage

```
read.blast2go(file, add_indirect_GO = FALSE)
```

Arguments

file	BLAST2GO file
add_indirect_GO	whether add indirect GO annotation

Value

a data frame with three columns: GENE, GO and ONTOLOGY

read.gaf

read.gaf

Description

parse GAF files

Usage

```
read.gaf(file, asis = FALSE, add_indirect_GO = FALSE)

parse_gff(file, asis = FALSE, add_indirect_GO = FALSE)
```

Arguments

file	GAF file
asis	logical, whether output the original contains of the file and only works if 'add_indirect_GO = FALSE'
add_indirect_GO	whether to add indirect GO annotation

Details

given a GAF file, this function extracts the information from it

Value

A data.frame. Original table if 'asis' works, otherwise contains 3 columns of 'GENE', 'GO' and 'ONTOLOGY'

set_auto_update	<i>Control auto-update of ontology databases</i>
-----------------	--

Description

When enabled, outdated local ontology SQLite databases will be automatically updated from remote mirrors.

Usage

```
set_auto_update(x = TRUE)
```

Arguments

x	logical, whether to enable auto-update (default: TRUE)
---	--

tcss_cutoff	<i>determine the topological cutoff for TCSS method</i>
-------------	---

Description

determine the topological cutoff for TCSS method

Usage

```
tcss_cutoff(
  OrgDb = NULL,
  keytype = "ENTREZID",
  ont,
  combine_method = "max",
  ppidata
)
```

Arguments

OrgDb	OrgDb object
keytype	keytype
ont	ontology: "BP", "MF", "CC"
combine_method	one of "max", "BMA", "avg", "rcmax", "rcmax.avg"
ppidata	A data.frame contains positive set and negative set. Positive set is PPI pairs that already verified. ppidata has three columns, column 1 and 2 are character, column 3 must be logical value:TRUE/FALSE.

Value

numeric, topological cutoff for TCSS subgraph construction. The returned value can be passed to [godata\(\)](#) via the cutoff argument together with processTCSS = TRUE.

Examples

```
## Not run:
library(org.Hs.eg.db)
library(STRINGdb)

string_db <- STRINGdb$new(version = "11.0", species = 9606,
  score_threshold = 700)
string_proteins <- string_db$get_proteins()

#get relationship
ppi <- string_db$get_interactions(string_proteins$protein_external_id)

ppi$from <- vapply(ppi$from, function(e)
  strsplit(e, "9606.")[[1]][2], character(1))
ppi$to <- vapply(ppi$to, function(e)
  strsplit(e, "9606.")[[1]][2], character(1))
len <- nrow(ppi)

#select length
s_len <- 100
pos_1 <- sample(len, s_len, replace = T)
#negative set
pos_2 <- sample(len, s_len, replace = T)
pos_3 <- sample(len, s_len, replace = T)
#union as ppidata
ppidata <- data.frame(pro1 = c(ppi$from[pos_1], ppi$from[pos_2]),
  pro2 = c(ppi$to[pos_1], ppi$to[pos_3]),
  label = c(rep(TRUE, s_len), rep(FALSE, s_len)),
  stringsAsFactors = FALSE)

cutoff <- tcss_cutoff(OrgDb = org.Hs.eg.db, keytype = "ENSEMBLPROT",
  ont = "BP", combine_method = "max", ppidata)

semData <- godata(annoDb = org.Hs.eg.db, keytype = "ENSEMBLPROT",
  ont = "BP", computeIC = TRUE, processTCSS = TRUE, cutoff = cutoff)
```

```
## End(Not run)
```

termSim	<i>termSim</i>
---------	----------------

Description

Measure similarities between two term vectors.

Usage

```
termSim(  
  t1,  
  t2,  
  semData,  
  method = c("Wang", "Resnik", "Rel", "Jiang", "Lin", "TCSS")  
)
```

Arguments

t1	Term vector
t2	Term vector
semData	GOSemSimDATA object
method	One of "Wang", "Resnik", "Rel", "Jiang", "Lin", "TCSS"

Details

Provide two term vectors, this function calculates their similarities.

The TCSS method requires semData generated by `godata()` with `computeIC = TRUE` and `processTCSS = TRUE`.

Value

score matrix

Author(s)

Guangchuang Yu <https://yulab-smu.top>

wangMethod_internal	<i>wangMethod</i>
---------------------	-------------------

Description

Method Wang for semantic similarity measuring

Usage

```
wangMethod_internal(ID1, ID2, ont = "BP")
```

Arguments

ID1	Ontology Term
ID2	Ontology Term
ont	Ontology

Value

semantic similarity score

Author(s)

Guangchuang Yu <https://yulab-smu.top>

Index

- * **classes**
 - GOSemSimDATA-class, [7](#)
- * **datasets**
 - go_term_table, [6](#)
- BiocParallel::BiocParallelParam, [9](#), [10](#)
- BiocParallel::bplapply(), [10](#)
- buildGOMap, [2](#)
- clusterSim, [3](#)
- clusterSim(), [4](#), [5](#), [8](#), [9](#), [11](#)
- combineScores, [4](#)
- geneSim, [4](#)
- geneSim(), [4](#), [8](#), [9](#), [11](#)
- get_organism, [5](#)
- GO (go_term_table), [6](#)
- go_term_table, [6](#)
- godata, [6](#)
- godata(), [14](#), [15](#)
- GOSemSimDATA-class, [7](#)
- goSim, [7](#)
- goSim(), [4](#), [5](#), [8](#), [9](#), [11](#)
- gotbl (go_term_table), [6](#)
- infoContentMethod, [8](#)
- mclusterSim, [9](#)
- mclusterSim(), [4](#), [5](#), [8](#), [9](#), [11](#)
- mgeneSim, [10](#)
- mgeneSim(), [4](#), [5](#), [8](#), [9](#), [11](#)
- mgoSim, [11](#)
- mgoSim(), [4](#), [5](#), [8](#), [9](#), [11](#)
- parse_gff (read.gaf), [12](#)
- read.blast2go, [12](#)
- read.gaf, [12](#)
- set_auto_update, [13](#)
- show, GOSemSimDATA-method
(GOSemSimDATA-class), [7](#)
- tcss_cutoff, [13](#)
- tcss_cutoff(), [6](#)
- termSim, [15](#)
- wangMethod_internal, [16](#)