Package: HiCParser (via r-universe)

October 9, 2026

Type Package

Title Parser for HiC data in R

Date 2025-07-22

Version 1.5.1

URL https://github.com/emaigne/HiCParser

BugReports https://github.com/emaigne/HiCParser/issues

Description This package is a parser to import HiC data into R. It accepts several type of data: tabular files, Cooler `.cool` or `.mcool` files, Juicer `.hic` files or HiC-Pro `.matrix` and `.bed` files. The HiC data can be several files, for several replicates and conditions. The data is formated in an InteractionSet object.

License LGPL

Encoding UTF-8

Roxygen list(markdown = TRUE)

biocViews Software, HiC, DataImport

Imports data.table, InteractionSet, GenomicRanges, SummarizedExperiment, Rcpp (>= 1.0.12), S4Vectors, gtools, pbapply, BiocGenerics, Seqinfo

LinkingTo Rcpp

Suggests rhdf5, BiocStyle, knitr, sessioninfo, testthat (>= 3.0.0)

Config/testthat/edition 3

VignetteBuilder knitr

Config/roxygen2/version 8.0.0

Config/pak/sysreqs zlib1g-dev

Repository https://bioc.r-universe.dev

Date/Publication 2026-07-07 07:42:53 UTC

RemoteUrl https://github.com/bioc/HiCParser

RemoteRef HEAD

RemoteSha 84b40db8cc1bb5ee344492b3505b8bb84cb3ec0e

Contents

HiCParser-package 2
mergeInteractionSet 3
parseCool 3
parseHiC 5
parseHiCPro 6
parseTabular 7

Index **9**

`HiCParser-package` *A multiple format Hi-C data parser*

Description

This package is a parser to import HiC data into R. It accepts several type of data: tabular files, Cooler '.cool' or '.mcool' files, Juicer '.hic' files or HiC-Pro '.matrix' and '.bed' files. The HiC data can be several files, for several replicates and conditions. The data is formated in an InteractionSet object.

Author(s)

Maintainer: Maigné Élise <elise.maigne@inrae.fr>

Authors:

- Maigné Élise <elise.maigne@inrae.fr>
- Zytnicki Matthias <matthias.zytnicki@inrae.fr>

See Also

Useful links:

- https://github.com/emaigne/HiCParser
- Report bugs at https://github.com/emaigne/HiCParser/issues

mergeInteractionSet *Merge two InteractionSet objects*

Description

Merge two different InteractionSet.

Usage

```
mergeInteractionSet(interactionSet1, interactionSet2, fill = NA)
```

Arguments

interactionSet1	The first InteractionSet.
interactionSet2	The second InteractionSet.
fill	Fill missing values with this.

Value

The merged InteractionSet.

Examples

```
path <- system.file("extdata", "hicsample_21.cool", package = "HiCParser")
object1 <- parseCool(path, conditions = 1, replicates = 1)
# Creating an object with a different condition
object2 <- parseCool(path, conditions = 2, replicates = 1)
objectMerged <- mergeInteractionSet(object1, object2)
```

parseCool *Parser for data in cool format*

Description

Parses interactions in .cool or .mcool format and returns an InteractionSet object.

Usage

```
parseCool(paths, binSize = NA, conditions, replicates)
```

Arguments

paths	A vector of paths to .cool or .mcool files.
binSize	The resolution (span of each position in number of bases). Optionally provided to select the appropriate resolution in .mcool files. Defaults to NULL.
conditions	A vector of condition names repeated along the replicates.
replicates	A vector of replicate names repeated along the conditions.

Details

To read .cool of .mcool files, the rhdf5 package is required. Please install it before running the function.

Value

An InteractionSet.

Examples

```
# EXAMPLE FOR .cool FORMAT
# Path to each file
pathsCool <- c(
    "path/to/condition-1.replicate-1.cool",
    "path/to/condition-1.replicate-2.cool",
    "path/to/condition-1.replicate-3.cool",
    "path/to/condition-2.replicate-1.cool",
    "path/to/condition-2.replicate-2.cool",
    "path/to/condition-2.replicate-3.cool"
)
# Condition and replicate of each file. Can be names instead of numbers.
conditions <- c(1, 1, 1, 2, 2, 2)
replicates <- c(1, 2, 3, 1, 2, 3)
if (FALSE) {
    library(rhdf5)
    object <- parseCool(
        paths,
        conditions = conditions,
        replicates = replicates
    )
}

# EXAMPLE FOR .mcool FORMAT
# Resolution
binSize <- 500000
# Path to each file
paths <- c(
    "path/to/condition-1.replicate-1.mcool",
    "path/to/condition-1.replicate-2.mcool",
    "path/to/condition-1.replicate-3.mcool",
    "path/to/condition-2.replicate-1.mcool",
    "path/to/condition-2.replicate-2.mcool",
```

```
    "path/to/condition-2.replicate-3.mcool"
)
# Condition and replicate of each file. Can be names instead of numbers.
conditions <- c(1, 1, 1, 2, 2, 2)
replicates <- c(1, 2, 3, 1, 2, 3)
if (FALSE) {
    # Instantiation of data set
    library(rhdf5)
    object <- parseCool(
        paths,
        conditions = conditions,
        replicates = replicates,
        binSize = binSize
    )
}
```

`parseHiC` *Parser for data in hic format*

Description

Parses interactions in `.hic` format and returns an InteractionSet object.

Usage

```
parseHiC(paths, binSize, conditions, replicates)
```

Arguments

`paths`	A vector of paths to `.hic` files.
`binSize`	The resolution (span of each position in number of bases) to select within the `.hic` files.
`conditions`	A vector of condition names repeated along the replicates.
`replicates`	A vector of replicate names repeated along the conditions.

Value

An InteractionSet.

Examples

```
# Path to each file
paths <- c(
    "path/to/condition-1.replicate-1.hic",
    "path/to/condition-1.replicate-2.hic",
    "path/to/condition-1.replicate-3.hic",
    "path/to/condition-2.replicate-1.hic",
    "path/to/condition-2.replicate-2.hic",
```

```
    "path/to/condition-2.replicate-3.hic"
)
# Replicate and condition of each file. Can be names instead of numbers.
conditions <- c(1, 1, 1, 2, 2, 2)
replicates <- c(1, 2, 3, 1, 2, 3)
# Resolution to select
binSize <- 500000
if (FALSE) {
    # Instantiation of data set
    hic.experiment <- parseHiC(
        paths,
        conditions = conditions,
        replicates = replicates,
        binSize = binSize
    )
}
```

`parseHiCPro` *Parser for HiCPro data*

Description

Parses interactions in pairs of `.matrix` and `.bed` files and returns an InteractionSet object.

Usage

```
parseHiCPro(matrixPaths, bedPaths, conditions, replicates)
```

Arguments

`matrixPaths`	A vector of paths to HiC-Pro matrix files.
`bedPaths`	A vector of paths to HiC-Pro bed files.
`conditions`	A vector of condition names repeated along the replicates.
`replicates`	A vector of replicate names repeated along the conditions.

Value

An InteractionSet.

Examples

```
# Path to each matrix file
matrixPaths <- c(
    "path/to/condition-1.replicate-1.matrix",
    "path/to/condition-1.replicate-2.matrix",
    "path/to/condition-1.replicate-3.matrix",
    "path/to/condition-2.replicate-1.matrix",
    "path/to/condition-2.replicate-2.matrix",
    "path/to/condition-2.replicate-3.matrix"
```

```
)

# Path to each bed file
bedPaths <- c(
    "path/to/condition-1.replicate-1.bed",
    "path/to/condition-1.replicate-2.bed",
    "path/to/condition-1.replicate-3.bed",
    "path/to/condition-2.replicate-1.bed",
    "path/to/condition-2.replicate-2.bed",
    "path/to/condition-2.replicate-3.bed"
)

# Condition and replicate of each file. Can be names instead of numbers.
conditions <- c(1, 1, 1, 2, 2, 2)
replicates <- c(1, 2, 3, 1, 2, 3)

if (FALSE) {
    # Instantiation of data set
    hic.experiment <- parseHiCPro(
        matrixPaths = matrixPaths,
        bedPaths = bedPaths,
        conditions = conditions,
        replicates = replicates
    )
}
```

`parseTabular` *Parser for tabular data*

Description

Read the file, produce an `InteractionSet` object.

Usage

```
parseTabular(path, sep = '\t')
```

Arguments

`path`	A path to a tabular file.
`sep`	The separator of the tabular file. Default to tabulation.

Details

Accepts a tabular file with `chromosome`, `position 1`, `position 2`, and multiple replicate columns listing interaction counts. Null interactions do not have to be listed. Values must be separated by tabulations. The header must be `chromosome position 1 position 2 x.y x.y x.y ...` with `x` replaced by condition names and `y` replaced by replicate names.

Value

An InteractionSet object.

Examples

```
path <- system.file("extdata", "hicsample_21.tsv", package = "HiCParser")
object <- parseTabular(path, sep = "\t")
```

Index

HiCParser *(*HiCParser-package*)*, 2
HiCParser-package, 2

InteractionSet, *3*

mergeInteractionSet, 3

parseCool, 3
parseHiC, 5
parseHiCPro, 6
parseTabular, 7