Package: HiCaptuRe (via r-universe)

November 1, 2026

Type Package

Title HiCaptuRe: Manipulating and integrating Capture Hi-C data

Version 1.3.8

URL https://github.com/LaureTomas/HiCaptuRe

Description Capture Hi-C is a set of techniques that enable the detection of genomic interactions involving regions of interest, known as baits. By focusing on selected loci, these approaches reduce sequencing costs while maintaining high resolution at the level of restriction fragments. HiCaptuRe provides tools to import, annotate, manipulate, and export Capture Hi-C data. The package accounts for the specific structure of bait–otherEnd interactions, facilitates integration with other omics datasets, and enables comparison across samples and conditions.

BugReports https://github.com/LaureTomas/HiCaptuRe/issues

License GPL-3

Encoding UTF-8

LazyData false

Depends R (>= 4.5.0)

Imports BiocGenerics, Biostrings, BSgenome, cli, data.table, dplyr, GenomeInfoDb, GenomicInteractions, GenomicRanges, InteractionSet, ggplot2, ggpubr, ggVennDiagram, gplots, igraph, IRanges, memoise, methods, S4Vectors, stringr, tibble, tidyr, UpSetR, utils

Suggests BSgenome.Hsapiens.NCBI.GRCh38, knitr, rmarkdown, DT, testthat, BiocStyle, kableExtra

biocViews Epigenetics, HiC, Sequencing, DataImport, Software

VignetteBuilder knitr

Config/roxygen2/version 8.1.0

Config/pak/sysreqs cmake libglpk-dev make libbz2-dev libicu-dev libjpeg-dev liblzma-dev libpng-dev libuv1-dev libxml2-dev libssl-dev xz-utils zlib1g-dev

Repository https://bioc.r-universe.dev

Date/Publication 2026-09-17 09:33:41 UTC

RemoteUrl https://github.com/bioc/HiCaptuRe

RemoteRef HEAD

RemoteSha 32908639d92fcf905da99a66a05a9337c9d191d0

Contents

annotate_interactions . . . 2
digest_genome . . . 3
distance_summary . . . 4
export_interactions . . . 5
getters . . . 6
HiCaptuRe-class . . . 7
interactionsByBaits . . . 7
interactionsByRegions . . . 8
intersect_interactions . . . 9
load_interactions . . . 10
peakmatrix2list . . . 11
plot_distance_summary . . . 11

Index **13**

`annotate_interactions` *Annotates HiCaptuRe object from load_interactions*

Description

This function annotate a HiCaptuRe object from load_interactions, based on a given annotations file

Usage

```
annotate_interactions(interactions, annotation, ...)
```

Arguments

`interactions`	HiCaptuRe object from `load_interactions`
`annotation`	full path to annotations file or a dataframe with 5 columns: chr, start, end, fragmentID, annotation
`...`	additional parameters for fread

Value

HiCaptuRe object annotated, with columns bait_1 and bait_2 substituted based on the given annotation

Examples

```
annotation <- system.file("extdata", "annotation_example.txt", package = "HiCaptuRe")
ibed1 <- system.file("extdata", "ibed1_example.zip", package = "HiCaptuRe")
interactions <- load_interactions(ibed1, select_chr = "19")
interactions <- annotate_interactions(interactions = interactions, annotation = annotation)
```

`digest_genome` *Digest genome for a specific restriction enzyme*

Description

This function takes a genome installed and generates its digest for a given restriction enzyme

Usage

```
digest_genome(
  genome = "GRCh38",
  RE_name = "HindIII",
  motif = NULL,
  cut_position = NULL,
  select_chr = c(seq_len(22), "X", "Y"),
  PAR_mask = TRUE,
  PAR_file = NULL,
  ...
)
```

Arguments

`genome`	character with the name of the genome version
`RE_name`	name of the restriction enzyme
`motif`	recognition motif of the restriction enzyme
`cut_position`	cut position of the restriction enzyme inside the motif
`select_chr`	a character vector containing the specific chromosomes to used from this genome, if NULL all chromosomes will be used
`PAR_mask`	a logical value where the Y chromosome should exclude the Pseudoautosomical Regions (PAR) or not
`PAR_file`	a full path to a file containing the coordinates of Y chromosome PAR with at least 3 columns with header: seqnames, start, end
`...`	extra arguments for read.table

Value

list object with 2 elements: a dataframe with the digested genome, and a the parameters used for the digestion.

Note

The package provides for a PAR coordinates file only for Homo sapiens for the genome version 38

The package provides the motives and cut positions for several restriction enzymes (HindIII, MboI, DpnII, EcoRI, BamHI)

Examples

```
digest <- digest_genome(genome = "GRCh38", RE_name = "HindIII", select_chr = "19")
```

---

distance_summary *Computes the number of interactions by distance*

Description

This function computes the number of interactions by distance for a given GenomicInteractions object

Usage

```
distance_summary(interactions, breaks = seq(0, 10^6, 10^5), sample = "sample")
```

Arguments

interactions	GenomicInteractions object from load_interactions
breaks	vector with breaks for split distances
sample	character variable with the name of the sample

Value

list with 2 tables: short_int_dist_table and long_int_dist_table, with the number of short interactions and long interactions respectively

Examples

```
ibed1 <- system.file("extdata", "ibed1_example.zip", package = "HiCaptuRe")
interactions1 <- load_interactions(ibed1, select_chr = "19")
df <- distance_summary(interactions = interactions1)
```

`export_interactions` *Export interactions in the desired output format*

Description

This function exports interactions in different formats

Usage

```
export_interactions(
  interactions,
  file,
  format = "ibed",
  over.write = FALSE,
  cutoff = 5,
  parameters = FALSE
)
```

Arguments

`interactions`	GenomicInteractions object from `load_interactions`
`file`	full path to desired output file (ibed, peakmatrix, washU, washUold, cytoscape, bedpe)
`format`	type of output format (ibed, peakmatrix, washU, washUold, cytoscape, bedpe, seqmonk, biginteract)
`over.write`	TRUE/FALSE to over write the output file
`cutoff`	Chicago score cutoff to export interactions
`parameters`	TRUE/FALSE to also export the parameters of the given object

Value

tibble object with the ibed table and save it in the desired output file

Examples

```
ibed1 <- system.file("extdata", "ibed1_example.zip", package = "HiCaptuRe")
interactions <- load_interactions(ibed1, select_chr = "19")
export_interactions(interactions = interactions, file = tempfile(), format = "ibed", over.write = TRUE)
```

getters *Internal functions to access data held in a HiCaptuRe object.*

Description

Use these functions to access data stored in each of the slots of a HiCapture object.

Usage

```
getParameters(x)

## S4 method for signature 'HiCaptuRe'
getParameters(x)

getByBaits(x)

## S4 method for signature 'HiCaptuRe'
getByBaits(x)

getByRegions(x)

## S4 method for signature 'HiCaptuRe'
getByRegions(x)
```

Arguments

x	A HiCaptuRe object

Value

getParameters(x) A named list of named vectors with all parameters used.

getByBaits(x) A list of tibbles with bait-centric summaries.

getByRegions(x) A list of 'GRanges' with region-centric summaries.

Examples

```
ibed1 <- system.file("extdata", "ibed1_example.zip", package = "HiCaptuRe")
interactions <- load_interactions(ibed1, select_chr = "19")
getParameters(interactions)

baits <- c("ENST00000332235", "ENST00000516525")
interactions_baits <- interactionsByBaits(interactions = interactions, baits = baits)
getByBaits(interactions_baits)

regions <- GenomicRanges::GRanges(seqnames = 19, ranges = IRanges::IRanges(start = c(500000, 1000000), end = c(5100
interactions_regions <- interactionsByRegions(interactions = interactions, regions = regions)
getByRegions(interactions_regions)
```

HiCaptuRe-class *HiCaptuRe Class*

Description

A S4 class to represent interactions between genomic regions

Usage

```
## S4 method for signature 'HiCaptuRe'
as.data.frame(x, row.names = NULL, optional = FALSE, ...)
```

Arguments

x	A HiCaptuRe object.
row.names	NULL or a character vector giving the row names for the data frame.
optional	logical. If TRUE, setting row names and converting column names is optional.
...	Additional arguments.

Value

A data.frame containing the interactions and metadata.

Slots

`parameters` List of parameters used to create the object and subsequence analysis

`ByBaits` List of Baits used by interactionsByBaits.

`ByRegions` List of Regions used by interactionsByRegions

Note

This class contains a GenomicInteractions object inside therefore all methods available to it can be used. This type of object should be created through the function load_interactions

interactionsByBaits *Filters HiCaptuRe object by baits*

Description

This function filters a HiCaptuRe object from load_interactions by a set of given bait(s)

Usage

```
interactionsByBaits(interactions, baits, sep = ",", invert = FALSE)
```

Arguments

interactions	a HiCaptuRe object
baits	character vector containing bait names
sep	character separating baits names when several baits in same fragment
invert	TRUE/FALSE if need those interactions that do NOT contain the given baits

Value

The returned object includes a filtered set of interactions and updates the ByBaits slot with a tibble summarizing bait-wise interaction statistics (number of interactions, other ends, etc.). Baits that are not present in the interaction data will have empty statistics.

Examples

```
ibed1 <- system.file("extdata", "ibed1_example.zip", package = "HiCaptuRe")
interactions <- load_interactions(ibed1, select_chr = "19")
baits <- c("ENST00000332235", "ENST00000516525")
interactions_baits <- interactionsByBaits(interactions = interactions, baits = baits)
```

---

interactionsByRegions *Filters HiCaptuRe object by overlaping regions*

Description

This function filters a HiCaptuRe object from load_interactions by overlaping regions

Usage

```
interactionsByRegions(
  interactions,
  regions,
  chr = NULL,
  start = NULL,
  end = NULL,
  invert = FALSE
)
```

Arguments

interactions	HiCaptuRe object
regions	full path to regions file (bed format) or a GRanges object
chr	column name of chromosome values
start	column name of start positions
end	column name of end positions
invert	TRUE/FALSE if need those interactions that do NOT overlaps with any regions

Value

HiCaptuRe object filtered by regions, by default with additional columns regarding overlap on each node. If invert=T no additional columns. And an additional slot ByRegions with region-centric statistics

Examples

```
ibed1 <- system.file("extdata", "ibed1_example.zip", package = "HiCaptuRe")
interactions <- load_interactions(ibed1, select_chr = "19")
regions <- GenomicRanges::GRanges(seqnames = 19, ranges = IRanges::IRanges(start = c(500000, 1000000), end = c(5100
interactions_regions <- interactionsByRegions(interactions = interactions, regions = regions)
```

---

intersect_interactions

Computes the intersect between a list of interactions objects

---

Description

This function computes all the possible intersects for a given list of HiCaptuRe objects

Usage

```
intersect_interactions(interactions_list, distance.boxplot = FALSE, ...)
```

Arguments

interactions_list	list of HiCaptuRe objects from load_interactions
distance.boxplot	logical, by default FALSE, plot a boxplot of log10 distance of each intersection in the upset plot
...	extra arguments for UpSetR

Value

A list with:

intersections A named list of intersected HiCaptuRe objects

upset An UpSetR plot

venn A ggVennDiagram plot (NULL if > 7 sets)

Examples

```
ibed1 <- system.file("extdata", "ibed1_example.zip", package = "HiCaptuRe")
interactions1 <- load_interactions(ibed1, select_chr = "19")
ibed2 <- system.file("extdata", "ibed2_example.zip", package = "HiCaptuRe")
interactions2 <- load_interactions(ibed2, select_chr = "19")
interactions_list <- list(ibed1 = interactions1, ibed2 = interactions2)
intersection <- intersect_interactions(interactions_list = interactions_list)
```

`load_interactions` *Loads interaction file into GenomicInteractions Object*

Description

This function loads interaction files from Chicago R package into a GenomicInteractions Object, and remove possible duplicated interactions

Usage

```
load_interactions(file, sep = "\t", ...)
```

Arguments

`file`	full path to the interaction file (seqmonk, ibed, washU)
`sep`	separator to read the file
`...`	arguments to pass to digest_genome

Value

HiCaptuRe object

Examples

```
ibed1 <- system.file("extdata", "ibed1_example.zip", package = "HiCaptuRe")
interactions <- load_interactions(ibed1, select_chr = "19")
```

peakmatrix2list *Creates a list of HiCaptuRe objects based on a peakmatrix*

Description

This function creates a list of HiCaptuRe objects separating all the samples included on a peakmatrix.

Usage

```
peakmatrix2list(peakmatrix, cutoff = 5)
```

Arguments

peakmatrix	HiCaptuRe object of a peakmatrix
cutoff	Chicago score cut-off to filter interactions

Value

A named list of HiCaptuRe objects, each corresponding to a sample (inferred from CS_* columns in the peakmatrix).

Examples

```
peakmatrix <- system.file("extdata", "peakmatrix_example.zip", package = "HiCaptuRe")
interactions <- load_interactions(peakmatrix, select_chr = "19")
interactions_list <- peakmatrix2list(peakmatrix = interactions)
```

plot_distance_summary *Generate the plot based on distance output*

Description

This function plots the distances by different approaches for the output of distance_summary

Usage

```
plot_distance_summary(distances, type_of_value = "absolute")
```

Arguments

distances	dataframes output from distance_summary
type_of_value	an element from: absolute, by_int_type, by_total

Details

The type_of_value argument could be: Absolute: plots the Absolute number of interactions. By_int_type: plots the number of interactions divided by the total number of interactions of each type. By_total: plots the number of interactions divided by the total number of interactions

Value

list with the plots

Examples

```
ibed1 <- system.file("extdata", "ibed1_example.zip", package = "HiCaptuRe")
interactions1 <- load_interactions(ibed1, select_chr = "19")
df <- distance_summary(interactions = interactions1)
plots <- plot_distance_summary(distances = df)
```

Index

annotate_interactions, 2
as.data.frame,HiCaptuRe-method
(HiCaptuRe-class), 7

digest_genome, 3, *10*
distance_summary, 4, *11*

export_interactions, 5

GenomicInteractions, *7*
getByBaits (getters), 6
getByBaits,HiCaptuRe-method (getters), 6
getByRegions (getters), 6
getByRegions,HiCaptuRe-method
(getters), 6
getParameters (getters), 6
getParameters,HiCaptuRe-method
(getters), 6
getters, 6

HiCaptuRe-class, 7

interactionsByBaits, 7, *7*
interactionsByRegions, *7*, 8
intersect_interactions, 9

load_interactions, *2*, *4*, *5*, *7*, *9*, 10

peakmatrix2list, 11
plot_distance_summary, 11