

Package: MSTree (via r-universe)

May 24, 2026

Title MSTree plotting minimum spanning tree directly from the output of ChewBBACA pipeline

Version 0.99.6

Description This package is used to generate a graph object from the output of chewBBACA pipeline (<https://chewbbaca.readthedocs.io/en/latest/>). Then, the generated graph object can be used to make a minimum spanning tree (MST). The minimum spanning tree can be customized using all the available arguments. This package consists of two functions: one to build the graph and another one for plotting.

License Artistic-2.0

Imports igraph, ggraph, ggplot2, utils, methods, NetPathMiner

Suggests RUnit, testthat, BiocGenerics, BiocStyle, knitr, rmarkdown

biocViews ComparativeGenomics, GenomicVariation, Clustering

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

VignetteBuilder knitr

Config/pak/sysreqs libfontconfig1-dev libfreetype6-dev libglpk-dev libicu-dev libxml2-dev

Repository <https://bioc.r-universe.dev>

Date/Publication 2026-05-15 10:44:33 UTC

RemoteUrl <https://github.com/bioc/MSTree>

RemoteRef HEAD

RemoteSha 08cdc1833921fa67b40aaaa275cd641f8a8f02e0

Contents

makeGraphFromChewBBACA	2
PlotMST	2

Index	5
--------------	----------

makeGraphFromChewBBACA

MSTree R package

Description

Make a graph object from the extracted alleles

Arguments

chewbbaca_ExtractCgMLST_output

Full path of the file name or a data frame.

max_allelic_difference

numeric; This is an optional argument, can be used to connect nodes that have a distance less than or equal to the specified number, useful to show clusters of isolates. The default is set to -1 which means no clustering is applied.

verbose

logical; set to TRUE to print on screen the progress. default is FALSE.

Details

Make a graph object and generate minimum spanning tree.

This function takes alleles matrix and returns a graph object

Value

Graph object.

Examples

```
my_graph <- makeGraphFromChewBBACA(system.file("extdata", "cgMLST95.csv",
  package = "MSTree"), max_allelic_difference=-1)
```

PlotMST

MSTree R package

Description

Using the igraph object generated from makeGraphFromChewBBACA function, PlotMST function will plot a minimum spanning tree.

Arguments

<code>igraph_object</code>	igraph object, output of the <code>makeGraphFromChewBBACA</code> function
<code>metadata</code>	data frame; This is an optional argument. If given, the function will assume the first column contains the isolates names and will add the remaining columns as metadata to the igraph object, useful for generating custom coloring of the nodes i.e. Year, Source, etc. The default is NULL
<code>show_clustering</code>	logical; If the user has used a value for <code>max_allelic_difference</code> when running <code>makeGraphFromChewBBACA</code> , the user has the option to show the clustering of nodes based on that threshold if set to TRUE, or FALSE to show the minimum spanning tree without any clustering between nodes, as if the user did not apply any clustering. The default is TRUE
<code>MST_edges_color</code>	character; This argument will allow the user to set the color of the edges that connect the nodes. The default is "black"
<code>cluster_edges_color</code>	character; This argument will allow the user to set the color of the edges that connect the clustered nodes. The default is "grey"
<code>MST_edges_width</code>	numeric; This argument will allow the user to set the width of the edges that connect the nodes. The default is 0.75
<code>cluster_edges_width</code>	numeric; This argument will allow the user to set the width of the edges that connect the clustered nodes. The default is 0.5
<code>edge_label_size</code>	numeric; This argument will allow the user to set the label size of the distances on the edges. The default is 3
<code>edge_label_dodge</code>	numeric; This argument will allow the user control the position of the distance on the edges. The default is 2
<code>node_color</code>	character; This argument will allow the user to choose the color of the nodes. The color can be specified by its name or using hexadecimal representation. Also, if the metadata argument is given, the user can specify a column name from the metadata data frame to color the nodes i.e. "Year". The default is "red"
<code>node_size</code>	numeric; This argument will allow the user to control the node size. The default is 3
<code>node_label_size</code>	numeric; This argument will allow the user to control the node label size. If set to zero, no labels will be shown. The default is 0
<code>show_legend</code>	logical; This argument will allow the user to show or hide the legend of the generated plot. The default is TRUE
<code>title</code>	character; This argument will allow the user to add a title to the generated plot. The default is NULL
<code>basic</code>	logical; This argument will allow the user to generate a very basic minimum spanning tree layout using the the package <code>NetPathMiner</code> . The default is FALSE

Details

The function *PlotMST* will make a minimum spanning tree using the output of *makeGraphFromChewBBACA* function. Many arguments are available to customize the minimum spanning tree.

Value

Graph object.

Examples

```
my_graph <- makeGraphFromChewBBACA(system.file("extdata", "cgMLST95.csv",
  package = "MSTree"), max_allelic_difference=-1)
mst <- PlotMST(my_graph, show_clustering = TRUE, show_legend=FALSE,
  MST_edges_color="#b97b29", node_color = "#3b17db",
  node_label_size = 3, title = "MST")
```

Index

`makeGraphFromChewBBACA`, [2](#)

`PlotMST`, [2](#)