Package: MantelCorr (via r-universe)

October 31, 2026

Title Compute Mantel Cluster Correlations

Version 1.83.0

Date 2005-17-10

Author Brian Steinmeyer and William Shannon

Description Computes Mantel cluster correlations from a (p x n)
numeric data matrix (e.g. microarray gene-expression data).

Maintainer Brian Steinmeyer <steinmeb@ilya.wustl.edu>

Depends R (>= 2.10)

Imports stats

License GPL (>= 2)

biocViews Clustering

Repository https://bioc.r-universe.dev

Date/Publication 2026-04-28 12:31:28 UTC

RemoteUrl https://github.com/bioc/MantelCorr

RemoteRef HEAD

RemoteSha 3b313abc382188e393e186a9724082427273fb21

Contents

ClusterGeneList 2
ClusterList 3
DistMatrices 4
GetClusters 5
GolubTrain 6
MantelCorrs 8
PermutatonTest 9

Index **11**

`ClusterGeneList` *Generate Genes from a Cluster List*

Description

'ClusterGeneList' produces a list of both significant and nonsignificant genes from each respective cluster type

Usage

```
ClusterGeneList(clus, clustlist.sig, x.data)
```

Arguments

`clus`	'clusters' object returned by 'GetClusters'
`clustlist.sig`	'SignificantClusters' object returned by 'ClusterList'
`x.data`	original (p x n) numeric data matrix (e.g., gene-expression data)

Value

A list with components:

`SignificantClusterGenes`
: significant cluster genes returned from 'ClusterList'

`NonSignificantClusterGenes`
: nonsignificant cluster genes returned from 'ClusterList'

Note

argument 'x.data' should have an ID gene variable, 'probes', attached as a 'dimnames' attribute

Author(s)

Brian Steinmeyer

See Also

'GetClusters' 'ClusterList'

Examples

```
# simulate a p x n microarray expression dataset, where p = genes and n = samples
data.sep <- rbind(matrix(rnorm(1000), ncol=50), matrix(rnorm(1000, mean=5), ncol=50))
noise <- matrix(runif(40000), ncol=1000)
data <- t(cbind(data.sep, noise))
data <- data[1:200, ]
# data has p = 1,050 genes and n = 40 samples
```

```
clusters.result <- GetClusters(data, 100, 100)
dist.matrices <- DistMatrices(data, clusters.result$clusters)
mantel.corrs <- MantelCorrs(dist.matrices$Dfull, dist.matrices$Dsubsets)
permutation.result <- PermutationTest(dist.matrices$Dfull, dist.matrices$Dsubsets, 100, 40, 0.05)

# generate both significant and non-significant gene clusters
cluster.list <- ClusterList(permutation.result, clusters.result$cluster.sizes, mantel.corrs)

# significant and non-significant cluster genes (expression values)
cluster.genes <- ClusterGeneList(clusters.result$clusters, cluster.list$SignificantClusters, data)
```

`ClusterList` *Generate a Cluster List*

Description

'ClusterList' generates a list of both significant and nonsignificant clusters, with cluster number, Mantel cluster correlation and size

Usage

```
ClusterList(p.val, clus.size, mantel.cors)
```

Arguments

`p.val`	permutation p-value returned from 'PermutationTest'
`clus.size`	vector of k cluster sizes returned from 'GetCluster'
`mantel.cors`	orignal, unpermuted k Mantel correlations returned from 'MantelCorrs'

Value

A list with components:

`SignificantClusters`
: clusters with significant Mantel correlation, equal to or larger than the permutation p-value returned by 'PermutationTest'

`NonSignificantClusters`
: clusters with nonsignificant Mantel correlation, smaller than the permutation p-value returned by 'PermutationTest'

Author(s)

Brian Steinmeyer

See Also

'PermutationTest'

Examples

```
# simulate a p x n microarray expression dataset, where p = genes and n = samples
data.sep <- rbind(matrix(rnorm(1000), ncol=50), matrix(rnorm(1000, mean=5), ncol=50))
noise <- matrix(runif(40000), ncol=1000)
data <- t(cbind(data.sep, noise))
data <- data[1:200, ]
# data has p = 1,050 genes and n = 40 samples

clusters.result <- GetClusters(data, 100, 100)
dist.matrices <- DistMatrices(data, clusters.result$clusters)
mantel.corrs <- MantelCorrs(dist.matrices$Dfull, dist.matrices$Dsubsets)
permutation.result <- PermutationTest(dist.matrices$Dfull, dist.matrices$Dsubsets, 100, 40, 0.05)

# generate both significant and non-significant gene clusters
cluster.list <- ClusterList(permutation.result, clusters.result$cluster.sizes, mantel.corrs)
```

`DistMatrices` *Compute Dissimilarity Matrices*

Description

'DistMatrices' uses 'dist' to compute dissimilarity matrices for 'data' and each cluster k from 'GetClusters'

Usage

```
DistMatrices(x.data, cluster.assignment)
```

Arguments

`x.data`	original 'data' matrix
`cluster.assignment`	cluster assignment vector, "clusters", returned by 'GetClusters'

Value

returns a list with two components:

`Dsubsets`	dissimilarity matrices for each cluster k
`Dfull`	dissimilarity matrix for the original 'data'

Note

'GetClusters' should be executed prior to 'DistMatrices'

Author(s)

Brian Steinmeyer

See Also

'GetClusters'

Examples

```
# simulate a p x n microarray expression dataset, where p = genes and n = samples
data.sep <- rbind(matrix(rnorm(1000), ncol=50), matrix(rnorm(1000, mean=5), ncol=50))
noise <- matrix(runif(40000), ncol=1000)
data <- t(cbind(data.sep, noise))
data <- data[1:200, ]
# data has p = 1,050 genes and n = 40 samples

clusters.result <- GetClusters(data, 100, 100)
dissimilarity.matrices <- DistMatrices(data, clusters.result$clusters)
```

GetClusters *Over-Partition a (p x n) Data Matrix using 'kmeans'*

Description

'GetClusters' uses an overly large k with the 'kmeans' function to over-partition p variables (rows = genes) from n objects (cols = samples) from a given data matrix 'x.data'

Usage

```
GetClusters(x.data, num.k, num.iters)
```

Arguments

x.data	p x n data matrix of numeric values
num.k	number of k partitions desired
num.iters	number of iterations - recommend >= 100

Value

'GetClusters' returns a list with the following components:

clusters	cluster assignment from 'kmeans'
cluster.sizes	size of each cluster k from 'kmeans'

Note

The input data matrix, x.data, must be numeric (e.g., gene-expression values). We recommend using 'num.k' = one-half the number of genes and 'num.iters' greater than 50

Author(s)

Brian Steinmeyer

See Also

'kmeans'

Examples

```
# simulate a p x n microarray expression dataset, where p = genes and n = samples
data.sep <- rbind(matrix(rnorm(1000), ncol=50), matrix(rnorm(1000, mean=5), ncol=50))
noise <- matrix(runif(40000), ncol=1000)
data <- t(cbind(data.sep, noise))
data <- data[1:200, ]
# data has p = 1,050 genes and n = 40 samples

clusters.result <- GetClusters(data, 100, 100)
```

GolubTrain *Golub Training Set*

Description

Samples were taken with Affymetrix Hgu6800 chips and expression levels measured on 7,129 genes (probes). The samples consist of 27 acute lymphoblastic leukemia (ALL) and 11 acute myeloid luekemia (AML) patients. The data values are raw (e.g. no standardization or gene filtering applied).

Usage

```
data(GolubTrain)
```

Format

A data frame of 7129 observations (genes) with the following 38 variables (samples):

X1 ALL

X2 ALL

X3 ALL

X4 ALL

X5 ALL

X6 ALL

X7 ALL

X8 ALL

X9 ALL

X10 ALL
X11 ALL
X12 ALL
X13 ALL
X14 ALL
X15 ALL
X16 ALL
X17 ALL
X18 ALL
X19 ALL
X20 ALL
X21 ALL
X22 ALL
X23 ALL
X24 ALL
X25 ALL
X26 ALL
X27 ALL
X28 AML
X29 AML
X30 AML
X31 AML
X32 AML
X33 AML
X34 AML
X35 AML
X36 AML
X37 AML
X38 AML

Source

http://www.broad.mit.edu/cgi-bin/cancer/datasets.cgi

References

Golub, T.R. Molecular Classification of Cancer: Class Discovery and Class Prediction by Gene Expression Monitoring. Science, vol 286, 531-537, 1999.

Examples

```
data(GolubTrain)
```

`MantelCorrs` *Compute Mantel Correlation(s)*

Description

'MantelCorrs' computes the Mantel correlation between two dissimilarity matrices

Usage

```
MantelCorrs(Dfull, Dsubsets)
```

Arguments

`Dfull`	distance matrix returned by 'DistMatrices' using original 'data'
`Dsubsets`	list of distance matrices from each k cluster or partition returned by 'DistMatrices'

Value

A list with k components

`where component i`
: Mantel correlation for cluster i, i = 1,...,k

Warning

The function is meant to be executed AFTER 'GetClustes' and 'DistMatrices' (see example)

Note

the value 'k' corresponds to the parameter 'num.k' in 'GetClusters'

Author(s)

Brian Steinmeyer

References

Mantel N: The detection of disease clustering and a generalized regression approach. Cancer Research. 27(2), 209-220 (1967).

See Also

'GetClusters' 'DistMatrices' 'kmeans'

Examples

```
# simulate a p x n microarray expression dataset, where p = genes and n = samples
data.sep <- rbind(matrix(rnorm(1000), ncol=50), matrix(rnorm(1000, mean=5), ncol=50))
noise <- matrix(runif(40000), ncol=1000)
data <- t(cbind(data.sep, noise))
data <- data[1:200, ]
# data has p = 1,050 genes and n = 40 samples

clusters.result <- GetClusters(data, 100, 100)
dist.matrices <- DistMatrices(data, clusters.result$clusters)
mantel.corrs <- MantelCorrs(dist.matrices$Dfull, dist.matrices$Dsubsets)
```

PermutatonTest *Permutation Test for Dissimilarity Matrices*

Description

'PermutationTest' computes and returns an empirical p-value from a null distribution generated by permuting 'Dfull' a total of 'num.per' times.

Usage

```
PermutationTest(Dfull, Dsubsets, num.per, num.chips, alpha)
```

Arguments

Dfull	dissimilarity matrix from the original (p x n) microarray expression data
Dsubsets	dissimilarity matrices from each k disjoint clusters returned by 'GetClusters'
num.per	number of permutations
num.chips	number of samples, 'n' from the original (p x n) data matrix
alpha	desired level of significance

Details

For each permutation, k Mantel correlations are computed by correlating the permuted 'Dfull' with each dissimilarity matrix 'Dsubsets' from the 'k' clusters returned by 'GetClusters'. The absolute value of the maximum Mantel cluster correlation is retained at each permutation. These 'num.per' maximum correlations are then used to generate a null distribution for distance metric independence, with the p-value taken from the (1 - 'alpha') percentile of this permutation distribution.

Value

returns the permuted p-value for the 'alpha' selected level of significance

Warning

(p x n) data matrix should be numeric (e.g. gene-expression levels)

Note

The function is meant to be executed AFTER 'GetClustes', 'DistMatrices' and 'MantelCorr' (see example)

Author(s)

Brian Steinmeyer

See Also

'GetClusters' 'DistMatrices' 'MantelCorrs'

Examples

```
# simulate a p x n microarray expression dataset, where p = genes and n = samples
data.sep <- rbind(matrix(rnorm(1000), ncol=50), matrix(rnorm(1000, mean=5), ncol=50))
noise <- matrix(runif(40000), ncol=1000)
data <- t(cbind(data.sep, noise))
data <- data[1:200, ]
# data has p = 1,050 genes and n = 40 samples

clusters.result <- GetClusters(data, 100, 100)
dist.matrices <- DistMatrices(data, clusters.result$clusters)
mantel.corrs <- MantelCorrs(dist.matrices$Dfull, dist.matrices$Dsubsets)
permutation.result <- PermutationTest(dist.matrices$Dfull, dist.matrices$Dsubsets, 100, 40, 0.05)
```

Index

∗ **cluster**
ClusterGeneList, 2
ClusterList, 3
DistMatrices, 4
GetClusters, 5
MantelCorrs, 8
PermutatonTest, 9
∗ **datasets**
GolubTrain, 6

ClusterGeneList, 2
ClusterList, 3

DistMatrices, 4

GetClusters, 5
GolubTrain, 6

MantelCorrs, 8

PermutationTest *(*PermutatonTest*)*, 9
PermutatonTest, 9