

Package: PathoStat (via r-universe)

October 12, 2026

Type Package

Title PathoStat Statistical Microbiome Analysis Package

Version 1.39.0

Date 2020-03-27

Author Solaiappan Manimaran <manimaran_1975@hotmail.com>, Matthew Bendall <bendall@gmail.gwu.edu>, Sandro Valenzuela Diaz <sandrolvalenzuelad@gmail.com>, Eduardo Castro <castronallar@gmail.com>, Tyler Faits <tfaits@gmail.com>, Yue Zhao <jasonzhao0307@gmail.com>, Anthony Nicholas Federico <anfed@bu.edu>, W. Evan Johnson <wej@bu.edu>

Maintainer Solaiappan Manimaran <manimaran_1975@hotmail.com>, Yue Zhao <jasonzhao0307@gmail.com>

Description The purpose of this package is to perform Statistical Microbiome Analysis on metagenomics results from sequencing data samples. In particular, it supports analyses on the PathoScope generated report files. PathoStat provides various functionalities including Relative Abundance charts, Diversity estimates and plots, tests of Differential Abundance, Time Series visualization, and Core OTU analysis.

URL <https://github.com/mani2012/PathoStat>

BugReports <https://github.com/mani2012/PathoStat/issues>

License GPL (>= 2)

Depends R (>= 3.5)

Imports limma, corpcor, matrixStats, reshape2, scales, ggplot2, rentrez, DT, tidyr, plyr, dplyr, phyloseq, shiny, stats, methods, XML, graphics, utils, BiocStyle, edgeR, DESeq2, ComplexHeatmap, plotly, webshot, vegan, shinyjs, glmnet, gmodels, ROCR, RColorBrewer, knitr, devtools, ape

Collate 'pathoStat.R' 'utils.R' 'taxonomy.R' 'biomarker.R' 'allClasses.R' 'visualization.R' 'differentialAnalysis.R'

biocViews Microbiome, Metagenomics, GraphAndNetwork, Microarray,
PatternLogic, PrincipalComponent, Sequencing, Software,
Visualization, RNASeq, ImmunoOncology

RoxygenNote 6.1.1

Encoding UTF-8

Suggests rmarkdown, testthat

VignetteBuilder knitr

Config/pak/sysreqs cmake libfontconfig1-dev libfreetype6-dev libfribidi-dev git libglpk-
dev make libharfbuzz-dev libmagick++-dev gsfonts libgit2-dev libicu-dev libjpeg-dev libpng-
dev libtiff-dev libuv1-dev libwebp-dev libxml2-dev libssl-dev perl libx11-dev zlib1g-dev

Repository <https://bioc.r-universe.dev>

Date/Publication 2026-04-28 12:44:26 UTC

RemoteUrl <https://github.com/bioc/PathoStat>

RemoteRef HEAD

RemoteSha feae7f1140a87875f98981e5069a208a20db7b18

Contents

Bootstrap_LOOCV_LR_AUC	3
Chisq_Test_Pam	4
findRAfromCount	4
findTaxonMat	5
findTaxonomy	6
findTaxonomy300	6
Fisher_Test_Pam	7
formatTaxTable	8
GET_PAM	8
getShinyInput	9
getShinyInputCombat	9
getShinyInputOrig	10
getSignatureFromMultipleGlmnet	10
grepTid	11
loadPathoscopeReports	11
loadPstat	12
log2CPM	13
LOOAUC_simple_multiple_noplot_one_df	13
LOOAUC_simple_multiple_one_df	14
PathoStat-class	14
percent	15
phyloseq_to_edgeR	16
plotPCAPlotly	16
plotPCoAPlotly	17
pstat_data	18
readPathoscopeData	19
runPathoStat	20

<i>Bootstrap_LOOCV_LR_AUC</i>	3
savePstat	20
setShinyInput	21
setShinyInputCombat	21
setShinyInputOrig	22
summarizeTable	22
TranslateIdToTaxLevel	23
Wilcox_Test_df	24
Index	25

Bootstrap_LOOCV_LR_AUC
<i>Do bootstrap and LOOCV</i>

Description

Do bootstrap and LOOCV

Usage

Bootstrap_LOOCV_LR_AUC(df, targetVec, nboot = 50)

Arguments

- | | |
|-----------|--|
| df | Row is sample, column is feature. Required |
| targetVec | y vector. Required |
| nboot | number of BOOTSTRAP |

Value

bootstrap loocv result dataframe

Examples

```
data('iris')
Bootstrap_LOOCV_LR_AUC(iris[,1:4],
c(rep(1,100), rep(0,50)), nboot = 3)
```

Chisq_Test_Pam	<i>Given PAM and disease/control annotation, do Chi-square test for each row of PAM</i>
----------------	---

Description

Given PAM and disease/control annotation, do Chi-square test for each row of PAM

Usage

```
Chisq_Test_Pam(pam, label.vec.num, pvalue.cutoff = 0.05)
```

Arguments

pam	Input data object that contains the data to be tested. Required
label.vec.num	The target binary condition. Required
pvalue.cutoff	choose p-value cut-off

Value

df.output object

Examples

```
tmp <- matrix(rbinom(12,1,0.5), nrow = 3)
rownames(tmp) <- c("a", "b", "c")
Chisq_Test_Pam(tmp, c(1,1,0,0))
```

findRAfromCount	<i>Return the Relative Abundance (RA) data for the given count OTU table</i>
-----------------	--

Description

Return the Relative Abundance (RA) data for the given count OTU table

Usage

```
findRAfromCount(count_otu)
```

Arguments

count_otu	Count OTU table
-----------	-----------------

Value

ra_otu Relative Abundance (RA) OTU table

Examples

```
data_dir <- system.file("data", package = "PathoStat")
infileName <- "pstat_data.rda"
pstat_test <- loadPstat(data_dir, infileName)
ra_otu <- findRAfromCount(phyloseq::otu_table(pstat_test))
```

findTaxonMat	<i>Find the Taxonomy Information Matrix</i>
--------------	---

Description

Find the Taxonomy Information Matrix

Usage

```
findTaxonMat(names, taxonLevels)
```

Arguments

names	Row names of the taxonomy matrix
taxonLevels	Taxon Levels of all tids

Value

taxmat Taxonomy Information Matrix

Examples

```
example_data_dir <- system.file("example/data", package = "PathoStat")
pathoreport_file_suffix <- "-sam-report.tsv"
datlist <- readPathoscopeData(example_data_dir, pathoreport_file_suffix,
input.files.name.vec = as.character(1:6))
dat <- datlist$data
ids <- rownames(dat)
tids <- unlist(lapply(ids, FUN = grepTid))
# taxonLevels <- findTaxonomy(tids[1:5])
# taxmat <- findTaxonMat(ids[1:5], taxonLevels)
```

findTaxonomy*Find the taxonomy for unlimited tids*

Description

Find the taxonomy for unlimited tids

Usage

```
findTaxonomy(tids)
```

Arguments

tids Given taxonomy ids

Value

taxondata Data with the taxonomy information

Examples

```
example_data_dir <- system.file("example/data", package = "PathoStat")
pathoreport_file_suffix <- "-sam-report.tsv"
datlist <- readPathoscopeData(example_data_dir, pathoreport_file_suffix,
input.files.name.vec = as.character(1:6))
dat <- datlist$data
ids <- rownames(dat)
tids <- unlist(lapply(ids, FUN = grepTid))
# taxonLevels <- findTaxonomy(tids[1:5])
```

findTaxonomy300*Find the taxonomy for maximum 300 tids*

Description

Find the taxonomy for maximum 300 tids

Usage

```
findTaxonomy300(tids)
```

Arguments

tids Given taxonomy ids

Value

taxondata Data with the taxonomy information

Examples

```
example_data_dir <- system.file("example/data", package = "PathoStat")
pathoreport_file_suffix <- "-sam-report.tsv"
datlist <- readPathoscopeData(example_data_dir,
  pathoreport_file_suffix, input.files.name.vec = as.character(1:6))
dat <- datlist$data
ids <- rownames(dat)
tids <- unlist(lapply(ids, FUN = grepTid))
# taxonLevels <- findTaxonomy300(tids[1:5])
```

Fisher_Test_Pam	<i>Given PAM and disease/control annotation, do Chi-square test for each row of PAM</i>
-----------------	---

Description

Given PAM and disease/control annotation, do Chi-square test for each row of PAM

Usage

```
Fisher_Test_Pam(pam, label.vec.num, pvalue.cutoff = 0.05)
```

Arguments

pam	Input data object that contains the data to be tested. Required
label.vec.num	The target binary condition. Required
pvalue.cutoff	choose p-value cut-off

Value

df.output object

Examples

```
tmp <- matrix(rbinom(12,1,0.5), nrow = 3)
rownames(tmp) <- c("a", "b", "c")
Fisher_Test_Pam(tmp, c(1,1,0,0))
```

formatTaxTable	<i>Format taxonomy table for rendering</i>
----------------	--

Description

Format taxonomy table for rendering

Usage

```
formatTaxTable(ttable)
```

Arguments

ttable Taxonomy table

Value

Formatted table suitable for rendering with. DT::renderDataTable

GET_PAM	<i>transform cpm counts to presence-absence matrix</i>
---------	--

Description

transform cpm counts to presence-absence matrix

Usage

```
GET_PAM(df)
```

Arguments

df Input data object that contains the data to be tested. Required

Value

df.output object

Examples

```
GET_PAM(data.frame(a = c(1,3,0), b = c(0,0.1,2)))
```

getShinyInput	<i>Getter function to get the shinyInput option</i>
---------------	---

Description

Getter function to get the shinyInput option

Usage

```
getShinyInput()
```

Value

shinyInput option

Examples

```
getShinyInput()
```

getShinyInputCombat	<i>Getter function to get the shinyInputCombat option</i>
---------------------	---

Description

Getter function to get the shinyInputCombat option

Usage

```
getShinyInputCombat()
```

Value

shinyInputCombat option

Examples

```
getShinyInputCombat()
```

getShinyInputOrig	<i>Getter function to get the shinyInputOrig option</i>
-------------------	---

Description

Getter function to get the shinyInputOrig option

Usage

```
getShinyInputOrig()
```

Value

shinyInputOrig option

Examples

```
getShinyInputOrig()
```

getSignatureFromMultipleGlmnet	<i>Use Lasso to do feature selection</i>
--------------------------------	--

Description

Use Lasso to do feature selection

Usage

```
getSignatureFromMultipleGlmnet(df.input, target.vec, nfolds = 10,
  logisticRegression = TRUE, nRun = 100, alpha = 1)
```

Arguments

df.input	Row is sample, column is feature. Required
target.vec	y vector. Required
nfolds	glmnet CV nfolds
logisticRegression	doing logistic regression or linear regression.
nRun	number of glmnet runs
alpha	same as in glmnet

Value

signature

Examples

```
data('iris')
getSignatureFromMultipleGlmnet(iris[,1:4],
c(rep(1,100), rep(0,50)), nfolds = 3, nRun = 10)
```

grepTid

Greps the tid from the given identifier string

Description

Greps the tid from the given identifier string

Usage

```
grepTid(id)
```

Arguments

id Given identifier string

Value

tid string

Examples

```
grepTid("ti|700015|org|Coriobacterium_glomerans_PW2")
```

loadPathoscopeReports *Loads all data from a set of PathoID reports. For each column in the PathoID report, construct a matrix where the rows are genomes and the columns are samples. Returns a list where each element is named according to the PathoID column. For example, ret[["Final.Best.Hit.Read.Numbers"]] on the result of this function will get you the final count matrix. Also includes elements "total_reads" and "total_genomes" from the first line of the PathoID report.*

Description

Loads all data from a set of PathoID reports. For each column in the PathoID report, construct a matrix where the rows are genomes and the columns are samples. Returns a list where each element is named according to the PathoID column. For example, ret[["Final.Best.Hit.Read.Numbers"]] on the result of this function will get you the final count matrix. Also includes elements "total_reads" and "total_genomes" from the first line of the PathoID report.

Usage

```
loadPathoscopeReports(reportfiles, nrows = NULL)
```

Arguments

reportfiles	Paths to report files
nrows	Option to read first N rows of PathoScope reports

Value

Returns a list where each element is named according to the PathoID column. For example, `ret[["Final.Best.Hit.Read.Numbers"]]` on the result of this function will get you the final count matrix. Also includes elements "total_reads" and "total_genomes" from the first line of the PathoID report.

Examples

```
input_dir <- system.file("example/data", package = "PathoStat")
reportfiles <- list.files(input_dir, pattern = "*-sam-report.tsv",
full.names = TRUE)
```

loadPstat

Load the R data(.rda) file with pathostat object

Description

Load the R data(.rda) file with pathostat object

Usage

```
loadPstat(indir = ".", inFileName = "pstat_data.rda")
```

Arguments

indir	Input Directory of the .rda file
infileName	File name of the .rda file

Value

pstat pathostat object (NULL if it does not exist)

Examples

```
data_dir <- system.file("data", package = "PathoStat")
infileName <- "pstat_data.rda"
pstat <- loadPstat(data_dir, infileName)
```

log2CPM	<i>Compute log2(counts per mil reads) and library size for each sample</i>
---------	--

Description

Compute log2(counts per mil reads) and library size for each sample

Usage

```
log2CPM(qcounts, lib.size = NULL)
```

Arguments

qcounts	quantile normalized counts
lib.size	default is colsums(qcounts)

Value

list containing log2(quantile counts per mil reads) and library sizes

Examples

```
log2CPM(matrix(1:12, nrow = 3))
```

L00AUC_simple_multiple_noplot_one_df
<i>LOOCV</i>

Description

LOOCV

Usage

```
L00AUC_simple_multiple_noplot_one_df(df, targetVec)
```

Arguments

df	Row is sample, column is feature. Required
targetVec	y vector. Required

Value

mean auc

Examples

```
data('iris')
LOOAUC_simple_multiple_noplot_one_df(iris[,1:4],
c(rep(1,100), rep(0,50)))
```

LOOAUC_simple_multiple_one_df	<i>LOOCV with ROC curve</i>
-------------------------------	-----------------------------

Description

LOOCV with ROC curve

Usage

```
LOOAUC_simple_multiple_one_df(df, targetVec)
```

Arguments

df	Row is sample, column is feature. Required
targetVec	y vector. Required

Value

the ROC

Examples

```
data('iris')
LOOAUC_simple_multiple_one_df(iris[,1:4],
c(rep(1,100), rep(0,50)))
```

PathoStat-class	<i>PathoStat class to store PathoStat input data including phyloseq object</i>
-----------------	--

Description

Contains all currently-supported BatchQC output data classes:

Details

- slots:
- average_count** a single object of class otu_tableOrNULL
 - besthit_count** a single object of class otu_tableOrNULL
 - highconf_count** a single object of class otu_tableOrNULL
 - lowconf_count** a single object of class otu_tableOrNULL

Examples

```
otumat = matrix(sample(1:100, 100, replace = TRUE), nrow = 10, ncol = 10)
rownames(otumat) <- paste0("OTU", 1:nrow(otumat))
colnames(otumat) <- paste0("Sample", 1:ncol(otumat))
taxmat = matrix(sample(letters, 70, replace = TRUE),
nrow = nrow(otumat), ncol = 7)
rownames(taxmat) <- rownames(otumat)
colnames(taxmat) <- c("Domain", "Phylum", "Class",
"Order", "Family", "Genus", "Species")
OTU = phyloseq::otu_table(otumat, taxa_are_rows = TRUE)
TAX = phyloseq::tax_table(taxmat)
physeq = phyloseq::phyloseq(OTU, TAX)
pathostat1(physeq)
```

percent	<i>Compute percentage</i>
---------	---------------------------

Description

Compute percentage

Usage

```
percent(x, digits = 2, format = "f")
```

Arguments

- x a number or a vector
- digits how many digit of percentage
- format numeric format, "f" for float

Value

the percentage

Examples

```
pecent.vec <- percent(c(0.9, 0.98))
```

phyloseq_to_edgeR	Convert phyloseq OTU count data into DGEList for edgeR package
Description	
Further details.	
Usage	
phyloseq_to_edgeR(physeq, group, method = "RLE", ...)	
Arguments	
physeq	(Required).
group	(Required). A character vector or factor giving the experimental group/condition for each sample/library.
method	(Optional).
...	Additional arguments passed on to
Value	
dispersion	
Examples	
<pre>data_dir_test <- system.file("data", package = "PathoStat") pstat_test <- loadPstat(indir=data_dir_test, inFile="pstat_data_2_L1.rda") phyloseq_to_edgeR(pstat_test, group="Sex")</pre>	
plotPCAPlotly	Plot PCA

Description

Plot PCA

Usage

```
plotPCAPlotly(df.input, condition.color.vec,
  condition.color.name = "condition", condition.shape.vec = NULL,
  condition.shape.name = "condition", columnTitle = "Title",
  pc.a = "PC1", pc.b = "PC2")
```

Arguments

<code>df.input</code>	Input data object that contains the data to be plotted. Required
<code>condition.color.vec</code>	color vector. Required
<code>condition.color.name</code>	color variable name. Required
<code>condition.shape.vec</code>	shape vector. Required
<code>condition.shape.name</code>	shape variable name. Required
<code>columnTitle</code>	Title to be displayed at top of heatmap.
<code>pc.a</code>	pc.1
<code>pc.b</code>	pc.2

Value

the plot

Examples

```
data('iris')
plotPCoAPlotly(t(iris[,1:4]),
condition.color.vec = c(rep(1,100), rep(0,50)),
condition.shape.vec = c(rep(0,100), rep(1,50)))
```

plotPCoAPlotly

Plot PCoA

Description

Plot PCoA

Usage

```
plotPCoAPlotly(physeq.input, condition.color.vec,
condition.color.name = "condition", condition.shape.vec = NULL,
condition.shape.name = "condition", method = "bray",
columnTitle = "Title", pc.a = "Axis.1", pc.b = "Axis.2")
```

Arguments

`physeq.input` Input data object that contains the data to be plotted. Required
`condition.color.vec` color vector. Required
`condition.color.name` color variable name. Required
`condition.shape.vec` shape vector. Required
`condition.shape.name` shape variable name. Required
`method` which distance metric
`columnTitle` Title to be displayed at top of heatmap.
`pc.a` pc.1
`pc.b` pc.2

Value

the plot

Examples

```

data_dir_test <- system.file("data", package = "PathoStat")
pstat_test <- loadPstat(indir=data_dir_test,
  inFile="pstat_data_2_L1.rda")
plotPCoAPlotly(pstat_test, condition.color.vec = rbinom(33,1,0.5),
  condition.shape.vec = rbinom(33,1,0.5))

```

pstat_data

pathostat object generated from example pathoscope report files

Description

This example data consists of 33 samples from a diet study with 11 subjects taking 3 different diets in random order

Usage

pstat

Format

pathostat object extension of phyloseq-class experiment-level object:

otu_table OTU table with 41 taxa and 33 samples

sample_data Sample Data with 33 samples by 18 sample variables

tax_table Taxonomy Table with 41 taxa by 9 taxonomic ranks

sample_data Phylogenetic Tree with 41 tips and 40 internal nodes

Value

pathostat object

readPathoscopeData	<i>Reads the data from PathoScope reports and returns a list of final guess relative abundance and count data</i>
--------------------	---

Description

Reads the data from PathoScope reports and returns a list of final guess relative abundance and count data

Usage

```
readPathoscopeData(input_dir = ".",
  pathoreport_file_suffix = "-sam-report.tsv", use.input.files = FALSE,
  input.files.path.vec = NULL, input.files.name.vec = NULL)
```

Arguments

input_dir	Directory where the tsv files from PathoScope are located
pathoreport_file_suffix	PathoScope report files suffix
use.input.files	whether input dir to pathoscope files or directly pathoscope files
input.files.path.vec	vector of pathoscope file paths
input.files.name.vec	vector of pathoscope file names

Value

List of final guess relative abundance and count data

Examples

```
example_data_dir <- system.file("example/data", package = "PathoStat")
pathoreport_file_suffix <- "-sam-report.tsv"
datlist <- readPathoscopeData(example_data_dir, pathoreport_file_suffix,
  input.files.name.vec = as.character(1:6))
```

runPathoStat	<i>Statistical Microbiome Analysis on the pathostat input and generates a html report and produces interactive shiny app plots</i>
--------------	--

Description

Statistical Microbiome Analysis on the pathostat input and generates a html report and produces interactive shiny app plots

Usage

```
runPathoStat(pstat = NULL, report_dir = ".",
             report_option_binary = "11111111", interactive = TRUE)
```

Arguments

pstat	phyloseq extension pathostat object
report_dir	Output report directory path
report_option_binary	9 bits Binary String representing the plots to display and hide in the report
interactive	when TRUE, opens the interactive shinyApp

Value

outfile The output file with all the statistical plots

Examples

```
runPathoStat(interactive = FALSE)
```

savePstat	<i>Save the pathostat object to R data(.rda) file</i>
-----------	---

Description

Save the pathostat object to R data(.rda) file

Usage

```
savePstat(pstat, outdir = ".", outfileName = "pstat_data.rda")
```

Arguments

pstat	pathostat object
outdir	Output Directory of the .rda file
outfileName	File name of the .rda file

Value

outfile .rda file

Examples

```
data_dir_test <- system.file("data", package = "PathoStat")
pstat_test <- loadPstat(indir=data_dir_test,
  inFile="pstat_data_2_L1.rda")
outfile <- savePstat(pstat_test)
```

setShinyInput	<i>Setter function to set the shinyInput option</i>
---------------	---

Description

Setter function to set the shinyInput option

Usage

```
setShinyInput(x)
```

Arguments

x	shinyInput option
---	-------------------

Value

shinyInput option

Examples

```
setShinyInput(NULL)
```

setShinyInputCombat	<i>Setter function to set the shinyInputCombat option</i>
---------------------	---

Description

Setter function to set the shinyInputCombat option

Usage

```
setShinyInputCombat(x)
```

Arguments

x	shinyInputCombat option
---	-------------------------

Value

shinyInputCombat option

Examples

```
setShinyInputCombat(NULL)
```

setShinyInputOrig	<i>Setter function to set the shinyInputOrig option</i>
-------------------	---

Description

Setter function to set the shinyInputOrig option

Usage

```
setShinyInputOrig(x)
```

Arguments

x	shinyInputOrig option
---	-----------------------

Value

shinyInputOrig option

Examples

```
setShinyInputOrig(NULL)
```

summarizeTable	<i>Summarize sample</i>
----------------	-------------------------

Description

Creates a table of summary metrics

Usage

```
summarizeTable(pstat)
```

Arguments

pstat	Input pstat
-------	-------------

Value

A data.frame object of summary metrics.

Examples

```
data_dir_test <- system.file("data", package = "PathoStat")
pstat_test <- loadPstat(indir=data_dir_test,
  inFile="pstat_data_2_L1.rda")
st.tmp <- summarizeTable(pstat_test)
```

TranslateIdToTaxLevel *Find the taxonomy for the given taxon id name*

Description

Find the taxonomy for the given taxon id name

Usage

```
TranslateIdToTaxLevel(pstat, input.id.vec, tax.level)
```

Arguments

pstat	pathostat object
input.id.vec	names containing id
tax.level	target taxon level

Value

target taxon level names

Examples

```
data_dir_test <- system.file("data", package = "PathoStat")
pstat_test <- loadPstat(indir=data_dir_test,
  inFile="pstat_data_2_L1.rda")
names.new <- TranslateIdToTaxLevel(pstat_test,
  c("ti|862962|org|Bacteroides_fragilis_638R",
    "ti|697329|org|Ruminococcus_albus_7" ),
  "genus")
```

Wilcox_Test_df	<i>Mann-whitney test for a dataframe</i>
----------------	--

Description

Mann-whitney test for a dataframe

Usage

```
Wilcox_Test_df(df, label.vec.num, pvalue.cutoff = 0.05)
```

Arguments

- df Input data object that contains the data to be tested. Required
- label.vec.num The target binary condition. Required
- pvalue.cutoff choose p-value cut-off

Value

df.output object

Examples

```
data('iris')
Wilcox_Test_df(t(iris[,1:4]),
c(rep(1,100), rep(0,50)))
```

Index

- * **datasets**
 - pstat_data, [18](#)
- Bootstrap_LOOCV_LR_AUC, [3](#)
- Chisq_Test_Pam, [4](#)
- findRAfromCount, [4](#)
- findTaxonMat, [5](#)
- findTaxonomy, [6](#)
- findTaxonomy300, [6](#)
- Fisher_Test_Pam, [7](#)
- formatTaxTable, [8](#)
- GET_PAM, [8](#)
- getShinyInput, [9](#)
- getShinyInputCombat, [9](#)
- getShinyInputOrig, [10](#)
- getSignatureFromMultipleGlmnet, [10](#)
- grepTid, [11](#)
- loadPathoscopeReports, [11](#)
- loadPstat, [12](#)
- log2CPM, [13](#)
- LOOAUC_simple_multiple_noplot_one_df, [13](#)
- LOOAUC_simple_multiple_one_df, [14](#)
- PathoStat-class, [14](#)
- pathostat1 (PathoStat-class), [14](#)
- percent, [15](#)
- phyloseq_to_edgeR, [16](#)
- plotPCAPlotly, [16](#)
- plotPCoAPlotly, [17](#)
- pstat (pstat_data), [18](#)
- pstat_data, [18](#)
- readPathoscopeData, [19](#)
- runPathoStat, [20](#)
- savePstat, [20](#)
- setShinyInput, [21](#)
- setShinyInputCombat, [21](#)
- setShinyInputOrig, [22](#)
- summarizeTable, [22](#)
- TranslateIdToTaxLevel, [23](#)
- Wilcox_Test_df, [24](#)