Package: RFGeneRank (via r-universe)

November 1, 2026

Title RFGeneRank: Cross-validated Stable Predictive Gene Ranking for Transcriptomics

Version 1.1.0

Description Tools to harmonize bulk RNA-seq matrices, optionally apply batch correction, and train cross-validated classification models using ranger, glmnet, or xgboost. Supports leakage-safe feature selection, permutation importance, SHAP-based interpretability, and calibration methods (Platt or isotonic). Provides stability metrics across folds, embeddings (PCA/UMAP), ROC visualization, SHAP dependence plots, and tidy ranked-gene tables for downstream analysis.

License MIT + file LICENSE

URL https://github.com/Abdulaziz-Albeshri/RFGeneRank

BugReports https://github.com/Abdulaziz-Albeshri/RFGeneRank/issues

Depends R (>= 4.5.0)

Imports ggplot2, limma, methods, pROC, ranger, stats, SummarizedExperiment, sva, AnnotationDbi, umap, scales, utils, S4Vectors, digest, mgcv, Matrix, glmnet, xgboost, patchwork

Suggests GEOquery, Biobase, edgeR, uwot, BiocStyle, knitr, org.Hs.eg.db, rmarkdown, DESeq2, MASS, matrixStats, BiocGenerics, fastshap, caret, testthat (>= 3.0.0), covr

Config/testthat/edition 3

VignetteBuilder knitr

biocViews Transcriptomics, RNASeq, GeneExpression, FeatureExtraction, Classification, Visualization, Software, StatisticalMethod, Alignment

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Collate 'globals.R' 'class_def.R' 'accessors.R' 'accessors_public.R'
'check_utils.R' 'batch_correct.R' 'calibrate.R'
'combat_helpers.R' 'compute_class_weights.R' 'confounding.R'
'crossval.R' 'id_map.R' 'plots_all.R' 'prepare_data.R'
'align_datasets.R' 'rank_genes.R' 'top_genes.R' 'Rzzz.R'
'package-doc.R' 'sign_importance.R' 'factor_dependence.R'
'validate_genes.R'

NeedsCompilation no

Config/pak/sysreqs make libpng-dev libxml2-dev libssl-dev python3 zlib1g-dev

Repository https://bioc.r-universe.dev

Date/Publication 2026-04-28 13:06:49 UTC

RemoteUrl https://github.com/bioc/RFGeneRank

RemoteRef HEAD

RemoteSha 6ba66af81a926961ca5fe509ae40b7865bbd5ee6

Contents

align_datasets . . . 3
apply_calibration . . . 5
calibrate_oof . . . 5
factor_dependence . . . 6
GeneRankFit-accessors . . . 8
id_map . . . 10
plot_confusion_heatmap . . . 11
plot_embed . . . 11
plot_embed_expr . . . 13
plot_importance . . . 14
plot_roc . . . 15
plot_roc_multi . . . 16
plot_shap_dependence . . . 17
plot_sign_importance . . . 19
prepare_data . . . 20
rank_genes . . . 22
rfgr_crossval . . . 24
rfgr_plot_suite . . . 25
shap_train_ranger . . . 27
sign_importance . . . 28
top_genes . . . 30
validate_genes . . . 31

Index **34**

`align_datasets` *Align and merge expression + metadata (genes by intersection; strict sample match)*

Description

`align_datasets()` ingests parallel lists of expression tables (matrices/data.frames) and metadata data.frames, cleans them, enforces strict sample alignment (`rownames(metadata) == colnames(expression)`), drops metadata rows with any NA (with a warning + structured report), merges by the intersection of genes, and returns the merged expression, metadata, and a `SummarizedExperiment` with gene IDs locked into `rowData(se)$gene_id`.

No regex recoding is performed. If a dataset lacks a `batch` column and `require_batch=TRUE`, a per-dataset batch factor ("Batch1", "Batch2", ...) is created.

Usage

```
align_datasets(
  expr_list,
  meta_list,
  prefer = NULL,
  require_batch = TRUE,
  tag_dataset = TRUE,
  gene_merge = "intersection",
  verbose = TRUE
)
```

Arguments

`expr_list`	list of matrices or data.frames; rows = genes, cols = samples. If a data.frame contains a gene-ID column, it will be moved into rownames. All expression values are coerced to numeric (double).
`meta_list`	list of data.frames; rows = samples (must be in rownames). Must contain a `state` column and (if `require_batch=TRUE`) a `batch` column. If `batch` is missing, it is auto-created per dataset as "Batch1", "Batch2", etc.
`prefer`	optional selector/renamer for metadata columns. Two forms are supported: • index form: c("2:state","5:batch") (select column 2 and 5, rename to state,batch) • name map: c("state=phenotype","batch=plate") (select phenotype, rename to state, etc.) Accepts either a single character vector applied to all datasets, or a named list specifying datasets individually. with one vector per dataset (names must match names(expr_list)/names(meta_list)). No value recoding is performed.
`require_batch`	logical (default TRUE). If TRUE and a dataset lacks `batch`, create a per-dataset batch factor ("Batch1", "Batch2", etc.).
`tag_dataset`	logical (default TRUE). If TRUE, add a `dataset` factor ("ds1","ds2",...) to the merged metadata.

gene_merge	character(1), default "intersection". Currently only intersection is supported (keeps only genes shared by all datasets).
verbose	logical. If TRUE (default), prints a brief summary and per-dataset stats.

Value

A list with:

expr Merged numeric matrix (genes x samples) with syntactic, unique gene IDs.

metadata Merged metadata (samples as rownames) with state/batch as factors.

se A SummarizedExperiment with assay "expr", colData = metadata, and rowData(se)$gene_id set to current rownames.

report List with per-dataset input/kept counts, NA-drop details, observed levels, and final shared-gene count.

Align and merge expression + metadata ...

Examples

```
# Single toy dataset: expression matrix (genes x samples)
expr <- matrix(
  rnorm(5 * 4),
  nrow = 5,
  dimnames = list(
    paste0("gene", 1:5),
    paste0("s1_", 1:4)
  )
)

# Matching metadata: one row per sample, with 'state' and 'batch' columns
meta <- data.frame(
  state = rep("Control", ncol(expr)),
  batch = rep("A",       ncol(expr))
)
rownames(meta) <- colnames(expr)

# Lists of length 1 for expression and metadata
expr_list <- list(A = expr)
meta_list <- list(A = meta)

aligned <- align_datasets(
  expr_list = expr_list,
  meta_list = meta_list
)
str(aligned)
```

apply_calibration *Apply stored calibration to a numeric vector of probabilities*

Description

Apply stored calibration to a numeric vector of probabilities

Usage

```
apply_calibration(fit, p)
```

Arguments

fit	GeneRankFit with stored calibration information.
p	numeric vector of positive-class probabilities

Value

numeric vector of calibrated probabilities (or original if none stored)

Examples

```
# Example probabilities
p <- runif(5)

# Minimal GeneRankFit without calibration (returns original p)
fit0 <- methods::new("GeneRankFit")
apply_calibration(fit0, p)
```

calibrate_oof *Calibrate out-of-fold probabilities (isotonic or Platt)*

Description

Fits a calibration model on the out-of-fold (OOF) positive-class probabilities and stores it inside the GeneRankFit object. No data leakage: uses OOF only.

Usage

```
calibrate_oof(fit, method = c("isotonic", "platt"))
```

Arguments

fit	GeneRankFit containing out-of-fold predictions and labels.
method	"isotonic" or "platt"

Value

GeneRankFit with stored calibration information.

Examples

```
# Example probabilities
p <- runif(5)

# Case 1: no calibration stored → returns original p
fit0 <- methods::new("GeneRankFit")
apply_calibration(fit0, p)

# Case 2: simple calibration function (illustration)
fit1 <- methods::new("GeneRankFit")
calibration(fit1) <- list(fun = function(x) x^0.8)
apply_calibration(fit1, p)
```

---

factor_dependence *Covariate dependence of gene contributions (SHAP/proxy; "expr" assay)*

Description

Covariate dependence of gene contributions (SHAP/proxy; "expr" assay)

Usage

```
factor_dependence(
  fit,
  se,
  covariates,
  method = c("shap", "proxy"),
  ngenes = 500L,
  gene_selection = c("importance", "variance"),
  nsim = 128L,
  bg_per_class = 64L,
  cache_dir = NULL,
  fdr_method = "BH",
  seed = 1L,
  pred_fun = NULL,
  pos_label = NULL,
  positive = NULL
)
```

Arguments

fit	Trained object containing out-of-fold predictions (n x k) and labels. For S4 wrappers (e.g., GeneRankFit), the finalized learner should be in A final fitted model and the training feature names may also be present. this function will train a temporary full-data model on-the-fly (not saved).
se	SummarizedExperiment with assay "expr" (genes x samples).
covariates	Character vector of covariate names in colData(se), e.g. c("sex","age").
method	"shap" (default; uses fastshap if available) or "proxy".
ngenes	Number of genes to test (default 500). Use "ALL" or NULL for all genes.
gene_selection	"importance" (default) or "variance".
nsim	SHAP Monte-Carlo permutations (default 128).
bg_per_class	Max background samples per class for SHAP (default 64).
cache_dir	Cache directory for SHAP matrices; default R user cache dir.
fdr_method	Multiple-testing correction (default "BH").
seed	RNG seed (default 1).
pred_fun	OPTIONAL user predictor: function(newdata) -> numeric p(positive). If provided, it takes precedence over the built-in predictor.
pos_label	OPTIONAL (legacy) positive class label; kept for back-compat.
positive	OPTIONAL override for positive class. Either a class label (character) or an index 1/2. If provided, it overrides pos_label.

Value

data.frame with columns: gene, covariate, test, stat, pval, fdr, effect, dependent. Attributes: "method","assay","genes_used","

Examples

```
#' # For reproducibility, set a fixed seed such as set.seed(1) before running this example.

# Tiny expression matrix
expr <- matrix(stats::rnorm(30), nrow = 6)
rownames(expr) <- paste0("gene", 1:6)
colnames(expr) <- paste0("sample", 1:5)

# Covariates
cd <- data.frame(
  label = factor(c("A", "A", "B", "B", "B")),
  sex   = factor(c("M", "F", "F", "M", "M")),
  age   = c(30, 40, 35, 50, 60)
)

se <- SummarizedExperiment::SummarizedExperiment(
  assays  = list(expr = expr),
  colData = cd
)
```

```
# Minimal mock GeneRankFit object with required slots
prob_mat <- matrix(
  stats::runif(5),
  ncol = 1,
  dimnames = list(colnames(se), "B")
)

fit <- methods::new(
  "GeneRankFit",
  oof = list(
    prob = prob_mat,
    y    = cd$label
  )
)
```

GeneRankFit-accessors *Accessors for GeneRankFit*

Description

Getter/setter accessors for GeneRankFit slots.

Usage

```
params(x)

## S4 method for signature 'GeneRankFit'
params(x)

oof(x)

## S4 method for signature 'GeneRankFit'
oof(x)

imp(x)

## S4 method for signature 'GeneRankFit'
imp(x)

imp(x) <- value

## S4 replacement method for signature 'GeneRankFit'
imp(x) <- value

calibration(x)

## S4 method for signature 'GeneRankFit'
```

```
calibration(x)

calibration(x) <- value

## S4 replacement method for signature 'GeneRankFit'
calibration(x) <- value
```

Arguments

x	A GeneRankFit object.
value	Replacement value.

Value

For getters:

`params(x)` A list of training parameters and metadata.

`oof(x)` A list of out-of-fold results including predictions and labels.

`imp(x)` A `data.frame` containing aggregated variable importance scores.

`calibration(x)` A list describing calibration settings.

For setters:

`imp(x) <- value` Returns the updated GeneRankFit object with modified importance data.

`calibration(x) <- value` Returns the updated GeneRankFit object with modified calibration settings.

Examples

```
fit <- methods::new("GeneRankFit")

# getters
params(fit)
oof(fit)
imp(fit)
calibration(fit)

# setters
imp(fit) <- data.frame(
  gene = c("GeneA", "GeneB"),
  importance = c(0.8, 0.3)
)
calibration(fit) <- list(
  method = "platt",
  fun = function(p) p
)

imp(fit)
calibration(fit)
```

id_map *Map gene identifiers using AnnotationDbi*

Description

A thin wrapper around `AnnotationDbi::select()` that preserves input preserves order and enables straightforward conversion between identifier types (e.g., ENTREZID → SYMBOL).

Usage

```
id_map(
  keys,
  from,
  to,
  OrgDb = org.Hs.eg.db::org.Hs.eg.db,
  drop_na = TRUE,
  unique = TRUE
)
```

Arguments

`keys`	character vector of gene IDs to map (e.g., ENTREZ IDs).
`from`	source keytype (e.g., "ENTREZID", "ENSEMBL", "SYMBOL").
`to`	destination keytype (e.g., "SYMBOL").
`OrgDb`	an `OrgDb` object. Defaults to `org.Hs.eg.db`.
`drop_na`	logical; if TRUE, drop rows with missing mapped values.
`unique`	logical; if TRUE, keep at most one mapping per input key, preferring the first match returned by `AnnotationDbi::select()`.

Value

data.frame with columns `from`, `to` in that order.

Examples

```
if (requireNamespace("org.Hs.eg.db", quietly = TRUE)) {
  x <- c("7157", "7158")  # ENTREZ IDs
  id_map(x, from = "ENTREZID", to = "SYMBOL")
}
```

plot_confusion_heatmap *Confusion-matrix heatmap*

Description

Confusion-matrix heatmap

Usage

```
plot_confusion_heatmap(cm, mode = c("counts", "rowpct"))
```

Arguments

cm	A 2x2 table as returned by val$<method>$conf_mat.
mode	Either "counts" or "rowpct".

Value

A ggplot object.

Examples

```
# For reproducibility, specify a fixed seed (e.g., set.seed(1)) before running this example.

true <- factor(rep(c("A", "B"), each = 5))
pred <- factor(sample(c("A", "B"), 10, replace = TRUE))

tab <- table(True = true, Predicted = pred)

plot_confusion_heatmap(tab)
```

plot_embed *Decision-space embedding (OOF probability space): PCA or UMAP*

Description

Embeds samples using the out-of-fold (OOF) probability space (2D). Good for inspecting decision geometry; for biology structure, prefer plot_embed_expr().

Usage

```
plot_embed(
  fit,
  type = c("pca", "umap"),
  engine = c("umap", "uwot"),
  neighbors = NULL,
  min_dist = NULL,
  metric = NULL,
  seed = NULL,
  point_size = 2,
  show_legend = TRUE,
  palette = NULL
)
```

Arguments

fit	GeneRankFit (must have OOF probabilities).
type	"pca" or "umap".
engine	UMAP engine if type="umap" ("umap" or "uwot").
neighbors, min_dist, metric, seed	UMAP params.
point_size	numeric
show_legend	logical
palette	optional manual color palette

Value

A ggplot object.

Examples

```
# For reproducibility, specify a fixed seed (e.g., set.seed(1)) before running this example.

# Toy 2D embedding for 10 samples
embed_df <- data.frame(
  sample = paste0("sample", 1:10),
  dim1   = rnorm(10),
  dim2   = rnorm(10),
  label  = factor(rep(c("A", "B"), each = 5))
)

head(embed_df)
```

`plot_embed_expr` *Expression-space embedding (PCA or UMAP) of top RF genes*

Description

Plots samples in the original expression space using the top RF-ranked genes. For PCA, axis labels include the percent variance explained. For UMAP, the title shows the engine and key parameters used.

Usage

```
plot_embed_expr(
  fit,
  se,
  n_top = 100,
  type = c("umap", "pca"),
  engine = c("umap", "uwot"),
  neighbors = 15,
  min_dist = 0.1,
  metric = "euclidean",
  zscore = TRUE,
  seed = NULL,
  point_size = 2,
  show_legend = TRUE,
  palette = NULL
)
```

Arguments

`fit`	GeneRankFit
`se`	SummarizedExperiment with assay "expr"
`n_top`	integer; number of top RF genes to use (default 100)
`type`	"umap" or "pca"
`engine`	UMAP engine, "umap" or "uwot" (used when type="umap")
`neighbors`, `min_dist`, `metric`	UMAP parameters
`zscore`	Logical; z-score samples x genes matrix before embedding (default TRUE)
`seed`	RNG seed for UMAP reproducibility (default uses stored pipeline seed if available).
`point_size`	numeric
`show_legend`	logical
`palette`	optional named vector of colors (names must match levels)

Value

A ggplot object.

Examples

```
# For reproducibility, specify a fixed seed (e.g., set.seed(1)) before running this example.

# Toy expression: 15 genes × 8 samples
expr <- matrix(rnorm(15 * 8), nrow = 15)
rownames(expr) <- paste0("gene", 1:15)
colnames(expr) <- paste0("sample", 1:8)

# Binary labels for samples
label <- factor(rep(c("A", "B"), each = 4))

se <- SummarizedExperiment::SummarizedExperiment(
  assays  = list(expr = expr),
  colData = data.frame(label = label)
)

se
```

---

plot_importance *Feature importance (top genes)*

Description

Uses fold-normalized mean importances aggregated across CV folds. To display gene SYMBOLs on the axes, set `map_to_symbol = TRUE`. (requires org.Hs.eg.db and RFGeneRank::top_genes()).

Usage

```
plot_importance(
  fit,
  top = 30,
  map_to_symbol = FALSE,
  from = "ENTREZID",
  to = "SYMBOL"
)
```

Arguments

`fit`	GeneRankFit from `rank_genes()`.
`top`	Integer; number of genes to display (default 30).
`map_to_symbol`	Logical; map gene IDs to symbols if available (default FALSE).
`from`	Keytype for input IDs (default "ENTREZID").
`to`	Keytype for output labels (default "SYMBOL").

Value

A ggplot object.

Examples

```
# Toy expression matrix: genes x samples
expr <- matrix(
  rnorm(10 * 20),
  nrow = 10,
  dimnames = list(
    paste0("gene", 1:10),
    paste0("sample", 1:20)
  )
)

# Binary phenotype stored in 'label' column
y <- factor(rep(c("Control", "Case"), each = 10))

se <- SummarizedExperiment::SummarizedExperiment(
  assays  = list(expr = expr),
  colData = data.frame(
    label    = y,
    row.names = colnames(expr)
  )
)

# Fit a small GeneRank model (note: no 'genes' argument)
fit <- rank_genes(
  se        = se,
  label_col = "label",
  n_top     = 10,
  trees     = 200
)

# Plot feature importance for the top-ranked genes
plot_importance(fit)
```

---

plot_roc *ROC curve from OOF probabilities (single model)*

Description

ROC curve from OOF probabilities (single model)

Usage

```
plot_roc(fit)
```

Arguments

fit	GeneRankFit with stored out-of-fold predictions and labels.

Value

A ggplot2 object containing the ROC curve derived from

Examples

```
expr <- matrix(
  rnorm(10 * 20),
  nrow = 10,
  dimnames = list(
    paste0("gene", 1:10),
    paste0("sample", 1:20)
  )
)

y <- factor(rep(c("Control", "Case"), each = 10))

se <- SummarizedExperiment::SummarizedExperiment(
  assays  = list(expr = expr),
  colData = data.frame(state = y)
)

fit <- rank_genes(se, label_col = "state", trees = 100)
plot_roc(fit)
```

---

plot_roc_multi *Multi-model ROC (guardrailed OOF)*

Description

Overlays ROC curves for one or more fits that expose $oof with p_use and y. Works with validate_genes() outputs.

Usage

```
plot_roc_multi(fits, title = "ROC (OOF, guardrailed)")
```

Arguments

fits	Named list of model results (e.g., list(ranger=val$ranger, ...)).
title	Character plot title.

Value

A ggplot object.

Examples

```
# Toy binary outcome
y <- factor(rep(c("Control", "Case"), each = 10))

# Positive-class probabilities (Case = positive class)
p_use1 <- runif(20)
p_use2 <- runif(20)

# Create minimal fit objects expected by plot_roc_multi()
fits <- list(
  Model_1 = list(
    oof = list(
      y = y,
      p_use = p_use1
    )
  ),
  Model_2 = list(
    oof = list(
      y = y,
      p_use = p_use2
    )
  )
)

plot_roc_multi(fits)
```

---

plot_shap_dependence *SHAP dependence scatter for one gene (cached-first, robust, fast)*

Description

SHAP dependence scatter for one gene (cached-first, robust, fast)

Usage

```
plot_shap_dependence(
  fit,
  se,
  gene,
  x = "age",
  color_by = NULL,
  palette = NULL,
  shap_mat = NULL,
  nsim = 64,
  pos_label = NULL,
  age_band_width = 10,
  band_alpha = 0.12,
  band_mode = c("significant", "top_k"),
  top_k = 1
)
```

Arguments

fit	GeneRankFit containing out-of-fold predictions and labels.
se	SummarizedExperiment with assay "expr".
gene	Character gene ID present in assay(se,"expr").
x	Covariate name in colData(se) for x-axis (default "age").
color_by	Optional grouping column name in colData(se); if NULL, no colour grouping.
palette	Optional character vector of colour names or hex codes. If color_by is: • numeric: palette (length >= 2) is used as a continuous gradient via scale_color_gradientn(). • categorical: palette is recycled/trimmed to the number of levels and used via scale_color_manual(). If palette is NULL, ggplot2 defaults are used, except for color_by = "sex" / "sex_clean" where a fixed pink/cyan palette is used.
shap_mat	Optional SHAP matrix (rows = samples, cols = genes).
nsim	Fastshap nsim if auto-computing (default 64).
pos_label	Positive class label (defaults to level 2 of outcome).
age_band_width	Width of shaded age bands (years) for sex plots.
band_alpha	Alpha of bands.
band_mode	"significant" (FDR<=0.05) or "top_k".
top_k	If band_mode="top_k", how many bins per group to shade.

Value

ggplot object.

Examples

```
expr <- matrix(
  rnorm(10 * 20),
  nrow = 10,
  dimnames = list(
    paste0("gene", 1:10),
    paste0("sample", 1:20)
  )
)

y <- factor(rep(c("Control", "Case"), each = 10))

se <- SummarizedExperiment::SummarizedExperiment(
  assays  = list(expr = expr),
  colData = data.frame(
    state = y,
    age   = seq_len(20) + 40
  )
)
```

```
fit <- rank_genes(se, label_col = "state", trees = 50)

# Minimal SHAP-like matrix: one column named by the gene
shap_mat <- matrix(
  rnorm(20),
  nrow = 20,
  dimnames = list(NULL, "gene1")
)

plot_shap_dependence(
  fit      = fit,
  se       = se,
  gene     = "gene1",
  x        = "age",
  shap_mat = shap_mat
)
```

`plot_sign_importance` *Signed feature importance (directional effect)*

Description

Visualizes direction-aware importances produced by `sign_importance()`. If `tab` is NULL, the function will try to read the stored importance table and require a `signed_importance` column to be present there.

Usage

```
plot_sign_importance(
  fit = NULL,
  tab = NULL,
  top = 30,
  map_to_symbol = FALSE,
  from = "ENTREZID",
  to = "SYMBOL",
  show_legend = TRUE,
  palette = NULL
)
```

Arguments

`fit`	GeneRankFit (optional if `tab` is supplied)
`tab`	data.frame from `sign_importance()` with columns: gene, importance, direction (-1/0/1), signed_importance
`top`	Integer; number of genes to show (default 30)
`map_to_symbol`	Logical; map x-axis labels to SYMBOLs (default FALSE)
`from`	Keytype for input IDs (default "ENTREZID")

to	Keytype for output labels (default "SYMBOL")
show_legend	Logical; show legend (default TRUE)
palette	Optional named vector for fill colors, e.g. c(`-1`="#3182bd", `1`="#de2d26", `0`="#9e9e9e")

Value

A ggplot object.

Examples

```
# Toy signed importance table for 5 genes
signed_imp <- data.frame(
  gene        = paste0("gene", 1:5),
  importance  = c(0.5, 0.4, 0.3, 0.2, 0.1),
  signed_effect = c(0.5, -0.4, 0.3, -0.2, 0.1)
)

head(signed_imp)
```

---

prepare_data *Prepare matrices + metadata: align, (log) transform, batch correct, prefilter*

Description

Prepare matrices + metadata: align, (log) transform, batch correct, prefilter

Usage

```
prepare_data(
  mats,
  metas,
  label_col,
  batch_col = NULL,
  n_var = 5000,
  log1p = TRUE,
  batch_method = c("none", "combat", "limma", "combat_seq"),
  counts = FALSE,
  filter_in_cv = FALSE,
  batch_correction_scope = c("global", "fold"),
  batch_covariates = NULL
)
```

Arguments

mats	list of numeric matrices (genes-by-samples)
metas	list of data.frames (rownames = sample IDs)
label_col	outcome column in metadata
batch_col	batch column in metadata (or NULL)
n_var	keep top-N variable genes globally (unsupervised)
log1p	logical; log1p transform before variance filter
batch_method	"none","combat","limma","combat_seq"
counts	logical; TRUE if raw counts (for combat_seq)
filter_in_cv	logical; if TRUE, skip global variance filter and let CV do it inside folds
batch_correction_scope	"global" or "fold" (fold correction happens inside CV)
batch_covariates	optional character vector of metadata column names used as covariates in batch correction

Value

SummarizedExperiment

Examples

```
set.seed(1)

expr <- matrix(stats::rnorm(20 * 10), nrow = 20)
rownames(expr) <- paste0("gene", 1:20)
colnames(expr) <- paste0("sample", 1:10)

label  <- factor(rep(c("A", "B"), each = 5))
batch  <- factor(rep(c("batch1", "batch2"), times = 5))

# Build lists of matrices + metadata as expected by prepare_data()
mats  <- list(expr)
metas <- list(data.frame(
  label = label,
  batch = batch,
  row.names = colnames(expr)
))

prep <- prepare_data(
  mats      = mats,
  metas     = metas,
  label_col = "label",
  batch_col = "batch"
)
prep
```

rank_genes *Rank genes with batch-aware cross-validation (UMAP-free)*

Description

Performs CV on a SummarizedExperiment, aggregates fold-normalized feature importances, and stores out-of-fold predictions. Supports K-fold, LOBO (Leave-One-Batch-Out), and group-K by batch. Batch correction, filtering, transforms, and standardization are applied *inside folds* using TRAIN-only statistics. If `auto_confounds=TRUE`, the function inspects batch~label association and will switch to LOBO and enable fold-safe batch correction if confounding is moderate/severe.

Usage

```
rank_genes(
  se,
  label_col = "state",
  n_top = 500,
  k = 5,
  trees = 1000,
  importance = c("permutation", "impurity"),
  class_weights = NULL,
  threads = max(1, parallel::detectCores() - 1),
  seed = 1,
  fold_batch_correction = FALSE,
  batch_col = NULL,
  batch_covariates = NULL,
  filter_low_expr = FALSE,
  min_prop = 0.2,
  transform = c("none", "log1p"),
  standardize = FALSE,
  cv = c("kfold", "lobo", "groupk"),
  auto_confounds = TRUE
)
```

Arguments

se	SummarizedExperiment
label_col	character; class-label column in colData(se)
n_top	integer; per-fold top-variance feature count (0 = off)
k	integer; number of folds (ignored by LOBO)
trees	integer; number of trees for ranger
importance	"permutation" or "impurity"
class_weights	named numeric vector or NULL (auto-computed if NULL and imbalance >= 1.5x)
threads	integer; CPU threads for ranger

seed	integer; RNG seed
fold_batch_correction	logical; if TRUE, do train-only batch removal per fold
batch_col	optional; name of batch column in colData(se)
batch_covariates	optional character vector of covariates for batch model
filter_low_expr	logical; drop genes expressed (>0) in < min_prop of TRAIN
min_prop	numeric in (0,1]; minimum TRAIN proportion to keep a gene
transform	"none" or "log1p"
standardize	logical; z-score by TRAIN mean/SD (applied to train+test)
cv	"kfold", "lobo", or "groupk"
auto_confounds	logical; if TRUE, auto-switch to LOBO and enable fold batch-correction when confounded

Value

GeneRankFit S4 object

Examples

```
# For reproducibility, specify a fixed seed (e.g., set.seed(1)) before running this example.

# Toy expression: 20 genes × 12 samples
expr <- matrix(stats::rnorm(20 * 12), nrow = 20)
rownames(expr) <- paste0("gene", 1:20)
colnames(expr) <- paste0("sample", 1:12)

# Binary labels
label <- factor(rep(c("A", "B"), each = 6))

se <- SummarizedExperiment::SummarizedExperiment(
  assays  = list(expr = expr),
  colData = data.frame(label = label)
)

# Rank genes with default settings
rg <- rank_genes(
  se        = se,
  label_col = "label"
)

str(rg)
```

`rfgr_crossval` *Batch-aware cross-validation with optional ComBat modes (incl. frozen ComBat)*

Description

Orchestrates leakage-safe CV for RFGeneRank with two ComBat modes:

- "none": no batch correction
- "train": train-only batch correction with leakage-safe application to TEST

Supports LOBO (leave-one-batch-out), Group K-Fold by batch, and standard K-Fold.

Usage

```
rfgr_crossval(
  expr,
  metadata,
  label_col = "state",
  batch_col = "batch",
  covariates = NULL,
  cv = c("lobo", "groupk", "kfold"),
  k = 5,
  combat_mode = c("none", "train"),
  rf_trees = 1000,
  seed = 1,
  verbose = TRUE
)
```

Arguments

`expr`	numeric matrix genes x samples (continuous scale: log2CPM or log2(TPM+1))
`metadata`	data.frame with SampleID, label_col, batch_col
`label_col`	character; target column in metadata (e.g., "state")
`batch_col`	character; batch/dataset column in metadata (e.g., "batch")
`covariates`	character vector of column names to *preserve* in ComBat (added to design)
`cv`	one of c("lobo","groupk","kfold")
`k`	integer; number of folds for "groupk" or "kfold"
`combat_mode`	one of c("none","train")
`rf_trees`	integer; number of trees for ranger
`seed`	integer; RNG seed
`verbose`	logical; emit progress messages

Value

list(auc_by_fold, mean_auc, settings, folds_info)

Examples

```
# Minimal runnable example: tiny dataset, fast evaluation
expr <- matrix(rnorm(10 * 6), nrow = 10)
rownames(expr) <- paste0("gene", 1:10)
colnames(expr) <- paste0("sample", 1:6)

label <- factor(rep(c("A", "B"), each = 3))
batch <- factor(rep(c("batch1", "batch2"), times = 3))

metadata <- data.frame(
  label = label,
  batch = batch,
  row.names = colnames(expr)
)

# Lightweight cross-validation: no ComBat, few trees
cv_res <- rfgr_crossval(
  expr        = expr,
  metadata    = metadata,
  label_col   = "label",
  batch_col   = "batch",
  cv          = "kfold",
  k           = 2,
  combat_mode = "none",
  rf_trees    = 10,
  verbose     = FALSE
)

cv_res
```

---

rfgr_plot_suite *One-call plot suite (optional file export)*

Description

Produces: importance, signed-importance, expression PCA, decision PCA, ROC overlay (if `val` provided), confusion heatmaps, and optional SHAP.

Usage

```
rfgr_plot_suite(fit, se, val = NULL, outdir = NULL, top = 30, shap_gene = NULL)
```

Arguments

fit	GeneRankFit from rank_genes().
se	SummarizedExperiment with assay "expr".
val	Optional result from validate_genes().
outdir	Optional directory to save PNGs (if not NULL).
top	Integer; number of genes in importance plots.
shap_gene	Optional gene ID for SHAP dependence.

Value

(Invisibly) list of ggplot objects.

Examples

```
# Toy expression matrix: genes x samples
expr <- matrix(
  rnorm(10 * 12),
  nrow = 10
)

# Use known human Entrez IDs as gene names so annotation works
rownames(expr) <- c(
  "1",    # A1BG
  "2",    # A2M
  "9",    # NAT1
  "1956", # EGFR
  "2064", # ERBB2
  "5290", # PIK3CA
  "5728", # PTEN
  "7422", # VEGFA
  "1950", # EDN1
  "7157"  # TP53
)

colnames(expr) <- paste0("sample", 1:12)

# Binary phenotype stored in 'label' column
label <- factor(rep(c("Control", "Case"), each = 6))

se <- SummarizedExperiment::SummarizedExperiment(
  assays  = list(expr = expr),
  colData = data.frame(
    label     = label,
    row.names = colnames(expr)
  )
)

# Fit a small GeneRank model
fit <- rank_genes(
  se        = se,
```

```
  label_col = "label",
  n_top     = 10,
  trees     = 100
)

# For this example, ensure the stored importance table has signed_importance information
# required by plot_sign_importance().
imp0 <- imp(fit)
if (is.null(imp0)) {
  imp0 <- data.frame(
    gene = character(),
    importance = numeric(),
    direction = integer(),
    signed_importance = numeric(),
    stringsAsFactors = FALSE
  )
}
if (!"direction" %in% colnames(imp0)) {
  imp0$direction <- 1L
}
if (!"signed_importance" %in% colnames(imp0)) {
  imp0$signed_importance <- imp0$importance * imp0$direction
}
imp(fit) <- imp0

# Generate a suite of diagnostic plots (returned as a list of ggplot objects)
plots <- rfgr_plot_suite(fit, se)

# Inspect available plots
names(plots)
```

---

shap_train_ranger *Compute a SHAP matrix using a single ranger model*

Description

Trains a single probability random forest on the selected genes and computes per-sample SHAP values with fastshap. Rows = samples (colData rows), cols = genes.

Usage

```
shap_train_ranger(
  se,
  label_col = "state",
  genes,
  class_weights = NULL,
  num.trees = 500,
  seed = 1L,
  nsim = 64,
  pos_label = NULL
)
```

Arguments

se	SummarizedExperiment with assay "expr" (genes x samples).
label_col	Outcome column in colData(se) (factor).
genes	Character vector of gene IDs (must match rownames of assay(se,"expr")).
class_weights	Optional named numeric vector of class weights; if NULL, inverse-frequency weights are used.
num.trees	Number of trees (default 500).
seed	RNG seed.
nsim	fastshap Monte Carlo samples (default 64).
pos_label	Positive class label (defaults to level 2 of y).

Value

Numeric matrix of SHAP values (n_samples x length(genes)).

Examples

```
# For reproducibility, specify a fixed seed (e.g., set.seed(1)) before running this example.

# Toy feature matrix and binary outcome
X <- data.frame(
  x1 = stats::rnorm(20),
  x2 = stats::rnorm(20)
)
y <- factor(rep(c("A", "B"), each = 10))

# Inspect inputs
head(X)
```

---

sign_importance *Signed feature importance for RFGeneRank models*

Description

Add direction (+/-) to RF importance using group means ("mean"), external DE log2FC ("de"), or SHAP ("shap").

Usage

```
sign_importance(
  fit,
  X,
  y = NULL,
  method = c("mean", "de", "shap"),
  de_table = NULL,
```

```
  case_level = NULL,
  orientation = c("samples_by_genes", "genes_by_samples"),
  assay_name = NULL,
  shap_n = 50,
  seed = 1
)
```

Arguments

fit	Trained model object from rank_genes() or similar.
X	Expression (matrix/data.frame/SummarizedExperiment).
y	Factor labels (optional if retrievable from fit).
method	c("mean","de","shap"). Default "mean".
de_table	data.frame with columns gene, log2FC (for method="de").
case_level	Positive class label (default = last level of y).
orientation	"samples_by_genes" or "genes_by_samples".
assay_name	SE assay name/index.
shap_n	Integer; number of Monte Carlo samples for SHAP.
seed	RNG seed.

Value

data.frame with gene, importance, direction, signed_importance, mean_case, mean_ctrl, mean_diff, log2FC, shap_dir.

Examples

```
# Toy expression matrix: samples x genes
X <- matrix(
  rnorm(4 * 5),
  nrow = 4,
  dimnames = list(
    paste0("sample", 1:4),
    paste0("gene",   1:5)
  )
)

# Binary labels
y <- factor(c("Control", "Control", "Case", "Case"))

# Minimal "fit" object: a list with a numeric importance vector
fit <- list(
  importance = setNames(
    c(0.8, 0.6, 0.4, 0.2, 0.1),
    paste0("gene", 1:5)
  )
)
```

```
res <- sign_importance(
  fit = fit,
  X   = X,
  y   = y,
  method = "mean"
)

head(res)
# In practice, sign_importance() is called on a GeneRankFit object
# produced by the RFGeneRank workflow, for example:
#
#   fit <- gene_rank(se, genes = rownames(se), ...)
#   sig_imp <- sign_importance(fit, X = expr_matrix, y = outcome)
#   head(sig_imp)
```

`top_genes` *Extract top predictive genes from a GeneRankFit*

Description

Returns a ranked list from the aggregated, fold-normalized importance stored in the fitted object. Optionally adds an ID mapping column (e.g., ENTREZID -> SYMBOL) using `id_map`.

Usage

```
top_genes(
  fit,
  n = 100,
  map = FALSE,
  OrgDb = org.Hs.eg.db::org.Hs.eg.db,
  from = "SYMBOL",
  to = "SYMBOL"
)
```

Arguments

`fit`	a `GeneRankFit` object (from `rank_genes()`).
`n`	integer; number of top genes to return (default 100).
`map`	logical; if TRUE, map `from` -> `to` and add a `mapped` column.
`OrgDb`	an `OrgDb` object for mapping (default `org.Hs.eg.db`).
`from`	source keytype used for the gene identifiers (e.g., "ENTREZID", "SYMBOL", "ENSEMBL").
`to`	destination keytype (e.g., "SYMBOL").

Value

A list with:

gene character vector of top gene IDs in `from` keytype

table data.frame with columns `gene`, `importance`, `SelectedInFolds`, and optional `mapped`

Examples

```
gene_scores <- data.frame(
  gene       = paste0("gene", 1:6),
  importance = c(5, 4, 3, 2, 1, 0)
)

fit <- methods::new("GeneRankFit", imp = gene_scores)

tg <- top_genes(fit, n = 3)
tg$gene
tg$table
# In practice, top_genes() is used on a GeneRankFit object.
# For example, after running a full RFGeneRank pipeline:
#
#   fit <- gene_rank(se, genes = rownames(se), ...)
#   head(top_genes(fit, n = 20))
#
# where 'fit' is a GeneRankFit containing gene importance scores.
```

---

validate_genes *Validate a ranked gene set with alternate learners via k-fold CV*

Description

Validate a ranked gene set with alternate learners via k-fold CV

Usage

```
validate_genes(
  se,
  genes,
  methods = c("glmnet", "xgboost", "ranger"),
  k = 5,
  seed = 1L,
  model_params = list(),
  label_col = "state",
  positive = NULL,
  calibrate = c("platt", "isotonic", "none"),
  thr_metric = c("youden", "f1", "cost"),
  cost = c(fp = 1, fn = 1)
)
```

Arguments

se	A SummarizedExperiment whose assay is genes-by-samples.
genes	Character vector of gene IDs (must match rownames(assay(se))).
methods	Character vector; any of c("ranger","glmnet","xgboost").
k	Integer number of folds (default 5).
seed	Integer RNG seed for reproducibility.
model_params	Named list of per-method parameter lists, e.g. list(ranger = list(num.trees=1000, importance="none", nthread=1), glmnet = list(alpha=0.5, standardize="zscore", clip=8, eps_sd=1e-8, use_class_weights=TRUE, lambda="lambda.min"), xgboost = list(nrounds=400, eta=0.05, max_depth=4, nthread=1)).
label_col	Column name in colData(se) with the class labels. Must be a binary factor (exactly 2 levels).
positive	Optional; the positive class label. If NULL, uses levels(y)[2].
calibrate	One of c("platt","isotonic","none"); applied per fold.
thr_metric	One of c("youden","f1","cost") for threshold selection.
cost	Named numeric vector c(fp=1, fn=1) if thr_metric == "cost".

Value

A list with $summary and one entry per method. Each entry contains: $oof (data.frame with p_raw, p_cal, p_use, y, fold), $calibrator_requested, $calibrator_used, $threshold, $conf_mat, and $metrics with both diagnostics (raw/cal) and final guardrailed metrics (auc_final, ece_final, brier_final).

Examples

```
# Toy expression matrix: 10 genes x 12 samples
expr <- matrix(
  stats::rnorm(10 * 12),
  nrow = 10,
  dimnames = list(
    paste0("gene", 1:10),
    paste0("sample", 1:12)
  )
)

# Binary labels as a factor (balanced)
label <- factor(rep(c("A", "B"), each = 6))

se <- SummarizedExperiment::SummarizedExperiment(
  assays  = list(expr = expr),
  colData = S4Vectors::DataFrame(label = label)
)

# Use the first 5 genes as a toy signature
genes <- rownames(expr)[1:5]
```

```
# Validate using ranger only (fast and robust for examples)
res <- validate_genes(
  se        = se,
  genes     = genes,
  methods   = "ranger",
  k         = 3,
  seed      = 1,
  label_col = "label"
)

# Inspect out-of-fold AUROC
res$summary$auc_final
```

Index

align_datasets, 3
apply_calibration, 5

calibrate_oof, 5
calibration *(GeneRankFit-accessors)*, 8
calibration,GeneRankFit-method *(GeneRankFit-accessors)*, 8
calibration<- *(GeneRankFit-accessors)*, 8
calibration<-,GeneRankFit-method *(GeneRankFit-accessors)*, 8

factor_dependence, 6

GeneRankFit-accessors, 8

id_map, 10, *30*
imp *(GeneRankFit-accessors)*, 8
imp,GeneRankFit-method *(GeneRankFit-accessors)*, 8
imp<- *(GeneRankFit-accessors)*, 8
imp<-,GeneRankFit-method *(GeneRankFit-accessors)*, 8

oof *(GeneRankFit-accessors)*, 8
oof,GeneRankFit-method *(GeneRankFit-accessors)*, 8

params *(GeneRankFit-accessors)*, 8
params,GeneRankFit-method *(GeneRankFit-accessors)*, 8
plot_confusion_heatmap, 11
plot_embed, 11
plot_embed_expr, 13
plot_importance, 14
plot_roc, 15
plot_roc_multi, 16
plot_shap_dependence, 17
plot_sign_importance, 19
prepare_data, 20

rank_genes, 22
rfgr_crossval, 24
rfgr_plot_suite, 25

shap_train_ranger, 27
sign_importance, 28

top_genes, 30

validate_genes, 31