

Package: Rhtslib (via r-universe)

July 17, 2024

Title HTSlib high-throughput sequencing library as an R package

Description This package provides version 1.18 of the 'HTSlib' C library for high-throughput sequence analysis. The package is primarily useful to developers of other R packages who wish to make use of HTSlib. Motivation and instructions for use of this package are in the vignette, `vignette(package = `Rhtslib`, `Rhtslib`)`.

biocViews DataImport, Sequencing

URL <https://bioconductor.org/packages/Rhtslib>, <http://www.htslib.org/>

BugReports <https://github.com/Bioconductor/Rhtslib/issues>

Version 3.1.0

License LGPL (>= 2)

Copyright Unless otherwise noted in the file, all files outside `src/htslib-1.18` or `inst/include` copyright Bioconductor; for files inside `src/htslib-1.18` or `inst/include`, see file `src/htslib-1.18/LICENSE`.

Encoding UTF-8

Imports tools, zlibbioc

LinkingTo zlibbioc

Suggests knitr, rmarkdown, BiocStyle

SystemRequirements libbz2 & liblzma & libcurl (with header files), GNU make

StagedInstall no

VignetteBuilder knitr

Repository <https://bioc.r-universe.dev>

RemoteUrl <https://github.com/bioc/Rhtslib>

RemoteRef HEAD

RemoteSha 31b99ff89ff09fa92f9f63643c93417f082b9ee1

Contents

Rhtslib-package	2
pkgconfig	3
Index	4

Rhtslib-package	<i>An R packaged HTSlib 1.18</i>
-----------------	----------------------------------

Description

This package is interesting to package developers only, and provides a compiled HTSlib for developers to use in their own packages. See the vignette for instructions on use.

Details

Instructions for use are in the vignette, available with `browseVignettes(package="Rhtslib")`

Author(s)

Nathaniel Hayden nhayden@fredhutch.org

References

The HTSlib included in the package is based on release 1.18 of HTSlib found at <https://github.com/samtools/htslib/releases/>

See Also

[pkgconfig](#)

Examples

```
packageDescription('Rhtslib')
Rhtslib:::htsVersion()
```

pkgconfig

Compiler configuration arguments for use of Rhtslib

Description

This function prints values for PKG_LIBS and PKG_CPPFLAGS variables for use in Makevars files. See vignette("Rhtslib") for details. The environment variable RHTSLIB_RPATH can be used to over-ride the inferred location of the installed package.

Usage

```
pkgconfig(opt = c("PKG_LIBS", "PKG_CPPFLAGS"))
```

Arguments

opt A scalar character from the list of available options; default is PKG_LIBS.

Value

The function prints the PKG_LIBS or PKG_CPPFLAGS value and returns an invisible NULL.

Author(s)

Nathaniel Hayden <mailto:nhayden@fredhutch.org>

Examples

```
pkgconfig("PKG_LIBS")
```

```
pkgconfig("PKG_CPPFLAGS")
```

Index

- * **manip**

- pkgconfig, [3](#)

- * **package**

- Rhtslib-package, [2](#)

htsVersion (Rhtslib-package), [2](#)

pkgconfig, [2](#), [3](#)

Rhtslib (Rhtslib-package), [2](#)

Rhtslib-package, [2](#)