Package: StatescopeR (via r-universe)

October 31, 2026

Type Package

Title StatescopeR framework for discovery of cell states from cell type-specific gene expression profiles inferred from bulk mRNA profiles

Version 1.1.3

Depends R (>= 4.5.0)

Imports S4Vectors, SummarizedExperiment, reticulate, methods, SingleCellExperiment, matrixStats, scrapper, basilisk, Matrix, ComplexHeatmap, ggplot2, cowplot, utils

Suggests BiocStyle, knitr, RefManageR, rmarkdown, sessioninfo, scRNAseq, testthat, edgeR

Description StatescopeR is an R wrapper around Statescope, a computational framework designed to discover cell states from cell type-specific gene expression profiles inferred from bulk RNA profiles.

License MIT + file LICENSE

Encoding UTF-8

StagedInstall no

biocViews GeneExpression, RNASeq, SingleCell, Bayesian, Transcriptomics, Software

URL https://github.com/tgac-vumc/StatescopeR

BugReports https://github.com/tgac-vumc/StatescopeR/issues

VignetteBuilder knitr

Config/testthat/edition 3

Config/roxygen2/version 8.1.1

Config/pak/sysreqs libpng-dev perl python3 zlib1g-dev

Repository https://bioc.r-universe.dev

Date/Publication 2026-10-30 16:14:26 UTC

RemoteUrl https://github.com/bioc/StatescopeR

RemoteRef HEAD

RemoteSha 0535cf1c7cfd60124f2385d24478bafd57fa6d46

Contents

barplot_stateloadings . . . 2
BLADE_deconvolution . . . 3
concatenate_statescores . . . 5
create_signature . . . 6
EcotypeDiscovery . . . 7
EcotypeRetrieval . . . 8
fetch_signature . . . 9
fraction_eval . . . 9
fraction_heatmap . . . 10
gather_true_fractions . . . 11
Refinement . . . 12
select_genes . . . 13
StateDiscovery . . . 14
StateRetrieval . . . 16
statescope . . . 17

Index **18**

`barplot_stateloadings` *Create a barplot of top stateloadings*

Description

Create a barplot of top stateloadings

Usage

```
barplot_stateloadings(Statescope, top_n = 1)
```

Arguments

`Statescope`	SummarizedExperiment object from StateDiscovery
`top_n`	integer selecting how many genes to show per state

Value

A barplot rendered to the active graphics device

Examples

```
#' ## Load StateDiscovered Statescope object
load(system.file("extdata", "example_Statescope_StateDiscovered.RData",
    package = "StatescopeR"
))

## Plot fraction heatmap
barplot_stateloadings(Statescope, top_n = 1)
```

BLADE_deconvolution *Run BLADE deconvolution*

Description

BLADE_deconvolution.R Runs BLADE to estimate cell fractions from bulk mRNA

Usage

```
BLADE_deconvolution(
  signature,
  bulk,
  genes,
  prior = NULL,
  cores = 1L,
  Alpha = 1L,
  Alpha0 = 1000L,
  Kappa0 = 1L,
  sY = 1L,
  Nrep = 10L,
  Nrepfinal = 1000L
)
```

Arguments

signature	SimpleList with mu and sigma, both nGene x nCelltype dataframes, respectively mean gene expression and mean-variance corrected variance per cell type
bulk	nSample x nGene mRNA to be deconvolved
genes	subset of genes to be used for deconvolution
prior	(optional) nSample x nCelltype matrix with prior fraction expectations
cores	number of cores to use for paralellization
Alpha	BLADE Hyperparameter
Alpha0	BLADE Hyperparameter
Kappa0	BLADE Hyperparameter
sY	BLADE Hyperparameter
Nrep	Number of BLADE initializations
Nrepfinal	Number of maximum optimization iterations

Value

SummarizedExperiment object with BLADE output and estimated fractions

Examples

```
if (requireNamespace("scRNAseq", quietly = TRUE)) {
    library(scRNAseq)
    library(scrapper)
    library(edgeR)
    ## Load SegerstolpePancreas data set
    scRNAseq <- SegerstolpePancreasData()

    ## remove duplicate genes
    scRNAseq <- scRNAseq[!duplicated(rownames(scRNAseq)), ]
    ## Subset to 1 healthy and 2 type 2 diabetes samples
    scRNAseq <- scRNAseq[, scRNAseq$individual %in% c(
        "H3",
        "T2D1", "T2D2"
    )]
    ## remove cells with no cell type label
    scRNAseq <- scRNAseq[, !is.na(scRNAseq$`cell type`)]

    ## remove very rare cell types (<100 cells in total data set)
    celltypes_to_remove <-
    names(table(scRNAseq$`cell type`)[(table(scRNAseq$`cell type`) < 100)])
    scRNAseq <- scRNAseq[, !scRNAseq$`cell type` %in% celltypes_to_remove]

    ## Create pseudobulk and normalize to cp10k
    pseudobulk <- scrapper::aggregateAcrossCells.se(scRNAseq,
        factors = scRNAseq$individual)
    assay(pseudobulk, 'normcounts') <-
     edgeR::cpm(assay(pseudobulk, 'sums')) / 100
    colnames(pseudobulk) = pseudobulk$factor.1 # Assign sample names

    ## Load signature
    load(system.file("extdata", "example_signature.RData",
        package = "StatescopeR"
    ))

    ## Load selected_genes
    load(system.file("extdata", "example_selected_genes.RData",
        package = "StatescopeR"
    ))

    ##  Load prior
    load(system.file("extdata", "example_prior.RData",
        package = "StatescopeR"
    ))

    ## Perform Deconvolution with BLADE
    Statescope <- BLADE_deconvolution(
        signature, pseudobulk, selected_genes,
        prior, 1L,
        Nrep = 1L
    )
```

```
    ## show estimated fractions
    S4Vectors::metadata(Statescope)$fractions
}
```

`concatenate_statescores` *Concatenate statescore lists into one data frame*

Description

`concatenate_statescores.R` Concatenate statescore lists into one data frame

Usage

```
concatenate_statescores(statescores)
```

Arguments

`statescores`	Named list of cell-type-specific statescore DataFrames, typically obtained from S4Vectors::metadata(Statescope)$statescores. Each DataFrame should contain samples as row names and score components as columns.

Value

A data frame containing samples as rows and concatenated cell-type-specific scores as columns.

Examples

```
## Load StateDiscovered Statescope object
load(system.file("extdata", "example_Statescope_StateDiscovered.RData",
    package = "StatescopeR"
))
# Extract state scores from a StateScope object
statescores <- S4Vectors::metadata(Statescope)$statescores

# Concatenate scores across cell types
concatenated_scores <- concatenate_statescores(statescores)
```

create_signature *Create scRNAseq Signature*

Description

create_signature Creates signature from scRNAseq data

Usage

```
create_signature(scRNAseq, hvg_genes = FALSE, n_hvg_genes = 3000L, labels)
```

Arguments

scRNAseq	SingleCellExperiment object of which to make signature
hvg_genes	boolean which chooses if mu and omega should be subset to highly variable genes or not
n_hvg_genes	int which allows the users to choose the number of highly variable genes
labels	character vector for the cell type labels

Value

SimpleList DataFrames for Mu (mean per gene per cell type) and Omega (variance corrected std.dev per gene per cell type)

Examples

```
if (requireNamespace("scRNAseq", quietly = TRUE)) {
    library(scRNAseq)
    library(edgeR)
    ## Load scRNaseq
    scRNAseq <- scRNAseq::SegerstolpePancreasData()

    ## remove NA cells
    scRNAseq <- scRNAseq[, !is.na(scRNAseq$`cell type`)]

    ## Normalize (cp10k) and logtransform scRNAseq
    cpm(scRNAseq) <- edgeR::cpm(scRNAseq)
    SingleCellExperiment::logcounts(scRNAseq) <- log1p(cpm(scRNAseq) / 100)

    ## Create signature
    signature <- create_signature(scRNAseq, labels = scRNAseq$`cell type`)
}
```

`EcotypeDiscovery` *Run EcotypeDiscovery*

Description

`EcotypeDiscovery.R` Discovers ecotypes from cell state scores

Usage

```
EcotypeDiscovery(
  Statescope,
  k = NA,
  max_clusters = 10L,
  n_iter = 10L,
  n_final_iter = 100L,
  min_cophenetic = 0.9,
  Ncores = 1L
)
```

Arguments

`Statescope`	SummarizedExperiment object from Statescope StateDiscovery.
`k`	number of cluster to choose, default is NA for automatic selection
`max_clusters`	maximum allowed states per cell type.
`n_iter`	Number of initial cNMF restarts.
`n_final_iter`	Number of final cNMF restarts.
`min_cophenetic`	Minimum cophenetic coefficient to determine K.
`Ncores`	number of cores to use for paralellization.

Value

SummarizedExperiment object with ecotypescores and loadings

Examples

```
## Load StateDiscovered Statescope object
load(system.file("extdata", "example_Statescope_StateDiscovered.RData",
    package = "StatescopeR"
))

#' ## Discover ecotypes
Statescope <- EcotypeDiscovery(Statescope, k = 2L, Ncores = 2L)

## Look at ecotypescores and ecotypeloadings
S4Vectors::metadata(Statescope)$ecotypescores
S4Vectors::metadata(Statescope)$ecotypeloadings
```

`EcotypeRetrieval` *Run EcotypeRetrieval*

Description

`EcotypeRetrieval.R` Retrieve states in an external dataset

Usage

```
EcotypeRetrieval(Statescope_StateRetrieved, Statescope_EcotypeDiscovered)
```

Arguments

`Statescope_StateRetrieved`	SummarizedExperiment object from Statescope StateRetrieval.
`Statescope_EcotypeDiscovered`	SummarizedExperiment object from Statescope EcotypeDiscovery

Value

SummarizedExperiment object with ecotypescores

Examples

```
## Load StateRetrieved Statescope object
load(system.file("extdata", "example_Statescope_StateDiscovered.RData",
    package = "StatescopeR"
))
Statescope_StateRetrieved = Statescope

## Load EcotypeDiscovered Statescope object
load(system.file("extdata", "example_Statescope_EcotypeDiscovered.RData",
    package = "StatescopeR"
))

Statescope_EcotypeDiscovered = Statescope

## Retrieve states in refined Statescope object
Statescope_EcotypeRetrieved <- EcotypeRetrieval(Statescope_StateRetrieved,
                Statescope_EcotypeDiscovered)

## Look at ecotypescores in external dataset
S4Vectors::metadata(Statescope_EcotypeRetrieved)$ecotypescores
```

fetch_signature *Fetch scRNAseq Signature*

Description

fetch_signature Fetches signature from StatescopeData repository

Usage

```
fetch_signature(tumor_type, n_celltypes)
```

Arguments

tumor_type	string choosing the tumor type from available signatures at: https://github.com/tgac-vumc/StatescopeData
n_celltypes	integer choosing the number of cell types of the signature from: https://github.com/tgac-vumc/StatescopeData

Value

SimpleList with DataFrames for Mu (mean per gene per cell type) and Omega (variance corrected std.dev per gene per cell type) and vector of selected genes for deconvolution chosen by AutoGeneS

Examples

```
signature <- fetch_signature('PDAC', 7)
selected_genes <- signature$selected_genes
```

fraction_eval *Create a barplot of TRUE vs estimated cfs*

Description

Create a barplot of TRUE vs estimated cfs

Usage

```
fraction_eval(Statescope, true_fractions)
```

Arguments

Statescope	SummarizedExperiment object from BLADE_deconvolution
true_fractions	s4 Dataframe with true fractions to compare with estimated fractions

Value

A barplot rendered to the active graphics device

Examples

```
## Load True fractions
load(system.file("extdata", "example_true_fractions.RData",
    package = "StatescopeR"
))

## Load Deconvolved Statescope object
load(system.file("extdata", "example_Statescope_Deconvolved.RData",
    package = "StatescopeR"
))

## ## Plot fraction correlation and RMSE per ct
fraction_eval(Statescope, true_fractions)
```

`fraction_heatmap` *Create a heatmap of the estimated fractions*

Description

Create a heatmap of the estimated fractions

Usage

```
fraction_heatmap(Statescope, ...)
```

Arguments

`Statescope`	SummarizedExperiment object from BLADE_deconvolution
`...`	other parameters to pass to [ComplexHeatmap::Heatmap()]

Value

A heatmap rendered to the active graphics device

Examples

```
## Load Deconvolved Statescope object
load(system.file("extdata", "example_Statescope_Deconvolved.RData",
    package = "StatescopeR"
))

## Plot fraction heatmap
fraction_heatmap(Statescope)
```

gather_true_fractions *Gather true fractions*

Description

gather_true_fractions Gathers true fractions of all cell types per sample from scRNAseq data

Usage

```
gather_true_fractions(scRNAseq, ids, label_col)
```

Arguments

scRNAseq	SingleCellExperiment object of which to gather fractions per sample
ids	character vector with ids of samples
label_col	character for the column name with the cell type labels

Value

DataFrame with fractions of all cell types per sample

Examples

```
if (requireNamespace("scRNAseq", quietly = TRUE)) {
    library(scRNAseq)
    ## Load data
    scRNAseq <- scRNAseq::SegerstolpePancreasData()
    ## Subset to 1 healthy and 3 type 2 diabetes samples
    scRNAseq <- scRNAseq[, scRNAseq$individual %in% c(
        "H3",
        "T2D1", "T2D2"
    )]
    ## remove NA cells
    scRNAseq <- scRNAseq[, !is.na(scRNAseq$`cell type`)]

    ## remove cells with less than 100 in total cohort
    celltypes_to_remove <- names(table(scRNAseq$`cell type`)
    [(table(scRNAseq$`cell type`) < 100)])
    scRNAseq <- scRNAseq[, !scRNAseq$`cell type` %in% celltypes_to_remove]

    true_fractions <- gather_true_fractions(scRNAseq,
        ids = scRNAseq$individual, label_col = "cell type"
    )
}
```

`Refinement` *Run Refinement*

Description

`Refinement.R` # Perform Gene Expression Refinement

Usage

```
Refinement(Statescope, signature, bulk, cores = 1L)
```

Arguments

`Statescope`	SummarizedExperiment object from BLADE_deconvolution
`signature`	SimpleList with mu and sigma, respectively mean gene expression and mean-variance corrected variance per cell type
`bulk`	mRNA to be refined
`cores`	number of cores to use for paralellization

Details

This function takes the output from BLADE_deconvolution and refines the cell type specific gene expression by reoptimizing the initial estimates. It reoptimzes by fixing the estimated fractions and weighing the objective function value in a way that it tries to resemble the bulk RNA expression more than initially

Value

updated SummarizedExperiment object with ct_specific_gep added

Examples

```
if (requireNamespace("scRNAseq", quietly = TRUE)) {
    library(scRNAseq)
    library(scrapper)
    library(edgeR)
    ## Load SegerstolpePancreas data set
    scRNAseq <- SegerstolpePancreasData()

    ## remove duplicate genes
    scRNAseq <- scRNAseq[!duplicated(rownames(scRNAseq)), ]

    ## Subset to 1 healthy and 2 type 2 diabetes samples
    scRNAseq <- scRNAseq[, scRNAseq$individual %in% c(
        "H3",
        "T2D1", "T2D2"
    )]
    ## remove cells with no cell type label
```

```
    scRNAseq <- scRNAseq[, !is.na(scRNAseq$`cell type`)]

    ## remove very rare cell types (<100 cells in total data set)
    celltypes_to_remove <- names(table(scRNAseq$`cell type`)
    [(table(scRNAseq$`cell type`) < 100)])
    scRNAseq <- scRNAseq[, !scRNAseq$`cell type` %in% celltypes_to_remove]

    ## Create pseudobulk and normalize to cp10k
    pseudobulk <- scrapper::aggregateAcrossCells.se(scRNAseq,
        factors = scRNAseq$individual)
    assay(pseudobulk, 'normcounts') <-
     edgeR::cpm(assay(pseudobulk, 'sums')) / 100
    colnames(pseudobulk) = pseudobulk$factor.1 # Assign sample names

    ## Load signature
    load(system.file("extdata", "example_signature.RData",
        package = "StatescopeR"
    ))

    ## Load Deconvolved Statescope object
    load(system.file("extdata", "example_Statescope_Deconvolved.RData",
        package = "StatescopeR"
    ))

    ## Run Refinement
    Statescope <- Refinement(Statescope, signature, pseudobulk, 2L)

    ## Show cell type specific gene expression profile estimates
    S4Vectors::metadata(Statescope)$ct_specific_gep
}
```

`select_genes` *Select genes using AutoGeneS*

Description

`select_genes.R` select genes using AutoGeneS for deconvolution

Usage

```
select_genes(scRNAseq, fixed_n_features = NA, n_hvg_genes = 3000L, labels)
```

Arguments

`scRNAseq`	SingleCellExperiment object to use for gene selection, should be same as signature dataset
`fixed_n_features`	integer number of genes to pick with autogenes, default is NA which lets autogenes itself pick
`n_hvg_genes`	int which allows the users to choose the number of highly variable genes
`labels`	character vector with cell type labels

Value

Vector of genes to use for deconvolution

Examples

```
if (requireNamespace("scRNAseq", quietly = TRUE)) {
    library(scRNAseq)
    library(edgeR)
    ## Load SegerstolpePancreas data set
    scRNAseq <- SegerstolpePancreasData()

    ## remove duplicate genes
    scRNAseq <- scRNAseq[!duplicated(rownames(scRNAseq)), ]

    ## Subset to 1 healthy and 2 type 2 diabetes samples
    scRNAseq <- scRNAseq[, scRNAseq$individual %in% c(
        "H3",
        "T2D1", "T2D2"
    )]
    ## remove cells with no cell type label
    scRNAseq <- scRNAseq[, !is.na(scRNAseq$`cell type`)]

    ## remove rare cell types (<100 cells in total data set)
    celltypes_to_remove <-names(table(scRNAseq$`cell type`)
        [(table(scRNAseq$`cell type`) < 100)])
    scRNAseq <- scRNAseq[, !scRNAseq$`cell type` %in% celltypes_to_remove]

    ## remove NA cells
    scRNAseq <- scRNAseq[, !is.na(scRNAseq$`cell type`)]

    ## Normalize (cp10k) and logtransform scRNAseq
    cpm(scRNAseq) <- edgeR::cpm(scRNAseq)
    logcounts(scRNAseq) <- log1p(cpm(scRNAseq) / 100)

    ## Select genes by autogenes
    selected_genes <- select_genes(scRNAseq, 3L,
        n_hvg_genes = 5L,
        labels = scRNAseq$`cell type`
    ) # 3 genes
}
```

`StateDiscovery` *Run StateDiscovery*

Description

`StateDiscovery.R` Discovers states from refined ct-specific gep

Usage

```
StateDiscovery(
  Statescope,
  k = NA,
  max_clusters = 10L,
  n_iter = 10L,
  n_final_iter = 100L,
  min_cophenetic = 0.9,
  Ncores = 1L
)
```

Arguments

Statescope	SummarizedExperiment object from Statescope Refinement.
k	number of cluster to choose, default is NA for automatic selection
max_clusters	maximum allowed states per cell type.
n_iter	Number of initial cNMF restarts.
n_final_iter	Number of final cNMF restarts.
min_cophenetic	Minimum cophenetic coefficient to determine K.
Ncores	number of cores to use for paralellization.

Value

SummarizedExperiment object with statescores per celltype added

Examples

```
## Load Refined Statescope object
load(system.file("extdata", "example_Statescope_Refined.RData",
    package = "StatescopeR"
))

## Discover states
Statescope <- StateDiscovery(Statescope, k = 2L, Ncores = 2L)

## Look at statescores and stateloadings
S4Vectors::metadata(Statescope)$statescores
S4Vectors::metadata(Statescope)$stateloadings
```

`StateRetrieval` *Run StateRetrieval*

Description

`StateRetrieval.R` Retrieve states in an external dataset

Usage

```
StateRetrieval(Statescope_Refined, Statescope_StateDiscovered)
```

Arguments

`Statescope_Refined`	SummarizedExperiment object from Statescope Refinement.
`Statescope_StateDiscovered`	SummarizedExperiment object from Statescope StateDiscovery

Value

SummarizedExperiment object with statescores per celltype added

Examples

```
## Load Refined Statescope object
load(system.file("extdata", "example_Statescope_Refined.RData",
    package = "StatescopeR"
))
Statescope_Refined = Statescope

## Load StateDiscovered Statescope object
load(system.file("extdata", "example_Statescope_StateDiscovered.RData",
    package = "StatescopeR"
))

Statescope_StateDiscovered = Statescope

## Retrieve states in refined Statescope object
Statescope_StateRetrieved <-
               StateRetrieval(Statescope_Refined, Statescope_StateDiscovered)

## Look at statescores in external dataset
S4Vectors::metadata(Statescope_StateRetrieved)$statescores
```

`statescope` *Python environments*

Description

Python environments

Usage

```
statescope
```

Index

barplot_stateloadings, 2
BLADE_deconvolution, 3

concatenate_statescores, 5
create_signature, 6

EcotypeDiscovery, 7
EcotypeRetrieval, 8

fetch_signature, 9
fraction_eval, 9
fraction_heatmap, 10

gather_true_fractions, 11

Refinement, 12

select_genes, 13
StateDiscovery, 14
StateRetrieval, 16
statescope, 17