

# Package: alabaster.string (via r-universe)

June 30, 2024

**Title** Save and Load Biostrings to/from File

**Version** 1.5.0

**Date** 2023-12-29

**Description** Save Biostrings objects to file artifacts, and load them back into memory. This is a more portable alternative to serialization of such objects into RDS files. Each artifact is associated with metadata for further interpretation; downstream applications can enrich this metadata with context-specific properties.

**License** MIT + file LICENSE

**Depends** Biostrings, alabaster.base

**Imports** utils, methods, S4Vectors

**Suggests** BiocStyle, rmarkdown, knitr, testthat

**VignetteBuilder** knitr

**RoxygenNote** 7.2.3

**biocViews** DataImport, DataRepresentation

**Repository** <https://bioc.r-universe.dev>

**RemoteUrl** <https://github.com/bioc/alabaster.string>

**RemoteRef** HEAD

**RemoteSha** a4cf6fd280c844f5897afc394d9f8a61f82a4c19

## Contents

readXStringSet . . . . .	2
saveObject,XStringSet-method . . . . .	3

<b>Index</b>	<b>4</b>
--------------	----------

---

readXStringSet	<i>Read an XStringSet from disk.</i>
----------------	--------------------------------------

---

### Description

Read a [XStringSet](#) object from its on-disk representation. This is usually not directly called by users, but is instead called by dispatch in [readObject](#).

### Usage

```
readXStringSet(path, metadata, ...)
```

### Arguments

path	String containing a path to a directory, itself created using the <a href="#">saveObject</a> method for <a href="#">XStringSet</a> objects.
metadata	Named list of metadata for this object, see <a href="#">readObjectFile</a> for details.
...	Further arguments passed to internal <a href="#">altReadObject</a> calls.

### Value

An [XStringSet](#) subclass containing DNA, RNA, protein or custom sequences. This may also be a [QualityScaledDNAStrngSet](#) with quality scores.

### See Also

"[saveObject,XStringSet-method](#)", to save an [XStringSet](#) to disk.

### Examples

```
library(Biostrings)
stuff <- DNAStrngSet(c("AAA", "CC", "G", "TTTT"))

tmp <- tempfile()
saveObject(stuff, tmp)
readObject(tmp)
```

---

saveObject,XStringSet-method  
*Save a XStringSet to disk*

---

## Description

Save a [XStringSet](#) to its on-disk representation.

## Usage

```
## S4 method for signature 'XStringSet'  
saveObject(x, path, ...)
```

## Arguments

x	A <a href="#">XStringSet</a> or any of its subclasses such as a <a href="#">QualityScaledXStringSet</a> .
path	String containing the path to a directory in which to save x.
...	Further arguments to pass to specific methods.

## Value

The contents of x are saved into a path, and NULL is invisibly returned.

## Author(s)

Aaron Lun

## See Also

[readXStringSet](#), to read the XStringSet back into the R session.

## Examples

```
library(Biostrings)  
stuff <- DNASTringSet(c("AAA", "CC", "G", "TTTT"))  
  
tmp <- tempfile()  
saveObject(stuff, tmp)  
list.files(tmp, recursive=TRUE)
```

# Index

altReadObject, [2](#)

loadXStringSet (readXStringSet), [2](#)

QualityScaledDNAStrngSet, [2](#)

QualityScaledXStringSet, [3](#)

readObject, [2](#)

readObjectFile, [2](#)

readXStringSet, [2](#), [3](#)

saveObject, [2](#)

saveObject, XStringSet-method, [3](#)

stageObject, XStringSet-method  
    (saveObject, XStringSet-method),  
    [3](#)

XStringSet, [2](#), [3](#)