

Package: clust SIGNAL (via r-universe)

October 9, 2026

Type Package

Title Clust SIGNAL: a spatial clustering method

Version 1.5.2

Description clust SIGNAL: clustering of Spatially Informed Gene expression with Neighbourhood Adapted Learning. A tool for adaptively smoothing and clustering gene expression data. clust SIGNAL uses entropy to measure heterogeneity of cell neighbourhoods and performs a weighted, adaptive smoothing, where homogeneous neighbourhoods are smoothed more and heterogeneous neighbourhoods are smoothed less. This not only overcomes data sparsity but also incorporates spatial context into the gene expression data. The resulting smoothed gene expression data is used for clustering and could be used for other downstream analyses.

License GPL-2

Encoding UTF-8

URL <https://sydneybiox.github.io/clust SIGNAL/>

BugReports <https://github.com/sydneybiox/clust SIGNAL/issues>

biocViews Clustering, Software, GeneExpression, Spatial, Transcriptomics, SingleCell

RoxygenNote 7.3.3

Depends R (>= 4.5.0), SpatialExperiment

Imports BiocParallel, BiocNeighbors, BiocSingular, bluster (>= 1.16.0), scater, harmony, SingleCellExperiment, SummarizedExperiment, methods, Matrix

Suggests knitr, BiocStyle, testthat (>= 3.0.0), aricode, ggplot2, patchwork, dplyr, scattermore

VignetteBuilder knitr

Config/pak/sysreqs

libglpk-dev libmagick++-dev gsfonts libicu-dev libxml2-dev libssl-dev zlib1g-dev

Repository <https://bioc.r-universe.dev>

Date/Publication 2026-09-09 03:28:01 UTC
RemoteUrl <https://github.com/bioc/clustSIGNAL>
RemoteRef HEAD
RemoteSha a1fa57cfdc01f9b63f19f131489ba3e8578e112a

Contents

adaptiveSmoothing	2
clustSIGNAL	3
ClustSignal_example	5
entropyMeasure	6
mEmbryo2	6
mHypothal	7
neighbourDetect	8
p1_clustering	9
p2_clustering	10
Index	12

adaptiveSmoothing	<i>Adaptive smoothing</i>
-------------------	---------------------------

Description

A function to perform a weighted, adaptive smoothing of the gene expression of each cell based on the heterogeneity of its neighbourhood. Heterogeneous neighbourhoods are smoothed less with higher weights given to cells belonging to same initial cluster as the index cell. Homogeneous neighbourhoods are smoothed more with similar weights given to most cells.

Usage

```
adaptiveSmoothing(spe, nnCells, NN = 30, kernel = c("G", "E"), spread = 0.3)
```

Arguments

spe	SpatialExperiment object containing neighbourhood entropy values of each cell.
nnCells	a character matrix of NN nearest neighbours - rows are index cells and columns are their nearest neighbours ranging from closest to farthest neighbour. For sort = TRUE, the neighbours belonging to the same initial cluster as the index cell are moved closer to it.
NN	an integer for the number of neighbouring cells the function should consider. The value must be greater than or equal to 1. Default value is 30.
kernel	a character for type of distribution to be used. The two valid values are "G" or "E" for Gaussian and exponential distributions, respectively. Default value is "G".

spread a numeric value for distribution spread, represented by standard deviation for Gaussian distribution and rate for exponential distribution. Default value is 0.3 for Gaussian distribution. The recommended value is 5 for exponential distribution.

Value

SpatialExperiment object including smoothed gene expression as an additional assay.

Examples

```
data(ClustSignal_example)

# requires matrix containing NN nearest neighbour cell labels (nnCells),
# generated using the neighbourDetect() function
spe <- clustSIGNAL::adaptiveSmoothing(spe, nnCells)
spe
```

clustSIGNAL

ClustSIGNAL

Description

Clustering method for spatially-resolved cell-state classification of spatial transcriptomics data. The tool generates and uses an adaptively smoothed, spatially-informed gene expression for clustering.

Usage

```
clustSIGNAL(
  spe,
  samples,
  dimRed_init = "None",
  dimRed_f = c("None", "embed.smooth"),
  batch = FALSE,
  batch_by = "None",
  NN = 30,
  kernel = c("G", "E"),
  spread = 0.3,
  sort = TRUE,
  threads = 1,
  outputs = c("c", "n", "s", "a"),
  clustParams = list(clust_c = 0, subclust_c = 0, iter.max = 30, k = 10, cluster.fun =
    "louvain")
)
```

Arguments

spe	a SpatialExperiment object containing spatial coordinates in 'spatialCoords' matrix and normalised gene expression in 'logcounts' assay.
samples	a character indicating name of colData(spe) column containing sample names.
dimRed_init	a character indicating the name of the reduced dimensions in the SpatialExperiment object (i.e., from reducedDimNames(spe)) to use for initial clustering step. Default value is 'None'.
dimRed_f	a character indicating the name of the reduced dimensions in the SpatialExperiment object (i.e., from reducedDimNames(spe)) to use for final clustering step. Two valid options are "None" (default), which triggers a PCA run on smoothed expression, and "embed.smooth", which triggers a search for externally-generated "embed.smooth" low embedding in reducedDimNames(spe).
batch	a logical parameter for whether to perform batch correction. Default value is FALSE.
batch_by	a character indicating name of colData(spe) column containing the batch names. Default value is 'None'.
NN	an integer for the number of neighbouring cells the function should consider. The value must be greater than or equal to 1. Default value is 30.
kernel	a character for type of distribution to be used. The two valid values are "G" or "E" for Gaussian and exponential distributions, respectively. Default value is "G".
spread	a numeric value for distribution spread, represented by standard deviation for Gaussian distribution and rate for exponential distribution. Default value is 0.3 for Gaussian distribution. The recommended value is 5 for exponential distribution.
sort	a logical parameter for whether to sort the neighbourhood by initial clusters. Default value is TRUE.
threads	a numeric value for the number of CPU cores to be used for the analysis. Default value set to 1.
outputs	a character for the type of output to return to the user. "c" for data frame of cell IDs and their respective ClustSIGNAL cluster labels, "n" for ClustSIGNAL cluster dataframe plus neighbourhood matrix, "s" for ClustSIGNAL cluster dataframe plus final SpatialExperiment object, or "a" for all 3 outputs. Default value is 'c'.
clustParams	a list of parameters for TwoStepParam clustering methods: clust_c is the number of centers to use for clustering with KmeansParam. By default set to 0, in which case the method uses either 3000 centers or 1/5th of the total cells in the data as the number of centers, whichever is lower. subclust_c is the number of centers to use for sub-clustering the initial clusters with KmeansParam. The default value is 0, in which case the method uses either 1 center or half of the total cells in the initial cluster as the number of centers, whichever is higher. iter.max is the maximum number of iterations to perform during clustering and sub-clustering with KmeansParam. Default value is 30. k is a numeric value indicating the k-value used for clustering and sub-clustering with NNGraphParam. Default value is 10. cluster.fun is a character indicating the graph clustering method used with NNGraphParam. By default, the Louvain method is used.

Value

a list of outputs depending on the type of outputs specified in the main function call.

1. clusters: a data frame of cell names and their ClustSIGNAL cluster classification.
2. neighbours: a character matrix containing cells IDs of each cell's NN neighbours.
3. spe_final: a SpatialExperiment object containing the original spe object data plus initial cluster and subcluster labels, entropy values, smoothed gene expression, and ClustSIGNAL cluster labels.

Examples

```
data(ClustSignal_example)

names(colData(spe))
# identify the column name with sample labels
samples = "sample_id"
res_list <- clustSIGNAL(spe, samples, outputs = "c")
```

ClustSignal_example	<i>Example data with SpatialExperiment object</i>
---------------------	---

Description

This example data was generated from the mouse embryo spatial transcriptomics dataset of 3 mouse embryos, with 351 genes and a total of 57536 cells. For running examples, we subset the data by selecting 1000 random cells from embryo 2, excluding any cells annotated as 'low quality'. After subsetting, we have expression for 351 genes from 1000 cells in embryo 2.

Usage

```
data(ClustSignal_example)
```

Format

spe a spatialExperiment object containing gene expression matrix with normalised counts, where rows indicate genes and columns indicate cells. Also, contains a cell metadata including cell IDs, sample IDs, cell type annotations, and x-y coordinates of cells. nnCells a matrix where each row corresponds to a cell in spe object, and the columns correspond to the nearest neighbors. regXclust a list where each element corresponds to a cell in spe object, and contains the cluster composition proportions.

Source

Integration of spatial and single-cell transcriptomic data elucidates mouse organogenesis, *Nature Biotechnology*, 2021. Webpage: <https://www.nature.com/articles/s41587-021-01006-2>

entropyMeasure	<i>Heterogeneity measure</i>
----------------	------------------------------

Description

A function to measure the heterogeneity of a cell's neighbourhood in terms of entropy. Generally, homogeneous neighbourhoods have low entropy and heterogeneous neighbourhoods have high entropy.

Usage

```
entropyMeasure(spe, regXclust)
```

Arguments

spe	SpatialExperiment object with initial cluster and subcluster labels.
regXclust	a numeric matrix of cells by subclusters, where the values are the proportion of initial subclusters in each cell's neighbourhood.

Value

SpatialExperiment object with entropy values associated with each cell.

Examples

```
data(ClustSignal_example)

# requires matrix containing cluster proportions of each neighbourhood
# (regXclust), generated using the neighbourDetect() function
spe <- clustSignal::entropyMeasure(spe, regXclust)
spe$entropy |> head()
```

mEmbryo2	<i>Mouse Embryo Data</i>
----------	--------------------------

Description

This dataset contains spatial transcriptomics data from 3 mouse embryos, with 351 genes and a total of 57536 cells. For vignettes, we subset the data by randomly selecting 5000 cells from embryo 2, excluding cells that were annotated as 'low quality'.

Usage

```
data(mEmbryo2)
```

Format

me_expr a gene expression matrix with normalised counts, where rows indicate genes and columns indicate cells. me_data a data frame of cell metadata including cell IDs, sample IDs, cell type annotations, and x-y coordinates of cells.

Source

Integration of spatial and single-cell transcriptomic data elucidates mouse organogenesis, *Nature Biotechnology*, 2021. Webpage: <https://www.nature.com/articles/s41587-021-01006-2>

mHypothal

Mouse Hypothalamus Data

Description

This dataset contains spatial transcriptomics data from 181 mouse hypothalamus samples, 155 genes and a total of 1,027,080 cells. For running the vignettes, we subset the data by selecting total 6000 cells from only 3 samples - Animal 1 Bregma -0.09 (2080 cells) and Animal 7 Bregmas 0.16 (1936 cells) and -0.09 (1984 cells), excluding cells that were annotated as 'ambiguous', and removed 20 genes that were assessed using a different technology.

Usage

```
data(mHypothal)
```

Format

mh_expr a gene expression matrix with normalised counts, where rows indicate genes and columns indicate cells. mh_data a data frame of cell metadata including cell IDs, sample IDs, cell type annotations, and x-y coordinates of cells.

Source

Molecular, Spatial and Functional Single-Cell Profiling of the Hypothalamic Preoptic Region, *Science*, 2018. Webpage: <https://www.science.org/doi/10.1126/science.aau5324>

neighbourDetect	<i>Cell neighbourhood detection</i>
-----------------	-------------------------------------

Description

A function to identify the neighbourhood of each cell. If `sort = TRUE`, the neighbourhoods are also sorted such that cells belonging to the same 'initial cluster' as the index cell are arranged closer to it.

Usage

```
neighbourDetect(spe, samples, NN = 30, sort = TRUE, threads = 1)
```

Arguments

<code>spe</code>	SpatialExperiment object with initial cluster and subcluster labels.
<code>samples</code>	a character indicating name of <code>colData(spe)</code> column containing sample names.
<code>NN</code>	an integer for the number of neighbouring cells the function should consider. The value must be greater than or equal to 1. Default value is 30.
<code>sort</code>	a logical parameter for whether to sort the neighbourhood by initial clusters. Default value is <code>TRUE</code> .
<code>threads</code>	a numeric value for the number of CPU cores to be used for the analysis. Default value set to 1.

Value

a list containing two items:

1. `nnCells`, a character matrix of NN nearest neighbours - rows are index cells and columns are their nearest neighbours ranging from closest to farthest neighbour. For `sort = TRUE`, the neighbours belonging to the same initial cluster as the index cell are moved closer to it.
2. `regXclust`, a numeric matrix of each cell's neighbourhood composition indicated by the proportion of initial subclusters (column) in each cell (row).

Examples

```
data(ClustSignal_example)

out_list <- clustSIGNAL::neighbourDetect(spe, samples = "sample_id")
out_list |> names()
```

p1_clustering	<i>Initial non-spatial clustering</i>
---------------	---------------------------------------

Description

A function to perform initial non-spatial clustering and sub-clustering of normalised gene expression to generate 'initial clusters' and 'initial subclusters'.

Usage

```
p1_clustering(
  spe,
  dimRed_init = "None",
  batch = FALSE,
  batch_by = "None",
  threads = 1,
  clustParams = list(clust_c = 0, subclust_c = 0, iter.max = 30, k = 10, cluster.fun =
    "louvain")
)
```

Arguments

spe	a SpatialExperiment object containing spatial coordinates in 'spatialCoords' matrix and normalised gene expression in 'logcounts' assay.
dimRed_init	a character indicating the name of the reduced dimensions in the SpatialExperiment object (i.e., from reducedDimNames(spe)) to use for initial clustering step. Default value is 'None'.
batch	a logical parameter for whether to perform batch correction. Default value is FALSE.
batch_by	a character indicating name of colData(spe) column containing the batch names. Default value is 'None'.
threads	a numeric value for the number of CPU cores to be used for the analysis. Default value set to 1.
clustParams	a list of parameters for TwoStepParam clustering methods: clust_c is the number of centers to use for clustering with KmeansParam. By default set to 0, in which case the method uses either 3000 centers or 1/5th of the total cells in the data as the number of centers, whichever is lower. subclust_c is the number of centers to use for sub-clustering the initial clusters with KmeansParam. The default value is 0, in which case the method uses either 1 center or half of the total cells in the initial cluster as the number of centers, whichever is higher. iter.max is the maximum number of iterations to perform during clustering and sub-clustering with KmeansParam. Default value is 30. k is a numeric value indicating the k-value used for clustering and sub-clustering with NNGraphParam. Default value is 10. cluster.fun is a character indicating the graph clustering method used with NNGraphParam. By default, the Louvain method is used.

Value

SpatialExperiment object with initial cluster and subcluster labels of each cell.

Examples

```
data(ClustSignal_example)

spe <- clustSIGNAL::p1_clustering(spe, dimRed_init = "PCA")
spe$nsCluster |> head()
spe$initCluster |> head()
```

p2_clustering	<i>Final non-spatial clustering</i>
---------------	-------------------------------------

Description

A function to perform clustering on adaptively smoothed gene expression data to generate ClustSIGNAL clusters.

Usage

```
p2_clustering(
  spe,
  dimRed_f = c("None", "embed.smooth"),
  batch = FALSE,
  batch_by = "None",
  threads = 1,
  clustParams = list(clust_c = 0, subclust_c = 0, iter.max = 30, k = 10, cluster.fun =
    "louvain")
)
```

Arguments

spe	SpatialExperiment object containing the adaptively smoothed gene expression.
dimRed_f	a character indicating the name of the reduced dimensions in the SpatialExperiment object (i.e., from reducedDimNames(spe)) to use for final clustering step. Two valid options are "None" (default), which triggers a PCA run on smoothed expression, and "embed.smooth", which triggers a search for "embed.smooth" low embedding in reducedDimNames(spe).
batch	a logical parameter for whether to perform batch correction. Default value is FALSE.
batch_by	a character indicating name of colData(spe) column containing the batch names. Default value is 'None'.
threads	a numeric value for the number of CPU cores to be used for the analysis. Default value set to 1.

clustParams a list of parameters for TwoStepParam clustering methods: **clust_c** is the number of centers to use for clustering with KmeansParam. By default set to 0, in which case the method uses either 3000 centers or 1/5th of the total cells in the data as the number of centers, whichever is lower. **subclust_c** is the number of centers to use for sub-clustering the initial clusters with KmeansParam. This parameter is not used in the final clustering step. **iter.max** is the maximum number of iterations to perform during clustering and sub-clustering with KmeansParam. Default value is 30. **k** is a numeric value indicating the k-value used for clustering with NNGraphParam. Default value is 10. **cluster.fun** is a character indicating the graph clustering method used with NNGraphParam. By default, the Louvain method is used.

Value

SpatialExperiment object containing clusters generated from smoothed data.

Examples

```
data(ClustSignal_example)

# For non-spatial clustering of normalised counts
spe <- clustSIGNAL::p2_clustering(spe)
spe$ClustSIGNAL |> head()
```

Index

* datasets

ClustSignal_example, [5](#)

mEmbryo2, [6](#)

mHypothal, [7](#)

adaptiveSmoothing, [2](#)

clustSIGNAL, [3](#)

ClustSignal_example, [5](#)

entropyMeasure, [6](#)

me_data (mEmbryo2), [6](#)

me_expr (mEmbryo2), [6](#)

mEmbryo2, [6](#)

mh_data (mHypothal), [7](#)

mh_expr (mHypothal), [7](#)

mHypothal, [7](#)

neighbourDetect, [8](#)

nnCells (ClustSignal_example), [5](#)

p1_clustering, [9](#)

p2_clustering, [10](#)

regXclust (ClustSignal_example), [5](#)

spe (ClustSignal_example), [5](#)