

Package: codelink (via r-universe)

September 24, 2026

Version 1.81.0

Title Manipulation of Codelink microarray data

Author Diego Diez

Maintainer Diego Diez <diego10ruiz@gmail.com>

Depends R (>= 2.10), BiocGenerics (>= 0.3.2), methods, Biobase (>= 2.17.8), limma

Imports annotate

Suggests genefilter, parallel, knitr

LazyLoad yes

Description This package facilitates reading, preprocessing and manipulating Codelink microarray data. The raw data must be exported as text file using the Codelink software.

License GPL-2

Collate Codelink-class.R CodelinkSet-class.R file.R data.R norm.R
plot.R CodelinkSet-methods.R CodelinkSet-tools.R
CodelinkSetUnique-class.R CodelinkSetUnique-methods.R filter.R
cluster.R

biocViews Microarray, OneChannel, DataImport, Preprocessing

ByteCompile yes

VignetteBuilder knitr

URL <https://github.com/ddiez/codelink>

BugReports <https://github.com/ddiez/codelink/issues>

Config/pak/sysreqs libpng-dev libxml2-dev libssl-dev zlib1g-dev

Repository <https://bioc.r-universe.dev>

Date/Publication 2026-04-28 12:31:34 UTC

RemoteUrl <https://github.com/bioc/codelink>

RemoteRef HEAD

RemoteSha fb0f534aa37ae95eb0b1072f2387e59ef8ff535e

Contents

arrayNew	2
arraySize	3
as.matrix.Codelink	3
averageProbes	4
bkgdCorrect	5
Codelink-class	6
codelink.example	7
CodelinkSet-class	8
CodelinkSetUnique-class	9
codPlot	9
codset	10
createWeights	11
cutCV	11
decDetect	12
dim.Codelink	13
fc2Cond	13
imageCodelink	14
logCodelink	15
mergeArray	16
na2false	17
normalize	17
plotCorrelation	19
plotCV	20
plotDensities	20
plotMA	21
printHead	22
readCodelink	23
readHeader	24
readHeaderXLS	25
reportCodelink	26
selCV	27
SNR	27
writeCodelink	28
Index	29

arrayNew	Create a new x11 device
----------	-------------------------

Description

Create a new x11 device with dimensions suited to be used with imageCodelink().

Usage

```
arrayNew(f=2, chip="rwgcod")
```

Arguments

chip	character; Codelink chip to be used in imageCodelink.
f	numerical; scaling factor.

Author(s)

Diego Diez

Examples

```
## Not run:
  data(codelink.example)
  arrayNew()
  imageCodelink(codelink.example)

## End(Not run)
```

arraySize	<i>Determine the size of the array</i>
-----------	--

Description

When loading Codelink arrays in text format (as exported from the Codelink software) this function retrieves the correct size of the array. This is useful because those files contain an indetermined number of empty lines at the end. Thus, reading the entire data matrix doesn't work.

Note

Not meant to be used directly.

Author(s)

Diego Diez

as.matrix.Codelink	<i>Return a matrix of intensity values</i>
--------------------	--

Description

Takes a Codelink object and returns a matrix with the intensity values available.

Usage

```
## S3 method for class 'Codelink'
as.matrix(x, ...)
```

Arguments

`x` an object of class "Codelink".
`...` additional arguments added to generic `as.matrix` since R-2.5.x

Value

A matrix with the intensity values.

Author(s)

Diego Diez

See Also

[as.matrix](#)

Examples

```
## Not run:  
data(codelink.example)  
mat <- as.matrix(codelink.example)  
is(mat)  
  
## End(Not run)
```

averageProbes

averageProbes

Description

Takes a CodelinkSet object and computes the average (mean) and sd of duplicated probes.

Usage

```
averageProbes(object, parallel = FALSE)
```

Arguments

`object` an object of class "CodelinkSet".
`parallel` whether to use a parallel version (requires package multicore).

Details

This function will compute the `mean()` and `sd()` on each duplicated probe (i.e. identical probe id as for `probeNames()`). `CodelinkSet` objects use the per-array index to enable unique identifiers needed for `ExpressionSet` derived objects. Although the method `probeNames()` provides access to `Codelink` probe ids, this is inconvenient when dealing with other packages that make use of `featureNames()` to obtain probe ids and feed them to the corresponding annotation package.

In such cases `CodelinkSet` objects are not compatible with methods working on `ExpressionSet` objects. To avoid this limitation it is possible to construct a `CodelinkSet` object containing unique identifiers (`CodelinkSetUnique` class) by averaging the intensities of all replicated probes. This is done by computing the `mean()`. The `sd()` is also computed and stored in the slot `sd`.

The current implementation takes a lot of time so a parallelized version of `lapply()` may be used through the package 'multicore'. This is controlled by the argument 'parallel' which is `FALSE` by default.

According to the authors it is not actually possible to use 'multicore' in a GUI environment like the R.app Cocoa application in R, because this interferes with the events loop. Therefore it is advised to use option 'parallel=TRUE' in an R session running in a shell.

Author(s)

Diego Diez

Examples

```
## Not run:
  data(codelink.example)
  foo <- averageProbes(codelink.example)

## End(Not run)
```

bkgdCorrect

Background correction of intensity values.

Description

Takes a `CodelinkSet` or `Codelink` object with Spot mean and Bkgd median values and performs background correction using one of the methods available.

Usage

```
bkgdCorrect(object, method = "half", preserve = FALSE, verbose = FALSE, offset = 0)

## S4 method for signature 'CodelinkSet'
codCorrect(object, method = "half", normexp.method="saddle", offset=0)
```

Arguments

object	an object of class CodelinkSet or Codelink.
method	the correction method to use, one of "none", "subtract", "half" and "normexp".
preserve	logical; if Smean and Bmedian slots should be preserved.
verbose	logical; if TRUE print some information with method normexp.
normexp.method	method used with normexp correction.
offset	numeric; value to add to intensities.

Details

Available methods are: . none: left intensities untouched. . subtract: simple subtraction of Bkgd median from Spot mean. . half: the same as above but avoid negative values setting all intensity values below zero to 0.5. . normexp: apply normexp background adjustment from package limma.

Value

An object of class Codelink with corrected intensity values, that is Ri slot.

Author(s)

Diego Diez

Examples

```
data(codset)
codset <- codCorrect(codset, method = "half")
```

Codelink-class	<i>Class Codelink</i>
----------------	-----------------------

Description

This is the storage class for Codelink data

Objects from the Class

Object are created after reading text codelink files with readCodelink()

Description

Codelink objects contain a single "list", which contains the following elements:

sample Object of class "character" containing the sample names

file Object of class "character" containing the file names

name Object of class "character" containing the probe ID

method Object of class "list" containing log information

Smean Object of class "matrix" containing spot mean intensities
Bmedian Object of class "matrix" containing background median intensities
Ri Object of class "matrix" containing raw intensities
Ni Object of class "matrix" containing normalized intensities
snr Object of class "matrix" containing signal to noise ratio values
flag Object of class "character" containing assigned flags

Note

More details are in the package vignette

Author(s)

Diego Diez

Examples

```
## Not run:
  data(codelink.example)

## End(Not run)
```

codelink.example	<i>Dataset of class 'Codelink'</i>
------------------	------------------------------------

Description

Dataset from a h20kcod (Codelink Human UniSet I 20k) array containing 2 samples and ~20000 probes.

Usage

```
data(codelink.example)
```

Format

A [Codelink](#) object containing 20469 probes and 2 samples.

Author(s)

Diego Diez

CodelinkSet-class	<i>Class CodelinkSet</i>
-------------------	--------------------------

Description

This is the storage class for Codelink data

Objects from the Class

Object are created after reading text codelink files with `readCodelinkSet()`

Description

CodelinkSet objects are derived from ExpressionSet and therefore inherits all their methods. Additional methods are defined to extract information:

Old Codelink-class objects can be converted into CodelinkSet instances using the function `Codelink2CodelinkSet`.

Extends

Directly extends class [ExpressionSet](#).

Methods

Class-specific methods:

`getWeight` Get the matrix of weights.

Author(s)

Diego Diez

Examples

```
## Not run:  
  data(codset)  
  
## End(Not run)
```

`CodelinkSetUnique-class`*Class CodelinkSetUnique*

Description

This is the storage class for Codelink data– with unique probes

Objects from the Class

Object are created after applying `averageProbes()` on an object of the class `CodelinkSet`

Description

`CodelinkSetUnique` objects are derived from `ExpressionSet` and therefore inherits all the methods.

Note

More details are in the package vignette

Author(s)

Diego Diez

Examples

```
## Not run:
  data(codelink.exprs)
  foo <- averageProbes(codelink.exprs)

## End(Not run)
```

`codPlot`*Diagnostic plots for CodelinkSet object.*

Description

This function performs several types of diagnostic plots using information from `CodelinkSet` objects.

Usage

```
codPlot(object, array, what = "ma", ...)
```

Arguments

object	a CodelinkSet object.
array	The array to use for plotting (by default array=1).
what	the type of plot (by default ma).
...	additional arguments passed to the appropriate functions.

Details

Plot types:

scatter Scatter plot of the selected array intensities vs. the median array, or a second array if specified.

ma MA plot of the selected array intensities vs. the median array, or a second array if specified. In the x-axis the value of A (mean abundance; $A = \text{Array1} + \text{Array2}$) is plotted. In the y-axis the value of M (difference; $M = \text{Array1} - \text{Array2}$) is plotted.

density The distribution of intensities for each array in the dataset is plotted as a kernel density.

image If the logical position of the probes in the array are available, this plot produces a pseudomage of the array. The values of the "intensity", "bg" or "snr" can be selected with the 'signal' parameter (default signal="bg"). Color range can be controled with 'high' and 'low' parameters.

Author(s)

Diego Diez

codset

Dataset of class 'CodelinkSet'

Description

Dataset from a h20kcod (Codelink Human UniSet I 20k) array containing 4 samples and ~20000 probes.

Usage

```
data(codelink.example)
```

Format

A [Codelink](#) object containing 20469 probes and 4 samples.

Author(s)

Diego Diez

createWeights	<i>Create weight for Codelink chips</i>
---------------	---

Description

Create a weight matrix based on probe type and flags.

Usage

```
createWeights(object, type.weights = NULL, flag.weights = NULL)
```

Arguments

object	an object of class "Codelink" or "CodelinkSet".
type.weights	named character vector of type weights used.
flag.weights	named character vector of flag weights used.

Author(s)

Diego Diez

Examples

```
data(codset)
w <- createWeights(codset)
```

cutCV	<i>Calculate cutoff based in CV.</i>
-------	--------------------------------------

Description

Takes a Codelink object and calculate cutoff based in CV.

Usage

```
cutCV(object, subset=c(1:dim(object)[2]))
```

Arguments

object	an object of class "Codelink".
subset	subset of arrays to calculate cutoff with

Details

First it computes the median of CV for each gene over all arrays. Then it computes the mean and sd of all medians. Finally:

$\text{cutoff} = \text{mean} + 3 * \text{sd}$

Author(s)

Diego Diez

Examples

```
## Not run:
# data: Normalized Codelink object merged.
cutoff <- cutCV(data)

## End(Not run)
```

decDetect

Determine decimal type of Codelink files

Description

Determine decimal type of Codelink files.

Usage

```
decDetect(file, nlines)
```

Arguments

file	the file to be read.
nlines	number of lines to skip.

Value

Decimal type.

Author(s)

Diego Diez

dim.Codelink	<i>Return the dimension of a Codelink object.</i>
--------------	---

Description

Takes a Codelink object and returns the dimension (genes x samples).

Usage

```
## S3 method for class 'Codelink'  
dim(x)
```

Arguments

x an object of class "Codelink".

Value

A numeric vector with the dimensions.

Author(s)

Diego Diez

Examples

```
## Not run:  
data(codelink.example)  
dim(codelink.example)  
  
## End(Not run)
```

fc2Cond	<i>Select probes based on fold change calculation</i>
---------	---

Description

Takes a Codelink object and calculate fold changes (M) between two conditions (samples). Then select genes based on those who pass the passed cutoff.

Usage

```
fc2Cond(object, cond1=NULL, cond2=NULL, fc=1.0, verbose=FALSE)
```

Arguments

object	an object of class "Codelink".
cond1	numeric or character; First condition to compute M.
cond2	numeric or character; Second condition to compute M.
fc	value of the fold change cutoff
verbose	logical; if some information is printed on the console.

Details

Conditions can be passed as characters or as numeric index from the sample slot. The intensities are internally transformed to log2 if needed. The M value is computed as:

$$M = \text{cond1} - \text{cond2}$$

Value

A logical vector indicating which genes pass the cutoff

Author(s)

Diego Diez

imageCodelink

Image plot of Codelink arrays

Description

Plot and image of a Codelink array if the layout information is found.

Usage

```
imageCodelink(object, array = 1, what = "bg",
              low="black", high="white", mar=c(1,1,1,1),
              gr=1, gc=1, log.it=FALSE, ...)
```

Arguments

object	an object of class "Codelink".
array	array to be used.
what	with data plot: bg, smean, ri, ni.
low	color used for low intensities.
high	color used for high intensities-
mar	character vector specifying margins.
gc	numerical; number of grid columns.

```
gr          numerical; number of grid rows.  
log.it      logical; if TRUE data is log2 transformed (if not yet).  
...         additional arguments passed to image.
```

Author(s)

Diego Diez

Examples

```
## Not run:  
  data(codelink.example)  
  imageCodelink(codelink.example)  
  
## End(Not run)
```

logCodelink

Application of logCodelink to Codelink object

Description

Takes a Codelink object and apply logCodelink to intensity values.

Usage

```
logCodelink(object)
```

Arguments

object an object of class "Codelink" or a list of genes.

Value

A Codelink object with logCodelink intensities.

Author(s)

Diego Diez

See Also

[log2](#)

Examples

```
## Not run:  
  data(codelink.example)  
  codelink.example <- logCodelink(codelink.example)  
  
## End(Not run)
```

`mergeArray`*Merge Codelink Bioarrays Data*

Description

Merge data in a Codelink Object corresponding to same samples. Need a vector indicating the classes and an optional vector indicating the labels of the merged samples.

Usage

```
mergeArray(object, class, names=NULL, method="mean",
           log.it=FALSE, merge.snr=TRUE)
```

Arguments

<code>object</code>	an object of class "Codelink".
<code>class</code>	a numeric vector indicating the classes.
<code>names</code>	an optional character vector indicating labels for each class.
<code>method</code>	the method used to summarize. Currently only "mean" supported.
<code>log.it</code>	logical; a logical indicating if log2 values should be returned.
<code>merge.snr</code>	logical; a logical indicating if SNR values should be merged.

Value

An object of class "Codelink".

Author(s)

Diego Diez

Examples

```
## Not run:
data(codelink.example)
codelink.example <- bkgdCorrect(codelink.example)
codelink.example <- normalize(codelink.example, log.it = FALSE)
codelink.example <- mergeArray(codelink.example, class = c(1,1),
                              names = "SAMPLE", log.it = TRUE)

## End(Not run)
```

na2false	<i>Set NAs to FALSE</i>
----------	-------------------------

Description

Takes a logical vector as input and set all NAs to FALSE. This may happens when comparison is done on NA values.

Usage

```
na2false(x)
```

Arguments

x a logical vector.

Value

A logical vector without NAs.

Author(s)

Diego Diez

Examples

```
## Not run:
a <- c(1, 2, 3, NA, 5)
b <- c(5, 4, NA, 2, 1)
sel <- a > b
sel <- na2false(sel)

## End(Not run)
```

normalize	<i>Normalization wrapper for Codelink/CodelinkSet objects.</i>
-----------	--

Description

Takes a CodelinkSet or Codelink object and applies normalization to intensity values.

Usage

```
## S4 method for signature 'Codelink'
normalize(object, method="quantiles", log.it=TRUE, preserve=FALSE, weights=NULL, loess.method="fast")

## S4 method for signature 'CodelinkSet'
normalize(object, method="quantile", log.it=TRUE, weights=NULL, loess.method="fast")

## S4 method for signature 'CodelinkSet'
codNormalize(object, method="quantile", log.it=TRUE, weights=NULL, loess.method="fast")
```

Arguments

<code>object</code>	an object of class <code>CodelinkSet</code> or <code>Codelink</code> .
<code>method</code>	method to use in normalization.
<code>log.it</code>	logical; if data should be log2.
<code>preserve</code>	logical; if <code>Ri</code> slot should be preserved.
<code>weights</code>	weights for method <code>CyclicLoess</code> .
<code>loess.method</code>	loess method to be used, default to 'fast'.

Details

Currently supported methods include "median", "quantile" and "loess". Normalization functions are borrowed from the `limma` package.

If a matrix of weights is passed for `CyclicLoess` normalization, a vector is constructed taking the lowest weight for each probe.

Value

A `CodelinkSet` or `Codelink` object with normalized intensity values.

Author(s)

Diego Diez

Examples

```
data(codset)
# Background correction.
codset <- codCorrect(codset, method = "half")
# Normalization.
codset <- normalize(codset, method = "quantile")
```

plotCorrelation	<i>Plot correlation scatterplot between two arrays</i>
-----------------	--

Description

Takes a Codelink object as argument and plot Correlation scatterplot of two arrays.

Usage

```
plotCorrelation(object, x=1, y=2, cutoff=FALSE, label="type", title=NULL, xlim=NULL, ylim=NULL)
```

Arguments

object	an object of class "Codelink".
x	array to be used in x axis.
y	array to be used in y axis.
cutoff	cutoff used to show fold change.
label	labels to shown.
title	The title of the plot.
xlim	range for the X axis.
ylim	range for the Y axis.

Author(s)

Diego Diez

See Also

[plot](#)

Examples

```
## Not run:  
  data(codelink.example)  
  plotCorrelation(codelink.example)  
  
## End(Not run)
```

plotCV	<i>Plot of CV</i>
--------	-------------------

Description

Takes a Codelink object and plot de distribution of CV after applying mergeCodelink.

Usage

```
plotCV(object, subset=c(1:dim(object)[2]), cutoff=NULL, title=NULL, legend.cex=1)
```

Arguments

object	an object of class "Codelink".
subset	subset of arrays to plot
cutoff	cutoff of CV to be shown.
title	title of the plot.
legend.cex	factor to apply to the fonts in the legend to fit.

Author(s)

Diego Diez

plotDensities	<i>Plot Densities</i>
---------------	-----------------------

Description

Takes a Codelink object and plot the distributions of intensities.

Usage

```
plotDensities(object, what = NULL, title = NULL, col = NULL,
  legend.title = NULL, legend.cex=1, ...)
```

Arguments

object	an object of class "Codelink"
what	what data to plot, one of "bg", "smean", "snr", "ri" or "ni"
title	title of the plot
col	vector of colors
legend.title	if provided, a title for the legend
legend.cex	font factor use in legend
...	further arguments to be passed to plot() and line() functions (e.g. lwd, etc.)

Author(s)

Diego Diez

Examples

```
## Not run:
  data(codelink.example)
  plotDensities(codelink.example)

## End(Not run)
```

plotMA

*MA plot***Description**

Takes a Codelink object and plot M vs A.

Usage

```
plotMA(object, array1 = 1, array2 = NULL, cutoff = c(-1, 1), label = NULL,
  type = NULL, high.list = NULL, high.col = "blue", high.pch = 21,
  high.bg = "cyan", snr = NULL, snr.cutoff = 1, legend.x = NULL, pch = ".",
  subset = NULL, title = NULL, xlim = NULL, ylim = NULL)
```

Arguments

object	an object of class "Codelink" or "MAarrayLM".
array1	first array to be used.
array2	second array to be used.
cutoff	cutoff to be used as fold change marker.
label	type of labeling used in legend.
type	spot type information.
high.list	list of genes highlighted.
high.col	color used for high genes.
high.pch	pch used for high genes.
high.bg	background color used for high genes.
snr	vector with SNR values, usually, taking rowMeans() from a SNR matrix.
snr.cutoff	SNR cutoff used for label spots.
legend.x	relative position of the legend.
pch	pch style used to main spots.
subset	subset of spots used to plot based on 'type' slot.
title	title of the plot.
xlim	range for the X axis.
ylim	range for the Y axis.

Details

This function has suffered recent re-working, to increase the usability and to clean a little bit the code.

If array2 is NULL a median array is computed using all available arrays. Then the values of M and A are computed using the following formula:

$$M = \text{array2} - \text{array1}$$

$$A = (\text{array2} + \text{array1}) / 2$$

If type information is available in the Codelink object, or provided through the 'type' argument, spots are colored based on that. DISCOVERY spots are plotted black with pch = "." whereas the other classes are plotted with different background colors, using gray as border to increase contrasts. For that pch = 21 is used. If snr is specified as label option, the SNR is used to label spots, if available in the Codelink object. In this case, the mean SNR across all arrays is used when array2 = NULL.

Some parameters may not be working right now, as the new function is using a different method to labels spots.

The legend is 'automagically' located, but this can be overridden with the legend.x argument.

In addition, a subset of the spots can be plotted based on type information when available. This allows, for example, to plot only DISCOVERY spots.

Author(s)

Diego Diez

Examples

```
## Not run:
  data(codelink.example)
  plotMA(codelink.example)

## End(Not run)
```

printHead

Print briefly a Codelink object

Description

Takes a Codelink object and print a summary information of the data estored. It is based on print-Head() from package limma.

Usage

```
printHead(x)
```

Arguments

x an object of class "Codelink".

Author(s)

Diego Diez

readCodelink

*Read Codelink Bioarrays Data***Description**

Read data exported as text by Codelink Software. It reads values (normalized by Codelink Software or not) flags and information about probes.

Usage

```
readCodelink(files = list.files(pattern = "TXT"), sample.name =
  NULL, flag, flag.weights, type.weights, dec = NULL,
  type = "Spot", preserve = FALSE, verbose = 2,
  file.type = "Codelink", check = TRUE, fix = FALSE, old
  = FALSE)
readCodelinkSet(filename, path, phenoData = NULL, ...)
```

Arguments

files	list of files to read.
sample.name	vector of same length as files with sample names.
flag	list with values to assign based on Flag quality values.
flag.weights	weights assigned to each probe flag.
type.weights	weights assigned to each probe type.
dec	character indicating the decimal character used in the files.
type	character indicating which base value to read from files.
preserve	logical, if TRUE Bkgd\stdev slot is not removed (if present).
verbose	numerical, set the level of information. Level 2 set as old behaviour. Level > 2 output some debug info.
file.type	exported file type, currently Codelink or XLS file formats supported.
check	logical, check for probe order consistency.
fix	logical, try to fix probe order consistency.
old	logical, whether NA is assigned to intensities based on flags.
filename	list of files.
path	path to the files.
phenoData	phenoData object with sample information.
...	further arguments to be passed.

Value

readCodelink returns an object of class "Codelink", whereas readCodelinkSet() returns a CodelinkSet object.

Author(s)

Diego Diez

Examples

```
## Not run:
# specify a different one.
f <- list.files(pattern = "TXT")
codset <- readCodelinkSet(filename = f)

# read a targets file with phenotypic information
# including sample names, file names and sample groups.
pdata = read.AnnotationDataFrame("targets.txt")
codset = readCodelinkSet(pdata$FileNames, phenoData=pdata)

data(codset)

## End(Not run)
```

readHeader

Read Header from Codelink Bioarrays Files

Description

Read the header of Codelink files and obtain usefull information.

Usage

```
readHeader(file, dec=FALSE)
```

Arguments

file	File to read.
dec	logical; If TRUE determine decimal point.

Value

A list with header and other usefull information.

Author(s)

Diego Diez

Examples

```
## Not run:
  files <- list.files(pattern = "TXT")
  head <- readHeader(files[1])

## End(Not run)
```

readHeaderXLS*Read Header from XLS exported Codelink Bioarrays Files*

Description

Read the header of Codelink files and obtain useful information.

Usage

```
readHeaderXLS(file, dec=FALSE)
```

Arguments

file	File to read.
dec	logical; If TRUE determine decimal point.

Details

This function is not meant to be used by normal users.

Value

A list with header and other usefull information.

Author(s)

Diego Diez

Examples

```
## Not run:
  files <- list.files(pattern = "TXT")
  head <- readHeaderHeader(files[1])

## End(Not run)
```

reportCodelink	<i>Write a report of genes selected in HTML</i>
----------------	---

Description

Takes a list of genes as argument and writes an HTML page containing information about these genes: Unigene, Genbank, Entrez Gene, etc.

Usage

```
reportCodelink(object, chip, filename = NULL, title = "Main title",  
               probe.type = FALSE, other = NULL, other.ord = NULL)
```

Arguments

object	an object of class "Codelink" or a list of genes.
chip	the chip description package.
filename	file name used in the report.
title	title used in the report.
probe.type	logical; if TRUE Probe type information is written.
other	list of vectors containing additional values to add to the report.
other.ord	slot name in other to order genes by.

Value

Nothing, only the HTML file generated.

Author(s)

Diego Diez

See Also

[htmlpage](#)

selCV	<i>Select based on CV cutoff.</i>
-------	-----------------------------------

Description

Takes a Codelink object and select genes based on CV cutoff.

Usage

```
selCV(object, cutoff)
```

Arguments

object	an object of class "Codelink".
cutoff	cutoff normally calculated with cutCV()

Value

A logical vector.

Author(s)

Diego Diez

SNR	<i>Calculate SNR</i>
-----	----------------------

Description

Compute SNR inside read.Codelink.

Usage

```
SNR(Smean, Bmedian, Bstdev)
```

Arguments

Smean	matrix of Smean intensities.
Bmedian	matrix of background median intensities.
Bstdev	matrix of background standard deviation.

Author(s)

Diego Diez

writeCodelink	<i>Write a Codelink object to file.</i>
---------------	---

Description

Export of the data from a codelink object to a text file.

Usage

```
writeCodelink(object, file, dec = ".", sep = "\t", flag = FALSE, chip)
```

Arguments

object	an object of class "Codelink".
file	filename to write object to.
dec	decimal character to use.
sep	delimiter character to use.
flag	should the Codelink flags be written.
chip	chip package to use, normally guessed.

Details

By default, intensities and SNR are wrote to the file. If set, the flag are also output. The header have "INTENSITY_", "SNR_" and "FLAG_" respectibely appendend to the sample name for those values. The default delimiter is the tab character, but that can be set with the sep argument. The default decimal character is the point.

Author(s)

Diego Diez

Examples

```
## Not run:
  data(codelink.example)
  writeCodelink(codelink.example, file = "foo.txt")

## End(Not run)
```

Index

* classes

- Codelink-class, 6
- CodelinkSet-class, 8
- CodelinkSetUnique-class, 9

* datasets

- codelink.example, 7
- codset, 10

* documentation

- arrayNew, 2
- arraySize, 3
- as.matrix.Codelink, 3
- averageProbes, 4
- bkgdCorrect, 5
- createWeights, 11
- cutCV, 11
- decDetect, 12
- dim.Codelink, 13
- fc2Cond, 13
- imageCodelink, 14
- logCodelink, 15
- mergeArray, 16
- na2false, 17
- normalize, 17
- plotCorrelation, 19
- plotCV, 20
- plotDensities, 20
- plotMA, 21
- printHead, 22
- readCodelink, 23
- readHeader, 24
- readHeaderXLS, 25
- reportCodelink, 26
- selCV, 27
- SNR, 27
- writeCodelink, 28

* utilities

- arrayNew, 2
- arraySize, 3
- as.matrix.Codelink, 3

- averageProbes, 4

- bkgdCorrect, 5

- createWeights, 11

- cutCV, 11

- decDetect, 12

- dim.Codelink, 13

- fc2Cond, 13

- imageCodelink, 14

- logCodelink, 15

- mergeArray, 16

- na2false, 17

- normalize, 17

- plotCorrelation, 19

- plotCV, 20

- plotDensities, 20

- plotMA, 21

- printHead, 22

- readCodelink, 23

- readHeader, 24

- readHeaderXLS, 25

- reportCodelink, 26

- selCV, 27

- SNR, 27

- writeCodelink, 28

- [,Codelink,ANY,ANY-method

- (Codelink-class), 6

- [,Codelink-method (Codelink-class), 6

- arrayNew, 2

- arraySize, 3

- as.matrix, 4

- as.matrix.Codelink, 3

- averageProbes, 4

- averageProbes,CodelinkSet-method
- (averageProbes), 4

- bkgdCorrect, 5

- class::CodelinkSet (CodelinkSet-class),
- 8

class::CodelinkSetUnique
 (CodelinkSetUnique-class), 9
 class:Codelink (Codelink-class), 6
 codCorrect (bkgdCorrect), 5
 codCorrect, CodelinkSet-method
 (bkgdCorrect), 5
 Codelink, 7, 10
 Codelink (Codelink-class), 6
 Codelink-class, 6
 codelink.example, 7
 Codelink2CodelinkSet
 (CodelinkSet-class), 8
 CodelinkSet (CodelinkSet-class), 8
 CodelinkSet-class, 8
 CodelinkSetUnique
 (CodelinkSetUnique-class), 9
 CodelinkSetUnique-class, 9
 codNormalize (normalize), 17
 codNormalize, CodelinkSet-method
 (normalize), 17
 codPlot, 9
 codPlot, CodelinkSet-method (codPlot), 9
 codPlot, MArrayLM-method (codPlot), 9
 codPreprocess (CodelinkSet-class), 8
 codPreprocess, CodelinkSet-method
 (CodelinkSet-class), 8
 codset, 10
 createWeights, 11
 createWeights, Codelink-method
 (createWeights), 11
 createWeights, CodelinkSet-method
 (createWeights), 11
 cutCV, 11

 decDetect, 12
 dim.Codelink, 13

 ExpressionSet, 8
 exprs, CodelinkSet-method
 (CodelinkSet-class), 8

 fc2Cond, 13

 getBkg (CodelinkSet-class), 8
 getBkg, CodelinkSet-method
 (CodelinkSet-class), 8
 getFlag (CodelinkSet-class), 8
 getFlag, CodelinkSet-method
 (CodelinkSet-class), 8

 getInfo (CodelinkSet-class), 8
 getInfo, CodelinkSet-method
 (CodelinkSet-class), 8
 getInt (CodelinkSet-class), 8
 getInt, CodelinkSet-method
 (CodelinkSet-class), 8
 getSNR (CodelinkSet-class), 8
 getSNR, CodelinkSet-method
 (CodelinkSet-class), 8
 getWeight (CodelinkSet-class), 8
 getWeight, CodelinkSet-method
 (CodelinkSet-class), 8

 htmlpage, 26

 imageCodelink, 14

 log2, 15
 logCodelink, 15

 mergeArray, 16

 na2false, 17
 normalize, 17
 normalize, Codelink-method (normalize),
 17
 normalize, CodelinkSet-method
 (normalize), 17

 plot, 19
 plotCorrelation, 19
 plotCV, 20
 plotDensities, 20
 plotDensities, Codelink-method
 (plotDensities), 20
 plotMA, 21
 printHead, 22
 probeNames (CodelinkSet-class), 8
 probeNames, CodelinkSet-method
 (CodelinkSet-class), 8
 probeNames, CodelinkSetUnique-method
 (CodelinkSet-class), 8
 probeTypes (CodelinkSet-class), 8
 probeTypes, CodelinkSet-method
 (CodelinkSet-class), 8

 readCodelink, 23
 readCodelinkSet (readCodelink), 23
 readHeader, 24
 readHeaderXLS, 25

reportCodelink, [26](#)

selCV, [27](#)

show, Codelink-method (Codelink-class), [6](#)

SNR, [27](#)

writeCodelink, [28](#)

writeCodelink, CodelinkSet-method
(writeCodelink), [28](#)