

Package: damidBind (via r-universe)

October 17, 2026

Type Package

Title Differential Binding and Expression Analysis for DamID-seq Data

Version 1.1.1

Description The damidBind package provides a straightforward formal analysis pipeline to analyse and explore differential DamID binding, gene transcription or chromatin accessibility between two conditions. The package imports processed data from DamID-seq experiments, either as external raw files in the form of binding bedGraphs and GFF/BED peak calls, or as internal lists of GRanges objects. After optionally normalising data, combining peaks across replicates and determining per-replicate peak occupancy, the package links bound loci to nearby genes. For RNA Polymerase DamID data, the package calculates occupancy over genes, and optionally calculates the FDR of significantly-enriched gene occupancy. damidBind then uses either limma (for conventional log2 ratio DamID binding data) or NOIseq (for counts-based CATaDa chromatin accessibility data) to identify differentially-enriched regions, or differentially expressed genes, between two conditions. The package provides a number of visualisation tools (volcano plots, Gene Ontology enrichment plots via ClusterProfiler and proportional Venn diagrams via BioVenn for downstream data exploration and analysis. An powerful, interactive IGV genome browser interface (powered by Shiny and igvShiny) allows users to rapidly and intuitively assess significant differentially-bound regions in their genomic context.

License GPL-3

Encoding UTF-8

biocViews DifferentialExpression, GeneExpression, Transcription, Epigenetics, Visualization, Sequencing, Software, GeneRegulation

Depends R (>= 4.4.0)

Imports ggplot2, ggrepel, dplyr, tibble, stringr, tools, fs, rlang, BiocParallel, AnnotationHub, DBI, ensemblDb, GenomeInfoDb,

IRanges, GenomicRanges, S4Vectors, rtracklayer, limma, NOISeq,
 BioVenn, clusterProfiler, enrichplot, forcats, scales,
 colorspace, ggnewscale, methods, stats, igvShiny, shiny, DT,
 dbscan, circlize, ComplexHeatmap, patchwork, splines, mgcv

Suggests testthat, curl, knitr, htmltools, rmarkdown, BiocStyle,
 bookdown, org.Dm.eg.db

RoxygenNote 7.3.3

VignetteBuilder knitr

URL <https://marshall-lab.org/damidBind>

BugReports <https://github.com/marshall-lab/damidBind/issues>

Config/pak/sysreqs libcairo2-dev cmake libfontconfig1-dev libfreetype6-dev libfribidi-dev libglpk-
 dev make libharfbuzz-dev libbz2-dev libcxx-dev liblzma-dev libpng-dev libuv1-dev libxml2-
 dev libssl-dev perl libnode-dev xz-utils zlib1g-dev

Repository <https://bioc.r-universe.dev>

Date/Publication 2026-06-19 08:31:10 UTC

RemoteUrl <https://github.com/bioc/damidBind>

RemoteRef HEAD

RemoteSha c287f1ca69009f5b5ac796685c6a9f07ed676e23

Contents

analyse_go_enrichment	3
analysisTable	6
browse_igv_regions	7
calculate_and_add_occupancy_pvals	9
calculate_occupancy	11
conditionNames	13
DamIDResults-class	14
differential_accessibility	15
differential_binding	17
enrichedCond1	19
enrichedCond2	20
expressed	21
extract_unique_sample_ids	22
filter_genes_by_fdr	23
get_ensdb_genes	25
inputData	27
load_data_genes	28
load_data_peaks	30
metadata,DamIDResults-method	33
plot_catada_mean_variance	34
plot_input_diagnostics	34
plot_limma_diagnostics	35
plot_venn	37

<i>analyse_go_enrichment</i>	3
plot_volcano	39
quantile_normalisation	42
reduce_regions	43
sample_labels_by_isolation	44
test_weighting_vs_bias_artifact	46
test_weighting_vs_bias_batch	47
Index	48

<i>analyse_go_enrichment</i>	<i>Perform Gene Ontology (GO) enrichment analysis for differentially bound/expressed regions</i>
------------------------------	--

Description

This function performs Gene Ontology (GO) enrichment analysis using ‘clusterProfiler’ for either the up-regulated or down-regulated regions/genes identified by ‘differential_binding()’ or ‘differential_accessibility()’. It automatically extracts the relevant gene IDs (gene_ids) and the background universe from the input ‘DamIDResults’ object.

Usage

```
analyse_go_enrichment(
  diff_results,
  direction = "cond1",
  org_db = org.Dm.eg.db::org.Dm.eg.db,
  ontology = "BP",
  pvalue_cutoff = 0.05,
  qvalue_cutoff = 0.2,
  plot_title = NULL,
  show_category = 12,
  label_format_width = 50,
  wrap_labels = FALSE,
  fit_labels = FALSE,
  abbrev_terms = FALSE,
  abbrevs = c(regulation = "reg."),
  theme_size = 14,
  use_gse = FALSE,
  save = NULL,
  save_results_path = NULL,
  maxGSSize = 1000,
  minGSSize = 10,
  clean_gene_symbols = TRUE
)
```

Arguments

<code>diff_results</code>	A 'DamIDResults' object, as returned by 'differential_binding()' or 'differential_accessibility()'.
<code>direction</code>	Character string. Specifies which set of genes to analyse, either using condition names, "cond1" or "cond2", or "all" (for all significantly enriched genes from either direction). Default is "cond1".
<code>org_db</code>	An OrgDb object specifying the organism's annotation database. For Drosophila, use 'org.Dm.eg.db::org.Dm.eg.db'.
<code>ontology</code>	Character string. The GO ontology to use: "BP" (Biological Process), "MF" (Molecular Function), or "CC" (Cellular Component). Default is "BP".
<code>pvalue_cutoff</code>	Numeric. Adjusted p-value cutoff for significance. Default: 0.05.
<code>qvalue_cutoff</code>	Numeric. Q-value cutoff for significance. Default: 0.2.
<code>plot_title</code>	Character string. Title for the generated dot plot.
<code>show_category</code>	Integer. Number of top enriched GO categories to display in the plot. Default: 12.
<code>label_format_width</code>	Integer. Max character length for GO term labels on the plot before wrapping. Default: 50.
<code>wrap_labels</code>	Logical. Whether to wrap label text (TRUE) or truncate (FALSE) if greater than 'label_format_width' (Default: FALSE)
<code>fit_labels</code>	Set 'label_format_width' to the largest label width (Default: FALSE)
<code>abbrev_terms</code>	Logical. Whether to abbreviate common GO term words. (Default: FALSE)
<code>abbrevs</code>	Named vector of abbreviations to use for 'abbrev_terms'. (Default: 'c("regulation" = "reg.")')
<code>theme_size</code>	Integer. Base theme size to set. Default: 14.
<code>use_gse</code>	Logical. Whether to use GSEA via 'gseGO' rather than GO enrichment analysis (via 'enrichGO'). (Default: FALSE)
<code>save</code>	List or 'NULL'. Controls saving the plot to a file (dot plot). If 'NULL', 'FALSE', or '0', the plot is not saved. If a 'list', it specifies saving parameters: <ul style="list-style-type: none"> • filename (character): The path and base name for the output file. If not specified, the default name "damidBind_GSEA_dotplot" is used. • format (character): File format ("pdf", "svg", or "png"). Default is "pdf". • width (numeric): Width of the plot in inches. Default is 6. • height (numeric): Height of the plot in inches. Default is 6.
<code>save_results_path</code>	Character string or NULL. If a path is provided (e.g., "go_results.csv"), the enrichment results table will be saved to this CSV file.
<code>maxGSSize</code>	Integer. Maximum size of gene sets to consider. Default: 1000.
<code>minGSSize</code>	Integer. Minimum size of gene sets to consider. Default: 10.
<code>clean_gene_symbols</code>	Logical. Removes snoRNAs and tRNAs (common sources of accidental bias between different NGS methods) from the gene lists prior to enrichment analysis. Default: TRUE.

Details

This function assumes that the 'analysis' slot in the 'diff_results' object contains a 'gene_id' column. If this column is not present, or cannot be processed, the function will return NULL.

Value

A list containing:

`enrich_go_object` 'enrichResult' object from 'clusterProfiler'.

`results_table` Data frame of enrichment results.

`dot_plot` 'ggplot' object of the dot plot.

NULL if no significant enrichment is found or if input validation fails.

Examples

```
# This example requires the 'org.Dm.eg.db' package
if (requireNamespace("org.Dm.eg.db", quietly = TRUE)) {
  # Helper function to create a sample DamIDResults object
  .generate_example_results <- function() {
    # Define a mock gene object. Note: Real, mappable FlyBase IDs are
    # used for the 'gene_id' column to ensure the example runs.
    mock_genes_gr <- GenomicRanges::GRanges(
      seqnames = S4Vectors::Rle("2L", 7),
      ranges = IRanges::IRanges(
        start = c(1000, 2000, 3000, 5000, 6000, 7000, 8000),
        end = c(1500, 2500, 3500, 5500, 6500, 7500, 20000000)
      ),
      gene_id = c(
        "FBgn0034439", "FBgn0031267", "FBgn0051138", "FBgn0031265",
        "FBgn0004655", "FBgn0000251", "FBgn0000252"
      ),
      gene_name = c("ap", "dpr1", "side", "dpr2", "eg", "bi", "br")
    )
    data_dir <- system.file("extdata", package = "damidBind")
    loaded_data <- load_data_peaks(
      binding_profiles_path = data_dir,
      peaks_path = data_dir,
      ensdb_genes = mock_genes_gr,
      quantile_norm = TRUE
    )
    diff_results <- differential_binding(
      loaded_data,
      cond = c("L4 Neurons" = "L4",
        "L5 Neurons" = "L5")
    )
    return(diff_results)
  }
  diff_results <- .generate_example_results()
}
```

```

# Run GO Enrichment for genes enriched in the first condition ("L4")
# Note: with tiny sample data, this may not find significant terms.
go_results <- analyse_go_enrichment(
  diff_results,
  direction = "L4",
  org_db = org.Dm.eg.db::org.Dm.eg.db
)

# Print the results table if any enrichment was found
if (!is.null(go_results)) {
  print(go_results$results_table)
}
}

```

analysisTable	<i>Access the differential binding analysis results</i>
---------------	---

Description

This function returns the full differential analysis table from the `DamIDResults` object.

Usage

```
analysisTable(object)
```

Arguments

`object` A `DamIDResults` object.

Value

A `data.frame` with the full analysis results.

See Also

[DamIDResults-class](#) for an overview of the class and all its methods.

Examples

```

# Helper function to create a sample DamIDResults object for examples
.generate_example_results <- function() {
  analysis_df <- data.frame(
    logFC = c(2, -2, 0.1), P.Value = c(0.01, 0.01, 0.9), B = c(4, 3, -1),
    gene_name = c("GeneA", "GeneB", "GeneC"),
    row.names = c("chr1:1-100", "chr1:101-200", "chr1:201-300")
  )
  new("DamIDResults",
    analysis = analysis_df,
    upCond1 = analysis_df[1, , drop = FALSE],

```

```

        upCond2 = analysis_df[2, , drop = FALSE],
        cond = c("Condition 1" = "C1", "Condition 2" = "C2"),
        data = list(test_category = "bound")
    )
}
mock_results <- .generate_example_results()
analysisTable(mock_results)

```

`browse_igv_regions` *Interactive IGV visualisation (Shiny + igvShiny) of differential regions*

Description

Launches a Shiny app with an embedded IGV browser and an interactive table listing differentially-bound regions (from ‘differential_binding()’ or ‘differential_accessibility()’ results). Clicking on a region in the table will pan IGV to that locus. Sample coverage and region tracks are loaded as quantitative/annotation tracks. A dedicated "Save as SVG" button is provided to export the current IGV view.

Usage

```

browse_igv_regions(
  diff_results,
  samples = NULL,
  use_unique_ids = TRUE,
  average_tracks = FALSE,
  export_data_archive = NULL,
  colour_cond1 = "#ff6600",
  colour_cond2 = "#2288dd",
  use_genome = NULL,
  padding_width = 20000,
  trackHeight = 65,
  peakColour = "darkgreen",
  trackColour = "#6666ff",
  host = "localhost",
  port = NULL
)

```

Arguments

<code>diff_results</code>	A ‘DamIDResults’ object, as returned by ‘differential_binding()’ or ‘differential_accessibility()’.
<code>samples</code>	Optional character vector of sample names to display (default: all in dataset).
<code>use_unique_ids</code>	Logical. When ‘TRUE’ (default), simplified unique sample names will be displayed. Set as ‘FALSE’ to use the full sample file names from loading.
<code>average_tracks</code>	Logical. If ‘TRUE’, displays the average signal for each condition instead of individual replicate tracks. (Default: ‘FALSE’)

export_data_archive	Character or NULL. If a filename is provided (e.g. "my_data"), the function exports all IGV tracks as a zip archive ("my_data.zip") and exits without launching the browser. (Default: NULL)
colour_cond1, colour_cond2	Colours for differentially-enriched region tracks.
use_genome	IGV genome name (inferred from peak annotations if not provided).
padding_width	Width to pad browser viewbox on either side of the peak (Default: 20000)
trackHeight	Height of bedGraph tracks (Default: 65)
peakColour	Colour for significant peaks track (Default: "darkgreen")
trackColour	Colour for bedGraph tracks (Default: "#6666ff")
host	Hostname for the server location (Default: "localhost").
port	Port for connection (if NULL (default) the port is assigned by Shiny).

Details

Alternatively, if 'export_data_archive' is provided, the function will bypass the browser and save all tracks (including averaged tracks) as a zip archive of bedGraph and BED files.

Value

Invisibly returns the Shiny app object if launching the browser, or the path to the zip archive if exporting data.

Examples

```
## Not run:
if (isTRUE(curl::has_internet()) && interactive()) {
  # This example launches an interactive Shiny app in a web browser

  .generate_example_results <- function() {
    mock_genes_gr <- GenomicRanges::GRanges(
      seqnames = S4Vectors::Rle("2L", 7),
      ranges = IRanges::IRanges(
        start = c(1000, 2000, 3000, 5000, 6000, 7000, 8000),
        end = c(1500, 2500, 3500, 5500, 6500, 7500, 20000000)
      ),
      gene_id = c("FBgn001", "FBgn002", "FBgn003", "FBgn004", "FBgn005", "FBgn006", "FBgn007"),
      gene_name = c("geneA", "geneB", "geneC", "geneD", "geneE", "geneF", "LargeTestGene")
    )
    data_dir <- system.file("extdata", package = "damidBind")
    loaded_data <- load_data_peaks(
      binding_profiles_path = data_dir,
      peaks_path = data_dir,
      ensdb_genes = mock_genes_gr,
      quantile_norm = TRUE
    )
    diff_results <- differential_binding(
      loaded_data,
```

```

        cond = c("L4 Neurons" = "L4",
                  "L5 Neurons" = "L5")
    )
    return(diff_results)
}
diff_results <- .generate_example_results()

# Launch the interactive browser
browse_igv_regions(diff_results)

# Export data instead of launching browser
browse_igv_regions(diff_results, export_data_archive = "L4_vs_L5_tracks")
}

## End(Not run)

```

calculate_and_add_occupancy_pvals

Calculate and add gene occupancy FDR

Description

This function calculates a p-value for gene occupancy scores. When adjusted for multiple-hypothesis testing, the resulting FDR may be used as a proxy for determining whether a gene is actively expressed in RNA Polymerase TaDa experiments. The function applies a permutation-based null model to each sample's binding profile to determine empirical p-values, and returns these as new columns in the input occupancy dataframe.

These p-values are then aggregated and

Usage

```

calculate_and_add_occupancy_pvals(
  binding_data,
  occupancy_df,
  null_model_iterations = 1e+05,
  return_per_replicate_fdr = FALSE,
  plot_diagnostics = FALSE,
  BPPARAM = BiocParallel::bpparam(),
  seed = NULL
)

```

Arguments

binding_data	A 'GRanges' object of binding profiles, where metadata columns represent samples. This is typically the 'binding_profiles_data' element from the list returned by 'load_data_genes'.
--------------	--

<code>occupancy_df</code>	A data frame of gene occupancies, typically the ‘occupancy’ element from the list returned by ‘load_data_genes’. It must contain sample columns and a ‘nfrags’ column.
<code>null_model_iterations</code>	Integer. The number of sampling iterations to build the FDR null model. Higher values are more accurate but slower. Default is 100000.
<code>return_per_replicate_fdr</code>	Logical. Returns individual FDR scores by applying BH adjustment on each individual sample. Use this option if not intending to apply downstream condition-level p-value aggregation via ‘differential_binding()’. (Default: FALSE)
<code>plot_diagnostics</code>	Logical. If TRUE, will plot the Tier 2 regression fits for the p-value prediction slope, intercept and mean squared error (MSE). (Default: FALSE)
<code>BPPARAM</code>	A ‘BiocParallelParam’ instance specifying the parallel backend to use for computation. See ‘BiocParallel::bpparam()’.
<code>seed</code>	An optional integer. If provided, it is used to set the random seed before the sampling process begins, ensuring that the FDR calculations are fully reproducible. If ‘NULL’ (default), results may vary between runs.

Details

The algorithm used here is substantially revised and adapted from the method described in Southall et al. (2013), Dev Cell, 26(1), 101-12. The broad principle is as follows:

1. For each sample, a null distribution of mean occupancy scores is simulated by repeatedly sampling random fragments from the genome-wide binding profile. This is done for various numbers of fragments.
2. A two-tiered regression model is fitted to the simulation results. This creates a statistical model that can predict the empirical p-value for any given occupancy score and fragment count.
3. This predictive model is then applied to the actual observed mean occupancy and fragment count for each gene in the ‘occupancy_df’.
4. The final set of p-values is adjusted using BH correction to generate FDR scores for each gene.
5. The FDR value for each gene in each sample is appended to the ‘occupancy_df’ in a new column.

Key differences from the original Southall et al. algorithm include fitting natural spline models, using WLS to account for heteroscedasticity of models, and sampling with replacement to generate the underlying null distribution.

This function is typically not called directly by the user, but is instead invoked via ‘load_data_genes(calculate_occupancy_pvals = TRUE)’.

Value

An updated version of the input ‘occupancy_df’ data frame, with new columns appended. For each sample column (e.g., ‘SampleA’), a corresponding p-value column (e.g., ‘SampleA_pval’) is added.

See Also

[load_data_genes()] which uses this function internally.

Examples

```
# Prepare sample binding data (GRanges object)
# Here, we'll load one of the sample files included with the package
# (this is a TF binding profile, which would not normally be used for
# occupancy calculations)
data_dir <- system.file("extdata", package = "damidBind")
bgraph_file <- file.path(data_dir, "Bsh_Dam_L4_r1-ext300-vs-Dam.kde-norm.gatc.2L.bedgraph.gz")

# The internal function `import_bedgraph_as_df` is used here for convenience.
# The column name 'score' will be replaced with the sample name.
binding_df <- damidBind::import_bedgraph_as_df(bgraph_file, colname = "Sample_1")

binding_gr <- GenomicRanges::GRanges(
  seqnames = binding_df$chr,
  ranges = IRanges::IRanges(start = binding_df$start, end = binding_df$end),
  Sample_1 = binding_df$Sample_1
)

# Create a mock occupancy data frame.
# In a real analysis, this would be generated by `calculate_occupancy()`.
mock_occupancy <- data.frame(
  name = c("geneA", "geneB", "geneC"),
  nfrags = c(5, 10, 2),
  Sample_1 = c(1.5, 0.8, -0.2),
  row.names = c("geneA", "geneB", "geneC")
)

# Calculate pvals.
# We use a low null_model_iterations for speed, and a seed for reproducibility.
occupancy_with_pvals <- calculate_and_add_occupancy_pvals(
  binding_data = binding_gr,
  occupancy_df = mock_occupancy,
  null_model_iterations = 100,
  BPPARAM = BiocParallel::SerialParam(),
  seed = 42
)

# View the result, which now includes a _pval column for Sample_1.
print(occupancy_with_pvals)
```

Description

For each interval in the 'regions' GRanges object, this function finds all overlapping fragments in 'binding_data' and computes a weighted mean of their signal values. Any metadata columns present in the input 'regions' object are preserved in the output data.frame.

Usage

```
calculate_occupancy(
  binding_data,
  regions,
  buffer = 0,
  BPPARAM = BiocParallel::bpparam()
)
```

Arguments

binding_data	A data.frame as produced by 'build_dataframes()'. It must contain columns 'chr', 'start', 'end', followed by numeric sample columns.
regions	A GRanges object of genomic intervals (e.g., genes or reduced peaks) over which to calculate occupancy.
buffer	Optional integer. Number of base pairs to expand each interval in 'regions' on both sides before calculating occupancy. Default is 0.
BPPARAM	A BiocParallel parameter object for parallel computation. Default is 'BiocParallel::bpparam()'.

Value

A data.frame with one row per region from the input 'regions' object. The output includes the weighted mean occupancy for each sample, 'nfrags' (number of overlapping fragments), and all original metadata columns from 'regions'. Rownames are generated from region coordinates to ensure uniqueness.

Examples

```
# Create a set of regions with metadata
regions_gr <- GenomicRanges::GRanges(
  "chrX", IRanges::IRanges(start = c(100, 500), width = 100),
  gene_name = c("MyGene1", "MyGene2"), score = c(10, 20)
)

# Create a mock binding data GRanges object
binding_gr <- GenomicRanges::GRanges(
  seqnames = "chrX",
  ranges = IRanges::IRanges(
    start = c(90, 150, 480, 550),
    end = c(110, 170, 520, 580)
  ),
  sampleA = c(1.2, 0.8, 2.5, 3.0),
  sampleB = c(1.0, 0.9, 2.8, 2.9)
)
```

```

)

# Calculate occupancy over the regions
# Use BiocParallel::SerialParam() for deterministic execution in examples
if (requireNamespace("BiocParallel", quietly = TRUE)) {
  occupancy_data <- calculate_occupancy(binding_gr, regions_gr,
    BPPARAM = BiocParallel::SerialParam()
  )
  print(occupancy_data)
}

```

conditionNames	<i>Access condition name mapping</i>
----------------	--------------------------------------

Description

This function returns the mapping of user-friendly display names to internal condition identifiers.

Usage

```
conditionNames(object)
```

Arguments

object A DamIDResults object.

Value

A named character vector.

See Also

[DamIDResults-class](#)

Examples

```

# Helper function to create a sample DamIDResults object for examples
.generate_example_results <- function() {
  analysis_df <- data.frame(
    logFC = c(2, -2, 0.1), P.Value = c(0.01, 0.01, 0.9), B = c(4, 3, -1),
    gene_name = c("GeneA", "GeneB", "GeneC"),
    row.names = c("chr1:1-100", "chr1:101-200", "chr1:201-300")
  )
  new("DamIDResults",
    analysis = analysis_df,
    upCond1 = analysis_df[1, , drop = FALSE],
    upCond2 = analysis_df[2, , drop = FALSE],
    cond = c("Condition 1" = "C1", "Condition 2" = "C2"),
    data = list(test_category = "bound")
  )
}

```

```

}
mock_results <- .generate_example_results()
conditionNames(mock_results)

```

DamIDResults-class *The DamIDResults Class*

Description

An S4 class to store the results of a differential analysis, as generated by [differential_binding](#) or [differential_accessibility](#). It contains the full analysis table, subsets of significantly changed regions, and associated metadata.

Slots

analysis A 'data.frame' containing the full differential analysis table from 'limma' or 'NOISEq'.

upCond1 A 'data.frame' of regions significantly enriched in the first condition.

upCond2 A 'data.frame' of regions significantly enriched in the second condition.

cond A named 'character' vector mapping user-friendly display names (the names) to the internal condition identifiers (the values) used in the analysis.

data A 'list' containing the initial input data used for the analysis, including the occupancy 'data.frame' and other metadata.

Accessor Methods

The following accessor functions are available for a DamIDResults object.

- [analysisTable](#)(object): Returns the full differential analysis table (a data.frame).
- [enrichedCond1](#)(object): Returns a data.frame of regions significantly enriched in the first condition.
- [enrichedCond2](#)(object): Returns a data.frame of regions significantly enriched in the second condition.
- [conditionNames](#)(object): Returns a named character vector mapping display names to internal identifiers.
- [inputData](#)(object): Returns a list containing the original input data used for the analysis.
- [expressed](#)(object, condition, fdr = 0.05, which = "any"): Returns a data.frame of genes considered expressed in 'condition', based on an FDR threshold of significantly enriched occupancy. Only available for analyses with FDR calculations, generated via `load_data_genes(calculate_occ = TRUE)`.

Generic Methods

The generic `plot()` function is also S4-enabled for this class. Calling `plot(object)` is equivalent to calling `plot_volcano(diff_results = object)`.

See Also

For more powerful and specific plotting functions, see [plot_volcano](#), [plot_venn](#), and [analyse_go_enrichment](#).

To explore the differential analysis results in an interactive IGV browser window, see [browse_igv_regions](#)

Examples

```
# Helper function to create a sample DamIDResults object for examples
.generate_example_results <- function() {
  analysis_df <- data.frame(
    logFC = c(2, -2, 0.1), P.Value = c(0.01, 0.01, 0.9), B = c(4, 3, -1),
    gene_name = c("GeneA", "GeneB", "GeneC"),
    row.names = c("chr1:1-100", "chr1:101-200", "chr1:201-300")
  )
  new("DamIDResults",
    analysis = analysis_df,
    upCond1 = analysis_df[1, , drop = FALSE],
    upCond2 = analysis_df[2, , drop = FALSE],
    cond = c("Condition 1" = "C1", "Condition 2" = "C2"),
    data = list(test_category = "bound")
  )
}
mock_results <- .generate_example_results()

# Show the object summary
mock_results

# Access different parts of the object
analysisTable(mock_results)
enrichedCond1(mock_results)
conditionNames(mock_results)
```

differential_accessibility

Differential accessibility analysis for CATaDa ('NOISEq' based)

Description

Setup and differential analysis for CATaDa chromatin accessibility experiments using 'NOISEq'. Accepts output from 'load_data_peaks', prepares a count matrix, performs 'NOISEq' analysis, and returns differentially-accessible loci.

Usage

```
differential_accessibility(data_list, cond, regex = FALSE, norm = "n", q = 0.8)
```

Arguments

<code>data_list</code>	List. Output from <code>load_data_peaks</code> .
<code>cond</code>	A named or unnamed character vector of length two. The values are strings or regular expressions used to identify samples for each condition. If the vector is named, the names are used as user-friendly display names for the conditions in plots and outputs. If unnamed, the match strings are used as display names. The order determines the contrast, e.g., <code>'cond[1]'</code> vs <code>'cond[2]'</code> .
<code>regex</code>	Logical. If <code>'TRUE'</code> , the strings in <code>'cond'</code> are treated as regular expressions for matching sample names. If <code>'FALSE'</code> (the default), fixed string matching is used.
<code>norm</code>	Normalisation method passed to <code>NOISeq</code> . Defaults to <code>"n"</code> (no normalisation), but <code>"uqua"</code> (upper quantile) or <code>"tmm"</code> (trimmed mean of M) are options if needed
<code>q</code>	Numeric. Q-value threshold for <code>NOISeq</code> significance (default 0.8).

Value

A `'DamIDResults'` object containing the results. Access slots using accessors (e.g., `'analysisTable(results)'`). The object includes:

<code>upCond1</code>	data.frame of regions enriched in condition 1
<code>upCond2</code>	data.frame of regions enriched in condition 2
<code>analysis</code>	data.frame of full results for all tested regions
<code>cond</code>	A named character vector mapping display names to internal condition names
<code>data</code>	The original <code>'data_list'</code> input

Examples

```
# NOTE: This example uses mock counts data, as the package's sample
# data is in log2-ratio format.
```

```
# Create a mock data_list with plausible count data
mock_occupancy_counts <- data.frame(
  name = c("peak1", "peak2", "peak3"),
  gene_name = c("GeneA", "GeneB", "GeneC"),
  gene_id = c("ID_A", "ID_B", "ID_C"),
  GroupA_rep1 = c(100, 20, 50), GroupA_rep2 = c(110, 25, 45),
  GroupB_rep1 = c(10, 200, 55), GroupB_rep2 = c(15, 220, 60),
  row.names = c("peak1", "peak2", "peak3")
)
```

```
mock_data_list <- list(
  occupancy = mock_occupancy_counts,
  test_category = "accessible"
)
```

```
# Run differential accessibility analysis
diff_access_results <- differential_accessibility(
  mock_data_list,
  cond = c("Group A" = "GroupA", "Group B" = "GroupB")
)
```

```
)

# View the results summary
diff_access_results
```

differential_binding *Differential binding/expression analysis ('limma')*

Description

Setup and differential analysis for occupancy/binding experiments using 'limma'. Accepts output from 'load_data_peaks' or 'load_data_genes', prepares an experiment matrix, fits linear models, and returns DE loci.

Usage

```
differential_binding(
  data_list,
  cond,
  regex = FALSE,
  fdr = 0.05,
  eBayes_trend = TRUE,
  eBayes_robust = TRUE,
  plot_diagnostics = interactive(),
  filter_occupancy = TRUE,
  filter_threshold = 0,
  filter_positive_enrichment = TRUE,
  p_combine_method = c("stouffer", "fisher")
)
```

Arguments

data_list	List. Output from load_data_peaks or load_data_genes.
cond	A named or unnamed character vector of length two. The values are strings or regular expressions used to identify samples for each condition. If the vector is named, the names are used as user-friendly display names for the conditions in plots and outputs. If unnamed, the match strings are used as display names. The order determines the contrast, e.g., 'cond[1]' vs 'cond[2]'.
regex	Logical. If 'TRUE', the strings in 'cond' are treated as regular expressions for matching sample names. If 'FALSE' (the default), fixed string matching is used.
fdr	Numeric. FDR threshold for significance (default 0.05).
eBayes_trend	Logical. If 'TRUE', the analysis will account for data heteroscedasticity, which is common in DamID-seq data. (default: TRUE)
eBayes_robust	Logical. If 'TRUE', the fitted trend should be robust to outliers. Only useful when 'eBayes_trend = TRUE'. Recommended for DamID-seq data. (default: TRUE)

plot_diagnostics
 Logical. If 'TRUE' (default for interactive sessions), plots limma diagnostics to assess eBayes moderation, using 'plot_limma_diagnostics'.

filter_occupancy
 NULL or integer. Filters out any locus with occupancy > 'filter_threshold' in fewer than this number of samples of any single condition when set. If set to TRUE, defaults to the minimum length of the two conditions. If FALSE or NULL, no filtering is applied. (default: TRUE)

filter_threshold
 Numeric. 'filter_occupancy' uses this value for thresholding the input data. (default: 0)

filter_positive_enrichment
 Logical. If 'TRUE' (default), regions are only considered significantly enriched if the mean score in the enriched condition is greater than zero. For example, for a region to be in 'upCond1', its logFC must be positive and its mean score in condition 1 must be > 0. Set to 'FALSE' to include all statistically significant changes.

p_combine_method
 Method to combine p-values from replicates (default: "fisher")

Value

A 'DamIDResults' object containing the results. Access slots using accessors:

enrichedCond1()
 data.frame of regions enriched in condition 1

enrichedCond2()
 data.frame of regions enriched in condition 2

analysisTable()
 data.frame of full results for all tested regions

conditionNames()
 A named character vector mapping display names to internal condition names

inputData()
 The original 'data_list' input

Examples

```
# Create a mock GRanges object for gene annotations
# This object, based on the package's unit tests, avoids network access.
mock_genes_gr <- GenomicRanges::GRanges(
  seqnames = S4Vectors::Rle("2L", 7),
  ranges = IRanges::IRanges(
    start = c(1000, 2000, 3000, 5000, 6000, 7000, 8000),
    end = c(1500, 2500, 3500, 5500, 6500, 7500, 20000000)
  ),
  strand = S4Vectors::Rle(GenomicRanges::strand(c("+", "-", "+", "+", "-", "-", "+"))),
  gene_id = c("FBgn001", "FBgn002", "FBgn003", "FBgn004", "FBgn005", "FBgn006", "FBgn007"),
  gene_name = c("geneA", "geneB", "geneC", "geneD", "geneE", "geneF", "LargeTestGene")
)
```

```
# Get path to sample data files included with the package
data_dir <- system.file("extdata", package = "damidBind")

# Load data
loaded_data <- load_data_peaks(
  binding_profiles_path = data_dir,
  peaks_path = data_dir,
  ensdb_genes = mock_genes_gr,
  quantile_norm = TRUE
)

# Run differential binding analysis
diff_results <- differential_binding(
  loaded_data,
  cond = c("L4 Neurons" = "L4", "L5 Neurons" = "L5")
)

# View the results summary
diff_results
```

enrichedCond1*Access Condition 1 enriched regions*

Description

This function returns the subset of regions significantly enriched in the first condition.

Usage

```
enrichedCond1(object)
```

Arguments

object A DamIDResults object.

Value

A data.frame.

See Also

[DamIDResults-class](#)

Examples

```
# Helper function to create a sample DamIDResults object for examples
.generate_example_results <- function() {
  analysis_df <- data.frame(
    logFC = c(2, -2, 0.1), P.Value = c(0.01, 0.01, 0.9), B = c(4, 3, -1),
    gene_name = c("GeneA", "GeneB", "GeneC"),
    row.names = c("chr1:1-100", "chr1:101-200", "chr1:201-300")
  )
  new("DamIDResults",
    analysis = analysis_df,
    upCond1 = analysis_df[1, , drop = FALSE],
    upCond2 = analysis_df[2, , drop = FALSE],
    cond = c("Condition 1" = "C1", "Condition 2" = "C2"),
    data = list(test_category = "bound")
  )
}
mock_results <- .generate_example_results()
enrichedCond1(mock_results)
```

enrichedCond2	<i>Access Condition 2 enriched regions</i>
---------------	--

Description

This function returns the subset of regions significantly enriched in the second condition.

Usage

```
enrichedCond2(object)
```

Arguments

object A DamIDResults object.

Value

A data.frame.

See Also

[DamIDResults-class](#)

Examples

```
# Helper function to create a sample DamIDResults object for examples
.generate_example_results <- function() {
  analysis_df <- data.frame(
    logFC = c(2, -2, 0.1), P.Value = c(0.01, 0.01, 0.9), B = c(4, 3, -1),
    gene_name = c("GeneA", "GeneB", "GeneC"),
```

```
        row.names = c("chr1:1-100", "chr1:101-200", "chr1:201-300")
    )
    new("DamIDResults",
        analysis = analysis_df,
        upCond1 = analysis_df[1, , drop = FALSE],
        upCond2 = analysis_df[2, , drop = FALSE],
        cond = c("Condition 1" = "C1", "Condition 2" = "C2"),
        data = list(test_category = "bound")
    )
}
mock_results <- .generate_example_results()
enrichedCond2(mock_results)
```

expressed	<i>Get expressed genes/loci by FDR</i>
-----------	--

Description

A method to filter genes or loci that are considered 'expressed' in a specific condition, based on a False Discovery Rate (FDR) threshold. The method is a wrapper around the [filter_genes_by_fdr](#) function.

Usage

```
expressed(object, condition, fdr = 0.05, which = "any")
```

Arguments

object	A DamIDResults object. This object must have been generated from data loaded with <code>load_data_genes</code> (<code>calculate_occupancy_pvals = TRUE</code>) for the underlying FDR columns to be present.
condition	A character string identifying the experimental condition to filter. This can be the internal identifier or the user-friendly display name.
fdr	Numeric. The FDR cutoff. Defaults to 0.05.
which	Character string, either 'any' or 'all'. Determines whether a gene must pass the FDR threshold in any or all replicates of the condition. Defaults to 'any'.

Value

A data.frame containing the gene_name and gene_id of genes that pass the filter.

See Also

[filter_genes_by_fdr](#), [DamIDResults-class](#), [load_data_genes](#)

Examples

```
.generate_fdr_example_results <- function() {
  occupancy_df <- data.frame(
    gene_name = c("geneA", "geneB", "geneC"),
    gene_id = c("FBgn01", "FBgn02", "FBgn03"),
    L4_rep1 = c(1.5, 0.2, 0.8),
    L4_rep2 = c(1.7, 0.9, 0.1),
    L5_rep1 = c(0.1, 0.1, 2.0),
    L4_rep1_FDR = c(0.01, 0.10, 0.04),
    L4_rep2_FDR = c(0.03, 0.02, 0.50),
    L5_rep1_FDR = c(0.80, 0.90, 0.01),
    row.names = c("geneA", "geneB", "geneC")
  )
  diff_results_base <- list(
    occupancy = occupancy_df,
    test_category = "expressed",
    matched_samples = list("L4" = c("L4_rep1", "L4_rep2"), "L5" = "L5_rep1")
  )
  new("DamIDResults",
    analysis = data.frame(row.names = rownames(occupancy_df)),
    upCond1 = data.frame(),
    upCond2 = data.frame(),
    cond = c("L4 mock" = "L4", "L5 mock" = "L5"),
    data = diff_results_base
  )
}
mock_fdr_results <- .generate_fdr_example_results()

# Get expressed in a condition (FDR <= 0.05)
expressed(mock_fdr_results, condition = "L4 mock")

# Get genes expressed with a more stringent FDR (<= 0.01)
expressed(mock_fdr_results, condition = "L4", fdr = 0.01)
```

extract_unique_sample_ids

Extract unique sample names from complex labels

Description

This function takes a vector of complex sample labels and iteratively constructs a simplified, unique name for each. It identifies all blocks of text that differ across the sample set and progressively adds them to a base name until the combination of the base name and a replicate identifier is unique for every sample.

Usage

```
extract_unique_sample_ids(
  sample_names,
```

```

    delimiter = "[_\\.]",
    replicate_pattern = "(n|N|r|rep|replicate|sample)\\d+"
  )

```

Arguments

sample_names A character vector of sample labels.

delimiter A regular expression used as a delimiter to split labels into blocks. (Default: `'[_\\.]'`)

replicate_pattern A regular expression used to identify the replicate block. (Default: `'(n|N|r|rep|replicate|sample)\\d+'`)

Value

A vector of simplified, unique names. If a unique name cannot be formed or essential information is missing for a sample, the original label for that sample is returned as a fallback.

Examples

```

labels <- c(
  "RNAPII_elav-GSE77860-n1-SRR3164378-2017-vs-Dam.scaled.kde-norm",
  "RNAPII_elav-GSE77860-n2-SRR3164379-2017-vs-Dam.scaled.kde-norm",
  "RNAPII_elav-GSE77860-n4-SRR3164380-2017-vs-Dam.scaled.kde-norm",
  "RNAPII_Wor-GSE77860-n1-SRR3164346-2017-vs-Dam.scaled.kde-norm",
  "RNAPII_Wor-GSE77860-n2-SRR3164347-2017-vs-Dam.scaled.kde-norm",
  "RNAPII_Wor-GSE77860-sample1-SRR2038537-2017-vs-Dam.scaled.kde-norm"
)
extract_unique_sample_ids(labels)

```

`filter_genes_by_fdr` *Filter genes by FDR within a specific condition*

Description

Filters a list of genes to retain only those that meet a specified False Discovery Rate (FDR) threshold. If the input is a `'DamIDResults'` object and a combined condition-level FDR has been calculated, that value is used. Otherwise, the function falls back to filtering against individual replicates.

Usage

```
filter_genes_by_fdr(data, fdr = 0.05, condition, which = "any")
```

Arguments

<code>data</code>	A 'DamIDResults' object or the 'list' returned by 'load_data_genes()'.
<code>fdr</code>	A numeric value between 0 and 1 specifying the FDR cutoff. (Default: 0.05)
<code>condition</code>	A character string identifying the experimental condition. This string should uniquely match the relevant sample columns (e.g., "L4" will match "L4_rep1_FDR" and "L4_rep2_FDR"). If 'data' is a 'DamIDResults' object, this can be either the internal identifier or the display name for the condition.
<code>which</code>	A character string, either '"any"' or '"all"'. Only applicable when falling back to individual replicate scores. (Default: '"any"')
	<ul style="list-style-type: none"> • If '"any"', a gene is kept if it meets the 'fdr' threshold in at least one replicate of the specified 'condition'. • If '"all"', a gene is kept only if it meets the 'fdr' threshold in all replicates of the specified 'condition'.

Details

This function is primarily used in workflows involving RNA Polymerase TaDa data, where an FDR is calculated for gene occupancy to determine if a gene is actively transcribed. It allows users to identify genes in a single condition that can be considered to be expressed (i.e. RNA Pol occupancy is significantly greater than background).

Note that while this is an effective proxy for gene expression, there are edge cases (e.g. paused polymerase, short genes directly adjacent to an expressed gene TSS or TES) where a gene may have significant occupancy but not, in fact, be transcribed.

The function locates the relevant FDR columns in the 'occupancy' table by searching for column names that end with '_FDR' and also contain the 'condition' string.

Value

A 'data.frame' containing the 'gene_name', 'gene_id', 'avg_occ', and the most significant FDR value found.

Examples

```
# Create a mock data object with an occupancy table containing FDR values,
# similar to the output of `load_data_genes(estimate_occupancy_pvals = TRUE)`
.generate_fdr_example_results <- function() {
  occupancy_df <- data.frame(
    gene_name = c("geneA", "geneB", "geneC"),
    gene_id = c("FBgn01", "FBgn02", "FBgn03"),
    L4_rep1 = c(1.5, 0.2, 0.8),
    L4_rep2 = c(1.7, 0.9, 0.1),
    L5_rep1 = c(0.1, 0.1, 2.0),
    L4_rep1_FDR = c(0.01, 0.10, 0.04),
    L4_rep2_FDR = c(0.03, 0.02, 0.50),
    L5_rep1_FDR = c(0.80, 0.90, 0.01),
    row.names = c("geneA", "geneB", "geneC")
  )
  diff_results_base <- list(
```

```

        occupancy = occupancy_df,
        test_category = "expressed",
        matched_samples = list("L4" = c("L4_rep1", "L4_rep2"), "L5" = "L5_rep1")
    )
    new("DamIDResults",
        analysis = data.frame(row.names = rownames(occupancy_df)),
        upCond1 = data.frame(),
        upCond2 = data.frame(),
        cond = c("L4 mock" = "L4", "L5 mock" = "L5"),
        data = diff_results_base
    )
}
mock_data <- .generate_fdr_example_results()

# Example 1: Get genes with FDR <= 0.05 in ANY L4 replicate.
# geneA (0.01, 0.03), geneB (0.02), and geneC (0.04) pass.
expressed_in_L4_any <- filter_genes_by_fdr(
    mock_data,
    fdr = 0.05,
    condition = "L4",
    which = "any"
)
print(expressed_in_L4_any)

# Example 2: Get genes with FDR <= 0.05 in ALL L4 replicates.
# Only geneA (0.01, 0.03) passes.
expressed_in_L4_all <- filter_genes_by_fdr(
    mock_data,
    fdr = 0.05,
    condition = "L4",
    which = "all"
)
print(expressed_in_L4_all)

# Example 3: Get genes with FDR <= 0.05 in any L5 replicate.
# geneC (0.01) and geneD (0.02) pass.
expressed_in_L5 <- filter_genes_by_fdr(
    mock_data,
    fdr = 0.05,
    condition = "L5",
    which = "any"
)
print(expressed_in_L5)

```

get_ensdb_genes

*Extract gene annotation from Ensembl via AnnotationHub EnsDb***Description**

Retrieves gene information for a given organism from the most appropriate Ensembl database hosted via Bioconductor's AnnotationHub and ensemblDb.

Usage

```
get_ensdb_genes(
  organism_keyword = "drosophila melanogaster",
  genome_build = NULL,
  ensembl_version = NULL,
  exclude_biotypes = c("transposable_element", "pseudogene"),
  include_gene_metadata = c("gene_id", "gene_name")
)
```

Arguments

<code>organism_keyword</code>	Character. Unique non-case-sensitive string to search for the organism (e.g., "drosophila melanogaster").
<code>genome_build</code>	Optional character. Genome build identifier to further restrict the EnsDb selection (e.g., "BDGP6").
<code>ensembl_version</code>	Optional integer. Specific Ensembl version to fetch. If NULL, the latest available version is used.
<code>exclude_biotypes</code>	Character vector. Gene biotypes to exclude from the result (default: c("transposable_element", "pseudogene")).
<code>include_gene_metadata</code>	Character vector. Metadata columns to keep for each gene (default: c("gene_id", "gene_name")).

Details

This function queries AnnotationHub for EnsDb objects matching a supplied organism keyword, with optional filtering by genome build and Ensembl version. Genes matching excluded biotypes are filtered out. Only user-selected metadata fields are retained in the genes output.

Value

List with:

<code>genes</code>	A GRanges object of genes (metadata columns per argument).
<code>ensembl_version</code>	Character. The Ensembl version string.
<code>genome_build</code>	Character. Genome build identifier.
<code>species</code>	Character. Latin binomial species name.
<code>common_name</code>	Character. Species common name.
<code>ah_id</code>	Character. The unique AnnotationHub identifier (e.g., "AH113672").
<code>ah_snapshot</code>	Date. The snapshot date of the AnnotationHub instance.

Examples

```

if (isTRUE(curl::has_internet())) {
# This example requires an internet connection and will download data.
dm_genes <- get_ensdb_genes(
  organism_keyword = "drosophila melanogaster",
  ensembl_version = 110
)

# View the fetched genes GRanges object
dm_genes$genes
}

```

inputData

*Access original input data and metadata***Description**

This function returns the original list of input data used to generate the results.

Usage

```
inputData(object)
```

Arguments

object A DamIDResults object.

Value

A list.

See Also

[DamIDResults-class](#)

Examples

```

# Helper function to create a sample DamIDResults object for examples
.generate_example_results <- function() {
  analysis_df <- data.frame(
    logFC = c(2, -2, 0.1), P.Value = c(0.01, 0.01, 0.9), B = c(4, 3, -1),
    gene_name = c("GeneA", "GeneB", "GeneC"),
    row.names = c("chr1:1-100", "chr1:101-200", "chr1:201-300")
  )
  new("DamIDResults",
    analysis = analysis_df,
    upCond1 = analysis_df[1, , drop = FALSE],
    upCond2 = analysis_df[2, , drop = FALSE],

```

```

        cond = c("Condition 1" = "C1", "Condition 2" = "C2"),
        data = list(test_category = "bound")
    )
}
mock_results <- .generate_example_results()
inputData(mock_results)

```

load_data_genes	<i>Load genome-wide binding data for gene expression (RNA polymerase occupancy)</i>
-----------------	---

Description

Reads RNA Polymerase DamID binding profiles either from bedGraph files or directly from a list of GRanges objects. Calculates binding occupancy summarised over genes.

Usage

```

load_data_genes(
  binding_profiles_path = NULL,
  binding_profiles = NULL,
  drop_samples = NULL,
  norm_method = c("none", "loess", "quantile", "rpm"),
  pre_scale = FALSE,
  quantile_norm = NULL,
  organism = "drosophila melanogaster",
  calculate_occupancy_pvals = TRUE,
  return_per_replicate_fdr = FALSE,
  occupancy_plot_diagnostics = interactive(),
  null_model_iterations = 1e+05,
  ensdb_genes = NULL,
  BPPARAM = BiocParallel::bpparam(),
  plot_diagnostics = interactive()
)

```

Arguments

binding_profiles_path	Character vector of directories or file globs containing log2 ratio binding tracks in bedGraph format. Wildcards ('*') supported.
binding_profiles	A list of GRanges objects (one per sample) or a single GRanges object containing multiple sample metadata columns.
drop_samples	A character vector of sample names or patterns to remove. Matching samples are removed from the analysis before normalisation and occupancy calculation. This can be useful for excluding samples that fail initial quality checks. Default: 'NULL' (no samples are dropped).

norm_method	<p>Character. Determines how raw genome-wide signal is normalised prior to establishing peak specific occupancy. Options are:</p> <ul style="list-style-type: none"> • "none" (default): Use original data. Recommended if loading CATaDa count data pre-processed via damidseq_pipeline --catada (which is natively RPM-normalised). • "loess": Uses the 'cyclicloess' method from 'limma'. • "quantile": Quantile normalisation. Forces identical target distributions. • "rpm": Reads Per Million scaling. A simple global scaling for raw un-normalised count data. Use with caution: do not use for log2 ratio data, and avoid if CATaDa data has already been RPM normalised (the default behaviour with 'damidseq_pipeline')
pre_scale	Logical. If TRUE, samples will be scaled without centering via base R 'scale(center=FALSE, scale=TRUE)', prior to normalisation being applied. Default is FALSE.
quantile_norm	Deprecated. Please use 'norm_method = "quantile"' instead.
organism	Organism string (lower case) to obtain genome annotation from (if not providing a custom 'ensdb_genes' object) Defaults to "drosophila melanogaster".
calculate_occupancy_pvals	Calculate occupancy p-values as a proxy for gene expression status (see details). Not used for differential expression analysis, but used when present for downstream analysis and plotting. (default: TRUE)
return_per_replicate_fdr	Legacy option of returning BH-adjusted RNA Polymerase occupancy FDR values per replicate. As of v0.99.12, unadjusted p-values are returned by default; these are then aggregated at the condition level during 'differential_binding()' and the aggregate p-values adjusted to gain statistical power. This option exists for legacy or unusual end-user applications. Use with caution. (default: FALSE)
occupancy_plot_diagnostics	Logical. If 'TRUE' (default in interactive sessions), diagnostic plots for the gene expression null model will be displayed.
null_model_iterations	Number of iterations to use to determine null model for FDR (default: 100000)
ensdb_genes	GRanges object: gene annotation. Automatically obtained from 'organism' if NULL.
BPPARAM	BiocParallel function (defaults to BiocParallel::bpparam())
plot_diagnostics	Logical. If 'TRUE' (the default in interactive sessions), diagnostic plots (PCA and correlation heatmap) will be generated and displayed for both the raw binding data and the summarised occupancy data.

Details

One of 'binding_profiles_path' or 'binding_profiles' must be provided.

When supplying GRanges lists for 'binding_profiles', each GRanges should contain exactly one numeric metadata column representing the binding signal, and 'binding_profiles' must be a named list, with element names used as sample names. Alternatively, a single GRanges object already containing multiple sample columns may be provided.

Value

List with elements:

```
binding_profiles_data
      GRanges: Merged binding profiles, with genomic coordinates and sample meta-
      data columns.

occupancy      data.frame: Occupancy values summarised over genes.

test_category  Character scalar; will be "expressed".

metadata       List: Data provenance and analysis metadata.
```

Examples

```
# Create a mock GRanges object for gene annotations
# This object avoids network access
# and includes a very long gene to ensure overlaps with sample data.
mock_genes_gr <- GenomicRanges::GRanges(
  seqnames = S4Vectors::Rle("2L", 7),
  ranges = IRanges::IRanges(
    start = c(1000, 2000, 3000, 5000, 6000, 7000, 8000),
    end = c(1500, 2500, 3500, 5500, 6500, 7500, 20000000)
  ),
  strand = S4Vectors::Rle(GenomicRanges::strand(c("+", "-", "+", "+", "-", "-", "+"))),
  gene_id = c("FBgn001", "FBgn002", "FBgn003", "FBgn004", "FBgn005", "FBgn006", "FBgn007"),
  gene_name = c("geneA", "geneB", "geneC", "geneD", "geneE", "geneF", "LargeTestGene")
)

# Get path to sample data files included with the package
data_dir <- system.file("extdata", package = "damidBind")

# Run loading function using sample files and mock gene annotations
# This calculates occupancy over genes instead of peaks.
loaded_data_genes <- load_data_genes(
  binding_profiles_path = data_dir,
  ensdb_genes = mock_genes_gr,
  norm_method = "none",
  calculate_occupancy_pvals = FALSE
)

# View the head of the occupancy table
head(loaded_data_genes$occupancy)
```

load_data_peaks	<i>Load genome-wide binding data and associated peak files or GRanges objects</i>
-----------------	---

Description

Reads DamID-seq log2 ratio binding data either from bedGraph files or directly from a list of GRanges objects, and associated peak regions either from GFF/bed files or from a list of GRanges objects. This function is suitable for transcription factor binding analyses. For peak discovery, use an external peak caller (e.g. 'find_peaks').

Usage

```
load_data_peaks(
  binding_profiles_path = NULL,
  peaks_path = NULL,
  binding_profiles = NULL,
  peaks = NULL,
  drop_samples = NULL,
  maxgap_loci = 1000,
  norm_method = c("none", "loess", "quantile", "rpm"),
  pre_scale = FALSE,
  quantile_norm = NULL,
  organism = "drosophila melanogaster",
  ensdb_genes = NULL,
  BPPARAM = BiocParallel::bpparam(),
  plot_diagnostics = interactive()
)
```

Arguments

binding_profiles_path	Character vector. Path(s) to directories or file globs containing log2 ratio binding tracks in bedGraph format. Wildcards ('*') supported.
peaks_path	Character vector. Path(s) to directories or file globs containing the peak calls in GFF or BED format.
binding_profiles	A list of GRanges objects (one per sample) or a single GRanges object containing multiple sample metadata columns.
peaks	A list of GRanges objects (one per sample) or a single GRanges object representing the union of peaks.
drop_samples	A character vector of sample names or patterns to remove. Matching samples are removed from the analysis before normalisation and occupancy calculation. This can be useful for excluding samples that fail initial quality checks. Default: 'NULL' (no samples are dropped).
maxgap_loci	Integer, the maximum bp distance between a peak boundary and a gene to associate that peak with the gene. Default: 1000.
norm_method	Character. Determines how raw genome-wide signal is normalised prior to establishing peak specific occupancy. Options are: <ul style="list-style-type: none"> "none" (default): Use original data. Recommended if loading CATaDa count data pre-processed via damidseq_pipeline --catada (which is natively RPM-normalised).

	<ul style="list-style-type: none"> • "loess": Uses the 'cyclicloess' method from 'limma'. • "quantile": Quantile normalisation. Forces identical target distributions. • "rpm": Reads Per Million scaling. A simple global scaling for raw un-normalised count data. Use with caution: do not use for log2 ratio data, and avoid if CATaDa data has already been RPM normalised (the default behaviour with 'damidseq_pipeline')
pre_scale	Logical. If TRUE, samples will be scaled without centering via base R 'scale(center=FALSE, scale=TRUE)', prior to normalisation being applied. default is FALSE; generally useful for DamID log-ratio data, but not recommended for CATaDa data.
quantile_norm	Deprecated. Please use 'norm_method = "quantile"' instead.
organism	Organism string (lower case) to obtain genome annotation from (if not providing a custom 'ensdb_genes' object) Default: "drosophila melanogaster".
ensdb_genes	GRanges object: gene annotation. Automatically obtained from 'organism' if NULL.
BPPARAM	BiocParallel function (defaults to BiocParallel::bpparam())
plot_diagnostics	Logical. If 'TRUE' (the default in interactive sessions), diagnostic plots (PCA and correlation heatmap) will be generated and displayed for both the raw binding data and the summarised occupancy data.

Details

One of 'binding_profiles_path' or 'binding_profiles' must be provided. Similarly, one of 'peaks_path' or 'peaks' must be provided.

When supplying GRanges lists for 'binding_profiles', each GRanges should contain exactly one numeric metadata column representing the binding signal, and all GRanges should be supplied as a named list, with element names used as sample names. Alternatively, a single GRanges object already containing multiple sample columns may be provided.

Value

A list with components:

binding_profiles_data	GRanges: Signal matrix for all regions, with genomic coordinates and sample metadata columns.
peaks	list(GRanges): All loaded peak regions.
pr	GRanges: Reduced (union) peak regions across samples.
occupancy	data.frame: Binding values summarised over reduced peaks, with overlap annotations.
test_category	Character scalar; will be "bound".
metadata	List: Data provenance and analysis metadata.

Examples

```
# Create a mock GRanges object for gene annotation
# This object, based on the package's unit tests, avoids network access
# and includes a very long gene to ensure overlaps with sample data.
mock_genes_gr <- GenomicRanges::GRanges(
  seqnames = S4Vectors::Rle("2L", 7),
  ranges = IRanges::IRanges(
    start = c(1000, 2000, 3000, 5000, 6000, 7000, 8000),
    end = c(1500, 2500, 3500, 5500, 6500, 7500, 20000000)
  ),
  strand = S4Vectors::Rle(GenomicRanges::strand(c("+", "-", "+", "+", "-", "-", "+"))),
  gene_id = c("FBgn001", "FBgn002", "FBgn003", "FBgn004", "FBgn005", "FBgn006", "FBgn007"),
  gene_name = c("geneA", "geneB", "geneC", "geneD", "geneE", "geneF", "LargeTestGene")
)

# Get path to sample data files included with the package
data_dir <- system.file("extdata", package = "damidBind")

# Run loading function using sample files and mock gene annotations
# Normalising with either 'quantile' or 'loess' is generally recommended
# for DamID log2 ratios
loaded_data <- load_data_peaks(
  binding_profiles_path = data_dir,
  peaks_path = data_dir,
  ensdb_genes = mock_genes_gr,
  norm_method = "quantile"
)

# View the structure of the output
str(loaded_data, max.level = 1)
```

```
metadata,DamIDResults-method
```

```
Access analysis metadata
```

Description

This method returns the provenance and annotation metadata for the analysis. It overrides the default metadata method for DamIDResults objects.

Usage

```
## S4 method for signature 'DamIDResults'
metadata(x, ...)
```

Arguments

```
x          A DamIDResults object.
...        Additional arguments (ignored).
```

Value

A nested list of metadata.

plot_catada_mean_variance

Plot mean-variance relationship for CATaDa results

Description

This diagnostic function assesses whether CATaDa occupancy signal follows the theoretical mean-variance relationship assumed by Negative Binomial models. It is only applicable to objects generated via the ‘differential_accessibility()’ function.

Usage

```
plot_catada_mean_variance(diff_results)
```

Arguments

`diff_results` A DamIDResults object.

Value

A ggplot object.

plot_input_diagnostics

Display diagnostic plots for input data

Description

This function creates and displays diagnostic plots (PCA and correlation heatmap) for both occupancy and raw binding data. It is called by ‘load_data_peaks’ and ‘load_data_genes’.

Usage

```
plot_input_diagnostics(loaded_data, drop_samples = NULL)
```

Arguments

`loaded_data` A list object, the output of ‘load_data_peaks’ or ‘load_data_genes’.

`drop_samples` An optional character vector of sample names or patterns to remove for this diagnostic check. When used, the occupancy data is subsetted, not recalculated, providing an approximation of the effect of dropping samples. Default: ‘NULL’.

Value

Returns the input ‘loaded_data’ object invisibly

Examples

```
# Mock ensdb data to avoid network access
mock_genes_gr <- GenomicRanges::GRanges(
  seqnames = S4Vectors::Rle("2L", 7),
  ranges = IRanges::IRanges(
    start = c(1000, 2000, 3000, 5000, 6000, 7000, 8000),
    end = c(1500, 2500, 3500, 5500, 6500, 7500, 20000000)
  ),
  gene_id = c("FBgn001", "FBgn002", "FBgn003", "FBgn004", "FBgn005", "FBgn006", "FBgn007"),
  gene_name = c("geneA", "geneB", "geneC", "geneD", "geneE", "geneF", "LargeTestGene")
)
data_dir <- system.file("extdata", package = "damidBind")

# Load the example package data
loaded_data <- load_data_peaks(
  binding_profiles_path = data_dir,
  peaks_path = data_dir,
  ensdb_genes = mock_genes_gr,
  plot_diagnostics = FALSE # don't call the function here ...
)

# Plot diagnostics
plot_input_diagnostics(loaded_data) # ... so that we can call it explicitly :/
```

plot_limma_diagnostics

Verify Underlying Assumptions for ‘limma’ Analysis

Description

This diagnostic function is a wrapper around the internal ‘._plot_limma_diagnostics_internal()’ function, to help assess whether the assumptions of the ‘limma’ empirical Bayes framework hold for a given dataset. It generates a series of plots to check for normality of residuals, homoscedasticity, and the mean-variance relationship, illustrating in particular the effect of ‘trend’ and ‘robust’ parameters to ‘limma::eBayes’.

During ‘limma’-based fits, the internal plot routine is called by default. This wrapper allows diagnostics to be displayed for any given log2 ratio-based ‘data_list’ object from ‘load_data_peaks()’ or ‘load_data_genes()’, and the effect of moderation parameters on the fit tested.

Usage

```
plot_limma_diagnostics(
  data_list,
```

```

    cond,
    drop_samples = NULL,
    filter_occupancy = TRUE,
    filter_threshold = 0,
    eBayes_trend = TRUE,
    eBayes_robust = TRUE,
    regex = FALSE
  )

```

Arguments

<code>data_list</code>	List. The output from ‘load_data_peaks’ or ‘load_data_genes’.
<code>cond</code>	A named character vector of length two defining the conditions for comparison, identical to the ‘cond’ argument in ‘differential_binding’.
<code>drop_samples</code>	An optional character vector of sample names or patterns to remove for this diagnostic check. Default: ‘NULL’.
<code>filter_occupancy</code>	NULL or integer. See ‘prep_data_for_differential_analysis’. Default is ‘TRUE’.
<code>filter_threshold</code>	Numeric. Threshold value for ‘filter_occupancy’. (default: 0)
<code>eBayes_trend</code>	Logical. See ‘limma::eBayes’. Default: ‘TRUE’
<code>eBayes_robust</code>	Logical. See ‘limma::eBayes’. Default: ‘TRUE’
<code>regex</code>	Logical. Whether to use regular expressions for matching condition names. Default is ‘FALSE’.

Details

The function first prepares the data and fits a linear model using the ‘limma’ package. It then calls an internal plotting routine to generate the following checks:

1. **Homoscedasticity (Residuals vs. Fitted):** A scatter plot of model residuals against fitted values. A random cloud around $y=0$ supports the assumption of constant variance.
2. **Effect of eBayes moderation:** Histograms of t-statistics before and after empirical Bayes moderation.
3. **Mean-variance trend (‘plotSA’):** The primary diagnostic for the ‘eBayes’ step, showing the relationship between average log2 occupancy and variance. Points should be evenly distributed around the blue trendline; any outliers are highlighted in red.

The function uses the internal ‘prep_data_for_differential_analysis’ function to ensure that the data being tested is identical to that used in the main differential analysis.

Value

Invisibly returns ‘NULL’. This function is called to generate diagnostic plots in the active graphics device.

Examples

```
mock_genes_gr <- GenomicRanges::GRanges(
  seqnames = S4Vectors::Rle("2L", 7),
  ranges = IRanges::IRanges(
    start = c(1000, 2000, 3000, 5000, 6000, 7000, 8000),
    end = c(1500, 2500, 3500, 5500, 6500, 7500, 20000000)
  ),
  gene_id = c("FBgn001", "FBgn002", "FBgn003", "FBgn004", "FBgn005", "FBgn006", "FBgn007"),
  gene_name = c("geneA", "geneB", "geneC", "geneD", "geneE", "geneF", "LargeTestGene")
)

data_dir <- system.file("extdata", package = "damidBind")

loaded_data <- load_data_peaks(
  binding_profiles_path = data_dir,
  peaks_path = data_dir,
  ensdb_genes = mock_genes_gr,
  quantile_norm = TRUE,
  plot_diagnostics = FALSE
)

conditions <- c("L4 Neurons" = "L4", "L5 Neurons" = "L5")

plot_limma_diagnostics(
  data_list = loaded_data,
  cond = conditions
)
```

plot_venn

Draw proportional Venn diagrams for differential binding analysis

Description

Generates a two-set proportional Venn diagram summarising the results of the differential binding analysis. The set union represents significant binding peaks that fail to show significant differences in occupancy; the exclusive regions of each set represent regions with enriched differential binding in that condition. Note that regions can be bound in both conditions, and still show differential occupancy. For gene expression analysis, the set of analysed genes can optionally be filtered by FDR such that the universe is restricted to only genes deemed expressed, as is typically expected for DEG representations.

Usage

```
plot_venn(
  diff_results,
  title = NULL,
  subtitle = "",
  set_labels = NULL,
```

```

    filename = NULL,
    font = "sans",
    format = c("pdf", "svg"),
    region_colours = c("#FFA500", "#2288DD", "#CCCCCC"),
    fdr_filter_threshold = NULL
  )

```

Arguments

<code>diff_results</code>	A ‘DamIDResults’ object, as returned by ‘differential_binding()’ or ‘differential_accessibility()’.
<code>title</code>	Plot title to use (default: generated from test condition context)
<code>subtitle</code>	Subtitle to use (default is empty).
<code>set_labels</code>	Character vector of length 2. Names for the two sets/circles (defaults to the analysis condition names).
<code>filename</code>	Character. Path at which to save the diagram, if not NULL.
<code>font</code>	Font name to use (default is "sans")
<code>format</code>	Character. Output plot format, "pdf" or "svg" (default "pdf").
<code>region_colours</code>	Character vector of length 2 or 3. Fill colours for each set region (default: c("#FFA500", "#2288DD", "#CCCCCC")).
<code>fdr_filter_threshold</code>	Numeric or NULL. If a value (e.g., 0.05) is provided, the universe of loci considered for the Venn diagram will be restricted to those that pass this FDR threshold in at least one sample. Used for illustrating DEGs with RNA Pol TaDa. If NULL (default), all tested loci are used.

Value

The function is called to generating a plot. It invisibly returns ‘NULL’.

Examples

```

# Helper function to create a sample DamIDResults object
.generate_example_results <- function() {
  mock_genes_gr <- GenomicRanges::GRanges(
    seqnames = S4Vectors::Rle("2L", 7),
    ranges = IRanges::IRanges(
      start = c(1000, 2000, 3000, 5000, 6000, 7000, 8000),
      end = c(1500, 2500, 3500, 5500, 6500, 7500, 20000000)
    ),
    gene_id = c("FBgn001", "FBgn002", "FBgn003", "FBgn004", "FBgn005", "FBgn006", "FBgn007"),
    gene_name = c("geneA", "geneB", "geneC", "geneD", "geneE", "geneF", "LargeTestGene")
  )
  data_dir <- system.file("extdata", package = "damidBind")
  loaded_data <- load_data_peaks(
    binding_profiles_path = data_dir,
    peaks_path = data_dir,
    ensdb_genes = mock_genes_gr,

```

```

        quantile_norm = TRUE
      )
      diff_results <- differential_binding(
        loaded_data,
        cond = c("L4 Neurons" = "L4",
                  "L5 Neurons" = "L5")
      )
      return(diff_results)
    }
  }
  diff_results <- .generate_example_results()

  # Generate the Venn diagram
  plot_venn(diff_results)

```

plot_volcano

Volcano plot of differentially bound/expressed loci

Description

Creates a volcano plot from the results of a differential analysis. The plot shows the log-fold change against a measure of statistical significance. The function offers extensive customisation for point appearance, gene labelling, and highlighting specific groups of loci.

Usage

```

plot_volcano(
  diff_results,
  labels = "all",
  fdr_filter_threshold = NULL,
  highlight_by = c("auto", "gene_name", "id"),
  plot_config = list(),
  label_config = list(),
  highlight = NULL,
  highlight_config = list(),
  label_display = list(),
  save = NULL
)

```

Arguments

- | | |
|--------------|--|
| diff_results | A ‘DamIDResults’ object, as returned by ‘differential_binding()’ or ‘differential_accessibility()’. |
| labels | <p>Character; one of “all”, “highlight”, or a character vector containing one or more group names from the ‘highlight’ list.</p> <ul style="list-style-type: none"> • “all” (default): Labels both the general significant loci (based on label_config) and any highlight groups where label = TRUE is set in highlight_config. |

	<ul style="list-style-type: none"> • "highlight": Labels all loci in the highlight list, ignoring label_config and the label toggle in highlight_config. • vector of group names: Labels only the specified groups from the highlight list.
fdr_filter_threshold	Numeric or NULL. If a value (e.g., 0.05) is provided, the volcano plot will only include loci that have an FDR value less than or equal to this threshold in at least one replicate of the two conditions being plotted. This requires that the data was loaded using 'load_data_genes' with 'calculate_occupancy_pvals = TRUE', which generates the necessary '_FDR' columns. If 'NULL' (default), no FDR-based filtering is performed.
highlight_by	Character; either "auto", "gene_name", or "id". Determines whether to use gene names ("gene_name") or locus ("id") for the highlight search. In "auto" mode (default), the function checks for matches in both columns and selects the one with the best coverage for each highlight group.
plot_config	<p>List. Names to override plot details (title, axes, size, colours, etc); see details.</p> <ul style="list-style-type: none"> • title, xlab, ylab (character) • ystat (character): The column name from 'analysisTable(diff_results)' to use for the y-axis (e.g., "minuslogp" or "B"). Default is "B". • base_size (integer): ggplot theme base font size. • sig_colour, nonsig_colour (colours) • sig_alpha, sig_size: alpha and size for significant points. • nonsig_alpha, nonsig_size: alpha and size for non-significant points.
label_config	<p>List. Fine-grained label controls; if missing or 'NULL', no labels are added (see details).</p> <ul style="list-style-type: none"> • genes: character vector to restrict labels to a subset (default: label all significant). • label_size: label size (numeric). • clean_names: logical; if 'TRUE', applies regex filtering to labels. • names_clean, names_clean_extra: regex to exclude from labels when clean_names is 'TRUE'. • max_overlaps: integer; maximum ggrepel overlaps. (default: 10)
highlight	List. A simple list where each element is a character vector of genes/loci to highlight. Each element of this list will correspond to a separate highlight group. If 'NULL', no highlight overlays are drawn.
highlight_config	<p>List. Additional highlight configuration options, applied consistently across all highlight groups. If missing or 'NULL', defaults are used.</p> <ul style="list-style-type: none"> • alpha: Numeric; transparency for highlight points (default: 1). • size: Numeric; size for highlight points (default: 2). • label: Logical; if 'TRUE', labels are added for all highlight groups (default: 'FALSE'). • colour: A list of colours, where each element corresponds to a highlight group in the 'highlight' list. If not specified or not enough colours are provided, a default hue palette is used.

- `label_size`: Numeric; label size (default: 4).
 - `max_overlaps`: Integer; maximum ggrepel overlaps for highlight labels (default: 10).
 - `sig_labels_only`: Logical; whether to only label significant loci in the set
 - `legend`: Logical; whether to draw a plot legend for the highlight groups (default: TRUE).
 - `legend_inside`: Logical; whether to draw the plot legend for the highlight groups inside the plot (default: TRUE).
 - `legend_inside_pos`: String, either 'r' (right) or 'l' (left). Presets for internal legend position in the bottom right or left corners of the plot. (default: 'r')
 - `legend_position_override`: Numeric. Manual override for internal legend positioning when not set to the default, NULL.
 - `legend_justification_override`: Numeric. Manual override for internal legend justification when not set to the default, NULL.
 - `label_fill`: logical; if 'TRUE', uses 'geom_label_repel', else 'geom_text_repel' (default: FALSE)
 - `text_col`: logical; if 'TRUE', text is coloured as per points, else black (default: FALSE)
 - `text_luminosity`: Numeric (0-100). When using 'text_col', setting a non-zero value will darken the luminosity of the highlight colour on text labels for increased contrast. 0 = no change; 100 = black. (default: 0)
- `label_display` List. Additional label display options for sampling dense labels in all groups. Uses KNN-based sampling to optimise display when not NULL.
- `scale`: Logical; if TRUE, labelled coordinate data are centred and scaled (using `scale(center = TRUE, scale = TRUE)`) before sampling. Note: this does not affect plotted values. (default: TRUE).
 - `r`: Numeric or "auto"; the sampling exclusion radius. If "auto", `r` is set to the median distance to the `k_for_r`-th nearest neighbour across all points. A smaller `r` keeps more points. (Default: 0.2).
 - `k_search`: Integer; maximum number of neighbours to find in the initial KNN search. Must be greater than or equal to both `k` and `k_for_r` (default: 30).
 - `k_priority`: Integer; number of neighbours used to infer the isolation priority score. Must be less than or equal to `k_search` (default: 30).
 - `k_for_r`: Integer; which neighbour to use for the "auto" `r` calculation (default: 30).
- `save` List or 'NULL'. Controls saving the plot to a file. If 'NULL', 'FALSE', or '0', the plot is not saved. If a list, it specifies saving parameters:
- `filename` (character): The path and base name for the output file (e.g., "my_volcano_plot"). If not specified, a default is used.
 - `format` (character): File format ("pdf", "svg", or "png"). Default is "pdf".
 - `width` (numeric): Width of the plot in inches. Default is 5.
 - `height` (numeric): Height of the plot in inches. Default is 4.

Value

A ‘ggplot’ object

Examples

```
# Helper function to create a sample DamIDResults object
.generate_example_results <- function() {
  mock_genes_gr <- GenomicRanges::GRanges(
    seqnames = S4Vectors::Rle("2L", 7),
    ranges = IRanges::IRanges(
      start = c(1000, 2000, 3000, 5000, 6000, 7000, 8000),
      end = c(1500, 2500, 3500, 5500, 6500, 7500, 20000000)
    ),
    gene_id = c("FBgn001", "FBgn002", "FBgn003", "FBgn004", "FBgn005", "FBgn006", "FBgn007"),
    gene_name = c("ap", "dpr1", "side", "mav", "geneE", "geneF", "LargeTestGene")
  )
  data_dir <- system.file("extdata", package = "damidBind")
  loaded_data <- load_data_peaks(
    binding_profiles_path = data_dir,
    peaks_path = data_dir,
    ensdb_genes = mock_genes_gr,
    quantile_norm = TRUE
  )
  diff_results <- differential_binding(
    loaded_data,
    cond = c("L4 Neurons" = "L4",
             "L5 Neurons" = "L5")
  )
  return(diff_results)
}
diff_results <- .generate_example_results()

# Generate a default volcano plot
plot_volcano(diff_results)

# Explicitly highlight a specific locus coordinate
plot_volcano(diff_results, highlight = list("My Peak" = "2L:1000-1500"))

# Label only specific highlight groups
plot_volcano(diff_results,
  highlight = list("Set A" = c("ap", "side"), "Set B" = "mav"),
  labels = "Set A")
```

Description

Performs quantile normalisation of a numeric matrix in native R, matching the algorithm used by ‘preprocessCore’ (including its tie-handling rule).

Usage

```
quantile_normalisation(x)
```

Arguments

x A numeric matrix; rows are features (e.g., genes), columns are samples/arrays.

Details

This function is a native R implementation of the standard quantile normalisation algorithm. It is designed to be a drop-in replacement for, and produce identical results to, the function of the same name in the ‘preprocessCore’ package.

This native R version is provided within ‘damidBind’ to avoid known issues where the ‘preprocessCore’ package can lead to errors or cause R to crash on some Linux systems due to conflicts with OpenMP and/or BLAS/LAPACK library configurations. By providing this native R implementation, ‘damidBind’ ensures it works reliably for all users without requiring them to recompile dependencies or manage system environment variables.

This implementation exactly mirrors the behaviour of the ‘preprocessCore’ library’s classic quantile normalisation, including its specific handling of ties: average ranks are computed for ties, and if the fractional part of a rank is greater than 0.4, the output value is the average of the two adjacent quantile means; otherwise, only the lower (floored) quantile mean is used.

The function stops if any NA, Inf, or NaN values are present in x.

Value

A numeric matrix of the same dimensions as x, quantile normalised.

Examples

```
set.seed(1)
x <- matrix(rnorm(9), nrow = 3)
quantile_normalisation(x)
```

reduce_regions

Reduce a list of GRanges to unique, non-overlapping regions

Description

Takes a list of GRanges objects (e.g., peak sets from multiple samples), combines them, and merges any overlapping or adjacent regions into a single, minimal set of genomic intervals.

Usage

```
reduce_regions(peaks)
```

Arguments

peaks A list of GRanges objects.

Value

A GRanges object containing the reduced (union) regions, with a 'name' metadata column in the format "chr:start-end".

Examples

```
# Create a list of GRanges objects with overlapping regions
gr1 <- GenomicRanges::GRanges("chr1", IRanges::IRanges(c(100, 200), width = 50))
gr2 <- GenomicRanges::GRanges("chr1", IRanges::IRanges(c(120, 300), width = 50))
gr_list <- list(gr1, gr2)

# Reduce the list to a single set of non-overlapping regions
reduced <- reduce_regions(gr_list)
print(reduced)
# The result combines overlapping regions [100-149] and [120-169] into [100-169].
```

sample_labels_by_isolation

Sample data points based on local isolation

Description

An issue with labelling points on dense plots (e.g., volcano plots) is that high point density prevents clear labelling, even with tools like 'ggrepel'. This function addresses this by retaining isolated points while sampling from points in higher-density regions. It takes a dataframe with Cartesian coordinates and returns a logical vector identifying which points to select for labelling. The result is a less cluttered plot where labels are present even in crowded areas, providing a better representation of the underlying data.

Usage

```
sample_labels_by_isolation(
  df,
  x_col,
  y_col,
  r,
  k_priority = 30,
  scale = TRUE,
  k_search = 30,
  k_for_r = 5
)
```

Arguments

<code>df</code>	A dataframe containing the point coordinates.
<code>x_col</code>	A character string with the name of the column containing x-coordinates.
<code>y_col</code>	A character string with the name of the column containing y-coordinates.
<code>r</code>	The exclusion radius. This can be a positive numeric value or the string "auto". If "auto", the radius is calculated as the median distance to the ' <code>k_for_r</code> '-th nearest neighbour across all points. A smaller ' <code>r</code> ' will result in more points being kept. Note: The interpretation of ' <code>r</code> ' depends on whether ' <code>scale</code> ' is ' <code>TRUE</code> '.
<code>k_priority</code>	An integer for calculating the isolation priority score. Must be less than or equal to ' <code>k_search</code> '. Default: 30.
<code>scale</code>	A logical value. If ' <code>TRUE</code> ', the coordinate data is centred and scaled (using ' <code>scale(center=TRUE, scale=TRUE)</code> ') before distance calculations. Defaults: ' <code>TRUE</code> '.
<code>k_search</code>	The maximum number of neighbours to find in the initial KNN search. This value must be greater than or equal to both ' <code>k_priority</code> ' and ' <code>k_for_r</code> '. Default: 30.
<code>k_for_r</code>	An integer specifying which neighbour to use for the 'auto' ' <code>r</code> ' calculation. Default: 5.

Details

The algorithm in detail: 1. If '`scale = TRUE`', the coordinate data is centred and scaled. 2. An exact k-nearest neighbour (KNN) search for all points is conducted using the '`dbscan::kNN`' function. 3. A priority score is calculated for each point, defined as the median distance to its '`k_priority`' nearest neighbours, and the list of points sorted by this score. 4. The function iterates through the sorted list of points in descending order: a. If a point has not yet been processed, it is marked as 'processed' and 'kept'. b. A radius search is performed around this point using '`dbscan::frNN`'. All neighbours within the specified exclusion radius '`r`' are then marked as 'processed' and will be ignored in subsequent iterations. 5. A logical vector is returned, where '`TRUE`' corresponds to a point that should be kept for labelling.

Value

A logical vector of length '`nrow(df)`'. '`TRUE`' indicates the point at that index should be kept for labelling.

Examples

```
library(ggplot2)
library(ggrepel)

# Generate sample data with a dense cluster
set.seed(42)
n_points <- 1000
cluster_data <- data.frame(
  x = rnorm(n_points, mean = 5, sd = 1),
  y = rnorm(n_points, mean = 5, sd = 1),
```

```

    label = paste("Point", 1:n_points)
  )

# Use the function to get a logical vector for filtering
kept_labels <- sample_labels_by_isolation(
  df = cluster_data,
  x_col = "x",
  y_col = "y",
  scale = FALSE,
  r = "auto",
  k_priority = 30,
  k_search = 30,
  k_for_r = 5
)

# Create the label dataframe for ggplot
label_df <- cluster_data[kept_labels, ]

# Plot the results
ggplot(cluster_data, aes(x = x, y = y)) +
  geom_point(colour = "grey70", alpha = 0.7) +
  geom_point(data = label_df, colour = "firebrick") +
  geom_text_repel(
    data = label_df,
    aes(label = label),
    min.segment.length = 0,
    box.padding = 0.25,
    max.overlaps = Inf
  ) +
  coord_fixed() +
  labs(
    title = "Sampled Labels",
    subtitle = paste(sum(kept_labels), "of", nrow(cluster_data), "points labelled"),
    caption = "Red points are selected for labelling."
  ) +
  theme_bw()

```

test_weighting_vs_bias_artifact

Test weighting discrepancy against systematic length bias

Description

Tests whether the discrepancy between weighted and simple means is driven by a systematic fragment-length score bias or by underlying biological/stochastic variance. It models any length-based bias by fitting a Generalized Additive Model (GAM) to all non-peak fragments, predicts the expected bias discrepancy per region, and compares it to the observed discrepancy.

Usage

```
test_weighting_vs_bias_artifact(diff_results, sample_name, plot = TRUE)
```

Arguments

diff_results	A 'DamIDResults' object
sample_name	Character string of the sample to analyse
plot	Logical. Whether to print the summary plots (Default: TRUE)

Value

A list containing the discrepancy data, the summary statistics, and a two-panel patchwork plot for verification and results.

test_weighting_vs_bias_batch

Test weighting discrepancy against systematic length bias (batch analysis)

Description

A wrapper for [test_weighting_vs_bias_artifact](#) that iterates through all samples present in a DamIDResults object and returns a summary table of the results.

Usage

```
test_weighting_vs_bias_batch(diff_results, plot_all = FALSE)
```

Arguments

diff_results	A DamIDResults object.
plot_all	Logical. Whether to print summary plots for every sample in the batch. (Default: FALSE)

Value

A data.frame summarising the bias test for each sample, including the median discrepancies, adjustment ratios, and individual p-values.

Index

* classes

DamIDResults-class, [14](#)

analyse_go_enrichment, [3](#), [15](#)
analysisTable, [6](#), [14](#)
analysisTable, DamIDResults-method
(analysisTable), [6](#)
analyze_go_enrichment
(analyse_go_enrichment), [3](#)

browse_igv_regions, [7](#), [15](#)

calculate_and_add_occupancy_pvals, [9](#)
calculate_occupancy, [11](#)
conditionNames, [13](#), [14](#)
conditionNames, DamIDResults-method
(conditionNames), [13](#)

DamIDResults (DamIDResults-class), [14](#)
DamIDResults-class, [14](#)
differential_accessibility, [14](#), [15](#)
differential_binding, [14](#), [17](#)

enrichedCond1, [14](#), [19](#)
enrichedCond1, DamIDResults-method
(enrichedCond1), [19](#)
enrichedCond2, [14](#), [20](#)
enrichedCond2, DamIDResults-method
(enrichedCond2), [20](#)
expressed, [14](#), [21](#)
expressed, DamIDResults-method
(expressed), [21](#)
extract_unique_sample_ids, [22](#)

filter_genes_by_fdr, [21](#), [23](#)

get_ensdb_genes, [25](#)

inputData, [14](#), [27](#)
inputData, DamIDResults-method
(inputData), [27](#)

load_data_genes, [21](#), [28](#)
load_data_peaks, [30](#)

metadata, DamIDResults-method, [33](#)

plot_catada_mean_variance, [34](#)
plot_input_diagnostics, [34](#)
plot_limma_diagnostics, [35](#)
plot_venn, [15](#), [37](#)
plot_volcano, [15](#), [39](#)

quantile_normalisation, [42](#)
quantile_normalization
(quantile_normalisation), [42](#)

reduce_regions, [43](#)

sample_labels_by_isolation, [44](#)

test_weighting_vs_bias_artifact, [46](#), [47](#)
test_weighting_vs_bias_batch, [47](#)