

# Package: epistack (via r-universe)

June 30, 2024

**Title** Heatmaps of Stack Profiles from Epigenetic Signals

**Version** 1.11.0

**Description** The epistack package main objective is the visualizations of stacks of genomic tracks (such as, but not restricted to, ChIP-seq, ATAC-seq, DNA methylation or genomic conservation data) centered at genomic regions of interest. epistack needs three different inputs: 1) a genomic score objects, such as ChIP-seq coverage or DNA methylation values, provided as a ``GRanges`` (easily obtained from ``bigwig`` or ``bam`` files). 2) a list of feature of interest, such as peaks or transcription start sites, provided as a ``GRanges`` (easily obtained from ``gtf`` or ``bed`` files). 3) a score to sort the features, such as peak height or gene expression value.

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** false

**Imports** GenomicRanges, SummarizedExperiment, BiocGenerics, S4Vectors, IRanges, graphics, plotrix, grDevices, stats, methods

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.2.0

**Depends** R (>= 4.1)

**Suggests** testthat (>= 3.0.0), BiocStyle, knitr, rmarkdown, EnrichedHeatmap, biomaRt, rtracklayer, covr, vdiff, magick

**Config/testthat/edition** 3

**VignetteBuilder** knitr

**biocViews** RNASeq, Preprocessing, ChIPSeq, GeneExpression, Coverage

**URL** <https://github.com/GenEpi-GenPhySE/epistack>

**Repository** <https://bioc.r-universe.dev>

**RemoteUrl** <https://github.com/bioc/epistack>

**RemoteRef** HEAD

**RemoteSha** 04b02caae4da07d0317cc93efc6dd9b1c2c8d792

## Contents

addBins	2
addMetricAndArrangeGRanges	3
addMetricAndArrangeRSE	4
GRanges2RSE	5
meanColor	6
plotAverageProfile	7
plotBinning	8
plotBoxMetric	9
plotEpistack	10
plotMetric	13
plotStackProfile	14
plotStackProfileLegend	15
redimMatrix	16
stackepi	17
stackepi_gr	18
<b>Index</b>	<b>19</b>

---

addBins	<i>addBins()</i>
---------	------------------

---

### Description

Add an optional bin metadata column to `gr`, to serve as annotations for the epistack plots.

### Usage

```
addBins(rse, nbins = 5L, bin = NULL)
```

### Arguments

<code>rse</code>	a SummarizedExperiment or a GRanges object.
<code>nbins</code>	an integer number, the number of bins.
<code>bin</code>	a vector containing pre-determined bins, in the same order as <code>gr</code> .

### Details

`nbins` is taken into account only if `bin` is `NULL`. `rse` should be sorted first, usually with the `addMetricAndArrangeGRanges()` function. `addBin(rse, bin = vec)` is equivalent to `rse$bin <- vec`, while `addBin(rse, nbins = 5)` will create 5 bins of equal size based on `rse` order.

### Value

the RangedSummarizedExperiment or GRanges object with a new bin metadata column

**See Also**

[addMetricAndArrangeGRanges plotBinning](#)

**Examples**

```
data("stackepi")
addBins(stackepi)

# 3 bins instead of 5
addBins(stackepi, nbins = 3)

# assign bins using a vector
addBins(stackepi, bin = rep(c("a", "b", "c"),
  length.out = length(stackepi)))
```

---

```
addMetricAndArrangeGRanges
      addMetricAndArrangeGRanges()
```

---

**Description**

Perform an inner join between a GRanges object and a data.frame. Sort the resulting GRanges based on a metric column.

**Usage**

```
addMetricAndArrangeGRanges(
  gr,
  order,
  gr_key = "name",
  order_key = "name",
  order_value = "exp",
  shuffle_tie = TRUE
)
```

**Arguments**

<code>gr</code>	a GRanges object.
<code>order</code>	a data.frame with at least two columns: keys and values.
<code>gr_key</code>	name of the gr metadata column containing unique names for each genomic region in gr. Usually gene names/id or peak id.
<code>order_key</code>	name of the order column that will be used as key for the inner join.
<code>order_value</code>	name of the order column that contain value used for sorting.
<code>shuffle_tie</code>	a boolean Value (TRUE / FALSE). When TRUE, shuffle the GRanges before sorting, mixing the ties.

**Details**

This utility function allow the addition of a metric column to genomic regions of interest. One of its common use case is to add gene expression values on a set of transcription start sites. The resulting GRanges object will only contain regions presents in both gr and order.

**Value**

a GRanges sorted in descending order.

**Examples**

```
data("stackepi_gr")
randomOrder <- data.frame(gene_id = stackepi_gr$gene_id,
  value = rnorm(length(stackepi_gr)))
addMetricAndArrangeGRanges(stackepi_gr,
  randomOrder, gr_key = "gene_id",
  order_key = "gene_id", order_value = "value")
```

---

addMetricAndArrangeRSE

*addMetricAndArrangeRSE()*

---

**Description**

Perform an inner join between a rangedSummarizedExperiment object and a data.frame. Sort the resulting rangedSummarizedExperiment based on a metric column.

**Usage**

```
addMetricAndArrangeRSE(
  rse,
  order,
  rse_key = "name",
  order_key = "name",
  order_value = "exp",
  shuffle_tie = TRUE
)
```

**Arguments**

rse	a rangedSummarizedExperiment object.
order	a data.frame with at least two columns: keys and values.
rse_key	name of the gr metadata column containing unique names for each genomic region in rowRanges(rse). Usually gene names/id or peak id.
order_key	name of the order column that will be used as key for the inner join.

order\_value name of the order column that contain value used for sorting.  
 shuffle\_tie a boolean Value (TRUE / FALSE). When TRUE, shuffle the GRanges before sorting, mixing the ties.

### Details

This utility function allow the addition of a metric column to genomic regions of interest. One of its common use case is to add gene expression values on a set of transcription start sites. The resulting GRanges object will only contain regions presents in both rse and order.

### Value

a rangedSummarizedExperiment sorted in descending order.

### Examples

```
data("stackepi")
randomOrder <- data.frame(
  gene_id = SummarizedExperiment::rowRanges(stackepi)$gene_id,
  value = rnorm(length(stackepi))
)
addMetricAndArrangeRSE(stackepi,
  randomOrder, rse_key = "gene_id",
  order_key = "gene_id", order_value = "value")
```

---

GRanges2RSE

*GRanges2RSE()*

---

### Description

Convert objects from the old input format (GRanges object) to the new recommended input format RangedSummarizedExperiment.

### Usage

```
GRanges2RSE(gr, patterns, names = patterns)
```

### Arguments

gr a GRanges object with matrix embeded as metadata columns.  
 patterns A character vector of column prefixes (can be regular expressions) that should match columns of gr.  
 names specify the desired names of the assays (if different from patterns).

### Details

Mostly used for backward compatibilities and unit testing.

**Value**

a RangedSummarizedExperiment.

**Examples**

```
data("stackepi_gr")
GRanges2RSE(stackepi_gr, patterns = c("window"))
GRanges2RSE(stackepi_gr, patterns = c("^window_"), names = c("DName"))
```

---

meanColor

*meanColor*

---

**Description**

Return the average color of a vector of colors, computed in the RGB space.

**Usage**

```
meanColor(colors)
```

**Arguments**

colors            a vector of colors

**Details**

Input colors can be either in html or color name formats. The alpha channel is supported but optional.

**Value**

a single color value

**See Also**

[redimMatrix](#)

**Examples**

```
meanColor(c("#000000FF", "#FFFFFF00", "#FFFF00FF", "#FF0000FF"))

# works with color names
meanColor(c("blue", "red"))

# Mix color names and HTML codes
meanColor(c("blue", "red", "#FFFF00FF"))

# works without alpha channel in inputs (but outputs an alpha channel):
meanColor(c("#000000", "#FFFFFF", "#FFFF00", "#FF0000"))
```

---

plotAverageProfile     *plotAverageProfile()*

---

### Description

Plot the average stack profiles +/- error (sd or sem). If a bin column is present in rowRanges(rse), one average profile is drawn for each bin.

### Usage

```
plotAverageProfile(
  rse,
  assay = NULL,
  x_labels = c("Before", "Anchor", "After"),
  palette = colorRampPalette(c("#DF536B", "black", "#61D04F")),
  alpha_for_se = 0.25,
  error_type = c("sd", "sem", "ci95"),
  reversed_z_order = FALSE,
  ylim = NULL,
  y_title = NULL,
  pattern = NULL
)
```

### Arguments

rse	a RangedSummarizedExperiment input. Aletrnatively: can be a GRanges object (for backward compatibility, pattern will be required).
assay	specify the name of the assay to plot, that should match one of assayNames(rse).
x_labels	x-axis labels.
palette	A vector of colors, or a function that returns a palette of n colors.
alpha_for_se	the transparency (alpha) value for the error band.
error_type	can be either "sd" (standard deviation), "sem" (standard error of the mean), or "ci95" (95% confidence interval). Default: "sd".
reversed_z_order	should the z-order of the curves be reversed (i.e. first or last bin on top?)
ylim	a vector of two numbers corresponding to the y-limits of the plot.
y_title	the y-axis title.
pattern	only if rse is of class GRanges. A single character that should match metadata of rse (can be a regular expression).

### Value

Display a plot.

**Examples**

```
data("stackepi")
plotAverageProfile(stackepi)
```

---

<code>plotBinning</code>	<i>plotBinning()</i>
--------------------------	----------------------

---

**Description**

Plot a vertical color bar of the bin column.

**Usage**

```
plotBinning(
  rse,
  target_height = 650,
  palette = colorRampPalette(c("#DF536B", "black", "#61D04F"))
)
```

**Arguments**

<code>rse</code>	a <code>RangedSummarizedExperiment</code> input with a column bin in <code>rowRanges(rse)</code> . Alternatively (for backward compatibility), a <code>GRanges</code> object or any object such as <code>rse\$bin</code> exists.
<code>target_height</code>	an integer, the approximate height (in pixels) of the final plot. Used to avoid overplotting artefacts.
<code>palette</code>	A vector of colors, or a function that returns a palette of n colors.

**Value**

Display a plot.

**Examples**

```
data("stackepi")
rse <- stackepi
rse <- addBins(rse, nbins = 3)
plotBinning(rse)

gr2 <- data.frame(bin = rep(c(1,2,3,4), each = 5))
plotBinning(gr2, palette = colorRampPalette(c("blue4", "forestgreen", "coral3", "goldenrod")))
```



---

plotBoxMetric	<i>plotBoxMetric()</i>
---------------	------------------------

---

### Description

Plot distribution of a metric values as boxplots depending of bins. If the bin is absent from gr, a single boxplot is drawn.

### Usage

```
plotBoxMetric(  
  rse,  
  metric = "expr",  
  title = "Metric",  
  trans_func = function(x) x,  
  ylim = NULL,  
  ylab = "metric",  
  palette = colorRampPalette(c("#DF536B", "black", "#61D04F"))  
)
```

### Arguments

rse	a RangedSummarizedExperiment input. Aletrnatively: can be a GRanges object (for backward compatibility).
metric	name of the column in rse metadata containing scores.
title	title of the plot.
trans_func	A function to transform value of x before plotting. Useful to apply log10 transformation (i.e. with trans_func = function(x) log10(x+1)).
ylim	limit of the y axis; format: ylim = c(min, max)
ylab	y-axis title
palette	A vector of colors, or a function that returns a palette of n colors.

### Value

Display a plot.

### Examples

```
data("stackepi")  
plotBoxMetric(  
  stackepi,  
  trans_func = function(x) x,  
  metric = "exp",  
  title = "Metric"  
)
```

---

plotEpistack	plotEpistack()
--------------	----------------

---

### Description

Given a list of genomic regions, epigenetic signals surrounding these regions, and a score for each regions, plot epigenetic stacks depending on the score. An optional bin column allow the grouping of several genomic regions to produce average profiles per bins.

### Usage

```
plotEpistack(
  rse,
  assays = NULL,
  tints = "gray",
  titles = NULL,
  legends = "",
  main = NULL,
  x_labels = c("Before", "Anchor", "After"),
  xlim = c(0, 1),
  ylim = NULL,
  metric_col = "exp",
  metric_title = "Metric",
  metric_label = "metric",
  metric_ylab = NULL,
  metric_transfunc = function(x) x,
  bin_palette = colorRampPalette(c("#DF536B", "black", "#61D04F")),
  npix_height = 650,
  n_core = 1,
  high_mar = c(2.5, 0.6, 4, 0.6),
  low_mar = c(2.5, 0.6, 0.3, 0.6),
  error_type = c("ci95", "sd", "sem"),
  reversed_z_order = FALSE,
  rel_widths = c(score = 0.35, bin = 0.08, assays = 0.35),
  rel_heights = c(1, 0.14, 0.3),
  patterns = NULL,
  ...
)
```

### Arguments

rse	a RangedSummarizedExperiment input. Aletrnatively: can be a GRanges object (for backward compatibility, pat patterns will be required).
assays	specify the name(s) and order of assay(s) to plot. A vector of names that should match assayNames(rse).
tints	a vector of colors to tint the heatmaps. Can alos be a function returning n colors, or a list of such palette functions.

titles	titles of each heatmap. Defaults to assays.
legends	legend names for the epistacks.
main	Main title for the figure.
x_labels	a character vector of length 3 used as x-axis labels.
zlim	the minimum and maximum z values the heatmap. Format: <code>zlim = c(min, max)</code> . <code>zlim</code> can also be specified of as a list of pairs of limits, on for each assay.
ylim	limits of the y axis for bottom plots. <code>ylim</code> can also be specified of as a list of pairs of limits, on for each assay. Format: <code>ylim = c(min, max)</code>
metric_col	a character, name of a column in <code>gr</code> such as expression value, peak height, pvalue, fold change, etc.
metric_title	title to be display on the leftmost plots.
metric_label	label of the leftmost plots.
metric_ylab	y axis label of the top left plot.
metric_transfunc	a function to transform value of <code>metric_col</code> before plotting. Useful to apply <code>log10</code> transformation (i.e. with <code>trans_func = function(x) log10(x+1)</code> ).
bin_palette	A vector of colors, or a function that returns a palette of n colors. Used to color average profiles per bin in the bottom plots.
npix_height	The matrix height is reduced to this number of rows before plotting. Useful to limit overplotting artefacts. It should roughlyly be set to the pixel height in the final heatmaps
n_core	number of core used to speedup the martrix resizing.
high_mar	a vector of numerical values corresponding to the margins of the top figures. <code>c(bottom, left, top, right)</code>
low_mar	a vector of numerical values corresponding to the margins of the bottom figures. <code>c(bottom, left, top, right)</code>
error_type	<code>error_type</code> , can be either "sd" (standard deviation), "sem" (standard error of the mean), or "ci95" (95% confidence interval). Default: "ci95".
reversed_z_order	For the bottom panels: should the z-order of the curves be reversed (i.e. first or last bin on top)?
rel_widths	A named vector of three elements of relative panel widths: <code>score</code> is the leftmost panel, <code>bin</code> is the optionnal binning panels, and <code>assays</code> are the panels of the stacked-matrices. Default to <code>c(score = .35, bin = .08, assays = .35)</code>
rel_heights	A vector of three elements of relative panel heights. Default to <code>c(1, .14, .3)</code>
patterns	only if <code>rse</code> is of class <code>GRanges</code> . A character vector of column prefixes (can be regular expressions) that should match columns of <code>rse</code> .
...	Arguments to be passed to <code>par</code> such as <code>cex</code>

## Details

This function produce a comprehensive figure including epigenetic heatmaps and average epigenetic profiles from a well formatted `RangedSummarizedExperiment` object with expected `rowData` metadata columns. It scales resonably well up to hundreds of thousands of genomic regions.

The visualisation is centered on an anchor, a set of genomic coordinated that can be transcription start sites or peak center for example. Anchor coordinates are those of the `GRanges` used as a `rowData` in the input `RangedSummarizedExperiment` object (hereafter `rse`).

Anchors are plotted from top to bottom in the same order as in `rse`. One should sort `rse` before plotting if needed.

`rse`'s `rowData` should have a metric column that is used in the leftmost plots. The name of the metric column must be specified to `metric_col`. The metric can be transformed before plotting if needed using the `metric_transfunc` parameter.

The matrix or matrices used to display the heatmap(s) should be passed as `assay(s)` in `rse`. Such matrix can be obtained using `EnrichedHeatmap::normalizeToMatrix()` for example. The assay names are then specified through `assays`.

If an optionnal `bin` column is present in `rse`'s `rowData`, it will be used to group genomic regions to performed average profile per bins in the bottom plots.

Epistack are multipanel plots build using `layout()`. Margins for the panels can be specified using `high_mar` and `low_mar` parameters if needed, especially to avoid text overlaps. The default value should be appropriate in most situations. Individual component can be plotted using severa epistack functions such has `plotStackProfile()` or `plotAverageProfile()`.

Plotting more than > 1000 regions can lead to overplotting issued as well as some plotting artefacts (such as horizontal white strips). Both issues can be resolved with fidling with the `npix_height` parameter. `npix_height` should be smaller than the number of regions, and in the same order of magnitude of the final heatmap height in pixels. Last minutes call to the `redimMatrix()` function will hapen before plotting using `npix_height` as target height. Parameter `n_core` is passed to `redimMatrix()` to speed up the down-scaling.

The input can also be a `GRanges` object for backward compatibility. See [GRanges2RSE](#). patterns would then be required.

## Value

Display a plot.

## See Also

[plotStackProfile](#), [plotAverageProfile](#), [redimMatrix](#), [normalizeToMatrix](#), [addMetricAndArrangeGRanges](#), [addBins](#)

## Examples

```
data("stackepi")
plotEpistack(stackepi,
  metric_col = "exp",
  ylim = c(0, 1),
  metric_transfunc = function(x) log10(x+1))
```

---

plotMetric	<i>plotMetric()</i>
------------	---------------------

---

## Description

Plot a vertical line chart of the metric column, in the same order as the input.

## Usage

```
plotMetric(  
  x,  
  trans_func = function(x) x,  
  title = "Metric",  
  ylim = NULL,  
  xlab = NULL,  
  ylab = NULL  
)
```

## Arguments

x	a numeric vector.
trans_func	a function to transform x values before plotting. Useful to apply log10 transformation (i.e. with <code>trans_func = function(x) log10(x+1)</code> ).
title	Title of the plot.
ylim	limit of the y axis; format: <code>ylim = c(min, max)</code>
xlab	x-axis title
ylab	y-axis title

## Value

Display a plot.

## See Also

[plotEpistack](#), [plotBoxMetric](#)

## Examples

```
data("stackepi")  
plotMetric(SummarizedExperiment::rowRanges(stackepi)$exp)
```

---

plotStackProfile      *plotStackProfile()*

---

### Description

Display a heatmap of an epigenetic track centered at genomic anchors such as Transcription Start Sites or peak center.

### Usage

```
plotStackProfile(
  rse,
  assay = NULL,
  x_labels = c("Before", "Anchor", "After"),
  title = "",
  zlim = NULL,
  palette = function(n) grDevices::hcl.colors(n, rev = TRUE),
  target_height = 650,
  summary_func = function(x) mean(x, na.rm = TRUE),
  n_core = 1,
  pattern = NULL
)
```

### Arguments

rse	a RangedSummarizedExperiment input. Alternatively: can be a GRanges object (for backward compatibility, pattern will be required).
assay	specify the name of the assay to plot, that should match one of assayNames(rse).
x_labels	a character vectors of length 3 used to label the x-axis.
title	The title of the heatmap
zlim	The minimum and maximum z values to match color to values. Format: zlim = c(min, max)
palette	a palette of color, (i.e. a function of parameter n that should return n colors).
target_height	The matrix height is reduced to this number of rows before plotting. Useful to limit overplotting artefacts. It should roughly be set to the pixel height in the final heatmap.
summary_func	function passed to redimMatrix(). Usually mean, but can be set to median or max for sparse matrices.
n_core	multicore option, passed to redimMatrix().
pattern	only if rse is of class GRanges. A character vector of length 1 of a column prefix (can be regular expressions) that should match columns of rse.

## Details

The visualisation is centered on an anchor, a set of genomic coordinated that can be transcription start sites or peak center for example. Anchor coordinates are those of the RangedSummarizedExperiment object used as an input (hereafter rse).

Anchors are plotted from top to bottom in the same order as in rse. One should sort rse before plotting if needed.

The matrix used to display the heatmap should be passed as assay of rse. Such matrix can be obtained using `EnrichedHeatmap::normalizeToMatrix()` for example.

This function scale reasonably wells up to hundred thousands of regions. Overplotting issues are solved by last-minute reduction of the matrix size using `redimMatrix()`.

## Value

Display a plot.

## See Also

[plotAverageProfile](#), [plotEpistack](#), [normalizeToMatrix](#), [plotStackProfileLegend](#)

## Examples

```
data("stackepi")
plotStackProfile(stackepi,
                 target_height = 650,
                 zlim = c(0, 1),
                 palette = colorRampPalette(c("white", "dodgerblue", "black")),
                 title = "DNA methylation")
```

---

plotStackProfileLegend

*plotStackProfileLegend()*

---

## Description

Utility function to plot the corresponding legend key of `plotStackProfile()`'s plots.

## Usage

```
plotStackProfileLegend(
  zlim,
  palette = colorRampPalette(c("white", "grey", "black")),
  title = NA
)
```

**Arguments**

zlim	the limits of the values to be displayed. Format: c(min, max)
palette	a palette of color, (i.e. a function of parameter n that should return n colors).
title	an optional title to be displayed below the color legend.

**Value**

Display a plot.

**See Also**

[plotStackProfile](#)

**Examples**

```
plotStackProfileLegend(zlim = c(0, 2),
  palette = colorRampPalette(c("white", "grey", "black")))
```

---

redimMatrix

*redimMatrix()*

---

**Description**

Reduce the input matrix size by applying a summary function on cells to be fused.

**Usage**

```
redimMatrix(
  mat,
  target_height = 100,
  target_width = 100,
  summary_func = function(x) mean(x, na.rm = TRUE),
  output_type = 0,
  n_core = 1
)
```

**Arguments**

mat	the input matrix.
target_height	height of the output matrix (should be smaller than or equal to nrow(mat)).
target_width	width of the output matrix (should be smaller than or equal to ncol(mat)).
summary_func	how to summarize cells? A function such as mean, median, max, or meanColors.
output_type	Type of the output, to be passed to vapply's FUN.VALUE.
n_core	number of core to use for parallel processing.



## Details

This function is used to reduce matrix right before plotting them in order to avoid overplotting issues as well as other plotting artefacts.

## Value

a resized matrix of size `target_width` x `target_height` where the `summary_fun` was apply to adjacent cells.

## See Also

[meanColor](#)

## Examples

```
data("stackepi")
mat <- SummarizedExperiment::assay(stackepi, "DNAME")
dim(mat)
smallMat <- redimMatrix(mat, target_height = 10, target_width = ncol(mat))
dim(smallMat)

# changing the summary function
mat <- matrix(sample(1:40,100,replace=TRUE),nrow=10,ncol=10)
dim(mat)
smallMat <- redimMatrix(mat, target_height = 5, target_width = ncol(mat),
  summary_func = function(x) max(x, na.rm = TRUE))
dim(smallMat)

# working with colors
colmat <- matrix(
  c("red", "red", "blue", "blue", "red", "blue", "blue", "green"),
  ncol = 2
)
redimMatrix(colmat, target_height = 2, target_width = 2,
  summary_func = meanColor, output_type = "color")
```

---

stackepi

*epistack example and test dataset*

---

## Description

DNA methylation profiles (from MBD-seq data) around transcription start sites of the 693 chr18 genes annotated on the pig genome (Sscrofa11.1), as well as gene expression levels in Transcript Per Million (TPM) measured by RNA-seq in the same duodenum sample.

## Usage

```
data("stackepi")
```

**Format**

A RangedSummarizedExperiment of the 693 rows, 2 rows metadata columns, and one assay containing the DNA methylation signal.

**Source**

This dataset was generated from ENSEMBL annotation data and data generated by our lab (publicly available soon).

---

stackepi\_gr

*epistack backward compatibility dataset*

---

**Description**

DNA methylation profiles (from MBD-seq data) around transcription start sites of the 693 chr18 genes annotated on the pig genome (Sscrofa11.1), as well as gene expression levels in Transcript Per Million (TPM) measured by RNA-seq in the same duodenum sample.

**Usage**

```
data("stackepi_gr")
```

**Format**

A GRanges of the 693 rows and 54 metadata columns, kept for unit-testing backward-compatibility.

**Source**

This dataset was generated from ENSEMBL annotation data and data generated by our lab (publicly available soon).

**See Also**

[GRanges2RSE](#)

# Index

## \* datasets

stackepi, [17](#)

stackepi\_gr, [18](#)

addBins, [2](#), [12](#)

addMetricAndArrangeGRanges, [3](#), [3](#), [12](#)

addMetricAndArrangeRSE, [4](#)

GRanges2RSE, [5](#), [12](#), [18](#)

meanColor, [6](#), [17](#)

normalizeToMatrix, [12](#), [15](#)

par, [11](#)

plotAverageProfile, [7](#), [12](#), [15](#)

plotBinning, [3](#), [8](#)

plotBoxMetric, [9](#), [13](#)

plotEpistack, [10](#), [13](#), [15](#)

plotMetric, [13](#)

plotStackProfile, [12](#), [14](#), [16](#)

plotStackProfileLegend, [15](#), [15](#)

redimMatrix, [6](#), [12](#), [16](#)

stackepi, [17](#)

stackepi\_gr, [18](#)