Package: goatea (via r-universe)

October 23, 2026

Type Package

Title Interactive Exploration of GSEA by the GOAT Method

Version 2.1.0

Description Geneset Ordinal Association Test Enrichment Analysis (GOATEA) provides a 'Shiny' interface with interactive visualizations and utility functions for performing and exploring automated gene set enrichment analysis using the 'GOAT' package. 'GOATEA' is designed to support large-scale and user-friendly enrichment workflows across multiple gene lists and comparisons, with flexible plotting and output options. Visualizations pre-enrichment include interactive 'Volcano' and 'UpSet' (overlap) plots. Visualizations post-enrichment include interactive geneset dotplot, geneset treeplot, gene-effectsize heatmap, gene-geneset heatmap and 'STRING' database of protein-protein-interactions network graph. 'GOAT' reference: Frank Koopmans (2024) <doi:10.1038/s42003-024-06454-5>.

URL https://github.com/mauritsunkel/goatea, https://mauritsunkel.github.io/goatea/

BugReports https://github.com/mauritsunkel/goatea/issues

License Apache License (>= 2)

Encoding UTF-8

LazyData false

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Config/testthat/edition 3

biocViews GeneSetEnrichment, NetworkEnrichment, Visualization, ShinyApps, GUI, Transcriptomics, Genetics, FunctionalGenomics, DifferentialExpression, Network

Depends R (>= 4.5.0), dplyr (>= 1.1.4)

Imports goat (>= 1.0), shiny (>= 1.10.0), shinyjs (>= 2.1.0), shinyjqui (>= 0.4.1), shinydashboard (>= 0.7.2), openxlsx (>= 4.2.7.1), upsetjs (>= 1.11.1), data.table (>= 1.18.2.1), ComplexHeatmap (>= 2.24.0), InteractiveComplexHeatmap (>= 1.12.0), tidyr (>= 1.3.1), purrr (>= 1.0.2), ggplot2 (>= 3.5.1), plotly (>= 4.10.4), igraph (>= 2.1.4), visNetwork (>= 2.1.2), arrow (>= 18.1.0.1), htmltools (>= 0.5.8.1), methods (>= 4.5.0), AnnotationDbi (>= 1.69.1), DT (>= 0.33), plyr (>= 1.8.9), tibble (>= 3.2.1), rlang (>= 1.1.6), DOSE (>= 4.4.0), enrichplot (>= 1.30.4), clusterProfiler (>= 4.18.4), EnhancedVolcano (>= 1.28.2), org.Hs.eg.db (>= 3.22.0), org.Mm.eg.db (>= 3.22.0), org.Dm.eg.db (>= 3.22.0), org.Mmu.eg.db (>= 3.22.0), org.Rn.eg.db (>= 3.22.0), org.Ce.eg.db (>= 3.22.0), org.Pt.eg.db (>= 3.22.0), org.Dr.eg.db (>= 3.22.0)

Suggests knitr, rmarkdown, BiocStyle, magick

VignetteBuilder knitr

Config/pak/sysreqs libcairo2-dev cmake libfontconfig1-dev libfreetype6-dev libfribidi-dev libglpk-dev make libharfbuzz-dev libicu-dev libpng-dev libuv1-dev libxml2-dev libssl-dev perl zlib1g-dev

Repository https://bioc.r-universe.dev

Date/Publication 2026-04-28 13:05:29 UTC

RemoteUrl https://github.com/bioc/goatea

RemoteRef HEAD

RemoteSha b2cd47cae961ba9e6f07824f1c04b8e3c3d88cde

Contents

calculate_geneSetRatio . . . 3
colorify . . . 4
colorify_map . . . 6
display_palettes . . . 7
example_Colameo_MS . . . 7
example_Colameo_RNA . . . 8
example_enrichment . . . 8
example_genelist . . . 9
example_genes_overview . . . 9
example_genesets . . . 10
example_ppi_data . . . 10
file_extension . . . 11
filter_enrichment . . . 11
get_base_folder . . . 13
get_ppigraph . . . 13
get_string_ppi . . . 14
get_terms_by_keywords . . . 15
get_visNetwork . . . 16

goatea_server . . . 17
goatea_ui . . . 17
hexcolor2rgba . . . 18
palette_name_mapping . . . 18
plot_ComplexHeatmap . . . 19
plot_EnhancedVolcano . . . 20
plot_gene_effectsize_ComplexHeatmap . . . 21
plot_genelists_overlap_upsetjs . . . 22
plot_splitdot . . . 23
plot_termtree . . . 24
process_string_input . . . 25
read_validate_genelist . . . 25
rename_gene_overview . . . 26
run_genelists_overlap . . . 27
run_geneset_enrichment . . . 28
scale_values_between . . . 29
set_significant_N_genes . . . 30
wrap_hovertip . . . 31
wrap_loader . . . 31

Index **33**

`calculate_geneSetRatio` *Calculate geneSetRatio per gene per enrichment contrast*

Description

Get a percentage of genesets the specific gene is included

Usage

```
calculate_geneSetRatio(enrichment_results, gene_overview_df)
```

Arguments

`enrichment_results`	list of enrichment results
`gene_overview_df`	dataframe with gene-wise information

Value

numerical vector of gene set ratios

Examples

```
calculate_geneSetRatio(
list(
  A = get(load(system.file("extdata", "example_enrichment.rda", package = "goatea"))),
  B = get(load(system.file("extdata", "example_enrichment.rda", package = "goatea")))
),
get(load(system.file("extdata", "example_genes_overview.rda", package = "goatea"))))
```

`colorify` *Create and/or modify color/gradient palettes*

Description

Note for colorblind use: "Okabe-Ito"

Addition of values happens before multiplication with factors.

Palette names are stripped of whitespace and lowered for name matching. All RColorBrewer and Viridis palettes are included.

All grDevices plotting functions are provided as palettes, simply use colors = "rainbow", "heat", "terrain", "topo" or "cm".

Usage

```
colorify(
  n = NULL,
  colors = character(0),
  colors_lock = NULL,
  colors_names = character(0),
  colors_breakpoints = numeric(0),
  gradient_n = n,
  gradient_space = c("rgb", "Lab"),
  gradient_interpolate = c("linear", "spline"),
  hf = 1,
  sf = 1,
  lf = 1,
  rf = 1,
  gf = 1,
  bf = 1,
  hv = 0,
  sv = 0,
  lv = 0,
  rv = 0L,
  gv = 0L,
  bv = 0L,
  alpha = 1,
  rev = FALSE,
  plot = FALSE,
```

```
  export = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

n	default: NULL, else integer, amount of colors to create, if palette selected and more colors requested they will be generated
colors	character (vector), combination of selecting palette(s) by name (options: see display_palettes()), and/or vector of R color names and/or color hexcodes
colors_lock	default: rep(FALSE, length(colors), numerical or logical index of colors (not) to be modified, if logical length != colors it will be cut or filled with TRUE/FALSE, prefix with '!' for logical vectors and '-' for numerical vectors to get inverse, see examples. If gradient_n %% length(colors) == 0, i.e. if gradient_n divisive by amount of colors without rest, set repeat given locking pattern
colors_names	default: character(0), else character vector of color names
colors_breakpoints	default: numeric(0), else numeric vector of breakpoints to colorRamp in between
gradient_n	default: n, else integer, amount of colors to output as gradient, after completing palette for n colors
gradient_space	default: "rgb", else "Lab", see ?grDevices::colorRamp()
gradient_interpolate	default: "linear", else "spline", see ? grDevices::colorRamp()
hf	hue factor, default: 1, multiply values by factor, proportional to base value of 1
sf	saturation factor, default: 1, multiply values by factor, proportional to base value of 1
lf	lightness/brightness factor, default: 1, multiply values by factor, proportional to base value of 1
rf	red factor, default: 1, multiply values by factor, proportional to base value of 1
gf	green factor, default: 1, multiply values by factor, proportional to base value of 1
bf	blue factor, default: 1, multiply values by factor, proportional to base value of 1
hv	hue value, default: 0, add value to values, linear from base value of 0
sv	saturation value, default: 0, add value to values, linear from base value of 0
lv	lightness/brightness value, default: 0, add value to values, linear from base value of 0
rv	red value, default: 0, add value to values, linear from base value of 0
gv	green value, default: 0, add value to values, linear from base value of 0
bv	blue value, default: 0, add value to values, linear from base value of 0
alpha	numeric, sets color alpha values

rev	default: FALSE, if TRUE, reverse order of colors
plot	default: FALSE, if TRUE plot pie chart of color palette
export	default: FALSE, if TRUE: export = getwd(), if export = "string/", save hexcodes, rgb, and hsl values to export/colorify.csv
verbose	default: TRUE, else FALSE - to log status messages
...	additional arguments to pass on

Details

Either generate theoretically maximally different colors, select an available R grDevices palette and/or modify the colors of the given gradient/palette

Value

vector of color hexcodes

Examples

```
colorify(10, plot = TRUE)
```

---

colorify_map *Colorify colorRamp between colors mapping to breakpoint values*

Description

Note that breakpoints and colors will be ordered ascendingly by breakpoints values

Usage

```
colorify_map(colors, breakpoints, ...)
```

Arguments

colors	hexcolor character vector
breakpoints	numeric vector matching colors per value
...	to pass arguments to grDevices::colorRamp

Value

function with colors and breaks attributes, can be called as function(c(values)) to return hexcolor-codes

display_palettes *Display R grDevices palettes*

Description

Use colorify() to select and modify the palettes, see its documentation. Note that discrete palettes with maximum n colors will be repeated in plotting.

Any numeric i_palettes over maximum amount of palettes are not displayed.

Contains all Viridis palettes, excluding Turbo.

Usage

```
display_palettes(n = 10, i_palettes = seq_len(1000), border = FALSE)
```

Arguments

n	integer, amount of colors to display
i_palettes	default: numeric vector as index/range for choosing palettes, or a combination of 'rcolorbrewer', 'viridis', 'rainbow' (grDevices Palettes) to show specific palettes
border	default: FALSE, if TRUE show color rectangle borders

Value

named vector with source and name of palettes, 'hcl' for grDevices::hcl.pals() and 'pal' for grDevices::palette.pals()

example_Colameo_MS *Example Colameo MS data*

Description

Mass spectrometry genelist from Colameo et al. 2021.

Usage

```
example_Colameo_MS
```

Format

A data frame with columns gene, symbol, effectsize, pvalue.

Source

Colameo et al. 2021 (PMID: 34396684)

example_Colameo_RNA *Example Colameo RNA data*

Description

RNA-seq genelist from Colameo et al. 2021.

Usage

```
example_Colameo_RNA
```

Format

A data frame with columns gene, symbol, effectsize, pvalue.

Source

Colameo et al. 2021 (PMID: 34396684)

example_enrichment *An example enrichment*

Description

A simulated example of an enrichemnt for testing or demonstration purposes.

Format

`enrichment`:
A data frame with 10 rows and 17 columns:
source origin
source_version org.Xx.eg.db
id DB.001
name geneset name 1, geneset name 2
parent_id DB.010, DB.020
ngenes_input 10, 30
ngenes 10, 30
genes 10000, 10001
ngenes_signif 10, 30
score_type effectsize
pvalue 0.05, 1
zscore -Inf, 0, Inf ...

Source

generated with `data-raw/example_data.R`

example_genelist *An example genelist*

Description

A simulated example of a genelist for testing or demonstration purposes.

Format

`genelist`:
A data frame with 100 rows and 4 columns:

symbol Gene_1, Gene_2
gene 10000, 10001
pvalue 0.05, 1
effectsize 2.5, 0 ...

Source

generated with `data-raw/example_data.R`

example_genes_overview *An example genes overview*

Description

A simulated example of a gene overview for testing or demonstration purposes.

Format

`genes overview`:
A data frame with 100 rows and ~11 columns:

gene 10000, 10001
symbol Gene_1, Gene_2
sample_efsi 2.5, 0
sample_pval 0.05, 1
sample_perc 0, 100
genelist_overlap "", "A", "B", "AB"
sample_geneSetRatio 0, 50, 100 ...

Source

generated with `data-raw/example_data.R`

example_genesets *Example genesets*

Description

A simulated example of a geneset for testing or demonstration purposes.

Format

`genesets`:
A data frame with 100 rows and 4 columns:

source origin
source_version org.Xx.eg.db
id DB.001
name geneset name 1, geneset name 2
parent_id DB.010, DB.020
genes 10000, 10001
ngenes 10, 30 ...

Source

generated with `data-raw/example_data.R`

example_ppi_data *An example ppi data*

Description

A simulated example of a ppi dataframe for testing or demonstration purposes.

Format

`ppi data`:
A data frame with 15 rows and 5 columns:

from_symbol gene_A, gene_B
to_symbol gene_A, gene_B
combined_score 0, 1000
from gene_A_ID, gene_B_ID
to gene_A_ID, gene_B_ID ...

Source

generated with `data-raw/example_data.R`

file_extension *Get file extension*

Description

Get file extension

Usage

```
file_extension(x)
```

Arguments

x	string filepath

Value

string file extension

Examples

```
file_extension('filename.ext')
```

filter_enrichment *Filter enrichment*

Description

Search and filter and sort or summarize (compiled) enrichment output.

Usage

```
filter_enrichment(
  df,
  genes_input = "",
  genes_any_all = c("any", "all"),
  terms_query = "",
  terms_query_all_any = c("any", "all"),
  terms_antiquery = "",
  terms_antiquery_all_any = c("any", "all"),
  min_ngenes = 0,
  min_ngenes_input = 0,
  min_ngenes_signif = 0,
  min_abs_zscore = 0,
  min_pvalue_adjust = 0,
  max_ngenes = 1e+06,
```

```
  max_ngenes_input = 1e+06,
  max_ngenes_signif = 1e+06,
  max_abs_zscore = 1e+06,
  max_pvalue_adjust = 1
)
```

Arguments

df	enrichment output dataframe
genes_input	default: UI input/character vector of genes to select df terms for
genes_any_all	default: 'any', else 'all', use to define to take only specific terms containing any or all associated genes
terms_query	dfeault: UI input/character vector of keywords to match (grepl) term names
terms_query_all_any	default: 'any', else 'all', defines if terms should match any or all of the query keywords given
terms_antiquery	dfeault: UI input/character vector of keywords to NOT match (grepl) term names
terms_antiquery_all_any	default: 'any', else 'all', defines if terms should NOT match any or all of the query keywords given
min_ngenes	default: 0, set higher to filter terms with less n genes
min_ngenes_input	default: 0, else set higher to filter terms with less n input genes
min_ngenes_signif	default: 0, set higher to filter terms with less n significant genes
min_abs_zscore	default: 0, set higher to filter terms with less absolute zscore
min_pvalue_adjust	default: 0, set higher to filter terms with lower multiple testing corrected p-value
max_ngenes	default: 0, set lower to filter terms with more n genes
max_ngenes_input	default: 0, else set lower to filter terms with more n input genes
max_ngenes_signif	default: 0, set lower to filter terms with more n significant genes
max_abs_zscore	default: 0, set lower to filter terms with more absolute zscore
max_pvalue_adjust	default: 1, set lower to filter terms with higher adjusted p-value for multiple correction

Value

filtered dataframe

Examples

```
filter_enrichment(
get(load(system.file("extdata", "example_enrichment.rda", package = "goatea"))),
min_ngenes = 15)
```

---

get_base_folder *Set base folder*

Description

sets/gets given folder path if provided else checks in order:

- path.expand("~") (tilde (~) expands to HOME folder path)
- Sys.getenv("R_USER") (set on R session start)
- Sys.getenv("USERPROFILE") (Windows specific)

Usage

```
get_base_folder(folder_path = NULL)
```

Arguments

folder_path	character, default NULL, else existing directory

Value

character folder path

Examples

```
get_base_folder()
```

---

get_ppigraph *Get PPI igraph*

Description

Uses Leiden clustering on modularity for community detection. Leiden was chosen as default as expected PPI data is not inherently hierarchical, which is why modularity optimalization is used on the graph topology. Expected PPI data comes from genes/proteins (of interest) selected from gene set enrichment analysis or differential expression analysis. Using clustering from terms is not possible, as genes can be in multiple terms. Leiden also scales well to large graphs, has consistent clustering outcomes and provides some inherent guarantees by its method, e.g. locally optimal assignment.

Usage

```
get_ppigraph(ppi_data, vertex_clustering = NULL)
```

Arguments

ppi_data	dataframe, PPI by aliases/ids in columns 'from' and 'to'
vertex_clustering	NULL, else numerical vector of cluster IDs

Value

igraph object of PPI data

References

Traag, V.A., Waltman, L. & van Eck, N.J. From Louvain to Leiden: guaranteeing well-connected communities. Sci Rep 9, 5233 (2019). https://doi.org/10.1038/s41598-019-41695-z

Examples

```
get_ppigraph(
  get(load(system.file("extdata", "example_ppi_data.rda", package = "goatea")))
)
```

---

get_string_ppi *Get STRING database Protein-Protein Interactions*

Description

STRING documentation: https://string-db.org/cgi/help?sessionId=baEZCS5u1RdM

Protocol used for downloading STRING files is https

Usage

```
get_string_ppi(
  aliases,
  score_threshold = 0L,
  organism = 9606L,
  network_type = "full",
  link_data = "combined_only",
  folder = tempdir(),
  version = "latest",
  versions = NULL
)
```

Arguments

aliases	character, vector with protein/gene symbols/aliases
score_threshold	integer, default: 0, to get all PPI, ranges between [0-1000], 200 for low, 400 for medium and 700 for high/stringent scoring PPI
organism	integer, default: 9606 (Homo Sapiens), see ?goat::load_genesets_go_bioconductor taxid parameter for possible organism taxIDs
network_type	character, default: 'full', else 'physical' for only STRING documented physical interactions
link_data	character, default: 'combined_only', else 'full' or 'detailed', see STRING documentation
folder	character, default: tempdir(), else given folder path for where to download STRING files, converted to .parquet for compression and query efficiency, if tempdir() the temporary directory with the downloaded files are removed after the R session
version	character, default: 'latest', else a version to check availability, e.g. "12.0", if version not available the available versions are printed
versions	NULL, else character vector with versions to choose from with version

Value

dataframe (tibble) with protein-protein interactions (symbols and STRING IDs) and STRING combined score

Examples

```
get_string_ppi(c("TP53", "EGFR", "BRCA1", "MTOR", "MYC", "SOX2"))
```

---

get_terms_by_keywords *Get term names by searching with (partial) keywords*

Description

Get term names by searching with (partial) keywords

Usage

```
get_terms_by_keywords(patterns, terms, pos_neg = "pos", all_any = "all")
```

Arguments

patterns	keywords to match (grepl) term names
terms	character vector to be grepl searched
pos_neg	return positive matches or negate matches
all_any	need all or any patterns to match search terms

Value

character vector with matching terms by patterns

Examples

```
get_terms_by_keywords('circa', c('circadian rhythm', 'no match', 'circadian clock'))
```

`get_visNetwork` *Get visNetwork graph*

Description

Gets visNetwork graph with ppigraph, and optionally genes overview, metadata

Usage

```
get_visNetwork(ppigraph, genes_overview = NULL, sample_name = NULL)
```

Arguments

`ppigraph`	igraph object, get from `get_ppigraph()`
`genes_overview`	(optional) dataframe, default: NULL, else metadata dataframe for ppigraph proteins/genes aliases
`sample_name`	(optional) character, default: NULL, else sample name found in genes_overview columns

Value

list of visNetwork nodes and edges and given ppigraph

Examples

```
ppi_graph <- get_ppigraph(
  get(load(system.file("extdata", "example_ppi_data.rda", package = "goatea")))
)
get_visNetwork(ppi_graph)
```

goatea_server *Server for goatea package*

Description

Server for goatea package

Usage

```
goatea_server(input, output, session, css_colors)
```

Arguments

input	Shiny input elements handling
output	Shiny input elements handling
session	Shiny handling reactivity in app
css_colors	see app.R, user set manual colors for the GOATEA UI

Value

Shiny server function

goatea_ui *UI for GOATEA package*

Description

UI for GOATEA package

Usage

```
goatea_ui()
```

Value

Shiny UI function

hexcolor2rgba *Hex code colors to rgba format*

Description

Hex code colors to rgba format

Usage

```
hexcolor2rgba(hexcolors, alpha = NULL)
```

Arguments

hexcolors	character (vector), hexcode colors (e.g. #FFFFFF)
alpha	numeric in range [0-1], default: NULL to use full opacity or given opacity (AA) in hexcolors (#RRGGBBAA)

Value

colors in rgba format

Examples

```
colors <- colorify(5)
hexcolor2rgba(colors)
hexcolor2rgba(colors, alpha = .5)
colors <- gsub('FF$', 75, colors)
hexcolor2rgba(colors)
hexcolor2rgba(colors, alpha = .5)
```

palette_name_mapping *Palette original name mapping*

Description

All ColorBrewer palettes overlap with grDevices palettes Viridis palettes, except "Magma", overlap with grDevices palettes

Usage

```
palette_name_mapping(palette)
```

Arguments

palette	string: name of palette, will be lower()ed and stripped of whitespace

Value

original palette name

`plot_ComplexHeatmap` *Plot ComplexHeatmap*

Description

Plot ComplexHeatmap from enrichment analysis results and corresponding genelist

Usage

```
plot_ComplexHeatmap(
  enrichment_result,
  genelist,
  genes = NULL,
  cluster_method = "single",
  n_cluster = 1,
  n_top_terms = NA,
  n_top_genes = NA,
  genelist_overlap = NULL,
  plot = FALSE
)
```

Arguments

`enrichment_result`	dataframe containing enrichment analysis results. Must include `name` (gene set names) and `symbol` (listed genes associated with gene sets)
`genelist`	dataframe with gene-level statistics, including at least `symbol`, `pvalue`, `effectsize`, and `signif` columns
`genes`	character, default: NULL, if genes given, these are prioritized for visualization
`cluster_method`	default: 'single', else one of hclust methods
`n_cluster`	default: 1, integer, number of hierarchical clusters to define
`n_top_terms`	default: NULL, if integer, plot only top genesets (recommended for visual clarity: 70)
`n_top_genes`	default: NULL, if integer, plot only top genes (recommended for visual clarity: 150)
`genelist_overlap`	(Optional) dataframe with gene overlap information, including `symbol` and `genelist_overlap`, see run_genelists_overlap()
`plot`	default: FALSE, if TRUE, display drawn ComplexHeatmap

Value

A **ComplexHeatmap** object displaying genesets (rows) and genes (columns), potentially clustered based on their binary associations. The heatmap includes:

- Row annotations: Gene set size, p-value, and average effect size.
- Column annotations: Gene p-values, effect sizes, and optional overlap categories.
- Customized row/column labels highlighting significant elements.
- A color-mapped heatmap showing clustering results.

Examples

```
plot_ComplexHeatmap(
 get(load(system.file("extdata", "example_enrichment.rda", package = "goatea")))[seq.int(1, 3), ],
  get(load(system.file("extdata", "example_genelist.rda", package = "goatea"))),
  n_cluster = 3,
  n_top_genes = 10
)
```

`plot_EnhancedVolcano` *Plot EnhancedVolcano*

Description

Plot EnhancedVolcano

Usage

```
plot_EnhancedVolcano(
  genelist,
  effectsize_threshold = 1,
  pvalue_threshold = 0.05,
  background_color = "black",
  foreground_color = "white",
  interactive = FALSE,
  legend_labels = c("NS", "FC", "P", "FC & P"),
  x_label = "effectsize (FC)",
  y_label = "-log10(pvalue) (P)",
  title = "Volcano plot",
  subtitle = "EnhancedVolcano",
  caption = paste0("N genes: ", nrow(genelist)),
  label_size = 3,
  legend_label_size = 14,
  axes_label_size = 18,
  point_size = 2
)
```

Arguments

genelist	UI value/list of tibbles/dataframes
effectsize_threshold	numeric, default: 1, threshold for showing significance on effectsize axis
pvalue_threshold	numeric, default: 0.05, threshold for showing significance on pvalue axis
background_color	default: 'black', else character hexcolor or colorname
foreground_color	default: 'white', else character hexcolor or colorname
interactive	default: FALSE, else TRUE
legend_labels	character vector, default: c('NS', 'FC', 'P', 'FC & P'), plot legend labels
x_label	character, default: 'effectsize (FC)', plot x-axis label
y_label	character, default: "'-log10(pvalue) (P)', plot y-axis label
title	character, default: 'Volcano plot', plot title
subtitle	character, default: 'EnhancedVolcano', plot subtitle
caption	character, default: paste0("N genes: ", nrow(genelist)), plot caption
label_size	numeric, default: 3, plot variable label size
legend_label_size	numeric, default: 14, plot legend label size
axes_label_size	numeric, default: 18, plot x- and y-axis lable sizes
point_size	numeric, default: 2, plot point size

Value

plotly or ggplot2 object

Examples

```
plot_EnhancedVolcano(
  get(load(system.file("extdata", "example_genelist.rda", package = "goatea")))
)
```

---

plot_gene_effectsize_ComplexHeatmap

Plot gene2effectsize ComplexHeatmap

Description

Plot gene2effectsize ComplexHeatmap

Usage

```
plot_gene_effectsize_ComplexHeatmap(
  genes,
  genes_overview,
  rows_dendrogram = TRUE,
  cols_dendrogram = TRUE,
  plot_n_genes = 50
)
```

Arguments

genes	character, genes to visualize
genes_overview	dataframe, containing columns: 'symbol', 'SAMPLE_efsi' and 'SAMPLE_pval'
rows_dendrogram	default: FALSE, TRUE to cluster rows and show dendrogram
cols_dendrogram	default: FALSE, TRUE to cluster columns and show dendrogram
plot_n_genes	integer, default: 50, NULL to plot all genes

Value

ComplexHeatmap object

Examples

```
plot_gene_effectsize_ComplexHeatmap(
  c('gene_1', 'gene_2', 'gene_3', 'gene_4', 'gene_5'),
  get(load(system.file("extdata", "example_genes_overview.rda", package = "goatea")))
)
```

---

plot_genelists_overlap_upsetjs

Visualize genelists gene overlap in an interactive UpSet plot

---

Description

UpSetJS examples: https://upset.js.org/integrations/r/articles/combinationModes.html#distinct-intersection-mode

Usage

```
plot_genelists_overlap_upsetjs(
  genelists,
  mode = "distinct",
  interactive = FALSE,
  main.color = "black",
  highlight.color = "green"
)
```

Arguments

genelists	UI value/list of tibbles/dataframes
mode	string, default: 'intersect', else 'distinct' or 'union' - how to overlap the listed genes
interactive	default: FALSE, else TRUE
main.color	default: 'white' else character hexcolor or colorname
highlight.color	default: 'green' else character hexcolor or colorname

Value

upset plot

Examples

```
plot_genelists_overlap_upsetjs(list(
  A = get(load(system.file("extdata", "example_genelist.rda", package = "goatea"))),
  B = get(load(system.file("extdata", "example_genelist.rda", package = "goatea")))
))
```

---

plot_splitdot *Plot splitdot plot*

Description

Plot splitdot plot

Usage

```
plot_splitdot(enrichment, topN = NA)
```

Arguments

enrichment	GOAT enrichment result
topN	default: NA to plot all, else integer to plot topN terms by adjusted pvalue

Value

ggplot2 object

Examples

```
plot_splitdot(
  get(load(system.file("extdata", "example_enrichment.rda", package = "goatea")))
)
```

`plot_termtree` *Plot semantic similarity termtree*

Description

Plot semantic similarity termtree

Usage

```
plot_termtree(
  genelist,
  genesets,
  map_organism = 9606,
  effectsize_threshold = 1,
  Nterms = NA,
  Nwords = 5,
  Nclusters = 3
)
```

Arguments

`genelist`	GOAT current genelist from selected enrichment sample
`genesets`	GOAT filtered genesets
`map_organism`	integer, default: 9606 (human) - input organism ID that will be mapped to org.Xx.eg.db
`effectsize_threshold`	numerical, default: 1 - genelist effectsize threshold
`Nterms`	integer, default: NA to plat all terms, integer sets amount of terms to plot
`Nwords`	integer, default: 5, sets N summarized words per cluster
`Nclusters`	integer, default: 1, sets N clusters of terms

Value

ggtree/gg/ggplot object

Examples

```
plot_termtree(
 genelist = get(load(system.file("extdata", "example_genelist.rda", package = "goatea"))),
 genesets = get(load(system.file("extdata", "example_genesets.rda", package = "goatea")))
)
```

process_string_input *Process Shiny area input string*

Description

Process Shiny area input string

Usage

```
process_string_input(string_input)
```

Arguments

string_input	siny string

Value

processed string - no whitespace, enters, only letters and numbers

Examples

```
process_string_input("test string \n")
```

read_validate_genelist *Read and validate a table with genes (that should be tested in overrepresentation-analysis) for compatibility with this R package#'*

Description

if 'pvalue' is not in the genelist columns, it is set and defaulted to 1 for visualization purposes if 'effectsize' is not in the genelist columns, it is set and defaulted to 0 for visualization purposes

Usage

```
read_validate_genelist(
  file,
  remove_non_numerical_ids = TRUE,
  remove_duplicated = TRUE,
  remove_Rik_genes = TRUE,
  remove_Gm_genes = TRUE,
  map_organism = NULL
)
```

Arguments

`file` full filepath to gene tibble in .csvs/.xlsx/.tsv

`remove_non_numerical_ids`
boolean, default TRUE, if non-numerical in gene column, remove

`remove_duplicated`
boolean, default TRUE, removes duplicated gene symbols/ids

`remove_Rik_genes`
boolean, default TRUE, grepl("Rik$") search and remove Riken non-canonical mouse genes

`remove_Gm_genes`
boolean, default TRUE, grepl("^Gm") search and remove Gm non-canonical mouse genes

`map_organism` default: NULL, if numeric taxid, used for selecting org.Xx.eg.db to map gene symbols to gene column via AnnotationDbi::mapIds(keytype = 'ALIAS') - if mapped to NA the genes are removed - need to download org.Xx.eg.db manually! Symbols are set toupper() to match formatting. Protein symbols could be used too.

- 9606 = Human (Homo sapiens) (org.Hs.eg.db)
- 9544 = Rhesus monkey (Macaca mulatta) (org.Mmu.eg.db)
- 10090 = Mouse (Mus musculus) (org.Mm.eg.db)
- 10116 = Rat (Rattus norvegicus) (org.Rn.eg.db)
- 7227 = Fruit fly (Drosophila melanogaster) (org.Dm.eg.db)
- 6239 = Worm (Caenorhabditis elegans) (org.Ce.eg.db)

Value

tibble dataframe with columns: symbol (string), gene (string as integer ID), pvalue (numeric), effestsize (numeric)

Examples

```
file_path <- system.file("extdata", "example_genelist.csv", package = "goatea")
read_validate_genelist(file = file_path)
```

`rename_gene_overview` *Rename the gene overview*

Description

Rename the gene overview

Usage

```
rename_gene_overview(names, genes_overview)
```

Arguments

names	names to rename gene overview
genes_overview	UI given genes overview dataframe (rv_genelists_overlap$gene_overview)

Value

genes overview renamed

---

run_genelists_overlap *Create gene overview through overlapping genelists information by overlapping significant genes*

Description

Create gene overview through overlapping genelists information by overlapping significant genes

Usage

```
run_genelists_overlap(genelists)
```

Arguments

genelists	UI value/list of tibbles/dataframes

Value

tibble/dataframe with (annotated) genes and p-value/effectsize info for each genelist, concluding with overlapping genelists by significant genes

Examples

```
run_genelists_overlap(list(
  A = get(load(system.file("extdata", "example_genelist.rda", package = "goatea"))),
  B = get(load(system.file("extdata", "example_genelist.rda", package = "goatea")))
))
```

`run_geneset_enrichment` *Perform geneset enrichment testing using any supported method*

Description

See original documentation at test_genesets

Usage

```
run_geneset_enrichment(
  genesets,
  genelist,
  method = "goat",
  score_type = "effectsize",
  padj_method = "BH",
  padj_sources = TRUE,
  padj_cutoff = 0.01,
  padj_min_signifgenes = 0L,
  ...
)
```

Arguments

genesets	tibble with genesets, must contain columns 'source', 'source_version', 'id', 'name', 'genes', 'ngenes', 'ngenes_signif'
genelist	tibble with genes, must contain column 'gene' and 'test'. gene = character column, which are matched against list column 'genes' in genesets tibble. test = boolean column (you can set all to FALSE if not performing Fisher-exact or hypergeometric test downstream)
method	method for overrepresentation analysis. Options: "goat", "hypergeometric", "fisherexact", "fisherexact_ease", "gsea", "idea"
score_type	string, default: "effectsize", alternatively set to "pvalue", "effectsize_up", "effectsize_down", "effectsize_abs"
padj_method	first step of multiple testing correction; method for p-value adjustment, passed to stats::p.adjust() via padjust_genesets(), e.g. set "BH" to compute FDR adjusted p-values (default) or "bonferroni" for a more stringent procedure
padj_sources	second step of multiple testing correction; apply Bonferroni adjustment to all p-values according to the number of geneset sources that were tested. Boolean parameter, set TRUE to enable (default) or FALSE to disable
padj_cutoff	cutoff for adjusted p-value, signif column is set to TRUE for all values lesser-equals
padj_min_signifgenes	if a value larger than zero is provided, this will perform additional post-hoc filtering; after p-value adjustment, set the pvalue_adjust to NA and signif to

	FALSE for all genesets with fewer than padj_min_signifgenes 'input genes that were significant' (ngenes_signif column in genesets table). So this does not affect the accuracy of estimated p-values, in contrast to prefiltering genesets prior to p-value computation or adjusting p-values
...	further parameters are passed to the respective stats method

Value

the input genesets, with results stored in columns 'pvalue', 'pvalue_adjust', 'signif' and 'zscore'

Examples

```
run_geneset_enrichment(
  get(load(system.file("extdata", "example_genesets.rda", package = "goatea"))),
  get(load(system.file("extdata", "example_genelist.rda", package = "goatea")))
)
```

---

scale_values_between *Scale values between given min/max*

Description

Scale values between given min/max

Usage

```
scale_values_between(
  values,
  old_min = min(values),
  old_max = max(values),
  new_min = 0,
  new_max = 100
)
```

Arguments

values	numeric (vector)
old_min	numeric, default: min(values), else set as current expected minimum of values
old_max	numeric, default: max(values), else set as current expected maximum of values
new_min	numeric, default: 0, else set to wanted new minimum value
new_max	numeric, default: 100, else set to wanted new maximum value

Value

scaled numeric values

Examples

```
scale_values_between(c(1,3,1,4,1,6,1,6,5,7))
```

`set_significant_N_genes` *Set significant and number of genes*

Description

Set significant and number of genes

Usage

```
set_significant_N_genes(
  genelist,
  significance_by = "pvalue_effectsize",
  pvalue_threshold = 0.05,
  effectsize_threshold = 1,
  keep_max_n_genes = FALSE,
  keep_max_n_genes_by = "pvalue"
)
```

Arguments

`genelist`	list, loaded genelist with goatea::read_validate_genelist()
`significance_by`	string, default: 'pvalue_effectsize', else 'pvalue' or 'effectsize' to set gene significance to TRUE/FALSE in 'signif' column
`pvalue_threshold`	numeric, default: 0.05, to set gene significance based on pvalue
`effectsize_threshold`	numeric, default: 1, to set gene significance based on effectsize
`keep_max_n_genes`	boolean, default: TRUE, filter down by pvalue to max n genes allowed by goat (max(goat::goat_nulldistributions$N))
`keep_max_n_genes_by`	string, default: 'pvalue', else 'effectsize', order genes based on lowest pvalues or highest absolute effect sizes

Value

genelist with added 'signif' column with TRUE/FALSE values

Examples

```
set_significant_N_genes(
  get(load(system.file("extdata", "example_genelist.rda", package = "goatea")))
)
```

wrap_hovertip *Wrap Shiny UI element with a hoverable tooltip contained in html div tags*

Description

Wrap Shiny UI element with a hoverable tooltip contained in html div tags

Usage

```
wrap_hovertip(ui_element, hovertip)
```

Arguments

ui_element	Shiny UI element to wrap with hovertext
hovertip	text that will show as hover popup

Value

tags$div element around given Shiny UI element

Examples

```
wrap_hovertip(shiny::actionButton('id_example', 'example'), 'example')
```

wrap_loader *Wrap Shiny UI element with a loading spinner contained in html div tags*

Description

Wrap Shiny UI element with a loading spinner contained in html div tags

Usage

```
wrap_loader(id, ui_element)
```

Arguments

id	string: id of loader, used with show/hide in server side
ui_element	wrapped Shiny UI element

Value

html div element wrapped around given Shiny UI element

Examples

```
wrap_loader('id_example', shiny::actionButton('id_example', 'example'))
```

Index

∗ **datasets**
    example_Colameo_MS, 7
    example_Colameo_RNA, 8

calculate_geneSetRatio, 3
colorify, 4
colorify_map, 6

display_palettes, 7

example_Colameo_MS, 7
example_Colameo_RNA, 8
example_enrichment, 8
example_genelist, 9
example_genes_overview, 9
example_genesets, 10
example_ppi_data, 10

file_extension, 11
filter_enrichment, 11

get_base_folder, 13
get_ppigraph, 13
get_string_ppi, 14
get_terms_by_keywords, 15
get_visNetwork, 16
goatea_server, 17
goatea_ui, 17

hclust, *19*
hexcolor2rgba, 18

palette_name_mapping, 18
plot_ComplexHeatmap, 19
plot_EnhancedVolcano, 20
plot_gene_effectsize_ComplexHeatmap, 21
plot_genelists_overlap_upsetjs, 22
plot_splitdot, 23
plot_termtree, 24
process_string_input, 25

read_validate_genelist, 25
rename_gene_overview, 26
run_genelists_overlap, 27
run_geneset_enrichment, 28

scale_values_between, 29
set_significant_N_genes, 30

test_genesets, *28*

wrap_hovertip, 31
wrap_loader, 31