

Package: plaid (via r-universe)

October 11, 2026

Title PLAID ultrafast gene set enrichment scoring

Version 1.1.1

Description PLAID (Pathway Level Average Intensity Detection) is an ultra-fast method to compute single-sample enrichment scores for gene expression or proteomics data. For each sample, plaid computes the gene set score as the average intensity of the genes/proteins in the gene set. The output is a gene set score matrix suitable for further analyses.

License GPL-3

URL <https://github.com/bigomics/plaid>,
<https://bigomics.github.io/plaid/>

BugReports <https://github.com/bigomics/plaid/issues>

Encoding UTF-8

Roxygen list(markdown = TRUE)

Suggests BiocStyle, knitr, rmarkdown, sparseMatrixStats, testthat (>= 3.0.0)

Config/testthat/edition 3

biocViews GeneSetEnrichment, GeneExpression, Proteomics

Depends R (>= 4.3.3)

Imports Matrix, MatrixGenerics, matrixStats, methods, collapse,
qlcMatrix, GSVA, fgsea, SummarizedExperiment, BiocSet, stats,
utils

VignetteBuilder knitr

Config/roxygen2/version 8.0.0

Config/pak/sysreqs libmagick++-dev gsfonts libicu-dev libpng-dev libxml2-dev libssl-dev zlib1g-dev

Repository <https://bioc.r-universe.dev>

Date/Publication 2026-08-11 13:13:03 UTC

RemoteUrl <https://github.com/bioc/plaid>

RemoteRef HEAD

RemoteSha be21d750376af7a1574bbe8896e5f4fbf93f646f

Contents

chunked_crossprod	2
colranks	3
cor_sparse_matrix	4
dualGSEA	4
fc_ttest	6
fc_ztest	7
gmt2mat	7
gset.rankcor	8
gset_averageCLR	10
gset_ttest	10
mat.rowsds	11
mat2gmt	11
matrix_metap	12
matrix_onesample_ttest	12
normalize_medians	13
plaid	14
read.gmt	16
replaid.auccell	17
replaid.gsva	18
replaid.scse	19
replaid.sing	21
replaid.ssgsea	22
replaid.ucell	24
sparse_colranks	25
write.gmt	26
Index	27

chunked_crossprod	<i>Chunked computation of cross product</i>
-------------------	---

Description

Compute crossprod (t(x) %*% y) for very large y by computing in chunks.

Usage

chunked_crossprod(x, y, chunk = NULL)

Arguments

- | | |
|-------|---|
| x | Matrix First matrix for multiplication. Can be sparse. |
| y | Matrix Second matrix for multiplication. Can be sparse. |
| chunk | Integer Chunk size (max number of columns) for computation. |

Value

Matrix. Result of matrix cross product.

colranks	<i>Compute columnwise ranks of matrix</i>
----------	---

Description

Computes columnwise rank of matrix. Can be sparse. Tries to call optimized functions from matrixStats.

Usage

```
colranks(
  X,
  sparse = NULL,
  signed = FALSE,
  keep.zero = FALSE,
  ties.method = "average"
)
```

Arguments

X	Input matrix
sparse	Logical indicating to use sparse methods
signed	Logical indicating using signed ranks
keep.zero	Logical indicating whether to keep zero as ranked zero
ties.method	Character Choice of ties.method

Value

Matrix of columnwise ranks with same dimensions as input.

Examples

```
# Create example matrix
set.seed(123)
X <- matrix(rnorm(100), nrow = 10, ncol = 10)
rownames(X) <- paste0("Gene", 1:10)
colnames(X) <- paste0("Sample", 1:10)

# Compute column ranks
ranks <- colranks(X)
print(ranks[1:5, 1:5])

# Compute signed ranks
signed_ranks <- colranks(X, signed = TRUE)
print(signed_ranks[1:5, 1:5])
```

cor_sparse_matrix	<i>Calculate sparse correlation matrix handling missing values</i>
-------------------	--

Description

Calculate sparse correlation matrix handling missing values

Usage

```
cor_sparse_matrix(G, mat)
```

Arguments

G	Sparse matrix containing gene sets
mat	Matrix of values

Details

If mat has no missing values, calculates correlation directly using corSparse. Otherwise computes column-wise correlations only using non-missing values.

Value

Correlation matrix between G and mat

dualGSEA	<i>Reimplementation of dualGSEA (Bull et al., 2024) but defaults with replaid backend. For the preranked test we still use fgsea. Should be much faster than original using fgsea + GSVA::ssGSEA.</i>
----------	---

Description

Reimplementation of dualGSEA (Bull et al., 2024) but defaults with replaid backend. For the preranked test we still use fgsea. Should be much faster than original using fgsea + GSVA::ssGSEA.

Usage

```
dualGSEA(
  X,
  y,
  G,
  gmt = NULL,
  gsetX = NULL,
  fc.method = c("fgsea", "rankcor", "ztest", "ttest", "cor")[2],
  ss.method = c("plaid", "replaid.ssgsea", "replaid.gsva", "ssgsea", "gsva")[1],
```

```

    metap.method = c("stouffer", "fisher", "maxp")[1],
    pv1 = NULL,
    pv2 = NULL,
    sort.by = "p.dual"
)

```

Arguments

<code>X</code>	Expression matrix with genes on rows and samples on columns
<code>y</code>	Binary vector (0/1) indicating group membership
<code>G</code>	Sparse matrix of gene sets. Non-zero entry indicates gene/feature is part of gene sets. Features on rows, gene sets on columns.
<code>gmt</code>	List of gene sets in GMT format
<code>gsetX</code>	Optional pre-computed matrix of gene set enrichment scores with gene sets on rows and samples on columns. If NULL (default), scores will be computed using the method specified by <code>ss.method</code> . Providing pre-computed scores improves efficiency when running multiple analyses.
<code>fc.method</code>	Method for fold change testing ("fgsea", "ztest", "ttest", "rankcor", "cor")
<code>ss.method</code>	Method for single-sample enrichment ("plaid", "replaid.ssgsea", "replaid.gsva", "ssgsea", "gsva")
<code>metap.method</code>	Method for combining p-values ("stouffer", "fisher" or "maxp"). Default "stouffer".
<code>pv1</code>	Pre-computed p-values from fold change test. If NULL, will be computed based on <code>fc.test</code> .
<code>pv2</code>	Pre-computed p-values from single sample test. If NULL, will be computed using <code>gset_ttest</code> .
<code>sort.by</code>	Column name to sort results by ("p.dual", "gsetFC", "p.fc", "p.ss"). Default "p.dual".

Value

Data frame with columns: `gsetFC` (gene set fold change), `size` (gene set size), `p.fc` (p-value from fold change test), `p.ss` (p-value from single sample test), `p.dual` (combined p-value), and `q.dual` (FDR-adjusted combined p-value).

Examples

```

# Create example expression matrix
set.seed(123)
X <- matrix(rnorm(1000), nrow = 100, ncol = 20)
rownames(X) <- paste0("GENE", 1:100)
colnames(X) <- paste0("Sample", 1:20)

# Create binary group vector
y <- rep(c(0, 1), each = 10)

# Create example gene sets

```

```
gmt <- list(
  "Pathway1" = paste0("GENE", 1:20),
  "Pathway2" = paste0("GENE", 15:35),
  "Pathway3" = paste0("GENE", 30:50)
)

# Perform dualGSEA with correlation test (fast method)
results_cor <- dualGSEA(X, y, G = NULL, gmt = gmt, fc.method = "cor", ss.method = "replaid.gsva")
print(head(results_cor))

# Perform dualGSEA with fgsea (requires fgsea package)
if (requireNamespace("fgsea", quietly = TRUE)) {
  results <- dualGSEA(X, y, G = NULL, gmt = gmt, fc.method = "fgsea", ss.method = "replaid.ssgsea")
  print(head(results))
}
```

fc_ttest

T-test statistical testing of differential enrichment

Description

This function performs statistical testing for differential enrichment using plaid

Usage

```
fc_ttest(fc, G, sort.by = "pvalue")
```

Arguments

fc	Vector of logFC values
G	Sparse matrix of gene sets. Non-zero entry indicates gene/feature is part of gene sets. Features on rows, gene sets on columns.
sort.by	Column name to sort results by ("pvalue", "gsetFC", or "none")

Value

Data frame with columns: gsetFC (gene set fold change), pvalue (p-value from one-sample t-test), and qvalue (FDR-adjusted p-value).

fc_ztest	<i>Z-test statistical testing of differential enrichment</i>
----------	--

Description

This function performs statistical testing for differential enrichment using plaid

Usage

```
fc_ztest(fc, G, zmat = FALSE, alpha = 0.5)
```

Arguments

fc	Vector of logFC values
G	Sparse matrix of gene sets. Non-zero entry indicates gene/feature is part of gene sets. Features on rows, gene sets on columns.
zmat	Logical indicating to return z-matrix
alpha	Scalar weight for SD estimation. Default 0.5.

Value

List with element: `z_statistic` (z-statistic from one-sample z-test), `p_value` (p-value from one-sample z-test), and `zmat` (z-matrix).

gmt2mat	<i>Convert GMT to Binary Matrix</i>
---------	-------------------------------------

Description

Convert a GMT file (Gene Matrix Transposed) to a binary matrix, where rows represent genes and columns represent gene sets. The binary matrix indicates presence or absence of genes in a gene set.

Usage

```
gmt2mat(  
  gmt,  
  max.genes = -1,  
  ntop = -1,  
  sparse = TRUE,  
  bg = NULL,  
  use.multicore = FALSE  
)
```

Arguments

gmt	List representing the GMT file: each element is a character vector representing a gene set.
max.genes	Max number of genes to include in the binary matrix. Default = -1 to include all genes.
ntop	Number of top genes to consider for each gene set. Default = -1 to include all genes.
sparse	Logical: create a sparse matrix. Default TRUE. If FALSE creates a dense matrix.
bg	Character vector of background gene set. Default NULL to consider all unique genes.
use.multicore	Logical: use parallel processing ('parallel' R package). Default FALSE. Deprecated.

Value

A binary matrix representing the presence or absence of genes in each gene set. Rows correspond to genes, and columns correspond to gene sets.

Examples

```
# Create example GMT data
gmt <- list(
  "Pathway1" = c("GENE1", "GENE2", "GENE3"),
  "Pathway2" = c("GENE2", "GENE4", "GENE5"),
  "Pathway3" = c("GENE1", "GENE5", "GENE6")
)

# Convert to binary matrix
mat <- gmt2mat(gmt)
print(mat)

# Create dense matrix instead of sparse
mat_dense <- gmt2mat(gmt, sparse = FALSE)
print(mat_dense)
```

gset.rankcor

Calculate gene set rank correlation

Description

Compute rank correlation between a gene rank vector/matrix and gene sets

Usage

```
gset.rankcor(rnk, gset, compute.p = FALSE, use.rank = TRUE)
```

Arguments

<code>rnk</code>	Numeric vector or matrix of gene ranks, with genes as row names
<code>gset</code>	Numeric matrix of gene sets, with genes as row/column names
<code>compute.p</code>	Logical indicating whether to compute p-values
<code>use.rank</code>	Logical indicating whether to rank transform <code>rnk</code> before correlation

Details

This function calculates sparse rank correlation between `rnk` and each column of `gset` using `qlcMatrix::corSparse()`. It handles missing values in `rnk` by computing column-wise correlations.

P-values are computed from statistical distribution

Value

Named list with components:

- `rho` - Matrix of correlation coefficients between `rnk` and `gset`
- `p.value` - Matrix of p-values for correlation (if `compute.p = TRUE`)
- `q.value` - Matrix of FDR adjusted p-values (if `compute.p = TRUE`)

Examples

```
# Create example rank vector
set.seed(123)
ranks <- rnorm(100)
names(ranks) <- paste0("GENE", 1:100)

# Create example gene sets as sparse matrix
gmt <- list(
  "Pathway1" = paste0("GENE", 1:20),
  "Pathway2" = paste0("GENE", 15:35),
  "Pathway3" = paste0("GENE", 30:50)
)
genesets <- gmt2mat(gmt)

# Calculate rank correlation
result <- gset.rankcor(ranks, genesets, compute.p = TRUE)
print(result$rho)
print(result$p.value)
```

gset_averageCLR	<i>Compute geneset expression as the average log-ration of genes in the geneset. Requires log-expression matrix X and (sparse) geneset matrix matG.</i>
-----------------	---

Description

Compute geneset expression as the average log-ration of genes in the geneset. Requires log-expression matrix X and (sparse) geneset matrix matG.

Usage

```
gset_averageCLR(X, matG, center = TRUE)
```

Arguments

X	Log-expression matrix with genes on rows and samples on columns
matG	Sparse gene set matrix with genes on rows and gene sets on columns
center	Logical indicating whether to center the results

Value

Matrix of gene set expression scores with gene sets on rows and samples on columns.

gset_ttest	<i>Perform t-test on gene set scores</i>
------------	--

Description

Perform t-test on gene set scores

Usage

```
gset_ttest(gsetX, y)
```

Arguments

gsetX	Matrix of gene set scores with gene sets on rows and samples on columns
y	Binary vector (0/1) indicating group membership

Value

Data frame with columns: diff (difference in means), statistic (t-statistic), pvalue (p-value), and other t-test results.

mat.rowsds	<i>Calculate row standard deviations for matrix</i>
------------	---

Description

Calculate row standard deviations for matrix

Usage

```
mat.rowsds(X)
```

Arguments

X	Input matrix (can be sparse or dense)
---	---------------------------------------

Value

Vector of row standard deviations.

mat2gmt	<i>Convert Binary Matrix to GMT</i>
---------	-------------------------------------

Description

Convert binary matrix to a GMT (Gene Matrix Transposed) list. The binary matrix indicates presence or absence of genes in each gene set. Rows represent genes and columns represent gene sets.

Usage

```
mat2gmt(mat)
```

Arguments

mat	Matrix with non-zero entries representing genes in each gene set. Rows represent genes and columns represent gene sets.
-----	---

Value

A list of vector representing each gene set. Each list element correspond to a gene set and is a vector of genes

Examples

```
# Create example binary matrix
mat <- matrix(0, nrow = 6, ncol = 3)
rownames(mat) <- paste0("GENE", 1:6)
colnames(mat) <- paste0("Pathway", 1:3)
mat[1:3, 1] <- 1 # Pathway1: GENE1, GENE2, GENE3
mat[c(2,4,5), 2] <- 1 # Pathway2: GENE2, GENE4, GENE5
mat[c(1,5,6), 3] <- 1 # Pathway3: GENE1, GENE5, GENE6

# Convert to GMT list
gmt <- mat2gmt(mat)
print(gmt)
```

matrix_metap	<i>Matrix version for combining p-values using fisher or stouffer method. Much faster than doing metap::sumlog() and metap::sumz()</i>
--------------	--

Description

Matrix version for combining p-values using fisher or stouffer method. Much faster than doing metap::sumlog() and metap::sumz()

Usage

```
matrix_metap(plist, method = "stouffer")
```

Arguments

- plist List of p-value vectors or matrix of p-values
- method Method for combining p-values ("fisher"/"sumlog" or "stouffer"/"sumz")

Value

Vector of combined p-values.

matrix_onesample_ttest	<i>Perform one-sample t-test on matrix with gene sets</i>
------------------------	---

Description

Perform one-sample t-test on matrix with gene sets

Usage

```
matrix_onesample_ttest(Fm, G)
```

Arguments

Fm	Vector of feature values (e.g., fold changes)
G	Sparse matrix of gene sets with genes on rows and gene sets on columns

Value

List containing mean, t-statistic, and p-value matrices.

normalize_medians	<i>Normalize column medians of matrix</i>
-------------------	---

Description

This function normalizes the column medians of matrix x. It calls optimized functions from the matrixStats package.

Usage

```
normalize_medians(x, ignore.zero = NULL)
```

Arguments

x	Input matrix
ignore.zero	Logical indicating whether to ignore zeros to exclude for median calculation

Value

Matrix with normalized column medians.

Examples

```
# Create example matrix
set.seed(123)
x <- matrix(rnorm(100), nrow = 10, ncol = 10)
x[1:3, 1:3] <- 0 # Add some zeros

# Normalize medians
x_norm <- normalize_medians(x)
head(x_norm)
```

plaid

Compute PLAID single-sample enrichment score

Description

Compute single-sample geneset expression as the average log-expression of genes in the geneset. Requires log-expression matrix X and (sparse) geneset matrix matG. If you have gene sets as a gmt list, please convert it first using the function `gmt2mat()`.

Usage

```
plaid(
  X,
  matG,
  stats = c("mean", "sum"),
  chunk = NULL,
  normalize = TRUE,
  nsmooth = 3,
  assay = "logcounts",
  min.genes = 5,
  max.genes = 500
)
```

Arguments

X	Log-transformed expr. matrix. Genes on rows, samples on columns. Also accepts SummarizedExperiment or SingleCellExperiment objects.
matG	Gene sets sparse matrix. Genes on rows, gene sets on columns. Also accepts BiocSet objects or GMT lists (named list of gene vectors).
stats	Score computation stats: mean or sum of intensity. Default 'mean'.
chunk	Logical: use chunks for large matrices. Default 'NULL' for autodetect.
normalize	Logical: median normalize results or not. Default 'TRUE'.
nsmooth	Smoothing parameter for more stable average when stats="mean". Default 3.
assay	Character: assay name to extract from SummarizedExperiment/SingleCellExperiment. Default "logcounts".
min.genes	Integer: minimum genes per gene set (for BiocSet/GMT input). Default 5.
max.genes	Integer: maximum genes per gene set (for BiocSet/GMT input). Default 500.

Details

PLAID needs the gene sets as sparse matrix. If you have your collection of gene sets as a list, we need first to convert the gmt list to matrix format.

We recommend to run PLAID on the log transformed expression matrix, not on the counts, as the average in the logarithmic space is more robust and is in concordance to calculating the geometric mean.

It is not necessary to normalize your expression matrix before running PLAID because PLAID performs median normalization of the enrichment scores afterwards.

It is recommended to use sparse matrix as PLAID relies on sparse matrix computations. But, PLAID is also fast for dense matrices.

PLAID can also be run on the ranked matrix. This corresponds to the singscore (Fouratan et al., 2018). PLAID can also be run on the (non-logarithmic) counts which can be used to calculate the scSE score (Pont et al., 2019).

PLAID is fast and memory efficient because it uses efficient sparse matrix computation. When input matrix is very large, PLAID performs 'chunked' computation by splitting the matrix in chunks.

Although *X* and *matG* are generally sparse, the result matrix *gsetX* generally is dense and can thus be very large. Example: computing gene set scores for 10K gene sets on 1M cells will create a 10K x 1M dense matrix which requires ~75GB memory.

PLAID now automatically detects and handles Bioconductor objects. If *X* is a *SummarizedExperiment* or *SingleCellExperiment*, it will extract the appropriate assay. If *matG* is a *BiocSet* object or GMT list, it will be converted to sparse matrix format automatically.

Value

Matrix of single-sample enrichment scores. Gene sets on rows, samples on columns.

Examples

```
library(plaid)

# Create example expression matrix
set.seed(123)
X <- matrix(rnorm(1000), nrow = 100, ncol = 10)
rownames(X) <- paste0("GENE", 1:100)
colnames(X) <- paste0("Sample", 1:10)

# Create example gene sets
gmt <- list(
  "Pathway1" = paste0("GENE", 1:20),
  "Pathway2" = paste0("GENE", 15:35),
  "Pathway3" = paste0("GENE", 30:50)
)
matG <- gmt2mat(gmt)

# Compute PLAID scores
gsetX <- plaid(X, matG)
print(dim(gsetX))
print(gsetX[1:3, 1:5])

# Use sum statistics instead of mean
gsetX_sum <- plaid(X, matG, stats = "sum")

# Using real data (if available in package)
extdata_path <- system.file("extdata", "pbmc3k-50cells.rda", package = "plaid")
if (file.exists(extdata_path)) {
```

```

load(extdata_path)
hallmarks <- system.file("extdata", "hallmarks.gmt", package = "plaid")
gmt <- read.gmt(hallmarks)
matG <- gmt2mat(gmt)
gsetX <- plaid(X, matG)
}

```

read.gmt

Read GMT File

Description

Read data from a GMT file (Gene Matrix Transposed). The GMT format is commonly used to store gene sets or gene annotations.

Usage

```
read.gmt(gmt.file, dir = NULL, add.source = FALSE, nrows = -1)
```

Arguments

gmt.file	Path to GMT file.
dir	(Optional) The directory where the GMT file is located.
add.source	(optional) Include the source information in the gene sets' names.
nrows	(optional) Number of rows to read from the GMT file.

Value

A list of gene sets: each gene set is represented as a character vector of gene names.

Examples

```

# Read GMT file (requires file to exist)
gmt_file <- system.file("extdata", "hallmarks.gmt", package = "plaid")
if (file.exists(gmt_file)) {
  gmt <- read.gmt(gmt_file)
  print(names(gmt))
  print(head(gmt[[1]]))

  # Read with source information
  gmt_with_source <- read.gmt(gmt_file, add.source = TRUE)
  print(head(names(gmt_with_source)))
}

```

replaid.auccell	<i>Fast calculation of AUCcell</i>
-----------------	------------------------------------

Description

Calculates single-sample enrichment AUCcell (Aibar et al., 2017) using plaid back-end. The computation is 10-100x faster than the original code.

Usage

```
replaid.auccell(  
  X,  
  matG,  
  aucMaxRank = NULL,  
  assay = "logcounts",  
  min.genes = 5,  
  max.genes = 500  
)
```

Arguments

X	Gene or protein expression matrix. Generally log transformed. See details. Genes on rows, samples on columns. Also accepts SummarizedExperiment or SingleCellExperiment objects.
matG	Gene sets sparse matrix. Genes on rows, gene sets on columns. Also accepts BiocSet objects or GMT lists.
aucMaxRank	Rank threshold (see AUCcell paper). Default aucMaxRank = 0.05*nrow(X).
assay	Character: assay name for Bioconductor objects. Default "logcounts".
min.genes	Integer: minimum genes per gene set. Default 5.
max.genes	Integer: maximum genes per gene set. Default 500.

Details

Computing the AUCcell score requires to compute the ranks of the expression matrix and approximating the AUC of a gene set. We have wrapped this in a single convenience function.

We have extensively compared the results of replaid.auccell and from the original AUCcell R package and we showed good concordance of results in the score, logFC and p-values.

Value

Matrix of single-sample AUCcell enrichment scores. Gene sets on rows, samples on columns.

Examples

```
# Create example expression matrix
set.seed(123)
X <- matrix(rnorm(500), nrow = 50, ncol = 10)
rownames(X) <- paste0("GENE", 1:50)
colnames(X) <- paste0("Sample", 1:10)

# Create example gene sets
gmt <- list(
  "Pathway1" = paste0("GENE", 1:15),
  "Pathway2" = paste0("GENE", 10:25)
)
matG <- gmt2mat(gmt)

# Compute AUCell scores
scores <- replaid.auccell(X, matG)
print(scores[1:2, 1:5])
```

replaid.gsva

Fast approximation of GSVa

Description

Calculates single-sample enrichment GSVa (Hänzelmann et al., 2013) using plaid back-end. The computation is 10-100x faster than the original code.

Usage

```
replaid.gsva(
  X,
  matG,
  tau = 0,
  rowtf = c("z", "ecdf")[1],
  assay = "logcounts",
  min.genes = 5,
  max.genes = 500
)
```

Arguments

X	Gene or protein expression matrix. Generally log transformed. See details. Genes on rows, samples on columns. Also accepts SummarizedExperiment or SingleCellExperiment objects.
matG	Gene sets sparse matrix. Genes on rows, gene sets on columns. Also accepts BiocSet objects or GMT lists.
tau	Rank weight parameter (see GSVa publication). Default tau=0.

rowtf	Row transformation method ("z" or "ecdf"). Default "z".
assay	Character: assay name for Bioconductor objects. Default "logcounts".
min.genes	Integer: minimum genes per gene set. Default 5.
max.genes	Integer: maximum genes per gene set. Default 500.

Details

Computing the GSVA score requires to compute the CDF of the expression matrix, ranking and scoring the genesets. We have wrapped this in a single convenience function.

We have extensively compared the results of `replaid.gsva` and from the original GSVA R package and we showed good concordance of results in the score, logFC and p-values.

In the original formulation, GSVA uses an empirical CDF to transform expression of each feature to a (0;1) relative expression value. For efficiency reasons, this is here approximated by a z-transform (center+scale) of each row.

Value

Matrix of single-sample GSVA enrichment scores. Gene sets on rows, samples on columns.

Examples

```
# Create example expression matrix
set.seed(123)
X <- matrix(rnorm(500), nrow = 50, ncol = 10)
rownames(X) <- paste0("GENE", 1:50)
colnames(X) <- paste0("Sample", 1:10)

# Create example gene sets
gmt <- list(
  "Pathway1" = paste0("GENE", 1:15),
  "Pathway2" = paste0("GENE", 10:25)
)
matG <- gmt2mat(gmt)

# Compute GSVA scores
scores <- replaid.gsva(X, matG)
print(scores[1:2, 1:5])
```

replaid.scse

Fast calculation of scSE score

Description

Calculates Single-Cell Signature Explorer (Pont et al., 2019) scores using `plaid` back-end. The computation is 10-100x faster than the original code.

Usage

```
replaid.scse(
  X,
  matG,
  removeLog2 = NULL,
  scoreMean = FALSE,
  assay = "logcounts",
  min.genes = 5,
  max.genes = 500
)
```

Arguments

<code>X</code>	Gene or protein expression matrix. Generally log transformed. See details. Genes on rows, samples on columns. Also accepts SummarizedExperiment or SingleCellExperiment objects.
<code>matG</code>	Gene sets sparse matrix. Genes on rows, gene sets on columns. Also accepts BiocSet objects or GMT lists.
<code>removeLog2</code>	Logical for whether to remove the Log2, i.e. will apply power transform (base2) on input (default TRUE).
<code>scoreMean</code>	Logical for whether computing sum or mean as score (default FALSE).
<code>assay</code>	Character: assay name for Bioconductor objects. Default "logcounts".
<code>min.genes</code>	Integer: minimum genes per gene set. Default 5.
<code>max.genes</code>	Integer: maximum genes per gene set. Default 500.

Details

Computing the scSE requires running plaid on the linear (not logarithmic) score and perform additional normalization by the total UMI per sample. We have wrapped this in a single convenience function:

To replicate the original "sum-of-UMI" scSE score, set `removeLog2=TRUE` and `scoreMean=FALSE`. scSE and plaid scores become more similar for `removeLog2=FALSE` and `scoreMean=TRUE`.

We have extensively compared the results from `replaid.scse` and from the original scSE (implemented in GO lang) and we showed almost identical results in the score, logFC and p-values.

Value

Matrix of single-sample scSE enrichment scores. Gene sets on rows, samples on columns.

Examples

```
# Create example expression matrix (log-transformed)
set.seed(123)
X <- log2(matrix(rpois(500, lambda = 10) + 1, nrow = 50, ncol = 10))
rownames(X) <- paste0("GENE", 1:50)
colnames(X) <- paste0("Sample", 1:10)
```

```
# Create example gene sets
gmt <- list(
  "Pathway1" = paste0("GENE", 1:15),
  "Pathway2" = paste0("GENE", 10:25)
)
matG <- gmt2mat(gmt)

# Compute scSE scores (original method)
scores <- replaid.scse(X, matG, removeLog2 = TRUE, scoreMean = FALSE)
print(scores[1:2, 1:5])

# Compute scSE scores (mean method)
scores_mean <- replaid.scse(X, matG, removeLog2 = TRUE, scoreMean = TRUE)
print(scores_mean[1:2, 1:5])
```

replaid.sing

Fast calculation of singscore

Description

Calculates single-sample enrichment singscore (Fouratan et al., 2018) using plaid back-end. The computation is 10-100x faster than the original code.

Usage

```
replaid.sing(X, matG, assay = "logcounts", min.genes = 5, max.genes = 500)
```

Arguments

X	Gene or protein expression matrix. Generally log transformed. See details. Genes on rows, samples on columns. Also accepts SummarizedExperiment or SingleCellExperiment objects.
matG	Gene sets sparse matrix. Genes on rows, gene sets on columns. Also accepts BiocSet objects or GMT lists.
assay	Character: assay name for Bioconductor objects. Default "logcounts".
min.genes	Integer: minimum genes per gene set. Default 5.
max.genes	Integer: maximum genes per gene set. Default 500.

Details

Computing the singscore requires to compute the ranks of the expression matrix. We have wrapped this in a single convenience function.

We have extensively compared the results of replaid.sing and from the original singscore R package and we showed identical result in the score, logFC and p-values.

Value

Matrix of single-sample singscore enrichment scores. Gene sets on rows, samples on columns.

Examples

```
# Create example expression matrix
set.seed(123)
X <- matrix(rnorm(500), nrow = 50, ncol = 10)
rownames(X) <- paste0("GENE", 1:50)
colnames(X) <- paste0("Sample", 1:10)

# Create example gene sets
gmt <- list(
  "Pathway1" = paste0("GENE", 1:15),
  "Pathway2" = paste0("GENE", 10:25)
)
matG <- gmt2mat(gmt)

# Compute singscore
scores <- replaid.sing(X, matG)
print(scores[1:2, 1:5])
```

replaid.ssgsea

Fast calculation of ssGSEA

Description

Calculates single-sample enrichment singscore (Barbie et al., 2009; Hänzelmann et al., 2013) using plaid back-end. The computation is 10-100x faster than the original code.

Usage

```
replaid.ssgsea(
  X,
  matG,
  alpha = 0,
  assay = "logcounts",
  min.genes = 5,
  max.genes = 500
)
```

Arguments

X Gene or protein expression matrix. Generally log transformed. See details. Genes on rows, samples on columns. Also accepts SummarizedExperiment or SingleCellExperiment objects.

matG	Gene sets sparse matrix. Genes on rows, gene sets on columns. Also accepts BiocSet objects or GMT lists.
alpha	Weighting factor for exponential weighting of ranks
assay	Character: assay name for Bioconductor objects. Default "logcounts".
min.genes	Integer: minimum genes per gene set. Default 5.
max.genes	Integer: maximum genes per gene set. Default 500.

Details

Computing ssGSEA score requires to compute the ranks of the expression matrix and weighting of the ranks. We have wrapped this in a single convenience function.

We have extensively compared the results of `replaid.ssgsea` and from the original GSVA R package and we showed highly similar results in the score, logFC and p-values. For $\alpha=0$ we obtain exact results, for $\alpha>0$ the results are highly similar but not exactly the same.

Value

Matrix of single-sample ssGSEA enrichment scores. Gene sets on rows, samples on columns.

Examples

```
# Create example expression matrix
set.seed(123)
X <- matrix(rnorm(500), nrow = 50, ncol = 10)
rownames(X) <- paste0("GENE", 1:50)
colnames(X) <- paste0("Sample", 1:10)

# Create example gene sets
gmt <- list(
  "Pathway1" = paste0("GENE", 1:15),
  "Pathway2" = paste0("GENE", 10:25)
)
matG <- gmt2mat(gmt)

# Compute ssGSEA scores (alpha = 0)
scores <- replaid.ssgsea(X, matG, alpha = 0)
print(scores[1:2, 1:5])

# Compute ssGSEA scores with weighting (alpha = 0.25)
scores_weighted <- replaid.ssgsea(X, matG, alpha = 0.25)
print(scores_weighted[1:2, 1:5])
```

replaid.ucell

*Fast calculation of UCell***Description**

Calculates single-sample enrichment UCell (Andreatta et al., 2021) using plaid back-end. The computation is 10-100x faster than the original code.

Usage

```
replaid.ucell(
  X,
  matG,
  rmax = 1500,
  assay = "logcounts",
  min.genes = 5,
  max.genes = 500
)
```

Arguments

X	Gene or protein expression matrix. Generally log transformed. See details. Genes on rows, samples on columns. Also accepts SummarizedExperiment or SingleCellExperiment objects.
matG	Gene sets sparse matrix. Genes on rows, gene sets on columns. Also accepts BiocSet objects or GMT lists.
rmax	Rank threshold (see Ucell paper). Default rmax = 1500.
assay	Character: assay name for Bioconductor objects. Default "logcounts".
min.genes	Integer: minimum genes per gene set. Default 5.
max.genes	Integer: maximum genes per gene set. Default 500.

Details

Computing ssGSEA score requires to compute the ranks of the expression matrix and truncation of the ranks. We have wrapped this in a single convenience function.

We have extensively compared the results of replaid.ucell and from the original UCell R package and we showed near exact results in the score, logFC and p-values.

Value

Matrix of single-sample UCell enrichment scores. Gene sets on rows, samples on columns.

Examples

```
# Create example expression matrix
set.seed(123)
X <- matrix(rnorm(500), nrow = 50, ncol = 10)
rownames(X) <- paste0("GENE", 1:50)
colnames(X) <- paste0("Sample", 1:10)

# Create example gene sets
gmt <- list(
  "Pathway1" = paste0("GENE", 1:15),
  "Pathway2" = paste0("GENE", 10:25)
)
matG <- gmt2mat(gmt)

# Compute UCell scores (default rmax = 1500)
scores <- replaid.ucell(X, matG)
print(scores[1:2, 1:5])

# Compute UCell scores with custom rmax
scores_custom <- replaid.ucell(X, matG, rmax = 1000)
print(scores_custom[1:2, 1:5])
```

sparse_colranks	<i>Compute column ranks for sparse matrix. Internally used by colranks()</i>
-----------------	--

Description

Compute column ranks for sparse matrix. Internally used by colranks()

Usage

```
sparse_colranks(X, signed = FALSE, ties.method = "average")
```

Arguments

X	Input matrix
signed	Logical: use or not signed ranks
ties.method	Character Choice of ties.method

Value

Sparse matrix of columnwise ranks with same dimensions as input.

write.gmt

*Write GMT File***Description**

Write gene sets to GMT file (Gene Matrix Transposed). The GMT format is commonly used to store gene sets or gene annotations.

Usage

```
write.gmt(gmt, file, source = NA)
```

Arguments

gmt	A list of gene sets in GMT format: each gene set is represented as a vector of gene names.
file	The file path to write the GMT file.
source	A character vector specifying the source of each gene set. If not provided, the names of the gene sets are used as the source.

Value

Does not return anything.

Examples

```
# Create example GMT data
gmt <- list(
  "Pathway1" = c("GENE1", "GENE2", "GENE3"),
  "Pathway2" = c("GENE2", "GENE4", "GENE5"),
  "Pathway3" = c("GENE1", "GENE5", "GENE6")
)

# Write to GMT file (creates file in temp directory)
temp_file <- tempfile(fileext = ".gmt")
write.gmt(gmt, temp_file)

# Write with custom source information
temp_file2 <- tempfile(fileext = ".gmt")
write.gmt(gmt, temp_file2, source = c("DB1", "DB2", "DB3"))

# Clean up
unlink(c(temp_file, temp_file2))
```

Index

`chunked_crossprod`, [2](#)
`colranks`, [3](#)
`cor_sparse_matrix`, [4](#)

`dualGSEA`, [4](#)

`fc_ttest`, [6](#)
`fc_ztest`, [7](#)

`gmt2mat`, [7](#)
`gset.rankcor`, [8](#)
`gset_averageCLR`, [10](#)
`gset_ttest`, [10](#)

`mat.rowsds`, [11](#)
`mat2gmt`, [11](#)
`matrix_metap`, [12](#)
`matrix_onesample_ttest`, [12](#)

`normalize_medians`, [13](#)

`plaid`, [14](#)

`read.gmt`, [16](#)
`replaid.auccell`, [17](#)
`replaid.gsva`, [18](#)
`replaid.scse`, [19](#)
`replaid.sing`, [21](#)
`replaid.ssgsea`, [22](#)
`replaid.ucell`, [24](#)

`sparse_colranks`, [25](#)

`write.gmt`, [26](#)