

Package: scDotPlot (via r-universe)

September 16, 2026

Title Cluster a Single-cell RNA-seq Dot Plot

Version 1.7.0

Description Dot plots of single-cell RNA-seq data allow for an examination of the relationships between cell groupings (e.g. clusters) and marker gene expression. The scDotPlot package offers a unified approach to perform a hierarchical clustering analysis and add annotations to the columns and/or rows of a scRNA-seq dot plot. It works with SingleCellExperiment and Seurat objects as well as data frames.

License Artistic-2.0

URL <https://github.com/ben-laufer/scDotPlot>

BugReports <https://github.com/ben-laufer/scDotPlot/issues>

biocViews Software, Visualization, DifferentialExpression, GeneExpression, Transcription, RNASeq, SingleCell, Sequencing, Clustering

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Depends R (>= 4.4.0)

Imports aplot, BiocGenerics, cli, dplyr, ggplot2, ggsci, ggtree, grDevices, magrittr, purrr, rlang, scales, scater, Seurat, SingleCellExperiment, stats, stringr, tibble, tidyr

Suggests AnnotationDbi, BiocStyle, knitr, rmarkdown, scan, scRNAseq, scuttle, SeuratObject, testthat, vdiff

VignetteBuilder knitr

Config/testthat/edition 3

LazyData false

Config/pak/sysreqs libcairo2-dev cmake libfontconfig1-dev libfreetype6-dev libglpk-dev make libicu-dev libpng-dev libuv1-dev libxml2-dev libssl-dev python3 zlib1g-dev

Repository <https://bioc.r-universe.dev>

Date/Publication 2026-04-28 13:03:18 UTC
RemoteUrl https://github.com/bioc/scDotPlot
RemoteRef HEAD
RemoteSha 52c611fd1881cc606056adc435edbe804b934dec

Contents

scDotPlot	2
Index	6

scDotPlot	<i>scDotPlot</i>
-----------	------------------

Description

Create dot plot of gene expression profiles that can be annotated with hierarchical clustering from [ggtree](#) using [aplot](#)

Usage

```
## S3 method for class 'SingleCellExperiment'
scDotPlot(
  object,
  features = features,
  group = NULL,
  block = NULL,
  swap_rownames = NULL,
  scale = FALSE,
  cluster = TRUE,
  clusterRows = cluster,
  clusterColumns = cluster,
  AverageThreshold = ifelse(scale == FALSE, 0, -Inf),
  NumDetectedThreshold = 0.01,
  groupAnno = FALSE,
  featureAnno = FALSE,
  treeWidth = 0.1,
  treeHeight = 0.1,
  annoWidth = 0.05,
  annoHeight = 0.02,
  annoColors = NULL,
  dotColors = NULL,
  groupLegends = TRUE,
  featureLegends = TRUE,
  fontSize = 11,
  fontFamily = "",
```

```
        flipPlot = FALSE,
        ...
    )

## S3 method for class 'Seurat'
scDotPlot(
  object,
  features = features,
  group = NULL,
  block = NULL,
  swap_rownames = NULL,
  scale = FALSE,
  cluster = TRUE,
  clusterRows = cluster,
  clusterColumns = cluster,
  AverageThreshold = ifelse(scale == FALSE, 0, -Inf),
  NumDetectedThreshold = 0.01,
  groupAnno = FALSE,
  featureAnno = FALSE,
  treeWidth = 0.1,
  treeHeight = 0.1,
  annoWidth = 0.05,
  annoHeight = 0.02,
  annoColors = NULL,
  dotColors = NULL,
  groupLegends = TRUE,
  featureLegends = TRUE,
  fontSize = 11,
  fontFamily = "",
  flipPlot = FALSE,
  ...
)

## Default S3 method:
scDotPlot(
  object,
  features = NULL,
  group = NULL,
  block = NULL,
  swap_rownames = NULL,
  scale = FALSE,
  cluster = TRUE,
  clusterRows = cluster,
  clusterColumns = cluster,
  AverageThreshold = ifelse(scale == FALSE, 0, -Inf),
  NumDetectedThreshold = 0.01,
  groupAnno = FALSE,
  featureAnno = FALSE,
```

```

    treeWidth = 0.1,
    treeHeight = 0.1,
    annoWidth = 0.05,
    annoHeight = 0.02,
    annoColors = NULL,
    dotColors = NULL,
    groupLegends = TRUE,
    featureLegends = TRUE,
    fontSize = 11,
    fontFamily = "",
    flipPlot = FALSE,
    ...
)

scDotPlot(object, ...)

```

Arguments

object	An object with normalized data • SingleCellExperiment • Seurat • A data.frame with the following columns: "NumDetected", "Feature", "Group", "Average"
features	Character vector with genes of interest
group	Column name from colData/metadata of the object to group cells by
block	Column name from colData of a SingleCellExperiment object to use as a blocking factor (e.g. batch or sample)
swap_rownames	Column name from rowData of a SingleCellExperiment object to match to features
scale	Logical indicating whether the data should be scaled and centered
cluster	Logical specifying whether to perform hierarchical clustering analysis on both the rows and columns
clusterRows	Logical specifying whether to perform hierarchical clustering analysis on the rows
clusterColumns	Logical specifying whether to perform hierarchical clustering analysis on the columns
AverageThreshold	Numeric specifying threshold for average expression, where values below AverageThreshold and NumDetectedThreshold are transparent
NumDetectedThreshold	Numeric specifying threshold for fraction of cells, where values below AverageThreshold and NumDetectedThreshold are transparent
groupAnno	Cell annotations that are stored as names of columns in colData of sce with annotations

featureAnno	Feature annotations that are stored as names of rows in rowData of sce with annotations
treeWidth	Numeric specifying width of the row tree relative to the dotPlot
treeHeight	Numeric specifying height of the column tree relative to the dotPlot
annoWidth	Numeric specifying the width of the row annotation relative to the dotPlot
annoHeight	Numeric specifying height of the column annotation relative to the dotPlot
annoColors	A list with a name for each annotation that contains a named vector of colors, where the name is the pairing of values to colors
dotColors	A character vector specifying the colors to be used in the gradient for the dots. If scale is set to TRUE, the first 3 colors will be used for the negative, zero, and positive values, respectively.
groupLegends	Logical indicating whether to show legends for group annotations
featureLegends	Logical indicating whether to show legends for feature annotations
fontSize	Numeric specifying the base font size in pts
fontFamily	Character specifying the base font family
flipPlot	Logical indicating whether to flip the x and y coordinates
...	Additional unused arguments

Details

The data for the dot plot is generated from different sources depending on the object:

- SingleCellExperiment: [plotDots](#)
- Seurat: [DotPlot](#)

Value

- When cluster = TRUE, a aplot object
- When cluster = FALSE, a ggplot2 object

References

<https://yulab-smu.top/pkgdocs/aplot.html#a-single-cell-example>

Examples

```
data("pbmc_small", package = "SeuratObject")
pbmc_small |>
  scDotPlot(features = Seurat::VariableFeatures(pbmc_small),
            group = "RNA_snn_res.1")
```

Index

`aplot`, [2](#)

`DotPlot`, [5](#)

`ggtree`, [2](#)

`plotDots`, [5](#)

`scDotPlot`, [2](#)

`Seurat`, [4](#)

`SingleCellExperiment`, [4](#)