

Package: shinyMethyl (via r-universe)

September 30, 2026

Title Interactive visualization for Illumina methylation arrays
Description Interactive tool for visualizing Illumina methylation array data. Both the 450k and EPIC array are supported.
Version 1.49.0
Imports Biobase, BiocGenerics, graphics, grDevices, htmltools, MatrixGenerics, methods, minfi, RColorBrewer, shiny, stats, utils
Suggests shinyMethylData, minfiData, BiocStyle, knitr, testthat
URL <https://github.com/Jfortin1/shinyMethyl>
BugReports <https://github.com/Jfortin1/shinyMethyl>
VignetteBuilder knitr
License Artistic-2.0
Encoding UTF-8
biocViews DNAMethylation, Microarray, TwoChannel, Preprocessing, QualityControl, MethylationArray
RoxygenNote 7.2.1
Config/pak/sysreqs cmake make libbz2-dev libicu-dev liblzma-dev libpng-dev libuv1-dev libxml2-dev libssl-dev libx11-dev xz-utils zlib1g-dev
Repository <https://bioc.r-universe.dev>
Date/Publication 2026-04-28 12:39:24 UTC
RemoteUrl <https://github.com/bioc/shinyMethyl>
RemoteRef HEAD
RemoteSha a5574f4fcf92a0f8430e0d493e445e64170427a5

Contents

runShinyMethyl	2
shinyMethylSet-class	3
shinySummarize-methods	5
Index	6

runShinyMethyl

Run the interactive shinyMethyl session

Description

Function to run the interactive shinyMethyl session from a shinyMethylSet object.

Usage

```
runShinyMethyl(shinyMethylSet1, shinyMethylSet2 = NULL)
```

Arguments

shinyMethylSet1

shinyMethylSet that must be extracted from an RGChannelSet object.

shinyMethylSet2

Optional shinyMethylSet that must be extracted from a GenomicRatioSet.

Value

No value returned. Instead the shinyMethyl interactive session is launched.

Author(s)

Jean-Philippe Fortin

See Also

[shinyMethylSet](#)

Examples

```
if (interactive()){  
  library(minfi)  
  library(minfiData)  
  baseDir <- system.file("extdata", package = "minfiData")  
  targets <- read.metharray.sheet(baseDir)  
  targets$Sample_Plate <- substr(targets$Slide,1,7)  
  RGSet <- read.metharray.exp(targets=targets)  
  summarized.data <- shinySummarize(RGSet)  
  runShinyMethyl(summarized.data)  
}
```

shinyMethylSet-class *shinyMethylSet* instances

Description

This class holds summarized data from Illumina methylation microarrays for interactive visualization purpose.

Usage

Constructor

```
shinyMethylSet(sampleNames = new("character"),
               phenotype = new("data.frame"),
               mQuantiles = new(vector("list",5)),
               betaQuantiles = new(vector("list",5)),
               methQuantiles = new(vector("list",5)),
               unmethQuantiles = new(vector("list",5)),
               cnQuantiles = new(vector("list",5)),
               greenControls = new(vector("list",12)),
               redControls = new(vector("list",12)),
               pca = new("list"),
               originObject = new("character"),
               array = new("character"))
```

Data extraction / Accessors

```
## S4 method for signature 'shinyMethylSet'
getMeth(object)
## S4 method for signature 'shinyMethylSet'
getUnmeth(object)
## S4 method for signature 'shinyMethylSet'
getBeta(object)
## S4 method for signature 'shinyMethylSet'
getM(object)
## S4 method for signature 'shinyMethylSet'
getCN(object)
## S4 method for signature 'shinyMethylSet'
pData(object)
## S4 method for signature 'shinyMethylSet'
sampleNames(object)
```

Arguments

object A shinyMethylSet.

sampleNames	A character vector
phenotype	A data.frame object.
methQuantiles	A list of 5 matrices containing several quantiles for the methylation values (between zero and infinity) separated by probe type and autosomal/sex probes. Each row is a quantile and each column is a sample.
unmethQuantiles	Similar to Meth
betaQuantiles	Similar to Meth but for Beta-values
mQuantiles	Similar to Meth but for M-values
cnQuantiles	Similar to Meth but for Copy Number
greenControls	A list containing the matrices of different raw control probes intensities in the green channel
redControls	Similar to greenControls but for the red channel
pca	List containing the PCA scores for the 20,000 most variable CpGs and the percentages of variance explained
originObject	Name of the minfi object from which the data were extracted
array	Name of the Illumina array platform: 450k or EPIC

Details

This class is a representation of a Meth matrix and a Unmeth matrix linked to a pData data frame.

A creationMethod slot is present to indicate from which object type the shinyMethylSet has been created: either a RGChannelSet or GenomicRatioSet

A MethylSet stores meth and Unmeth.

Constructor

Instances are constructed using the shinyMethylSet function with the arguments outlined above.

Accessors

In the following code, object is a shinyMethylSet.

getMeth(object), getUnmeth(object) Get the Meth or Unmeth matrix.

getBeta(object) get Beta, see details.

getM(object) get M-values, see details.

getCN(object) get copy number values which are defined as the sum of the methylation and unmethylation channel.

sampleNames(object) Get the sampleNames

combine(object1, object2) combine shinyMethylSet objects

Author(s)

Jean-Philippe Fortin

See Also

Objects of this class are typically created by using the function [shinySummarize](#) on a [RGChannelSet](#) or [GenomicRatioSet](#).

Examples

```
showClass("shinyMethylSet")
```

shinySummarize-methods

Summarizing a large 450K experiment into a shinyMethylSet

Description

Summarizing methylation data from a [RGChannelSet](#) or [GenomicRatioSet](#) into a [shinyMethylSet](#) needed to launch the interactive interface of shinyMethyl. That works for both the 450k and EPIC arrays.

Usage

```
## S4 method for signature 'RGChannelSet'
shinySummarize(object)
## S4 method for signature 'GenomicRatioSet'
shinySummarize(object)
```

Arguments

object Either a [RGChannelSet](#) or a [GenomicRatioSet](#).

Details

Either a [RGChannelSet](#) is transformed into a [shinyMethylSet](#), or a [GenomicRatioSet](#) is transformed to a [shinyMethylSet](#)

Author(s)

Jean-Philippe Fortin

See Also

[shinyMethylSet](#) for the output object and [RGChannelSet](#) or [GenomicRatioSet](#) for the input object.

Examples

```
if (require(minfiData)){
  library(minfiData)
  summarized.data <- shinySummarize(RGsetEx)
}
```

Index

*** methods**
 shinySummarize-methods, 5

combine (shinyMethylSet-class), 3
combine, shinyMethylSet, shinyMethylSet-method
 (shinyMethylSet-class), 3

GenomicRatioSet, 5
getBeta (shinyMethylSet-class), 3
getBeta, shinyMethylSet-method
 (shinyMethylSet-class), 3
getCN (shinyMethylSet-class), 3
getCN, shinyMethylSet-method
 (shinyMethylSet-class), 3
getGreenControls
 (shinyMethylSet-class), 3
getM (shinyMethylSet-class), 3
getM, shinyMethylSet-method
 (shinyMethylSet-class), 3
getMeth (shinyMethylSet-class), 3
getMeth, shinyMethylSet-method
 (shinyMethylSet-class), 3
getPCA (shinyMethylSet-class), 3
getRedControls (shinyMethylSet-class), 3
getUnmeth (shinyMethylSet-class), 3
getUnmeth, shinyMethylSet-method
 (shinyMethylSet-class), 3

orderBy (shinyMethylSet-class), 3

pData (shinyMethylSet-class), 3
pData, shinyMethylSet-method
 (shinyMethylSet-class), 3

RGChannelSet, 5
runShinyMethyl, 2

sampleNames (shinyMethylSet-class), 3
sampleNames, shinyMethylSet-method
 (shinyMethylSet-class), 3
shinyMethylSet, 2, 5
shinyMethylSet (shinyMethylSet-class), 3
shinyMethylSet-class, 3
shinySummarize, 5
shinySummarize
 (shinySummarize-methods), 5
shinySummarize, GenomicRatioSet-method
 (shinySummarize-methods), 5
shinySummarize, RGChannelSet-method
 (shinySummarize-methods), 5
shinySummarize-methods, 5
show, shinyMethylSet-method
 (shinyMethylSet-class), 3