

Package: strandCheckR (via r-universe)

October 8, 2026

Type Package

Title Calculate strandness information of a bam file

Version 1.31.0

Maintainer Thu-Hien To <tothuhien@gmail.com>

Description This package aims to quantify and remove putative double strand DNA from a strand-specific RNA sample. There are also options and methods to plot the positive/negative proportions of all sliding windows, which allow users to have an idea of how much the sample was contaminated and the appropriate threshold to be used for filtering.

URL <https://github.com/UofABioinformaticsHub/strandCheckR>

BugReports <https://github.com/UofABioinformaticsHub/strandCheckR/issues>

License GPL (>= 2)

LazyData TRUE

Encoding UTF-8

Depends ggplot2 (>= 4.0.0), Rsamtools, S4Vectors

Imports BiocGenerics, dplyr, Seqinfo, GenomicAlignments, GenomicRanges, gridExtra, IRanges, grid, methods, reshape2, rlang, stats, stringr, TxDb.Hsapiens.UCSC.hg38.knownGene, tidyselect

biocViews RNASeq, Alignment, QualityControl, Coverage, ImmunoOncology

RoxygenNote 7.3.3

VignetteBuilder knitr

Suggests BiocStyle, knitr, magrittr, rmarkdown, testthat

Config/pak/sysreqs
make libbz2-dev libicu-dev liblzma-dev libpng-dev libxml2-dev libssl-dev xz-utils zlib1g-dev

Repository <https://bioc.r-universe.dev>

Date/Publication 2026-04-28 12:48:23 UTC

RemoteUrl <https://github.com/bioc/strandCheckR>

RemoteRef HEAD

RemoteSha 03d5abbba66188f486f41ecf734a1d50f0aa5e11

Contents

checkPairedEnd	2
filterDNA	3
getStrandFromBamFile	5
getStrandFromReadInfo	7
getWinOverlapEachIRange	8
getWinOverlapEachReadFragment	9
getWinOverlapGRanges	10
intersectWithFeature	11
plotHist	12
plotWin	13
Index	16

checkPairedEnd	<i>Test whether a bam file is single-end or paired-end</i>
----------------	--

Description

Check the first 100000 first reads of the bam file to see whether it is single-end or paired-end

Usage

```
checkPairedEnd(file, yieldSize = 1e+05)
```

Arguments

- file the input bam file. Your bamfile should be sorted and have an index file located at the same path as well.
- yieldSize the number of reads to be checked, 100000 by default.

Value

return TRUE if the input file is paired end, and FALSE if it is single end

Examples

```
file <- system.file('extdata', 's1.sorted.bam', package = 'strandCheckR')
checkPairedEnd(file)
```

filterDNA*Filter reads coming from double strand sequences from a bam File*

Description

Filter putative double strand DNA from a strand specific RNA-seq using a window sliding across the genome.

Usage

```
filterDNA(  
  file,  
  destination,  
  statFile = "out.stat",  
  sequences,  
  mapqFilter = 0,  
  paired,  
  yieldSize = 1e+06,  
  winWidth = 1000L,  
  winStep = 100L,  
  readProp = 0.5,  
  threshold = 0.7,  
  pvalueThreshold = 0.05,  
  useCoverage = FALSE,  
  mustKeepRanges,  
  getWin = FALSE,  
  minCov = 0,  
  maxCov = 0,  
  errorRate = 0.01  
)
```

Arguments

file	the input bam file to be filtered. Your bamfile should be sorted and have an index file located at the same path.
destination	the file path where the filtered output will be written
statFile	the file to write the summary of the results
sequences	the list of sequences to be filtered
mapqFilter	every read that has mapping quality below mapqFilter will be removed before any analysis. If missing, the entire bam file will be read.
paired	if TRUE then the input bamfile will be considered as paired-end reads. If missing, 100 thousands first reads will be inspected to test if the input bam file in paired-end or single-end.
yieldSize	by default is 1e6, i.e. the bam file is read by block of reads whose size is defined by this parameter. It is used to pass to same parameter of the scanBam function.

winWidth	the length of the sliding window, 1000 by default.
winStep	the step length to sliding the window, 100 by default.
readProp	a read is considered to be included in a window if at least readProp of it is in the window. Specified as a proportion. 0.5 by default.
threshold	the strand proportion threshold to test whether to keep a window or not. 0.7 by default
pvalueThreshold	the threshold for the p-value in the test of keeping windows. 0.05 by default
useCoverage	if TRUE, then the strand information in each window corresponds to the sum of coverage coming from positive/negative reads; and not the number of positive/negative reads as default.
mustKeepRanges	a GRanges object; all reads that map to those ranges will be kept regardless the strand proportion of the windows containing them.
getWin	if TRUE, the function will not only filter the bam file but also return a data frame containing the information of all windows of the original and filtered bam file.
minCov	if useCoverage=FALSE, every window that has less than minCov reads will be rejected regardless the strand proportion. If useCoverage=TRUE, every window has max coverage least than minCov will be rejected. 0 by default
maxCov	if useCoverage=FALSE, every window that has more than maxCov reads will be kept regardless the strand proportion. If useCoverage=TRUE, every window with max coverage more than maxCov will be kept. If 0 then it doesn't have effect on selecting window. 0 by default.
errorRate	the probability that an RNA read takes the false strand. 0.01 by default.

Details

filterDNA reads a bam file containing strand specific RNA reads, and filter reads coming from putative double strand DNA. Using a window sliding across the genome, we calculate the positive/negative proportion of reads in each window. We then use logistic regression to estimate the strand proportion of reads in each window, and calculate the p-value when comparing that to a given threshold. Let π be the strand proportion of reads in a window.

Null hypothesis for positive window: $\pi \leq threshold$.

Null hypothesis for negative window: $\pi \geq 1 - threshold$.

Only windows with p-value $\leq$ pvalueThreshold are kept. For a kept positive window, each positive read in this window is kept with the probability $(P-M)/P$ where P be the number of positive reads, and M be the number of negative reads. That is because those M negative reads are supposed to come from double-strand DNA, then there should be also M positive reads among the P positive reads come from double-strand DNA. In other words, there are only $(P-M)$ positive reads come from RNA. Each negative read is kept with the probability equalling the rate that an RNA read of your sample has wrong strand, which is errorRate. Similar for kept negative windows.

Since each alignment can be belonged to several windows, then the probability of keeping an alignment is the maximum probability defined by all windows that contain it.

Value

if getWin is TRUE: a DataFrame object which could also be obtained by the function getStrandFromBamFile

See Also

[getStrandFromBamFile](#), [plotHist](#), [plotWin](#)

Examples

```
file <- system.file('extdata', 's2.sorted.bam', package = 'strandCheckR')
out_bam <- tempfile(fileext = ".bam")
out_log <- tempfile(fileext = ".log")
filterDNA(file, sequences = '10', destination = out_bam, statFile = out_log)
```

getStrandFromBamFile *Get the strand information of all windows from bam files*

Description

Get the number of positive/negative reads/coverage of all sliding windows from the bam input files

Usage

```
getStrandFromBamFile(
  files,
  sequences,
  mapqFilter = 0,
  yieldSize = 1e+06,
  winWidth = 1000L,
  winStep = 100L,
  readProp = 0.5,
  paired
)
```

Arguments

files	the input bam files. Your bamfiles should be sorted and have their index files located at the same path.
sequences	character vector used to restrict analysed alignments to a subset of chromosomes (i.e. sequences) within the provided bam file. These correspond to chromosomes/scaffolds of the reference genome to which the reads were mapped. If absent, the whole bam file will be read. NB: This must match the chromosomes as defined in your reference genome. If the reference chromosomes were specified using the 'chr' prefix, ensure the supplied vector matches this specification.
mapqFilter	every read that has mapping quality below mapqFilter will be removed before any analysis.
yieldSize	by default is 1e6, i.e. the bam file is read by block of reads whose size is defined by this parameter. It is used to pass to same parameter of the scanBam function.
winWidth	the width of the sliding window, 1000 by default.

<code>winStep</code>	the step length to sliding the window, 100 by default.
<code>readProp</code>	A read is considered to be included in a window if at least <code>readProp</code> of it is in the window. Specified as a proportion. 0.5 by default.
<code>paired</code>	if TRUE then the input bamfile will be considered as paired-end reads. If missing, 100 thousands first reads will be inspected to test if the input bam file in paired-end or single-end.

Details

This function moves along the specified chromosomes (i.e. sequences) using a sliding window approach, and counts the number of reads in each window which align to the +/- strands of the reference genome. As well as the number of reads, the total coverage for each strand is also returned for each window, representing the total number of bases covered.

Average coverage for the entire window can be simply calculated by dividing the total coverage by the window size.

Value

a `DataFrame` object containing the number of positive/negative reads and coverage of each window sliding across the bam file. The returned `DataFrame` has 10 columns:

Type: can be either SE if the input file contains single-end reads, or R1/R2 if the input file contains paired-end reads.

Seq: the reference sequence (chromosome/scaffold) that the reads were mapped to.

Start: the start position of the sliding window.

End: the end position of the sliding window.

NbPos/NbNeg: number of positive/negative reads that overlap the sliding window.

CovPos/CovNeg: number of bases coming from positive/negative reads that were mapped in the sliding window.

MaxCoverage: the maximum coverage within the sliding window.

File: the name of the input file.

See Also

[filterDNA](#), [plotHist](#), [plotWin](#)

Examples

```
file <- system.file('extdata', 's1.sorted.bam', package = 'strandCheckR')
win <- getStrandFromBamFile(file, sequences='10')
win
```

getStrandFromReadInfo *Get the strand information of all windows from read information*

Description

Get the number of positive/negative reads of all windows from read information obtained from [Rsamtools::scanBam()]

Usage

```
getStrandFromReadInfo(  
  readInfo,  
  winWidth = 1000L,  
  winStep = 100L,  
  readProp = 0.5,  
  subset = NULL  
)
```

Arguments

readInfo	a list containing read information returned by [Rsamtools::scanBam()].
winWidth	the length of the sliding window, 1000 by default.
winStep	the step length to sliding the window, 100 by default.
readProp	A read is considered to be included in a window if at least readProp of it is in the window. Specified as a proportion. 0.5 by default.
subset	an integer vector specifying the subset of reads to consider

Value

a DataFrame object containing the number of positive/negative reads and coverage of each window sliding .

See Also

[filterDNA](#), [getStrandFromBamFile](#)

Examples

```
library(Rsamtools)  
file <- system.file('extdata', 's2.sorted.bam', package = 'strandCheckR')  
readInfo <- scanBam(file, param =  
  ScanBamParam(what = c("pos", "cigar", "strand")))  
getStrandFromReadInfo(readInfo[[1]], 1000, 100, 0.5)
```

getWinOverlapEachIRange

Get the ranges of sliding windows that overlap each range of an IRanges object.

Description

Get the ranges of sliding windows that overlap each range of an IRanges object.

Usage

```
getWinOverlapEachIRange(
  x,
  winWidth = 1000L,
  winStep = 100L,
  readProp = 0.5,
  maxWin = Inf
)
```

Arguments

x	an IRanges object containing the start and end position of each read fragment.
winWidth	the width of the sliding window, 1000 by default.
winStep	the step length to sliding the window, 100 by default.
readProp	A read is considered to be included in a window if at least readProp of it is in the window. Specified as a proportion.
maxWin	The maximum window ID

Details

This finds the windows that overlap each range of the input IRanges object. Each range corresponds to a read fragment. This allows the total number of read fragments within a window to be calculated simply using [IRanges::coverage()].

Value

An IRanges object containing the index of the windows overlapping each read fragment

Examples

```
library(IRanges)
x <- IRanges(start=round(runif(100,1000,10000)),width=100)
getWinOverlapEachIRange(x)
```

getWinOverlapEachReadFragment

Get the window ranges that overlap each read fragment

Description

Calculate the window ranges that overlap each read fragment

Usage

```
getWinOverlapEachReadFragment(
  readInfo,
  strand,
  winWidth,
  winStep,
  readProp,
  useCoverage = FALSE,
  subset = NULL
)
```

Arguments

readInfo	a list contains the read information
strand	the considering strand
winWidth	the width of the sliding window, 1000 by default.
winStep	the step length to sliding the window, 100 by default.
readProp	a read fragment is considered to be included in a window if and only if at least readProp percent of it is in the window.
useCoverage	either base on coverage or number of reads
subset	if we consider only a subset of the input reads

Value

If useCoverage=FALSE: an IRanges object which contains the range of sliding windows that overlap each read fragment. If useCoverage=TRUE: a list of two objects, the first one is the later IRanges object, the second one is an integer-Rle object which contains the coverage of the input readInfo

Examples

```
library(Rsamtools)
file <- system.file('extdata', 's2.sorted.bam', package = 'strandCheckR')
readInfo <- scanBam(file, param =
  ScanBamParam(what = c("pos", "cigar", "strand")))
getWinOverlapEachReadFragment(readInfo[[1]], "+", 1000, 100, 0.5)
```

getWinOverlapGRanges *Get the sliding windows that overlap a GRanges object*

Description

Get the sliding windows that overlap a GRanges object.

Usage

```
getWinOverlapGRanges(  
  x,  
  seqInfo,  
  winWidth = 1000L,  
  winStep = 100L,  
  nbOverlapBases = 1  
)
```

Arguments

x	a GRanges object, which defines the coordinates of the ranges in the reference genome that all reads mapped to those ranges must be kept by the filtering method filterDNA.
seqInfo	a data frame that contains some key information of the sequences
winWidth	the length of the sliding window, 1000 by default.
winStep	the step length to sliding the window, 100 by default.
nbOverlapBases	a window is considered to overlap with a range of x if it overlaps with at least nbOverlapBases bases.

Details

This finds the windows that overlaps the positive/negative strand of a GRanges object. The GRanges object, which is mustKeepRanges in the filterDNA method, defines the coordinates of the ranges in the reference genome that all reads mapped to those ranges must be kept by the filtering method filterDNA. This method makes use of the method getWinOverlapEachIRange by pretending each given range as the range of a read. Since the widths of x are not necessarily the same (as normal read lengths), we use nbOverlapBases to specify the minimum number of bases that a window should overlap with a range of x, instead of using proportion as readProp in getWinOverlapEachIRange.

Value

A list of two logical vectors (for positive and negative strand) defining which windows that overlap with the given GRanges object.

Examples

```
library(GenomicRanges)
x <- GRanges(seqnames = "10", ranges = IRanges(start = c(10000, 15000),
end=c(20000, 30000)), strand = c("+", "-"))
seqInfo <- data.frame("Sequence"=10, "FirstBaseInPart"=1)
getWinOverlapGRanges(x, seqInfo)
seqInfo <- data.frame("Sequence"=10, "FirstBaseInPart"=10000000)
getWinOverlapGRanges(x, seqInfo)
```

`intersectWithFeature` *Intersect the windows data frame with an annotation data frame*

Description

Intersect the windows with an annotation data frame to get features that overlap with each window

Usage

```
intersectWithFeature(
  windows,
  annotation,
  getFeatureInfo = FALSE,
  overlapCol = "OverlapFeature",
  mcolsAnnot,
  collapse,
  ...
)
```

Arguments

<code>windows</code>	data frame containing the strand information of the sliding windows. Windows can be obtained using the function <code>getStrandFromBamFile</code> .
<code>annotation</code>	a Grange object that you want to intersect with your windows. It can have <code>mcols</code> which contains the information or features that could be able to integrate to the input windows
<code>getFeatureInfo</code>	whether to get the information of features in the <code>mcols</code> of annotation data or not. If <code>FALSE</code> the return windows will have an additional column indicating whether a window overlaps with any range of the annotation data. If <code>TRUE</code> the return windows will contain the information of features that overlap each window
<code>overlapCol</code>	the column name of the return windows indicating whether a window overlaps with any range of the annotation data.
<code>mcolsAnnot</code>	the column names of the <code>mcols</code> of the annotation data that you want to get information
<code>collapse</code>	character which is used collapse multiple features that overlap with a same window into a string. If missing then we don't collapse them.
<code>...</code>	used to pass parameters to <code>GenomicRanges::findOverlaps</code>

Value

the input windows DataFrame with some additional columns

See Also

[getStrandFromBamFile](#), [plotHist](#), [plotWin](#)

Examples

```
bamfilein = system.file('extdata', 's2.sorted.bam', package = 'strandCheckR')
windows <- getStrandFromBamFile(file = bamfilein)
#add chr before chromosome names to be consistent with the annotation
windows$Seq <- paste0('chr', windows$Seq)
library(TxDb.Hsapiens.UCSC.hg38.knownGene)
annot <- transcripts(TxDb.Hsapiens.UCSC.hg38.knownGene)
# get the transcript names that overlap with each window
windows <- intersectWithFeature(windows, annot, mcolsAnnot='tx_name')
# just want to know whether there's any transcript that
# overlaps with each window
windows <- intersectWithFeature(windows, annot, overlapCol='OverlapTranscript')
plotHist(windows, facets = 'OverlapTranscript')
plotWin(windows, facets = 'OverlapTranscript')
```

plotHist

Plot the histogram of positive proportions

Description

Plot the histogram of positive proportions of the input data frame coming from `getStrandFromBamFile`

Usage

```
plotHist(
  windows,
  save = FALSE,
  file = "hist.pdf",
  groupBy = NULL,
  normalizeBy = NULL,
  split = c(10, 100, 1000),
  breaks = 100,
  useCoverage = FALSE,
  heatmap = FALSE,
  ...
)
```

Arguments

windows	data frame containing the strand information of the sliding windows. Windows can be obtained using the function <code>getStrandFromBamFile</code> .
save	if TRUE, then the plot will be save into the file given by file parameter
file	the file name to save to plot
groupBy	the columns that will be used to split the data.
normalizeBy	instead of using the raw read count/coverage, we will normalize it to a proportion by dividing it to the total number of read count/coverage of windows that have the same value in the normalizeBy columns.
split	an integer vector that specifies how you want to partition the windows based on the coverage. By default <code>split = c(10,100,1000)</code> , which means that your windows will be partitionned into 4 groups, those have coverage < 10, from 10 to 100, from 100 to 1000, and > 1000
breaks	an integer giving the number of bins for the histogram
useCoverage	if TRUE then plot the coverage strand information, otherwise plot the number of reads strand information. FALSE by default
heatmap	if TRUE, then use heat map to plot the histogram, otherwise use barplot. FALSE by default.
...	used to pass parameters to <code>facet_wrap</code>

Value

If heatmap=FALSE: a ggplot object

See Also

[getStrandFromBamFile](#), [plotWin](#)

Examples

```
bamfilein = system.file('extdata', 's1.sorted.bam', package = 'strandCheckR')
win <- getStrandFromBamFile(file = bamfilein, sequences='10')
plotHist(win)
```

plotWin

Plot the number of reads vs the proportion of '+' stranded reads.

Description

Plot the number of reads vs the proportion of '+' stranded reads of all windows from the input data frame.

Usage

```
plotWin(
  windows,
  split = c(10, 100, 1000),
  threshold = c(0.6, 0.7, 0.8, 0.9),
  save = FALSE,
  file = "win.pdf",
  groupBy = NULL,
  useCoverage = FALSE,
  ...
)
```

Arguments

windows	data frame containing the strand information of the sliding windows. Windows should be obtained using the function getStrandFromBamFile to ensure the correct data structure.
split	an integer vector that specifies how you want to partition the windows based on coverage. By default <code>split = c(10,100,1000)</code> , partition windows into 4 groups based on these values.
threshold	a numeric vector between 0.5 & 1 that specifies which threshold lines to draw on the plot. The positive windows above the threshold line (or negative windows below the threshold line) will be kept when using filterDNA .
save	if TRUE, then the plot will be save into the file given by file parameter
file	the file name to save to plot
groupBy	the column that will be used to split the data (which will be used in the facets method of ggplot2).
useCoverage	if TRUE then plot the coverage strand information, otherwise plot the number of reads strand information. FALSE by default
...	used to pass parameters to <code>facet_wrap</code> during plotting

Details

This function will plot the proportion of '+' stranded reads for each window, against the number of reads in each window. The threshold lines indicate the hypothetical boundary where windows will contain reads to kept or discarded using the filtering methods of [filterDNA](#). Any plot can be easily modified using standard ggplot2 syntax (see Examples)

Value

The plot will be returned as a standard ggplot2 object

See Also

[getStrandFromBamFile](#), [plotHist](#)

Examples

```
bamfilein = system.file('extdata','s2.sorted.bam',package = 'strandCheckR')
windows <- getStrandFromBamFile(file = bamfilein,sequences = '10')
plotWin(windows)

# Change point colour using ggplot2
library(ggplot2)
plotWin(windows) +
scale_colour_manual(values = rgb(seq(0, 1, length.out = 4), 0, 0))
```

Index

checkPairedEnd, [2](#)

filterDNA, [3](#), [6](#), [7](#), [14](#)

getStrandFromBamFile, [5](#), [5](#), [7](#), [12–14](#)

getStrandFromReadInfo, [7](#)

getWinOverlapEachIRange, [8](#)

getWinOverlapEachReadFragment, [9](#)

getWinOverlapGRanges, [10](#)

intersectWithFeature, [11](#)

plotHist, [5](#), [6](#), [12](#), [12](#), [14](#)

plotWin, [5](#), [6](#), [12](#), [13](#), [13](#)