

Package: webbioc (via r-universe)

July 24, 2024

Version 1.77.0

Date 2009-02-05

Title Bioconductor Web Interface

Author Colin A. Smith <colin@colinsmith.org>

Maintainer Colin A. Smith <colin@colinsmith.org>

Depends R (>= 1.8.0), Biobase, affy, multtest, annaffy, vsn, gcrma, qvalue

Imports multtest, qvalue, stats, utils, BiocManager

SystemRequirements Unix, Perl (>= 5.6.0), Netpbm

Description An integrated web interface for doing microarray analysis using several of the Bioconductor packages. It is intended to be deployed as a centralized bioinformatics resource for use by many users. (Currently only Affymetrix oligonucleotide analysis is supported.)

License GPL (>= 2)

URL <http://www.bioconductor.org/>

LazyLoad yes

biocViews Infrastructure, Microarray, OneChannel, DifferentialExpression

Repository <https://bioc.r-universe.dev>

RemoteUrl <https://github.com/bioc/webbioc>

RemoteRef HEAD

RemoteSha fe751f54ed261858caaab94ea35cd2e347539153

Contents

installReps	2
mt.wrapper	2
Index	5

installReps	<i>Install all repository packages</i>
-------------	--

Description

Using reposTools, install/update all packages from given repositories.

Usage

```
installReps(repNames = "aData", lib = .libPaths()[1],
            type = getOption("pkgType"))
```

Arguments

repNames	A character vector containing repository names. A listing of known repository names can be found with the getReposOption() function.
lib	A path to install/update the packages. If this directory does not exist, it will be created (if possible).
type	type of package do download

Author(s)

Colin A. Smith <webbioc@colinsmith.org>

mt.wrapper	<i>Multiple Testing Wrapper Function</i>
------------	--

Description

A wrapper for some of the functionality for the multtest package. It also includes hooks to calculate q-values with John D. Storey's 'q-value.R' code.

Usage

```
mt.wrapper(proc, X, classlabel, test="t", rawpcalc="Parametric", side="abs", ...)
```

Arguments

proc	A character string containing the name of the multiple testing procedure for which adjusted p -values are to be computed. This vector should include any of the following: "Bonferroni", "Holm", "Hochberg", "SidakSS", "SidakSD", "BH", "BY", "maxT", "minP", "q".
X	A data frame or matrix, with m rows corresponding to variables (hypotheses) and n columns to observations. In the case of gene expression data, rows correspond to genes and columns to mRNA samples. The data can be read using read.table .

<code>classlabel</code>	A vector of integers corresponding to observation (column) class labels. For k classes, the labels must be integers between 0 and $k - 1$. For the <code>blockf</code> test option, observations may be divided into n/k blocks of k observations each. The observations are ordered by block, and within each block, they are labeled using the integers 0 to $k - 1$.
<code>test</code>	<p>A character string specifying the statistic to be used to test the null hypothesis of no association between the variables and the class labels.</p> <p>If <code>test="t"</code>, the tests are based on two-sample Welch t-statistics (unequal variances).</p> <p>If <code>test="t.equalvar"</code>, the tests are based on two-sample t-statistics with equal variance for the two samples. The square of the t-statistic is equal to an F-statistic for $k = 2$.</p> <p>If <code>test="wilcoxon"</code>, the tests are based on standardized rank sum Wilcoxon statistics.</p> <p>If <code>test="f"</code>, the tests are based on F-statistics.</p> <p>If <code>test="pairt"</code>, the tests are based on paired t-statistics. The square of the paired t-statistic is equal to a block F-statistic for $k = 2$.</p> <p>If <code>test="blockf"</code>, the tests are based on F-statistics which adjust for block differences (cf. two-way analysis of variance).</p>
<code>rawpcalc</code>	A character string specifying how to calculate nominal/raw p-values. The possible choices are "Parametric" or "Permutation".
<code>side</code>	<p>A character string specifying the type of rejection region.</p> <p>If <code>side="abs"</code>, two-tailed tests, the null hypothesis is rejected for large absolute values of the test statistic.</p> <p>If <code>side="upper"</code>, one-tailed tests, the null hypothesis is rejected for large values of the test statistic.</p> <p>If <code>side="lower"</code>, one-tailed tests, the null hypothesis is rejected for small values of the test statistic.</p>
<code>...</code>	Further arguments for <code>mt.maxT</code> , <code>mt.minP</code> , <code>qvalue</code> .

Value

A data frame with components

<code>index</code>	Vector of row indices, between 1 and <code>nrow(X)</code> , where rows are sorted first according to their adjusted p -values, next their unadjusted p -values, and finally their test statistics.
<code>teststat</code>	Vector of test statistics, ordered according to <code>index</code> . To get the test statistics in the original data order, use <code>teststat[order(index)]</code> .
<code>rawp</code>	Vector of raw (unadjusted) p -values, ordered according to <code>index</code> .
<code>adjp</code>	Vector of adjusted p -values, ordered according to <code>index</code> .
<code>plover</code>	For <code>mt.minP</code> function only, vector of "adjusted p -values", where ties in the permutation distribution of the successive minima of raw p -values with the observed p -values are counted only once. Note that procedures based on <code>plover</code> do not control the FWER. Comparison of <code>plover</code> and <code>adjp</code> gives an idea of the discreteness of the permutation distribution. Values in <code>plover</code> are ordered according to <code>index</code> .

Author(s)

Colin A. Smith <webbioc@colinsmith.org>

Index

* **file**

installReps, [2](#)

mt.wrapper, [2](#)

installReps, [2](#)

mt.minP, [3](#)

mt.wrapper, [2](#)

read.table, [2](#)